

## Proposal for amendments to Regulation No. 106 (Uniform provisions concerning the approval of pneumatic tyres for agricultural vehicles and their trailers)

The text reproduced below was prepared by the experts from the European Tyre and Rim Technical Organisation (ETRTO).

### Proposal:

Paragraph 2.16. amend the table by adding diameter code 'd' 28.5 as follows:

...

"d" symbol expressed by codes	Value to be used for the calculation in paras. 6.2.1 and 6.4 (mm)
...	...
26.5	673
<b>28.5.5</b>	<b>724</b>
30.5	775

...

Annex 5, table7, add the following entries:

"

Tyre size designation	Theoretical rim width code (A1)	Nominal section width (S1) (mm)	Overall diameter (D) (mm)	Nominal rim diameter (d) (mm)
...				
<b>24X8.00-12</b>	<b>6.5</b>	<b>204</b>	<b>610</b>	<b>305</b>
<b>24X10.00-12</b>	<b>8</b>	<b>254</b>	<b>610</b>	<b>305</b>
<b>26X8.00-12</b>	<b>6.5</b>	<b>204</b>	<b>660</b>	<b>305</b>
<b>26X8.00-14</b>	<b>6.5</b>	<b>204</b>	<b>660</b>	<b>356</b>
<b>27X10.00-14</b>	<b>8</b>	<b>254</b>	<b>686</b>	<b>356</b>
<b>27X12.00-14</b>	<b>9.5</b>	<b>304</b>	<b>686</b>	<b>356</b>
<b>28X9.00-14</b>	<b>7</b>	<b>227</b>	<b>711</b>	<b>356</b>
<b>28X10.00-12</b>	<b>8</b>	<b>254</b>	<b>711</b>	<b>305</b>
<b>28X10.00-15</b>	<b>8</b>	<b>254</b>	<b>711</b>	<b>381</b>
<b>28X11.00-14</b>	<b>9</b>	<b>281</b>	<b>711</b>	<b>356</b>
<b>28X11.00-15</b>	<b>9</b>	<b>281</b>	<b>711</b>	<b>381</b>
<b>28X12.00-12</b>	<b>9.5</b>	<b>304</b>	<b>711</b>	<b>305</b>
<b>29X9.00-14</b>	<b>7</b>	<b>227</b>	<b>737</b>	<b>356</b>
<b>29X9.00-15</b>	<b>7</b>	<b>227</b>	<b>737</b>	<b>381</b>
<b>29X9.00-16</b>	<b>7</b>	<b>227</b>	<b>737</b>	<b>406</b>

<i>Tyre size designation</i>	<i>Theoretical rim width code (A1)</i>	<i>Nominal section width (S1) (mm)</i>	<i>Overall diameter (D) (mm)</i>	<i>Nominal rim diameter (d) (mm)</i>
<b>29X9.50-15</b>	<b>7.5</b>	<b>240</b>	<b>737</b>	<b>381</b>
<b>29X11.00-14</b>	<b>9</b>	<b>281</b>	<b>737</b>	<b>356</b>
<b>29X11.00-16</b>	<b>9</b>	<b>281</b>	<b>737</b>	<b>406</b>
<b>30X9.00-14</b>	<b>7</b>	<b>227</b>	<b>762</b>	<b>356</b>
<b>30X10.00-14</b>	<b>8</b>	<b>254</b>	<b>762</b>	<b>356</b>
<b>30X10.00-15</b>	<b>8</b>	<b>254</b>	<b>762</b>	<b>381</b>
<b>30X11.00-14</b>	<b>9</b>	<b>281</b>	<b>762</b>	<b>356</b>
<b>31X10.00-17</b>	<b>8</b>	<b>254</b>	<b>787</b>	<b>432</b>
<b>32X10.00-16</b>	<b>8</b>	<b>254</b>	<b>813</b>	<b>406</b>
<b>32X10.00-18</b>	<b>8</b>	<b>254</b>	<b>813</b>	<b>457</b>
...				

"

Annex 5, table 9, add the following entry:

"

<i>Tyre size designation</i>	<i>Theoretical rim width code (A1)</i>	<i>Nominal section width (S1) (mm)</i>		<i>Overall diameter (D) (mm)</i>		<i>Nominal rim diameter (d) (mm)</i>
		<i>Radial</i>	<i>Diagonal</i>	<i>Radial</i>	<i>Diagonal</i>	
...						
<b>11L-16 IND</b>	<b>8</b>	<b>290</b>		<b>850</b>		<b>406</b>
...						

"

---