## Proposal for amendments of Regulation No. 14 (Safety-belt anchorages)

## Submitted by the expert from Germany

The text reproduced below was prepared by the expert from Germany. It introduces amendments to Regulation No. 14 (Safety-belt anchorages). The modifications to the existing text of the UN Regulation are marked in bold for new or strikethrough for deleted characters.

## I. Proposal

Specifications 5.3.1., amend to read:

"5.3.1. Any vehicle in categories M and N (except those vehicles of categories M2 or M3 which belong to Classes I and A <sup>1)</sup>) shall be equipped with safety belt anchorages which satisfy the requirements of this regulation.

If vehicles of categories M2 or M3 which belong to Classes I or A  $^{1)}$  are fitted with safety-belt anchorages, these anchorages shall satisfy the requirements of this regulation."

Specifications 5.3.5., amend to read:

- "5.3.5. In every seating position marked in Annex 6 with symbol  $\frac{11}{17}$ , three anchorages shall be provided. Two anchorages may be provided if one of the following conditions is fulfilled:
- 5.3.5.1. There is a seat or other parts of the vehicle conforming to Regulation No. 80, Appendix 1, paragraph 3.5. directly in front, or
- 5.3.5.2. No part of the vehicle is in the reference zone, or capable of being in the reference zone when the vehicle is in motion, or
- 5.3.5.3. Parts of the vehicle within the said reference zone comply with the energy absorbing requirements set out in Regulation No 80, Appendix 6.
- 5.3.5.4. Paragraphs 5.3.5.1. 5.3.5.3. shall not apply to a driver's seat."

## II. Justification

Currently opinions differ between different Technical Services which requirements to apply and how to approve a driver's seat with regard to its seat-belt. The proposed amendments clarify that for a driver's seat only a 3-point-belt shall be permitted.