Informal document No. 13 (46th GRPE, 19-23 May 2003, agenda item 10.)

EPA's Proposal for Nonroad Diesel Engines & Fuel



May 2003

U.S. Environmental Protection Agency Office of Transportation and Air Quality

Scope of the Proposal

- Proposal applies to nonroad diesels of all sizes, from 3 to 3,000 hp
 - Used in a diversity of applications-- construction, farming, mining, industrial
- Proposed fuel provisions apply to fuel used in nonroad diesels, locomotives, and marine engines
 - But not to home heating fuel
 - Nonroad fuel is not currently regulated by EPA
- Proposal addresses serious health and welfare impacts from nonroad diesel fuel and equipment-
 - ozone, fine PM
 - in addition, diesel exhaust is likely to be carcinogenic to humans
- These sources currently contribute 44% of total mobile source diesel PM and 12% of total mobile source NOx nationwide.
 - Their contributions range even higher in many urban areas and will grow in the future.

2

Proposal Overview

- A systems approach of reducing nonroad fuel sulfur levels to enable advanced emission control technology
 - similar to 2007 diesel truck and fuel rule
- 500 ppm maximum sulfur nonroad diesel fuel in 2007
 - based on substantial health benefits from sulfate and PM reductions
- 15 ppm nonroad fuel in 2010
 - to enable engine standards
- Engine standards representing reductions of >95% PM and ~90% NOx
 - Standards phase in starting in 2008, fully phased in by 2014
- Enhanced certification test requirements to ensure in-use emissions reductions

3

Proposed Engine Standards Program

500 ppm NR fuel 15 ppm NR fuel 2004 2005 2006 2007 2008 2009 2010 2011 2012 2013 2014 2015 Tier 1 <25 PM (reductions w/oxidation catalysts or engine-based control) 25-75 PM (reduction w/oxidation catalysts or engine-based control) PM: 100% existing Tier 2 PM:100% 75-175 NOx: 50% 50% 100% existing Tier 3 PM: 100% 175-750 NOx: 50% 50% 50% 100% PM &NOx: 50% >750 existing Tier 2 50% 100%

Percentages indicate portion of sales required to meet advanced emission control technology standards

4