



**Economic and Social
Council**

Distr.
GENERAL

ECE/TRANS/WP.29/2008/41
7 December 2007

Original: ENGLISH

ECONOMIC COMMISSION FOR EUROPE

INLAND TRANSPORT COMMITTEE

World Forum for Harmonization of Vehicle Regulations

One-hundred-and-forty-fourth session
Geneva, 11 - 14 March 2008
Item 4.2.14. of the provisional agenda

1958 AGREEMENT

Consideration of draft amendments to existing Regulations

Proposal for Supplement 3 to the 02 series of amendments to Regulation No. 46
(Devices for indirect vision)

Submitted by the Working Party on General Safety Provisions */

The text reproduced below was adopted by the Working Party on General Safety Provisions (GRSG) at its ninety-third session (ECE/TRANS/WP.29/GRSG/72, para. 23). It is based on ECE/TRANS/WP.29/GRSG/2007/24, as modified and reproduced in Annex VI to the report. It is submitted to WP.29 and AC.1 for consideration.

*/ In accordance with the programme of work of the Inland Transport Committee for 2006-2010 (ECE/TRANS/166/Add.1, programme activity 02.4), the World Forum will develop, harmonize and update Regulations in order to enhance performance of vehicles. The present document is submitted in conformity with that mandate.

Insert a new paragraph 2.1.2.13., to read:

"2.1.2.13. "surveillance camera-monitor-recording device" means a camera and either a monitor or recording equipment other than the camera-monitor device defined in paragraph 2.1.2. which can be fitted to the inside or outside of the vehicle in order to provide fields of vision other than those specified in paragraph 15.2.4 or to provide a security system within or around the vehicle."

Insert a new paragraph 15.3.6., to read:

"15.3.6. The provisions of this Regulation do not apply to the surveillance camera-monitor-recording devices defined in paragraphs 2.1.2.13. Exterior surveillance cameras either shall be mounted at least 2 m above the ground when the vehicle is under a load corresponding to its maximum technical permissible mass, or, if their lower edge is less than 2 m from the ground, shall not project more than 50 mm beyond the overall width of the vehicle measured without this device and have a radii of curvature of not less than 2.5 mm."
