

New «advance and alternative location» danger warning and prohibitory signs?

Group of Experts on Road Signs and Signals
Geneva, 29 May 2017
UNECE Secretariat



UNECE

- 1. Signs shall be so placed that the drivers for whom they are intended can recognize them easily and in time. They shall normally be placed on the side of the road appropriate to the direction of traffic; they may, however, be placed or repeated above the carriageway. Any sign placed on the side of the road appropriate to the direction of traffic shall be repeated above or on the other side of the carriageway if local conditions are such that it might not be seen in time by the drivers for whom it is intended.**


- 2. All signs shall apply to the drivers from whom they are intended over the whole width of the carriageway open to traffic. However, signs may be made to apply to only one or to several lanes of the carriageway when lanes are defined by longitudinal markings. I**

3. Danger warning signs shall be placed at such distance from the danger point as will make them most effective both by day and by night, having regard to road and traffic conditions, including the normal speed of vehicles and the distance at which the sign is visible.

4. The distance between the sign and the beginning of a dangerous section of road may be shown in an additional panel H, 1 of Annex 1, section H to this Convention and placed in accordance with the provisions of that section; this information must be given when the distance between the sign and the beginning of the dangerous section of road cannot be judged by drivers and is not what they might normally expect.

Chapter II: Road signs, Article 6

- All signs shall apply to the drivers for whom they are intended over the whole width of the carriageway open to traffic
- Signs may be made to apply to only one or to several lanes of the carriageway when lanes are defined by longitudinal markings.



E,1^c























Robert.Nowak@unece.org



www.unece.org