

## **COMMITTEE OF EXPERTS ON THE TRANSPORT OF DANGEROUS GOODS AND ON THE GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS**

### Sub-Committee of Experts on the Transport of Dangerous Goods

Twenty-fifth session  
Geneva, 5-14 July 2004  
Item 8 of the provisional agenda

### **HARMONIZATION WITH THE INTERNATIONAL ATOMIC ENERGY AGENCY (IAEA) REGULATIONS FOR THE SAFE TRANSPORT OF RADIOACTIVE MATERIAL**

#### TRANSSC IX and CSS approved changes for the 2005 Edition of the IAEA Transport Regulations

#### Transmitted by the International Atomic Energy Agency (IAEA)

This paper summarizes the changes that were approved by the June 2004 meeting of the Committee on Safety Standards (CSS). All changes as already approved by the March 2004 TRANSSC meeting were endorsed by CSS without any further change. These changes are still subject to approval by the IAEA Board of Governors in September 2004. These changes are in addition to the minor changes already approved by the September 2002 Review Panel and previously submitted to the UN SCETDG in July 2003 as Working Paper ST/SG/AC.10/C.3/2003/2.

The combined approved changes are presented in UN format with UN paragraph numbers in Working Paper ST/SG/AC.10/C.3/2004/11 prepared by the UN Secretariat for the July 2004 meeting of the SCETDG.

CSS endorsed the changes as submitted in this paper for approval by the IAEA Board of Governors when they meet in September 2004. The decisions of the IAEA Board of Governors in September 2004 will be submitted for the December 2004 SCETDG meeting.

CHANGES FOR THE 2005 EDITION OF THE IAEA TRANSPORT REGULATIONS  
AS APPROVED BY TRANSSC IX and CSS

**Changes in paragraph numbers**

NOTE. The changes as approved by TRANSSC and CSS have resulted in several changes to paragraph numbers as follows:

Para # in 2005	Para # in 2003
301	302
302	301
303	305
304	308
305	309
306	310
307	311
308	304
309	313
310	312
311	303
312	314
313	315
314	316
--	306
--	307

In Section 5 of the 2005 edition para 534 is a new paragraph. As a result paras 534/582 of the 2003 edition have been renumbered as paras 535/583 in the 2005 edition.

In Section 6 of the 2005 edition para 662 has been renumbered as para 653. As a result, paras 653/661 of the 2003 edition have been renumbered as paras 654/662 in the 2005 edition

Where the approved changes to text are affected by the new paragraph numbers the required renumbering of the paragraph is indicated as a note with the relevant change as approved.

**Other approved changes**

In addition to the changes approved by TRANSSC IX and CSS there are minor changes that were approved earlier in the process. These approved minor changes are reported separately.

Change	Para	Existing text in TS-R-1 (2003)	Text as approved by TRANSSC IX
1	204	204. <i>Multilateral approval</i> shall mean approval by the relevant <i>competent authority</i> <b>both</b> of the country of origin of the <i>design</i> or <i>shipment</i> and of each country through or into which the <i>consignment</i> is to be transported. The term “through or into” - specifically excludes “over”, i.e. the approval and notification requirements shall not apply to a country over which <i>radioactive material</i> is carried in an <i>aircraft</i> , provided that there is no scheduled stop in that country.	204. <i>Multilateral approval</i> shall mean approval by the relevant <i>competent authority</i> of the country of origin of the <i>design</i> or <i>shipment</i> , <b>as applicable</b> , and <b>also, where the <i>consignment</i> is to be transported through or into any other country, approval by the <i>competent authority</i> of that country.</b> The term “through or into” specifically excludes “over”, i.e. the approval and notification requirements shall not apply to a country over which <i>radioactive material</i> is carried in an <i>aircraft</i> , provided that there is no scheduled stop in that country.
3	212	212. <i>Consignor</i> shall mean any person, organization or government which prepares a <i>consignment</i> for transport, <b>and is named as <i>consignor</i> in the transport documents.</b>	212. <i>Consignor</i> shall mean any person, organization or government which prepares a <i>consignment</i> for transport.  549. The <i>consignor</i> shall include in the transport documents with each <i>consignment</i> <b>the identification of the consignor and consignee, including their names and addresses and</b> the following information, as applicable in the order given: <b>(NOTE. PARA. 549 TO BE REN UMBERED AS 550)</b>
10	303	303. Workers shall receive appropriate training concerning the radiation hazards involved and the precautions to be observed in order to ensure restriction of their exposure and that of other persons who might be affected by their actions.	303. Workers shall receive appropriate training concerning <b>radiation protection including</b> the precautions to be observed in order <b>to restrict their occupational exposure and the exposure</b> of other persons who might be affected by their actions. <b>(NOTE. Para. 303 to be renumbered as 311)</b>
11	305	305. For occupational exposures arising from transport activities, where it is assessed that the effective dose:  (a) <b>is most unlikely to exceed 1 mSv in a year, neither special work patterns nor detailed monitoring nor dose assessment programmes nor individual record keeping shall be required;</b>  (b) is likely to be between 1 and 6 mSv in a year, a dose assessment programme via work place monitoring or individual monitoring shall be conducted;  (c) is likely to exceed 6 mSv in a year, individual monitoring shall be conducted.  When individual monitoring or work place monitoring is conducted, appropriate records shall be kept.	305. For occupational exposures arising from transport activities, where it is assessed that the effective dose:  (a) is likely to be between 1 and 6 mSv in a year, a dose assessment programme via work place monitoring or individual monitoring shall be conducted;  (b) is likely to exceed 6 mSv in a year, individual monitoring shall be conducted.  When individual monitoring or work place monitoring is conducted, appropriate records shall be kept.  <b>(NOTE. Para. 305 to be renumbered as 303)</b>

Change	Para	Existing text in TS-R-1 (2003)	Text as approved by TRANSSC IX																																																																								
12	Table I footnote (a)	(a) $A_1$ and/or $A_2$ values for these parent radionuclides include contributions from daughter radionuclides with half-lives less than 10 days.	<p>(a) <math>A_1</math> and/or <math>A_2</math> values for these parent radionuclides include contributions from daughter radionuclides with half-lives less than 10 days, <b>as listed in the following:</b></p> <table border="0"> <tr> <td>Mg 28</td> <td>Al 28</td> </tr> <tr> <td>Ar 42</td> <td>K 42</td> </tr> <tr> <td>Ca 47</td> <td>Sc 47</td> </tr> <tr> <td>Ti 44</td> <td>Sc 44</td> </tr> <tr> <td>Fe 52</td> <td>Mn 52m</td> </tr> <tr> <td>Fe 60</td> <td>Co 60m</td> </tr> <tr> <td>Zn 69m</td> <td>Zn 69</td> </tr> <tr> <td>Ge 68</td> <td>Ga 68</td> </tr> <tr> <td>Rb 83</td> <td>Kr 83m</td> </tr> <tr> <td>Sr 82</td> <td>Rb 82</td> </tr> <tr> <td>Sr 90</td> <td>Y 90</td> </tr> <tr> <td>Sr 91</td> <td>Y 91m</td> </tr> <tr> <td>Sr 92</td> <td>Y 92</td> </tr> <tr> <td>Y 87</td> <td>Sr 87m</td> </tr> <tr> <td>Zr 95</td> <td>Nb 95m</td> </tr> <tr> <td>Zr 97</td> <td>Nb 97m, Nb 97</td> </tr> <tr> <td>Mo 99</td> <td>Tc 99m</td> </tr> <tr> <td>Tc 95m</td> <td>Tc 95</td> </tr> <tr> <td>Tc 96m</td> <td>Tc 96</td> </tr> <tr> <td>Ru 103</td> <td>Rh 103m</td> </tr> <tr> <td>Ru 106</td> <td>Rh 106</td> </tr> <tr> <td>Pd 103</td> <td>Rh 103m</td> </tr> <tr> <td>Ag 108m</td> <td>Ag 108</td> </tr> <tr> <td>Ag 110m</td> <td>Ag 110</td> </tr> <tr> <td>Cd 115</td> <td>In 115m</td> </tr> <tr> <td>In 114m</td> <td>In 114</td> </tr> <tr> <td>Sn 113</td> <td>In 113m</td> </tr> <tr> <td>Sn 121m</td> <td>Sn 121</td> </tr> <tr> <td>Sn 126</td> <td>Sb 126m</td> </tr> <tr> <td>Te 118</td> <td>Sb 118</td> </tr> <tr> <td>Te 127m</td> <td>Te 127</td> </tr> <tr> <td>Te 129m</td> <td>Te 129</td> </tr> <tr> <td>Te 131m</td> <td>Te 131</td> </tr> <tr> <td>Te 132</td> <td>I 132</td> </tr> <tr> <td>I 135</td> <td>Xe 135m</td> </tr> <tr> <td>Xe 122</td> <td>I 122</td> </tr> </table>	Mg 28	Al 28	Ar 42	K 42	Ca 47	Sc 47	Ti 44	Sc 44	Fe 52	Mn 52m	Fe 60	Co 60m	Zn 69m	Zn 69	Ge 68	Ga 68	Rb 83	Kr 83m	Sr 82	Rb 82	Sr 90	Y 90	Sr 91	Y 91m	Sr 92	Y 92	Y 87	Sr 87m	Zr 95	Nb 95m	Zr 97	Nb 97m, Nb 97	Mo 99	Tc 99m	Tc 95m	Tc 95	Tc 96m	Tc 96	Ru 103	Rh 103m	Ru 106	Rh 106	Pd 103	Rh 103m	Ag 108m	Ag 108	Ag 110m	Ag 110	Cd 115	In 115m	In 114m	In 114	Sn 113	In 113m	Sn 121m	Sn 121	Sn 126	Sb 126m	Te 118	Sb 118	Te 127m	Te 127	Te 129m	Te 129	Te 131m	Te 131	Te 132	I 132	I 135	Xe 135m	Xe 122	I 122
Mg 28	Al 28																																																																										
Ar 42	K 42																																																																										
Ca 47	Sc 47																																																																										
Ti 44	Sc 44																																																																										
Fe 52	Mn 52m																																																																										
Fe 60	Co 60m																																																																										
Zn 69m	Zn 69																																																																										
Ge 68	Ga 68																																																																										
Rb 83	Kr 83m																																																																										
Sr 82	Rb 82																																																																										
Sr 90	Y 90																																																																										
Sr 91	Y 91m																																																																										
Sr 92	Y 92																																																																										
Y 87	Sr 87m																																																																										
Zr 95	Nb 95m																																																																										
Zr 97	Nb 97m, Nb 97																																																																										
Mo 99	Tc 99m																																																																										
Tc 95m	Tc 95																																																																										
Tc 96m	Tc 96																																																																										
Ru 103	Rh 103m																																																																										
Ru 106	Rh 106																																																																										
Pd 103	Rh 103m																																																																										
Ag 108m	Ag 108																																																																										
Ag 110m	Ag 110																																																																										
Cd 115	In 115m																																																																										
In 114m	In 114																																																																										
Sn 113	In 113m																																																																										
Sn 121m	Sn 121																																																																										
Sn 126	Sb 126m																																																																										
Te 118	Sb 118																																																																										
Te 127m	Te 127																																																																										
Te 129m	Te 129																																																																										
Te 131m	Te 131																																																																										
Te 132	I 132																																																																										
I 135	Xe 135m																																																																										
Xe 122	I 122																																																																										

Change	Para	Existing text in TS-R-1 (2003)	Text as approved by TRANSSC IX
			<p> <b>Cs 137</b>      <b>Ba 137m</b>  <b>Ba 131</b>      <b>Cs 131</b>  <b>Ba 140</b>      <b>La 140</b>  <b>Ce 144</b>      <b>Pr 144m, Pr 144</b>  <b>Pm 148m</b>      <b>Pm 148</b>  <b>Gd 146</b>      <b>Eu 146</b>  <b>Dy 166</b>      <b>Ho 166</b>  <b>Hf 172</b>      <b>Lu 172</b>  <b>W 178</b>      <b>Ta 178</b>  <b>W 188</b>      <b>Re 188</b>  <b>Re 189</b>      <b>Os 189m</b>  <b>Os 194</b>      <b>Ir 194</b>  <b>Ir 189</b>      <b>Os 189m</b>  <b>Pt 188</b>      <b>Ir 188</b>  <b>Hg 194</b>      <b>Au 194</b>  <b>Hg 195m</b>      <b>Hg 195</b>  <b>Pb 210</b>      <b>Bi 210</b>  <b>Pb 212</b>      <b>Bi 212, Tl 208, Po 212</b>  <b>Bi 210m</b>      <b>Tl 206</b>  <b>Bi 212</b>      <b>Tl 208, Po 212</b>  <b>At 211</b>      <b>Po 211</b>  <b>Rn 222</b>      <b>Po 218, Pb 214, At 218, Bi 214, Po 214</b>  <b>Ra 223</b>      <b>Rn 219, Po 215, Pb 211, Bi 211, Po 211, Tl 207</b>  <b>Ra 224</b>      <b>Rn 220, Po 216, Pb 212, Bi 212, Tl 208, Po 212</b>  <b>Ra 225</b>      <b>Ac 225, Fr 221, At 217, Bi 213, Tl 209, Po 213, Pb 209</b>  <b>Ra 226</b>      <b>Rn 222, Po 218, Pb 214, At 218, Bi 214, Po 214</b>  <b>Ra 228</b>      <b>Ac 228</b>  <b>Ac 225</b>      <b>Fr 221, At 217, Bi 213, Tl 209, Po 213, Pb 209</b>  <b>Ac 227</b>      <b>Fr 223</b>  <b>Th 228</b>      <b>Ra 224, Rn 220, Po 216, Pb 212, Bi 212, Tl 208, Po 212</b>  <b>Th 234</b>      <b>Pa 234m, Pa 234</b>  <b>Pa 230</b>      <b>Ac 226, Th 226, Fr 222, Ra 222, Rn 218, Po 214</b>  <b>U 230</b>      <b>Th 226, Ra 222, Rn 218, Po 214</b>  <b>U 235</b>      <b>Th 231</b>  <b>Pu 241</b>      <b>U 237</b>  <b>Pu 244</b>      <b>U 240, Np 240m</b>  <b>Am 242m</b>      <b>Am 242, Np 238</b>  <b>Am 243</b>      <b>Np 239</b>  <b>Cm 247</b>      <b>Pu 243</b>  <b>Bk 249</b>      <b>Am 245</b>  <b>Cf 253</b>      <b>Cm 249</b> </p>

Change	Para	Existing text in TS-R-1 (2003)	Text as approved by TRANSSC IX
13	Table I footnote (b)	<p>(b) Parent nuclides and their progeny included in secular equilibrium are listed in the following:</p> <p>Sr-90 Y-90 Zr-93 Nb-93m Zr-97 Nb-97 Ru-106 Rh-106 Cs-137 Ba-137m <b>Ce-134 La-134</b> Ce-144 Pr-144 Ba-140 La-140 Bi-212 Tl-208 (0.36), Po-212 (0.64) Pb-210 Bi-210, Po-210 Pb-212 Bi-212, Tl-208 (0.36), Po-212 (0.64) <b>Rn-220 Po-216</b> Rn-222 Po-218, Pb-214, Bi-214, Po-214 Ra-223 Rn-219, Po-215, Pb-211, Bi-211, Tl-207 Ra-224 Rn-220, Po-216, Pb-212, Bi-212, Tl-208 (0.36), Po-212 (0.64) Ra-226 Rn-222, Po-218, Pb-214, Bi-214, Po-214, Pb-210, Bi-210, Po-210 Ra-228 Ac-228 <b>Th-226 Ra-222, Rn-218, Po-214</b> Th-228 Ra-224, Rn-220, Po-216, Pb-212, Bi-212, Tl-208 (0.36), Po-212 (0.64) Th-229 Ra-225, Ac-225, Fr-221, At-217, Bi-213, Po-213, Pb-209 Th-nat Ra-228, Ac-228, Th-228, Ra-224, Rn-220, Po-216, Pb-212, Bi-212, Tl-208 (0.36), Po-212 (0.64) Th-234 Pa-234m U-230 Th-226, Ra-222, Rn-218, Po-214 U-232 Th-228, Ra-224, Rn-220, Po-216, Pb-212, Bi-212, Tl-208 (0.36), Po-212 (0.64) U-235 Th-231 U-238 Th-234, Pa-234m U-nat Th-234, Pa-234m, U-234, Th-230, Ra-226, Rn-222, Po-218, Pb-214, Bi-214, Po-214, Pb-210, Bi-210, Po-210</p>	<p>(b) Parent nuclides and their progeny included in secular equilibrium are listed in the following:</p> <p>Sr-90 Y-90 Zr-93 Nb-93m Zr-97 Nb-97 Ru-106 Rh-106 <b>Ag-108m Ag-108</b> Cs-137 Ba-137m Ce-144 Pr-144 Ba-140 La-140 Bi-212 Tl-208 (0.36), Po-212 (0.64) Pb-210 Bi-210, Po-210 Pb-212 Bi-212, Tl-208 (0.36), Po-212 (0.64) Rn-222 Po-218, Pb-214, Bi-214, Po-214 Ra-223 Rn-219, Po-215, Pb-211, Bi-211, Tl-207 Ra-224 Rn-220, Po-216, Pb-212, Bi-212, Tl-208 (0.36), Po-212 (0.64) Ra-226 Rn-222, Po-218, Pb-214, Bi-214, Po-214, Pb-210, Bi-210, Po-210 Ra-228 Ac-228 Th-228 Ra-224, Rn-220, Po-216, Pb-212, Bi-212, Tl-208 (0.36), Po-212 (0.64) Th-229 Ra-225, Ac-225, Fr-221, At-217, Bi-213, Po-213, Pb-209 Th-nat Ra-228, Ac-228, Th-228, Ra-224, Rn-220, Po-216, Pb-212, Bi-212, Tl-208 (0.36), Po-212 (0.64) Th-234 Pa-234m U-230 Th-226, Ra-222, Rn-218, Po-214 U-232 Th-228, Ra-224, Rn-220, Po-216, Pb-212, Bi-212, Tl-208 (0.36), Po-212 (0.64) U-235 Th-231 U-238 Th-234, Pa-234m U-nat Th-234, Pa-234m, U-234, Th-230, Ra-226, Rn-222, Po-218, Pb-214, Bi-214, Po-214, Pb-210, Bi-210, Po-210 Np-237 Pa-233 Am-242m Am-242 Am-243 Np-239</p>

Change	Para	Existing text in TS-R-1 (2003)	Text as approved by TRANSSC IX
		<p><b>U-240</b>    <b>Np-240m</b>  Np-237    Pa-233  Am-242m   Am-242  Am-243    Np-239</p>	
14	402	<p>402. For individual radionuclides which are not listed in Table I the determination of the basic radionuclide values referred to in para. 401 shall require <b>competent authority approval or, for international transport, multilateral approval. Where the chemical form of each radionuclide is known,</b> it is permissible to use the <math>A_2</math> value related to its solubility class as recommended by the International Commission on Radiological Protection, if the chemical forms under both normal and accident conditions of transport are taken into consideration. Alternatively, the radionuclide values in Table II may be used without obtaining <i>competent authority</i> approval.</p>	<p>402. For individual radionuclides which are not listed in Table I the determination of the basic radionuclide values referred to in para. 401 shall require <i>multilateral approval</i>. It is permissible to use <b>an <math>A_2</math> value calculated using a dose coefficient for the appropriate lung absorption type</b>, as recommended by the International Commission on Radiological Protection, if the chemical forms <b>of each radionuclide</b> under both normal and accident conditions of transport are taken into consideration. Alternatively, the radionuclide values in Table II may be used without obtaining <i>competent authority</i> approval.</p>
15	TABLE II	<p>TABLE II (first column)</p> <p><i>Radioactive contents</i></p> <p>Only beta or gamma emitting nuclides are known to be present</p> <p><b>Only</b> alpha emitting nuclides are known to be present</p> <p>No relevant data are available</p>	<p>TABLE II (first column)</p> <p><i>Radioactive contents</i></p> <p>Only beta or gamma emitting nuclides are known to be present.</p> <p>Alpha emitting nuclides, <b>but no neutron emitters</b> are known to be present</p> <p><b>Neutron emitting nuclides are known to be present or</b> no relevant data are available</p>
17	419	<p>419. The mass of uranium hexafluoride in a <i>package</i> shall not exceed a value that would lead to an ullage smaller than 5% at the maximum temperature of the <i>package</i> as specified for the plant systems where the <i>package</i> shall be used. The uranium hexafluoride shall be in solid form and the internal pressure of the <i>package</i> shall be below atmospheric pressure when presented for transport.</p>	<p><b>419. Packages containing uranium hexafluoride shall not contain: _</b></p> <p><b>(a) a mass of uranium hexafluoride different from that authorized for the package design,</b></p> <p><b>(b) a mass of uranium hexafluoride greater than a value that would lead to an ullage smaller than 5% at the maximum temperature of the package as specified for the plant systems where the package shall be used, or</b></p> <p><b>(c) uranium hexafluoride other than in solid form or at an internal pressure above atmospheric pressure when presented for transport.</b></p>

Change	Para	Existing text in TS-R-1 (2003)	Text as approved by TRANSSC IX
18	502	<p>502. Before each <i>shipment</i> of any <i>package</i>, the following requirements shall be fulfilled:</p> <p>(a) For any <i>package</i> it shall be ensured that all the requirements specified in the relevant provisions of these Regulations have been satisfied.</p> <p>(b) It shall be ensured that lifting attachments which do not meet the requirements of para. 607 have been removed or otherwise rendered incapable of being used for lifting the <i>package</i>, in accordance with para. 608.</p> <p>(c) For each <i>Type B(U)</i>, <i>Type B(M)</i> and <i>Type C package</i> and for each <i>package</i> containing <i>fissile material</i>, it shall be ensured that all the requirements specified in the approval certificates have been satisfied.</p> <p>(d) Each <i>Type B(U)</i>, <i>Type B(M)</i> and <i>Type C package</i> shall be held until equilibrium conditions have been approached closely enough to demonstrate compliance with the requirements for temperature and pressure unless an exemption from these requirements has received <i>unilateral approval</i>.</p> <p>(e) For each <i>Type B(U)</i>, <i>Type B(M)</i> and <i>Type C package</i>, it shall be ensured by inspection and/or appropriate tests that all closures, valve and other openings of the <i>containment system</i> through which the <i>radioactive contents</i> might escape are properly closed and, where appropriate, sealed in the manner for which the demonstrations of compliance with the requirements of paras 656 and 669 were made.</p> <p>(f) For each <i>special form radioactive material</i>, it shall be ensured that all the requirements specified in the approval certificate and the relevant provisions of these Regulations have been satisfied.</p> <p>(g) For <i>packages</i> containing <i>fissile material</i> the measurement specified in para. 674(b) and the tests to demonstrate closure of each <i>package</i> as specified in para. 677 shall be performed where applicable.</p> <p>(h) For each <i>low dispersible radioactive material</i>, it shall be ensured that all the requirements specified in the approval certificate and the relevant provisions of these Regulations have been satisfied.</p>	<p>502. Before each <i>shipment</i> of any <i>package</i>, the following requirements shall be fulfilled:</p> <p>(a) For any <i>package</i> it shall be ensured that all the requirements specified in the relevant provisions of these Regulations have been satisfied.</p> <p>(b) It shall be ensured that lifting attachments which do not meet the requirements of para. 607 have been removed or otherwise rendered incapable of being used for lifting the <i>package</i>, in accordance with para. 608.</p> <p>(c) <b>For each package requiring competent authority approval</b>, it shall be ensured that all the requirements specified in the approval certificates have been satisfied.</p> <p>(d) Each <i>Type B(U)</i>, <i>Type B(M)</i> and <i>Type C package</i> shall be held until equilibrium conditions have been approached closely enough to demonstrate compliance with the requirements for temperature and pressure unless an exemption from these requirements has received <i>unilateral approval</i>.</p> <p>(e) For each <i>Type B(U)</i>, <i>Type B(M)</i> and <i>Type C package</i>, it shall be ensured by inspection and/or appropriate tests that all closures, valve and other openings of the <i>containment system</i> through which the <i>radioactive contents</i> might escape are properly closed and, where appropriate, sealed in the manner for which the demonstrations of compliance with the requirements of paras 656 and 669 were made.</p> <p>(f) For each <i>special form radioactive material</i>, it shall be ensured that all the requirements specified in the approval certificate and the relevant provisions of these Regulations have been satisfied.</p> <p>(g) For <i>packages</i> containing <i>fissile material</i> the measurement specified in para. 674(b) and the tests to demonstrate closure of each <i>package</i> as specified in para. 677 shall be performed where applicable.</p> <p>(h) For each <i>low dispersible radioactive material</i>, it shall be ensured that all the requirements specified in the approval certificate and the relevant provisions of these Regulations have been satisfied.</p>

Change	Para	Existing text in TS-R-1 (2003)	Text as approved by TRANSSC IX
19	503	503. A <i>package</i> shall not contain any other items except such articles and documents as are necessary for the use of the <i>radioactive material</i> . This requirement shall not preclude the transport of <i>low specific activity material</i> or <i>surface contaminated objects</i> with other items. The transport of such articles and documents in a <i>package</i> , or of <i>low specific activity material</i> or <i>surface contaminated objects</i> with other items may be permitted provided that there is no interaction between them and the <i>packaging</i> or its <i>radioactive contents</i> that would reduce the safety of the <i>package</i> .	503. A <b>package shall not contain any items other than those that are necessary for the use of the radioactive material. The interaction between these items and the package, under the conditions of transport applicable to the design, shall not reduce the safety of the package.</b>
20	Table VIII footnote “c”	Table VIII footnote “c”  <sup>c</sup> UN 2977 and UN 2978 are special cases without a unique relationship with the Schedules.	Table VIII footnote “c”  <sup>c</sup> <b>In the case of non-fissile or fissile excepted uranium hexafluoride, the UN 2978 and the proper shipping name and description, “RADIOACTIVE MATERIAL, URANIUM HEXAFLUORIDE, non-fissile or fissile excepted,” takes precedence over other UN numbers applicable to non-fissile and fissile excepted. In the case of uranium hexafluoride that is fissile material the UN 2977 and the proper shipping name, “RADIOACTIVE MATERIAL, URANIUM HEXAFLUORIDE, FISSILE,” takes precedence over other UN numbers applicable to fissile material.</b>
22	537	537. Each <i>package</i> which conforms to:  (a) an <i>IP-1</i> , an <i>IP-2</i> or an <i>IP-3 design</i> shall be legibly and durably marked on the outside of the <i>packaging</i> with “TYPE IP-1”, “TYPE IP-2” or “TYPE IP-3” as appropriate; (b) a <i>Type A package design</i> shall be legibly and durably marked on the outside of the <i>packaging</i> with “TYPE A”; (c) an <i>IP-2</i> , an <i>IP-3</i> or a <i>Type A package design</i> shall be legibly and durably marked on the outside of the <i>packaging</i> with the international <i>vehicle</i> registration code (VRI Code) of the country of origin of <i>design</i> and the name of the manufacturers, or other identification of the <i>packaging</i> specified by the <i>competent authority</i> .	537. Each <i>package</i> which conforms to:  (a) an <i>IP-1</i> , an <i>IP-2</i> or an <i>IP-3 design</i> shall be legibly and durably marked on the outside of the <i>packaging</i> with “TYPE IP-1”, “TYPE IP-2” or “TYPE IP-3” as appropriate; (b) a <i>Type A package design</i> shall be legibly and durably marked on the outside of the <i>packaging</i> with “TYPE A”; (c) an <i>IP-2</i> , an <i>IP-3</i> or a <i>Type A package design</i> shall be legibly and durably marked on the outside of the <i>packaging</i> with the international <i>vehicle</i> registration code (VRI Code) of the country of origin of <i>design</i> and <b>either</b> the name of the <b>manufacturer</b> or other identification of the <i>packaging</i> specified by the <i>competent authority of the country of origin of design</i> .
23	566	566. Loading of <i>freight containers</i> and accumulation of <i>packages</i> , <i>overpacks</i> and <i>freight containers</i> shall be controlled as follows:	566. Loading of <i>freight containers</i> and accumulation of <i>packages</i> , <i>overpacks</i> and <i>freight containers</i> shall be controlled as follows:

Change	Para	Existing text in TS-R-1 (2003)	Text as approved by TRANSSC IX
		<p>(a) Except under the condition of <i>exclusive use</i>, the total number of <i>packages, overpacks</i> and <i>freight containers</i> aboard a single <i>conveyance</i> shall be so limited that the total sum of the <i>transport indexes</i> aboard the <i>conveyance</i> does not exceed the values shown in Table IX. <b>For consignments of LSA-I material there shall be no limit on the sum of the transport indexes.</b></p> <p>(b) <b>Where a consignment is transported under exclusive use, there shall be no limit on the sum of the transport indexes aboard a single conveyance.</b></p> <p>(c) The <i>radiation level</i> under routine conditions of transport shall not exceed 2 mSv/h at any point on, and 0.1 mSv/h at 2 m from, the external surface of the <i>conveyance</i>, except for <i>consignments</i> transported under <i>exclusive use</i> by road or rail, for which the radiation limits around the <i>vehicle</i> are set forth in para 572(b) and (c).</p> <p>(d) The total sum of the <i>criticality safety indexes</i> in a <i>freight container</i> and aboard a <i>conveyance</i> shall not exceed the values shown in Table X.</p>	<p>(a) Except under the condition of <i>exclusive use</i>, <b>and for consignments of LSA-I material</b>, the total number of <i>packages, overpacks</i> and <i>freight containers</i> aboard a single <i>conveyance</i> shall be so limited that the total sum of the <i>transport indexes</i> aboard the <i>conveyance</i> does not exceed the values shown in Table IX.</p> <p>(b) The <i>radiation level</i> under routine conditions of transport shall not exceed 2 mSv/h at any point on, and 0.1 mSv/h at 2 m from, the external surface of the <i>conveyance</i>, except for <i>consignments</i> transported under <i>exclusive use</i> by road or rail, for which the radiation limits around the <i>vehicle</i> are set forth in para 572(b) and (c).</p> <p>(c) The total sum of the <i>criticality safety indexes</i> in a <i>freight container</i> and aboard a <i>conveyance</i> shall not exceed the values shown in Table X.</p> <p><b>(NOTE: Para. 566 to be renumbered as 567))</b></p>
24	622 and consequential changes in 624, 625, 627, 628 and 646b and other consequential changes	<p>622. A <i>package</i>, to be qualified as a <i>Type IP-2</i>, shall be designed to meet the requirements for <i>Type IP-1</i> as specified in para. 621 and, in addition, if it were subjected to the tests specified in paras 722 and 723, it would prevent:</p> <p>(a) loss or dispersal of the <i>radioactive contents</i>; and</p> <p>(b) <b>loss of shielding integrity which would result in</b> more than a 20% increase in the <i>radiation level</i> at any external surface of the <i>package</i>.</p>	<p>622. A <i>package</i>, to be qualified as a <i>Type IP-2</i>, shall be designed to meet the requirements for <i>Type IP-1</i> as specified in para. 621 and, in addition, if it were subjected to the tests specified in paras 722 and 723, it would prevent:</p> <p>(a) loss or dispersal of the <i>radioactive contents</i>; and</p> <p>(b) more than a 20% increase in the <b>maximum radiation level</b> at any external surface of the <i>package</i>.</p>
26	652 and 662 and consequential changes	<p>652. <b>Except as required in para. 617 for a package transported by air</b>, a <i>package</i> shall be so designed that, under the ambient condition specified in para. 653, the temperature of the accessible surfaces of a <i>package</i> shall not exceed 50°C, unless the <i>package</i> is transported under <i>exclusive use</i>.</p>	<p>652. A <i>package</i> shall be so designed that, under the ambient condition specified in para. 653 <b>and in the absence of insolation</b>, the temperature of the accessible surfaces of a <i>package</i> shall not exceed 50 °C, unless the <i>package</i> is transported under <i>exclusive use</i>.</p> <p>652 bis. Except as required in para. 617 for a <i>package</i> transported by air, the maximum temperature of any surface readily accessible during transport of a <i>package</i> <b>under exclusive use</b> shall not exceed 85°C in the absence of insolation under the ambient conditions specified in para. 653. Account may be taken of barriers or screens intended to give protection to persons without</p>

Change	Para	Existing text in TS-R-1 (2003)	Text as approved by TRANSSC IX
		<p>662. Except as required in para. 617 for a <i>package</i> transported by air, the maximum temperature of any surface readily accessible during transport of a <i>package</i> shall not exceed 85°C in the absence of insolation under the ambient conditions specified in para. 653. <b>The package shall be carried under exclusive use, as specified in para. 652, if this maximum temperature exceeds 50°C.</b> Account may be taken of barriers or screens intended to give protection to persons without the need for the barriers or screens being subject to any test.</p>	<p>the need for the barriers or screens being subject to any test.</p> <p style="text-align: center;"><b>(PARA. 652 BIS TO BE NUMBERED AS 653)</b></p> <p>662 : deleted and replaced with 652bis as above</p>
27	<p>418 and 672</p> <p>NOTE. In original proposal: Current para 672, as modified, becomes new para 417bis</p>	<p>418. <i>Packages</i> containing <i>fissile material</i> shall not contain:</p> <p>(a) a mass of <i>fissile material</i> different from that authorized for the <i>package design</i>,</p> <p>(b) any radionuclide or <i>fissile material</i> different from those authorized for the <i>package design</i>, or</p> <p>(c) contents in a form or physical or chemical state, or in a spatial arrangement, different from those authorized for the <i>package design</i>,</p> <p>as specified in their certificates of approval where appropriate.</p>	<p>418. <b>Unless excepted by para. 672</b> <i>packages</i> containing <i>fissile material</i> shall not contain:</p> <p>(a) a mass of <i>fissile material</i> different from that authorized for the <i>package design</i>,</p> <p>(b) any radionuclide or <i>fissile material</i> different from those authorized for the <i>package design</i>, or</p> <p>(c) contents in a form or physical or chemical state, or in a spatial arrangement, different from those authorized for the <i>package design</i>,</p> <p>as specified in their certificates of approval where appropriate.</p> <p style="text-align: center;"><b>672. no change</b></p>
31	672	<p>672</p> <p>.....</p> <p>(a).....</p> <p>.....(iii) there is not more than 5 g of <i>fissile material</i> in any 10 litre volume of material.</p> <p>Neither beryllium nor deuterium <b>in hydrogenous material enriched in deuterium</b> shall be present in quantities exceeding 1% of the applicable consignment mass limits provided in Table XII.</p> <p>(b)Uranium enriched.....</p>	<p>672</p> <p>.....</p> <p>(a).....</p> <p>.....(iii) there is not more than 5 g of <i>fissile material</i> in any 10 litre volume of material.</p> <p>Neither beryllium nor deuterium shall be present in quantities exceeding 1% of the applicable consignment mass limits provided in Table XII, <b>except for deuterium in natural concentration in hydrogen..</b></p> <p>(b)Uranium enriched.....</p>

Change	Para	Existing text in TS-R-1 (2003)	Text as approved by TRANSSC IX
32	672	<p>672. <i>Fissile material</i> meeting one of the provisions (a)–(d) of this paragraph is excepted from the requirement to be transported in <i>packages</i> that comply with paras 673–682 as well as the other requirements of these Regulations that apply to <i>fissile material</i>. Only one type of exception is allowed per <i>consignment</i>.</p> <p>(a) A mass limit per <i>consignment</i> such that:</p> $\frac{\text{mass of uranium-235 (g)} + \text{mass of other fissile material (g)}}{X} \leq \frac{1}{Y}$ <p>where X and Y are the mass limits defined in Table XII, provided that either:</p> <p>(i) each individual <i>package</i> contains not more than 15 g of <i>fissile material</i>; for unpackaged material, this quantity limitation shall apply to the <i>consignment</i> being carried in or on the <i>conveyance</i>, or  .....  .....or any combination of those radionuclides.</p>	<p>672. <i>Fissile material</i> meeting one of the provisions (a)–(d) of this paragraph is excepted from the requirement to be transported in <i>packages</i> that comply with paras 673–682 as well as the other requirements of these Regulations that apply to <i>fissile material</i>. Only one type of exception is allowed per <i>consignment</i>.</p> <p>(a) A mass limit per <i>consignment</i> such that:</p> $\frac{\text{mass of uranium-235 (g)} + \text{mass of other fissile material (g)}}{X} \leq \frac{1}{Y}$ <p>where X and Y are the mass limits defined in Table XII, provided <b>that the smallest external dimension of each package is not less than 10 cm and</b> that either:</p> <p>(i) each individual <i>package</i> contains not more than 15 g of <i>fissile material</i>; for unpackaged material, this quantity limitation shall apply to the <i>consignment</i> being carried in or on the <i>conveyance</i>, or  .....  .....or any combination of those radionuclides.</p>
38	677	<p>677. For a <i>package</i> in isolation, it shall be assumed that water can leak into or out of all void spaces of the <i>package</i>, including those within the <i>containment system</i>. However, if the <i>design</i> incorporates special features to prevent such leakage of water into or out of certain void spaces, even as a result of error, absence of leakage may be assumed in respect of those void spaces. Special features shall include the following:</p> <p>(a) Multiple high standard water barriers, each of which would remain watertight if the <i>package</i> were subject to the tests prescribed in para. 682(b), a high degree of quality control in the manufacture, maintenance and repair of <i>packagings</i> and tests to demonstrate the closure of each <i>package</i> before each <i>shipment</i>; or</p> <p>(b) For <i>packages</i> containing uranium hexafluoride only:</p> <p>(i) <i>packages</i> where, following the tests prescribed in para. 682(b), there is no physical contact between the valve and any other component of the <i>packaging</i> other than at its original point of attachment and where, in addition, following the test prescribed in para. 728 the valves</p>	<p>677. For a <i>package</i> in isolation, it shall be assumed that water can leak into or out of all void spaces of the <i>package</i>, including those within the <i>containment system</i>. However, if the <i>design</i> incorporates special features to prevent such leakage of water into or out of certain void spaces, even as a result of error, absence of leakage may be assumed in respect of those void spaces. Special features shall include the following:</p> <p>(a) Multiple high standard water barriers, each of which would remain watertight if the <i>package</i> were subject to the tests prescribed in para. 682(b), a high degree of quality control in the manufacture, maintenance and repair of <i>packagings</i> and tests to demonstrate the closure of each <i>package</i> before each <i>shipment</i>; or</p> <p>(b) For <i>packages</i> containing uranium hexafluoride <b>only, with maximum uranium enrichment of 5 mass percent uranium-235:</b></p> <p>(i) <i>packages</i> where, following the tests prescribed in para. 682(b), there is no physical contact between the valve and any other component of the <i>packaging</i> other than at its original point of attachment and where, in addition, following the test prescribed in para. 728 the</p>

Change	Para	Existing text in TS-R-1 (2003)	Text as approved by TRANSSC IX
		<p>remain leaktight; and</p> <p>(ii) a high degree of quality control in the manufacture, maintenance and repair of <i>packagings</i> coupled with tests to demonstrate closure of each <i>package</i> before each <i>shipment</i>.</p>	<p>valves remain leaktight; and</p> <p>(ii) a high degree of quality control in the manufacture, maintenance and repair of <i>packagings</i> coupled with tests to demonstrate closure of each <i>package</i> before each <i>shipment</i>.</p>
39	709	<p>709. Specimens that comprise or simulate <i>radioactive material</i> enclosed in a sealed capsule may be excepted from:</p> <p>(a) The tests prescribed in paras 705 and 706 provided the mass of the <i>special form radioactive material</i> is less than 200 g and they are alternatively subjected to the Class 4 impact test prescribed in the International Organization for Standardization document ISO 2919: “Sealed Radioactive Sources —Classification” [11], and</p> <p>(b) The test prescribed in para. 708 provided they are alternatively subjected to the Class 6 temperature test specified in the International Organization for Standardization document ISO 2919: “Sealed Radioactive Sources —Classification” [11].</p>	<p>709. Specimens that comprise or simulate <i>radioactive material</i> enclosed in a sealed capsule may be excepted from:</p> <p>(a) The tests prescribed in paras 705 and 706 provided the mass of the <i>special form radioactive material</i></p> <p>i) <i>is less than 200 g and they are alternatively subjected to the Class 4 impact test prescribed in the International Organization for Standardization document ISO 2919: “Sealed Radioactive Sources – Classification” [11], or</i></p> <p>ii) <i>is less than 500 g and they are alternatively subjected to the Class 5 impact test prescribed in the International Organization for Standardization document ISO 2919: “Sealed Radioactive Sources – Classification” [11], and</i></p> <p>(b) The test prescribed in para. 708 provided they are alternatively subjected to the Class 6 temperature test specified in the International Organization for Standardization document ISO 2919: “Sealed Radioactive Sources —Classification” [11].</p>
42	805	<p>805. The approval of <i>designs</i> for <i>packages</i> containing 0.1 kg or more of uranium hexafluoride requires that:</p> <p>(a) <b>After 31 December 2000</b>, each <i>design</i> that meets the requirements of para. 632 shall require <i>multilateral approval</i>. <b>After 31 December 2003</b>, each <i>design</i> that meets the requirements of paras 629–631 shall require <i>unilateral approval</i> by the <i>competent authority</i> of the country of origin of the <i>design</i>;</p> <p>(b) The application for approval shall include all information necessary to satisfy the <i>competent authority</i> that the <i>design</i> meets the requirements of para. 629, and a specification of the applicable <i>quality assurance</i> programme as required in para. 310;</p>	<p>805. The approval of <i>designs</i> for <i>packages</i> containing 0.1 kg or more of uranium hexafluoride requires that:</p> <p>(a) <b><i>Each design that meets the requirements of para. 632 shall require multilateral approval.</i></b></p> <p>(a bis) <b><i>Each design that meets the requirement of paras 629-631 shall require unilateral approval by the competent authority of the country of origin of the design, unless multilateral approval is otherwise required by these regulations.</i></b></p> <p>(b) The application for approval shall include all information necessary to satisfy the <i>competent authority</i> that the <i>design</i> meets the requirements of para. 629, and a specification of the applicable <i>quality assurance</i> programme as required in para. 310;</p> <p><b>(NOTE. Reference to para 310 to be changed as reference to para 306)</b></p>

Change	Para	Existing text in TS-R-1 (2003)	Text as approved by TRANSSC IX
		(c) The <i>competent authority</i> shall establish an approval certificate stating that the approved <i>design</i> meets the requirements of para. 629 and shall attribute to that <i>design</i> an identification mark.	(c) The <i>competent authority</i> shall establish an approval certificate stating that the approved <i>design</i> meets the requirements of para. 629 and shall attribute to that <i>design</i> an identification mark.
49	817	817. <i>Packagings</i> manufactured to a <i>package design</i> approved by the <i>competent authority</i> under the provisions of the 1985 or 1985 (As Amended 1990) Editions of these Regulations may continue to be used <b>until 31 December 2003</b> , subject to: the mandatory programme of <i>quality assurance</i> in accordance with the requirements of para. 310; the activity limits and material restrictions of Section IV; and, for a <i>package</i> containing <i>fissile material</i> and transported by air, the requirement of para. 680. <b>After this date use may continue subject, additionally, to multilateral approval of package design.</b> Changes in the <i>design</i> of the <i>packaging</i> or in the nature or quantity of the authorized <i>radioactive contents</i> which, as determined by the <i>competent authority</i> , would significantly affect safety shall require that this Edition of the Regulations be met in full. All <i>packagings</i> for which manufacture begins after 31 December 2006 shall meet this Edition of the Regulations in full.	817. <i>Packagings</i> manufactured to a <i>package design</i> approved by the <i>competent authority</i> under the provisions of the 1985 or 1985 (As Amended 1990) Editions of these Regulations may continue to be used, subject to: <b>multilateral approval of package design</b> , the mandatory programme of <i>quality assurance</i> in accordance with the requirements of para. 310; the activity limits and material restrictions of Section IV; and, for a <i>package</i> containing <i>fissile material</i> and transported by air, the requirement of para. 680. Changes in the <i>design</i> of the <i>packaging</i> or in the nature or quantity of the authorized <i>radioactive contents</i> which, as determined by the <i>competent authority</i> , would significantly affect safety shall require that this Edition of the Regulations be met in full. All <i>packagings</i> for which manufacture begins after 31 December 2006 shall meet this Edition of the Regulations in full.  <b>(NOTE. Reference to para 310 to be changed as reference to para 306)</b>
52	819	819. The <i>competent authority</i> shall be informed of the serial number of each <i>packaging</i> manufactured to a <i>design</i> approved under paras 806, 809, 812, and 816–817. <b>The <i>competent authority</i> should, consistent with para. 311, maintain a - register of such serial numbers.</b>	819. The <i>competent authority</i> shall be informed of the serial number of each <i>packaging</i> manufactured to a <i>design</i> approved under paras 806, 809, 812, and 816–817
54	820	820. <i>Multilateral approval</i> shall be required for:  (a) the <i>shipment</i> of <i>Type B(M) packages</i> not conforming with the requirements of para. 637 or designed to allow controlled intermittent venting; (b) the <i>shipment</i> of <i>Type B(M) packages</i> containing <i>radioactive material</i> with an activity greater than 3000 $A_1$ or 3000 $A_2$ , as appropriate, or 1000 TBq, whichever is the lower; (c) the <i>shipment</i> of <i>packages</i> containing <i>fissile materials</i> if the sum of the <i>criticality safety indexes</i> of the <i>packages</i> exceeds 50; and	820. <i>Multilateral approval</i> shall be required for:  (a) the <i>shipment</i> of <i>Type B(M) packages</i> not conforming with the requirements of para. 637 or designed to allow controlled intermittent venting; (b) the <i>shipment</i> of <i>Type B(M) packages</i> containing <i>radioactive material</i> with an activity greater than 3000 $A_1$ or 3000 $A_2$ , as appropriate, or 1000 TBq, whichever is the lower; (c) the <i>shipment</i> of <i>packages</i> containing <i>fissile materials</i> if the sum of the <i>criticality safety indexes</i> of the <i>packages</i> <b>in a single freight container or in a single conveyance</b> exceeds 50. <b>Excluded from this requirement shall be shipments by seagoing vessels, if the sum of</b>

Change	Para	Existing text in TS-R-1 (2003)	Text as approved by TRANSSC IX
		(d) <i>radiation protection programmes</i> for shipments by special use vessels according to para. 575(a).	<b>the criticality safety indexes does not exceed 50 for any hold, compartment or defined deck area and the distance of 6m between groups of packages or overpacks as required in table X is met;</b> and (d) <i>radiation protection programmes</i> for shipments by special use vessels - according to para. 575(a).
55	824	824. Each <i>consignment</i> transported <b>internationally</b> under <i>special arrangement</i> shall require <i>multilateral approval</i> .	824. Each <i>consignment</i> transported under <i>special arrangement</i> shall require <i>multilateral approval</i> .
56	833	833. Each approval certificate of the <i>design</i> of a <i>package</i> issued by a <i>competent authority</i> shall include the following information:  (a) Type of certificate. (b) The <i>competent authority</i> identification mark. (c) The issue date and an expiry date. (d) Any restriction on the modes of transport, if appropriate. (e) List of applicable national and international regulations, including the edition of the IAEA Regulations for the Safe Transport of Radioactive Material under which the <i>design</i> is approved. (f) The following statement: “This certificate does not relieve the consignor from compliance with any requirement of the government of any country through or into which the package will be transported.” (g) References to certificates for alternative <i>radioactive contents</i> , other <i>competent authority</i> validation, or additional technical data or information, as deemed appropriate by the <i>competent authority</i> . (h) A statement authorizing <i>shipment</i> where <i>shipment</i> approval is required under para. 820, if deemed appropriate. (i) Identification of the <i>packaging</i> . (j) Description of the <i>packaging</i> by a reference to the drawings or specification of the <i>design</i> . If deemed appropriate by the <i>competent authority</i> , a reproducible illustration, not larger than 21 cm by 30 cm, showing the make-up of the <i>package</i> should also be provided, accompanied by a brief description of the <i>packaging</i> , including materials of manufacture, gross	833. Each approval certificate of the <i>design</i> of a <i>package</i> issued by a <i>competent authority</i> shall include the following information:  (a) Type of certificate. (b) The <i>competent authority</i> identification mark. (c) The issue date and an expiry date. (d) Any restriction on the modes of transport, if appropriate. (e) List of applicable national and international regulations, including the edition of the IAEA Regulations for the Safe Transport of Radioactive Material under which the <i>design</i> is approved. (f) The following statement: “This certificate does not relieve the consignor from compliance with any requirement of the government of any country through or into which the package will be transported.” (g) References to certificates for alternative <i>radioactive contents</i> , other <i>competent authority</i> validation, or additional technical data or information, as deemed appropriate by the <i>competent authority</i> . (h) A statement authorizing <i>shipment</i> where <i>shipment</i> approval is required under para. 820, if deemed appropriate. (i) Identification of the <i>packaging</i> . (j) Description of the <i>packaging</i> by a reference to the drawings or specification of the <i>design</i> . If deemed appropriate by the <i>competent authority</i> , a reproducible illustration, not larger than 21 cm by 30 cm, showing the make-up of the <i>package</i> should also be provided, accompanied by a brief description of the <i>packaging</i> , including materials of manufacture, gross mass, general outside dimensions and

Change	Para	Existing text in TS-R-1 (2003)	Text as approved by TRANSSC IX
		<p>mass, general outside dimensions and appearance.</p> <p>(k) Specification of the <i>design</i> by reference to the drawings.</p> <p>(l) A specification of the authorized <i>radioactive content</i>, including any restrictions on the <i>radioactive contents</i> which might not be obvious from the nature of the <i>packaging</i>. This shall include the physical and chemical forms, the activities involved (including those of the various isotopes, if appropriate), amounts in grams (for <i>fissile material</i>), and whether <i>special form radioactive material</i> or <i>low dispersible radioactive material</i>, if applicable.</p> <p>(m) Additionally, for <i>packages</i> containing <i>fissile material</i>:</p> <p>(i) a detailed description of the authorized <i>radioactive contents</i>;</p> <p>(ii) the value of the <i>criticality safety index</i>;</p> <p>(iii) reference to the documentation that demonstrates the criticality safety of the contents;</p> <p>(iv) any special features, on the basis of which the absence of water from certain void spaces has been assumed in the criticality assessment;</p> <p>(v) any allowance (based on para. 674(b)) for a change in neutron multiplication assumed in the criticality assessment as a result of actual irradiation experience; and</p> <p>(vi) the ambient temperature range for which the <i>package design</i> has been approved.</p> <p>(n) For <i>Type B(M) packages</i>, a statement specifying those prescriptions of paras 637, 653, 654 and 657–664 with which the <i>package</i> does not conform and any amplifying information which may be useful to other <i>competent authorities</i>.</p> <p>(o) A detailed listing of any supplementary operational controls required for preparation, loading, carriage, unloading and handling of the <i>consignment</i>, including any special stowage provisions for the safe dissipation of heat.</p> <p>(p) Reference to information provided by the applicant relating to the use of the <i>packaging</i> or specific actions to be taken prior to <i>shipment</i>.</p> <p>(q) A statement regarding the ambient conditions assumed for purposes of <i>design</i> if these are not in accordance with those specified in paras 653, 654 and 664, as applicable.</p>	<p>appearance.</p> <p>(k) Specification of the <i>design</i> by reference to the drawings.</p> <p>(l) A specification of the authorized <i>radioactive content</i>, including any restrictions on the <i>radioactive contents</i> which might not be obvious from the nature of the <i>packaging</i>. This shall include the physical and chemical forms, the activities involved (including those of the various isotopes, if appropriate), amounts in grams (for <i>fissile material</i>), and whether <i>special form radioactive material</i> or <i>low dispersible radioactive material</i>, if applicable.</p> <p>(m) Additionally, for <i>packages</i> containing <i>fissile material</i>:</p> <p>(i) a detailed description of the authorized <i>radioactive contents</i>;</p> <p>(ii) the value of the <i>criticality safety index</i>;</p> <p>(iii) reference to the documentation that demonstrates the criticality safety of the contents;</p> <p>(iv) any special features, on the basis of which the absence of water from certain void spaces has been assumed in the criticality assessment;</p> <p>(v) any allowance (based on para. 674(b)) for a change in neutron - multiplication assumed in the criticality assessment as a result of actual irradiation experience; and</p> <p>(vi) the ambient temperature range for which the <i>package design</i> has been approved.</p> <p>(n) For <i>Type B(M) packages</i>, a statement specifying those prescriptions of paras 637, 653, 654 and 657–664 with which the <i>package</i> does not conform and any amplifying information which may be useful to other <i>competent authorities</i>.</p> <p><b>(n) (bis) For <i>packages</i> containing more than 0.1 kg of uranium hexafluoride a statement specifying those prescriptions of para 632 that apply, if any, and any amplifying information which may be useful to other <i>competent authorities</i>.</b></p> <p>(o) A detailed listing of any supplementary operational controls required for preparation, loading, carriage, unloading and handling of the <i>consignment</i>, including any special stowage provisions for the safe dissipation of heat.</p> <p>(p) Reference to information provided by the applicant relating to the use of the <i>packaging</i> or specific actions to be taken prior to <i>shipment</i>.</p> <p>(q) A statement regarding the ambient conditions assumed for purposes of <i>design</i> if these are not in accordance with those specified in paras 653, 654 and 664, as applicable.</p>

Change	Para	Existing text in TS-R-1 (2003)	Text as approved by TRANSSEC IX
		<ul style="list-style-type: none"> <li>(r) A specification of the applicable <i>quality assurance</i> programme as required in para. 310.</li> <li>(s) Any emergency arrangements deemed necessary by the <i>competent authority</i>.</li> <li>(t) If deemed appropriate by the <i>competent authority</i>, reference to the identity of the applicant.</li> <li>(u) Signature and identification of the certifying official.</li> </ul>	<ul style="list-style-type: none"> <li>(r) A specification of the applicable <i>quality assurance</i> programme as required in para. 310.</li> <li>(s) Any emergency arrangements deemed necessary by the <i>competent authority</i>.</li> <li>(t) If deemed appropriate by the <i>competent authority</i>, reference to the identity of the applicant.</li> <li>(u) Signature and identification of the certifying official.</li> </ul> <p><b>(NOTE. (n) bis to be changed to (o) and all subsequent sub paras to be changed accordingly)</b></p>
57	833	<p>833. Each approval certificate of the <i>design</i> of a <i>package</i> issued by a <i>competent authority</i> shall include the following information:</p> <ul style="list-style-type: none"> <li>(a) Type of certificate.</li> <li>(b) The <i>competent authority</i> identification mark.</li> <li>(c) The issue date and an expiry date.</li> <li>(d) Any restriction on the modes of transport, if appropriate.</li> <li>(e) List of applicable national and international regulations, including the edition of the IAEA Regulations for the Safe Transport of Radioactive Material under which the <i>design</i> is approved.</li> <li>(f) The following statement: “This certificate does not relieve the consignor from compliance with any requirement of the government of any country through or into which the package will be transported.”</li> <li>(g) References to certificates for alternative <i>radioactive contents</i>, other <i>competent authority</i> validation, or additional technical data or information, as deemed appropriate by the <i>competent authority</i>.</li> <li>(h) A statement authorizing <i>shipment</i> where <i>shipment</i> approval is required under para. 820, if deemed appropriate.</li> <li>(i) Identification of the <i>packaging</i>.</li> <li>(j) Description of the <i>packaging</i> by a reference to the drawings or specification of the <i>design</i>. If deemed appropriate by the <i>competent authority</i>, a reproducible illustration, not larger than 21 cm by 30 cm, showing the make-up of the <i>package</i> should also be provided, accompanied by a brief description of the <i>packaging</i>, including materials of manufacture, gross</li> </ul>	<p>833. Each approval certificate of the <i>design</i> of a <i>package</i> issued by a <i>competent authority</i> shall include the following information:</p> <ul style="list-style-type: none"> <li>(a) Type of certificate.</li> <li>(b) The <i>competent authority</i> identification mark.</li> <li>(c) The issue date and an expiry date.</li> <li>(d) Any restriction on the modes of transport, if appropriate.</li> <li>(e) List of applicable national and international regulations, including the edition of the IAEA Regulations for the Safe Transport of Radioactive Material under which the <i>design</i> is approved.</li> <li>(f) The following statement: “This certificate does not relieve the consignor from compliance with any requirement of the government of any country through or into which the package will be transported.”</li> <li>(g) References to certificates for alternative <i>radioactive contents</i>, other <i>competent authority</i> validation, or additional technical data or information, as deemed appropriate by the <i>competent authority</i>.</li> <li>(h) A statement authorizing <i>shipment</i> where <i>shipment</i> approval is required under para. 820, if deemed appropriate.</li> <li>(i) Identification of the <i>packaging</i>.</li> <li>(j) Description of the <i>packaging</i> by a reference to the drawings or specification of the <i>design</i>. If deemed appropriate by the <i>competent authority</i>, a reproducible illustration, not larger than 21 cm by 30 cm, showing the make-up of the <i>package</i> should also be provided, accompanied by a brief description of the <i>packaging</i>, including materials of manufacture, gross mass, general outside dimensions and</li> </ul>

Change	Para	Existing text in TS-R-1 (2003)	Text as approved by TRANSSEC IX
		<p>mass, general outside dimensions and appearance.</p> <p>(k) Specification of the <i>design</i> by reference to the drawings.</p> <p>(l) A specification of the authorized <i>radioactive content</i>, including any restrictions on the <i>radioactive contents</i> which might not be obvious from the nature of the <i>packaging</i>. This shall include the physical and chemical forms, the activities involved (including those of the various isotopes, if appropriate), amounts in grams (for <i>fissile material</i>), and whether <i>special form radioactive material</i> or <i>low dispersible radioactive material</i>, if applicable.</p> <p>(m) Additionally, for <i>packages</i> containing <i>fissile material</i>:</p> <p>(i) a detailed description of the authorized <i>radioactive contents</i>;</p> <p>(ii) the value of the <i>criticality safety index</i>;</p> <p>(iii) reference to the documentation that demonstrates the criticality safety of the contents;</p> <p>(iv) any special features, on the basis of which the absence of water from certain void spaces has been assumed in the criticality assessment;</p> <p>(v) any allowance (based on para. 674(b)) for a change in neutron multiplication assumed in the criticality assessment as a result of actual irradiation experience; and</p> <p>(vi) the ambient temperature range for which the <i>package design</i> has been approved.</p> <p>(n) For <i>Type B(M) packages</i>, a statement specifying those prescriptions of paras 637, 653, 654 and 657–664 with which the <i>package</i> does not conform and any amplifying information which may be useful to other <i>competent authorities</i>.</p> <p>(o) A detailed listing of any supplementary operational controls required for preparation, loading, carriage, unloading and handling of the <i>consignment</i>, including any special stowage provisions for the safe dissipation of heat.</p> <p>(p) Reference to information provided by the applicant relating to the use of the <i>packaging</i> or specific actions to be taken prior to <i>shipment</i>.</p> <p>(q) A statement regarding the ambient conditions assumed for purposes of <i>design</i> if these are not in accordance with those specified in paras 653, 654 and 664, as applicable.</p>	<p>appearance.</p> <p>(k) Specification of the <i>design</i> by reference to the drawings.</p> <p>(l) A specification of the authorized <i>radioactive content</i>, including any restrictions on the <i>radioactive contents</i> which might not be obvious from the nature of the <i>packaging</i>. This shall include the physical and chemical forms, the activities involved (including those of the various isotopes, if appropriate), amounts in grams (for <i>fissile material</i>), and whether <i>special form radioactive material</i> or <i>low dispersible radioactive material</i>, if applicable.</p> <p><b>(l) (bis) A description of the <i>containment system</i></b></p> <p>(m) Additionally, for <i>packages</i> containing <i>fissile material</i>:</p> <p>(i) a detailed description of the authorized <i>radioactive contents</i>;</p> <p><b>(i bis) A description of the <i>confinement system</i></b></p> <p>(ii) the value of the <i>criticality safety index</i>;</p> <p>(iii) reference to the documentation that demonstrates the criticality safety of the contents;</p> <p>(iv) any special features, on the basis of which the absence of water from certain void spaces has been assumed in the criticality assessment;</p> <p>(v) any allowance (based on para. 674(b)) for a change in neutron - multiplication assumed in the criticality assessment as a result of actual irradiation experience; and</p> <p>(vi) the ambient temperature range for which the <i>package design</i> has been approved.</p> <p>(n) For <i>Type B(M) packages</i>, a statement specifying those prescriptions of paras 637, 653, 654 and 657–664 with which the <i>package</i> does not conform and any amplifying information which may be useful to other <i>competent authorities</i>.</p> <p>(o) A detailed listing of any supplementary operational controls required for preparation, loading, carriage, unloading and handling of the <i>consignment</i>, including any special stowage provisions for the safe dissipation of heat.</p> <p>(p) Reference to information provided by the applicant relating to the use of the <i>packaging</i> or specific actions to be taken prior to <i>shipment</i>.</p> <p>(q) A statement regarding the ambient conditions assumed for purposes of <i>design</i> if these are not in accordance with those specified in paras 653, 654 and 664, as applicable.</p>

Change	Para	Existing text in TS-R-1 (2003)	Text as approved by TRANSSC IX
		<p>(r) A specification of the applicable <i>quality assurance</i> programme as required in para. 310.</p> <p>(s) Any emergency arrangements deemed necessary by the <i>competent authority</i>.</p> <p>(t) If deemed appropriate by the <i>competent authority</i>, reference to the identity of the applicant.</p> <p>(u) Signature and identification of the certifying official.</p>	<p>(r) A specification of the applicable <i>quality assurance</i> programme as required in para. 310.</p> <p>(s) Any emergency arrangements deemed necessary by the <i>competent authority</i>.</p> <p>(t) If deemed appropriate by the <i>competent authority</i>, reference to the identity of the applicant.</p> <p>(u) Signature and identification of the certifying official.</p> <p><b>(NOTE. Subpara (l) (bis) to be changed to subpara (m) and all subsequent subparas to be changed accordingly)</b></p> <p><b>(NOTE item (i bis) in above subpara (m) to be changed to item ii and all subsequent items to be changed accordingly)</b></p>
59	Schedules	<p>Schedule 5, Part 9 (b) For unpackaged <i>LSA-I</i> in a <i>freight container</i> or <i>tank</i>, or where an <i>exclusive use consignment</i> in a <i>freight container</i> is packaged <i>LSA-I</i> and no other UN Number commodities are present in the <i>freight container</i>, the UN Number "2912" shall be displayed on all four sides of the <i>freight container</i> or <i>tank</i>, either in the lower half of the placards shown in Fig. 6, and against the white background, or on the placards shown in Fig. 7.</p> <p>Schedule 6, Part 9 (b) Where an <i>exclusive use consignment</i> in a <i>freight container</i> is non-fissile or fissile-excepted <i>LSA-II</i> and no other UN Number commodities are present in the <i>freight container</i>, "3321" shall be displayed on all four sides of the <i>freight container</i>, either in the lower half of the placards shown in Fig. 6, and against the white background, or on the placards shown in Fig. 7. In the case of <i>fissile material</i> transported as <i>LSA-II</i>, "3324" shall be displayed on the placards.</p> <p>Schedule 7, Part 9 (b) Where an <i>exclusive use consignment</i> in a <i>freight container</i> is non-fissile or fissile-excepted <i>LSA-III</i> and no other UN Number commodities are present in the <i>freight container</i>, "3322" shall be displayed on all four sides of the <i>freight container</i>, either in the lower half of the placards shown in Fig. 6, and against the white background, or on the placards shown in Fig. 7. In the case of <i>fissile material</i> transported as <i>LSA-III</i>, "3325" shall be displayed on the placards.</p>	<p>Schedule 5, Part 9 (b) For unpackaged <i>LSA-I</i> in a <i>freight container</i> or <i>tank</i>, or where an <i>exclusive use consignment</i> in a <i>freight container</i> is packaged <i>LSA-I</i> and no other UN Number commodities are present in the <i>freight container</i>, the UN Number "2912" shall be displayed on all four sides of the <i>freight container</i> or <i>tank</i>, either in the lower half of the placards shown in Fig. 6, and against the white background, or on the placards shown in Fig. 7. <b>However if the packages contain non-fissile or fissile-excepted uranium hexafluoride, "2978" shall be displayed.</b></p> <p>Schedule 6, Part 9 (b) Where an <i>exclusive use consignment</i> in a <i>freight container</i> is non-fissile or fissile-excepted <i>LSA-II</i> and no other UN Number commodities are present in the <i>freight container</i>, "3321" shall be displayed on all four sides of the <i>freight container</i>, either in the lower half of the placards shown in Fig. 6, and against the white background, or on the placards shown in Fig. 7. In the case of <i>fissile material</i> transported as <i>LSA-II</i>, "3324" shall be displayed on the placards. <b>However if the packages contain non-fissile or fissile-excepted uranium hexafluoride, "2978" shall be displayed. If the packages contain uranium hexafluoride that is fissile material, "2977" shall be displayed.</b></p> <p>Schedule 7, Part 9 (b) Where an <i>exclusive use consignment</i> in a <i>freight container</i> is non-fissile or fissile-excepted <i>LSA-III</i> and no other UN Number commodities are present in the <i>freight container</i>, "3322" shall be displayed on all four sides of the <i>freight container</i>, either in the lower half of the placards shown in Fig. 6, and against the white background, or on the placards shown in Fig. 7. In the case of <i>fissile material</i> transported as <i>LSA-III</i>, "3325" shall be displayed on the placards. <b>However if the packages contain non-fissile or fissile-excepted uranium hexafluoride, "2978" shall be displayed. If the</b></p>

Change	Para	Existing text in TS-R-1 (2003)	Text as approved by TRANSSC IX
		<p>Schedule 9, Part 9 (c) Where an <i>exclusive use consignment</i> in a <i>freight container</i> is non-fissile or fissile-excepted <i>radioactive material</i> in <i>Type A packages</i> and no other UN Number commodities are present in the <i>freight container</i>, "2915" shall be displayed on all four sides of the <i>freight container</i>, either in the lower half of the placards shown in Fig. 6, and against the white background, or on the placards shown in Fig. 7. In the case of <i>fissile material</i> transported in <i>Type A packages</i>, "3327" shall be displayed on the placards.</p>	<p><b>packages contain uranium hexafluoride that is fissile material, "2977" shall be displayed.</b></p> <p>Schedule 9, Part 9 (c) Where an <i>exclusive use consignment</i> in a <i>freight container</i> is non-fissile or fissile-excepted <i>radioactive material</i> in <i>Type A packages</i> and no other UN Number commodities are present in the <i>freight container</i>, "2915" shall be displayed on all four sides of the <i>freight container</i>, either in the lower half of the placards shown in Fig. 6, and against the white background, or on the placards shown in Fig. 7. In the case of <i>fissile material</i> transported in <i>Type A packages</i>, "3327" shall be displayed on the placards. <b>However if the Type A packages contain non-fissile or fissile-excepted uranium hexafluoride, "2978" shall be displayed. If the packages contain uranium hexafluoride that is fissile material, "2977" shall be displayed.</b></p>
61	106, 107, 220bis, 301-315 (partly paragraph reordering), 562	<p><b>NOTE. ONLY THE PARAGRAPHS WHICH THE REVIEW PANEL RECOMMENDS TO BE REVISED ARE LISTED HERE</b></p> <p>302. <b>In transport</b>, protection and safety shall be optimized in order that the magnitude of individual doses, the number of persons exposed, and the likelihood of incurring exposure shall be kept as low as reasonably achievable, economic and social factors being taken into account, <b>and doses to persons shall be below the relevant dose limits.</b> A structured and systematic approach shall be adopted and shall include consideration of the interfaces between transport and other activities.</p> <p><b>306. Radioactive material shall be segregated sufficiently from workers and from members of the public. The following values for dose shall be used for the purpose of calculating segregation distances or radiation levels:</b></p> <p>(a) for workers in regularly occupied working areas a dose of <b>5 mSv in a year;</b></p> <p>(b) for members of the public, in areas where the public has regular access, a dose of <b>1 mSv in a year to the critical group, taking account of exposures expected to be delivered by all other relevant sources and practices under control.</b></p>	<p><b>302. Doses to persons shall be below the relevant dose limits.</b> Protection and safety shall be optimized in order that the magnitude of individual doses, the number of persons exposed, and the likelihood of incurring exposure shall be kept as low as reasonably achievable, economic and social factors being taken into account, <b>within the restriction that the doses to individuals be subject to dose constraints.</b> A structured and systematic approach shall be adopted and shall include consideration of the interfaces between transport and other activities. <b>(NOTE. Para 302 to be renumbered as 301)</b></p> <p><b>306. deleted</b></p>

Change	Para	Existing text in TS-R-1 (2003)	Text as approved by TRANSSC IX
		<p><b>307. Radioactive material shall be sufficiently segregated from undeveloped photographic film. The basis for determining segregation distances for this purpose shall be that the radiation exposure of undeveloped photographic film due to the transport of radioactive material be limited to 0.1 mSv per consignment of such film.</b></p> <p>562. Packages, overpacks and freight containers containing radioactive material shall be segregated during transport and during storage in transit:</p> <p>(a) from places occupied by persons and from undeveloped photographic film, for radiation exposure control purposes, in accordance with paras 306 and 307, and</p> <p>(b) from other dangerous goods in accordance with para. 506.</p>	<p><b>307. deleted</b></p> <p>562. Packages, overpacks and freight containers containing radioactive material <b>and unpackaged radioactive material</b> shall be segregated during transport and during storage in transit:</p> <p><b>(a) from workers in regularly occupied working areas by distances calculated using a dose criterion of 5 mSv in a year and conservative model parameters;</b></p> <p><b>(b) from members of the critical group of the public, in areas where the public has regular access, by distances calculated using a dose criterion of 1 mSv in a year and conservative model parameters;</b></p> <p><b>(c) from undeveloped photographic film by distances calculated using a radiation exposure criterion for undeveloped photographic film due to the transport of radioactive material of 0.1 mSv per consignment of such film;</b> and</p> <p><b>(d) from other dangerous goods in accordance with para. 506.</b></p>
62	533, 533bis, 549	<p>533. Packages and overpacks shall be assigned to either category I-WHITE, II-YELLOW or III-YELLOW in accordance with the conditions specified in Table VII and with the following requirements:</p> <p>(a) For a package or overpack, both the transport index and the surface radiation level conditions shall be taken into account in determining which is the appropriate category. Where the transport index satisfies the condition for one category but the surface radiation level satisfies the condition for a different category, the package or overpack shall be assigned to the higher category. For this purpose, category I-WHITE shall be regarded as the lowest category.</p> <p>(b) The transport index shall be determined following the procedures specified in paras 526 and 527.</p> <p>(c) If the surface radiation level is greater than 2 mSv/h, the package or overpack shall be transported under exclusive use and under the provisions of paras 572(a), 574 or 578, as appropriate.</p>	<p>533. Packages and overpacks shall be assigned to either category I WHITE, II-YELLOW or III-YELLOW in accordance with the conditions specified in Table VII and with the following requirements:</p> <p>(a) For a package or overpack, both the transport index and the surface radiation level conditions shall be taken into account in determining which is the appropriate category. Where the transport index satisfies the condition for one category but the surface radiation level satisfies the condition for a different category, the package or overpack shall be assigned to the higher category. For this purpose, category I-WHITE shall be regarded as the lowest category.</p> <p>(b) The transport index shall be determined following the procedures specified in paras 526 and 527.</p> <p>(c) If the surface radiation level is greater than 2 mSv/h, the package or overpack shall be transported under exclusive use and under the provisions of paras 572(a), 574 or 578, as appropriate.</p>

Change	Para	Existing text in TS-R-1 (2003)	Text as approved by TRANSSC IX
		<p>(d) A <i>package</i> transported under a <i>special arrangement</i> shall be assigned to category III-YELLOW.</p> <p>(e) An <i>overpack</i> which contains <i>packages</i> transported under <i>special arrangement</i> shall be assigned to category III-YELLOW.</p> <p>549. The <i>consignor</i> shall include in the transport documents with each <i>consignment</i> the following information, as applicable in the order given:</p> <p>(a) The proper shipping name, as specified in Table VIII;</p> <p>(b) The United Nations Class number “7”;</p> <p>(c) The United Nations number assigned to the material as specified in Table VIII, preceded by the letters “UN”;</p> <p>(d) The name or symbol of each radionuclide or, for mixtures of radionuclides, an appropriate general description or a list of the most restrictive nuclides;</p> <p>(e) A description of the physical and chemical form of the material, or a notation that the material is <i>special form radioactive material</i> or <i>low dispersible radioactive material</i>. A generic chemical description is acceptable for chemical form;</p> <p>(f) The maximum activity of the <i>radioactive contents</i> during transport expressed in units of becquerels (Bq) with an appropriate SI prefix (see Annex II). For <i>fissile material</i>, the mass of <i>fissile material</i> in units of grams (g), or appropriate multiples thereof, may be used in place of activity;</p> <p>(g) The category of the <i>package</i>, i.e. I-WHITE, II-YELLOW, III-YELLOW;</p>	<p>(d) A <i>package transported under a special arrangement shall be assigned to category III-YELLOW except under the provisions of para 533 bis.</i></p> <p>(e) An <i>overpack which contains packages transported under special arrangement shall be assigned to category III-YELLOW except under the provisions of para 533 bis.</i></p> <p><b>533 bis For each package or overpack the UN number and proper shipping name shall be determined (see Table VIII). In all cases of international transport of packages requiring competent authority design or shipment approval, for which different approval types apply in the different countries concerned by the shipment, the UN number, proper shipping name, categorization, labelling and marking shall be in accordance with the certificate of the country of origin of design.</b></p> <p><b>(NOTE. Para 533 bis to be numbered as 534 and references to para 533 bis in above para 533 to be changed as references to para 534)</b></p> <p>549. The <i>consignor</i> shall include in the transport documents with each <i>consignment</i> the following information, as applicable in the order given:</p> <p>(a) The proper shipping name, as specified in <b>accordance with the provisions of para 533 bis</b>;</p> <p>(b) The United Nations Class number “7”;</p> <p>(c) The United Nations number assigned to the material as specified in <b>accordance with the provisions of para 533 bis</b>, preceded by the letters “UN”;</p> <p>(d) The name or symbol of each radionuclide or, for mixtures of radionuclides, an appropriate general description or a list of the most restrictive nuclides;</p> <p>(e) A description of the physical and chemical form of the material, or a notation that the material is <i>special form radioactive material</i> or <i>low dispersible radioactive material</i>. A generic chemical description is acceptable for chemical form;</p> <p>(f) The maximum activity of the <i>radioactive contents</i> during transport expressed in units of becquerels (Bq) with an appropriate SI prefix (see Annex II). For <i>fissile material</i>, the mass of <i>fissile material</i> in units of grams (g), or appropriate multiples thereof, may be used in place of activity;</p> <p>(g) The category of the <i>package</i>, i.e. I-WHITE, II-YELLOW, III-YELLOW;</p>

Change	Para	Existing text in TS-R-1 (2003)	Text as approved by TRANSSC IX
		<p>(h) The <i>transport index</i> (categories II-YELLOW and III-YELLOW only);</p> <p>(i) For <i>consignments</i> including <i>fissile material</i> other than <i>consignments</i> excepted under para. 672, the <i>criticality safety index</i>;</p> <p>(j) The identification mark for each <i>competent authority</i> approval certificate (<i>special form radioactive material, low dispersible radioactive material, special arrangement, package design, or shipment</i>) applicable to the <i>consignment</i>;</p> <p>(k) For <i>consignments</i> of more than one <i>package</i>, the information contained in para. 549(a) to (j) shall be given for each <i>package</i>. For <i>packages</i> in an <i>overpack, freight container, or conveyance</i>, a detailed statement of the contents of each <i>package</i> within the <i>overpack, freight container, or conveyance</i> and, where appropriate, of each <i>overpack, freight container, or conveyance</i> shall be included. If <i>packages</i> are to be removed from the <i>overpack, freight container, or conveyance</i> at a point of intermediate unloading, appropriate transport documents shall be made available;</p> <p>(l) Where a <i>consignment</i> is required to be shipped under <i>exclusive use</i>, the statement “EXCLUSIVE USE SHIPMENT”; and</p> <p>(m) For <i>LSA-II, LSA-III, SCO-I</i> and <i>SCO-II</i>, the total activity of the <i>consignment</i> as a multiple of <math>A_2</math>.</p>	<p>(h) The <i>transport index</i> (categories II-YELLOW and III-YELLOW only);</p> <p>(i) For <i>consignments</i> including <i>fissile material</i> other than <i>consignments</i> excepted under para. 672, the <i>criticality safety index</i>;</p> <p>(j) The identification mark for each <i>competent authority</i> approval certificate (<i>special form radioactive material, low dispersible radioactive material, special arrangement, package design, or shipment</i>) applicable to the <i>consignment</i>;</p> <p>(k) For <i>consignments</i> of more than one <i>package</i>, the information contained in para. 549(a) to (j) shall be given for each <i>package</i>. For <i>packages</i> in an <i>overpack, freight container, or conveyance</i>, a detailed statement of the contents of each <i>package</i> within the <i>overpack, freight container, or conveyance</i> and, where appropriate, of each <i>overpack, freight container, or conveyance</i> shall be included. If <i>packages</i> are to be removed from the <i>overpack, freight container, or conveyance</i> at a point of intermediate unloading, appropriate transport documents shall be made available;</p> <p>(l) Where a <i>consignment</i> is required to be shipped under <i>exclusive use</i>, the statement “EXCLUSIVE USE SHIPMENT”; and</p> <p>(m) For <i>LSA-II, LSA-III, SCO-I</i> and <i>SCO-II</i>, the total activity of the <i>consignment</i> as a multiple of <math>A_2</math>.</p> <p><b>(NOTE. References to para 533 bis to be changed to references to para 534)</b></p>