

Original: ENGLISH only

ECONOMIC COMMISSION FOR EUROPE

INLAND TRANSPORT COMMITTEE

Working Party on the Transport of Dangerous Goods

**Ad hoc Working Group on the Harmonization of RID/ADR/ADN
with the UN Recommendations on the Transport of Dangerous Goods
(Geneva, 22-24 May 2007)**

**HARMONIZATION WITH THE UNITED NATIONS
MODEL REGULATIONS ON THE TRANSPORT OF DANGEROUS GOODS**

Draft proposal of amendments to RID/ADR/ADN

Note by the UNECE secretariat

The UNECE secretariat has prepared a draft proposal of amendments to RID/ADR/ADN on the basis of the decisions taken by the UN Committee of Experts on the Transport of Dangerous Goods and on the Globally Harmonized System of Classification and Labelling of Chemicals at its December 2006 session. This document also takes into account the decisions taken for the modification of Chapter 6.2 by the RID/ADR/ADN Joint meeting during its March 2007 session.

The United Nations documents of reference are ST/SG/AC.10/34, -/Add.1 and -/Corr.1.

Striken out text means that the amendment does not seem relevant for RID/ADR/ADN. Text underlined means alternative wording proposed by the secretariat. Text in square brackets means that the Working Group of the Joint Meeting should discuss the relevance of the text for RID/ADR/ADN. Additional information, such as references and comments, is also provided in square brackets.

*/ Informal document. Not issued as an official United Nations document. Circulated only to delegations participating in the work of the Joint Meeting of the RID Committee of Experts and the Working Party on the Transport of Dangerous Goods.

DRAFT AMENDMENTS TO RID/ADR/ADN

PART 1

Chapter 1.1

~~1.1.1.6~~ — Insert the following new heading "*Transport of dangerous goods by post*".

In the first paragraph:

~~replace "national postal authorities" with "appropriate national authorities" (twice);~~

~~in the first sentence, replace "the mail" with "mail transported internationally";~~

~~in the second sentence, insert "international" before "transport of dangerous goods";~~

~~in the third sentence, insert "international" before "mail".~~

~~In (a), at the beginning, insert ", assigned to Category B (UN 3373) only," after "Infectious substances" and, at the end, replace "infectious substances" with "UN 3373".~~

~~Insert a new note at the end to read as follows:~~

~~*"NOTE: The Acts of the Universal Postal Union do not apply to the domestic transport of dangerous goods by mail. Domestic transport of dangerous goods in the mail are subject to the provisions of the appropriate national authorities."*~~

~~1.1.2~~ — Delete the section. Renumber 1.1.3 as 1.1.2 and 1.1.3.1 as 1.1.2.1.

~~*Consequential amendments:*~~

~~*2.0.4.2 and 3.1.2.6 — Replace "1.1.3" with "1.1.2".*~~

~~2.2.2.3~~ 1.1.3.2 (c) Amend the first sentence to read as follows:

~~"2.2.2.3 gases of Division 2.2 Groups A and O (according to 2.2.2.1), if the pressure of the gas in the receptacle or tank at a temperature of 20 °C does not exceed 200 kPa (2 bar) and if the gas is not a liquefied or a refrigerated liquefied gas are not subject to these Regulations if they are transported at a pressure of less than 200 kPa at 20 °C and are not liquefied or refrigerated liquefied gases."~~

Chapter 1.2

1.2.1 Amend the definition of "*Competent authority*" to read as follows:

~~*"Competent authority means any body or authority designated or otherwise recognized as such for any purpose in connection with these Regulations;"*~~ [Does not apply for RID/ADR/ADN]

~~In the definition of "*Freight container*", at the end, replace "see 2.7.2" with "a freight container may be used as a packaging" and add the following new paragraph at the end:~~

~~In the Note under the definition of "*Container*", add "Nevertheless, a container may be used as a packaging for the carriage of radioactive material."~~

~~"A small freight container is that which has either any overall outer dimension less than 1.5 m, or an internal volume of not more than 3 m³. Any other freight container is considered to be a large freight container.".~~ [\[Does not apply for RID/ADR/ADN\]](#)

Delete the note after the definition of "*Package*".

~~Amend~~ [In](#) the definition of "*Packaging*", [amend the text before the parenthesis](#) to read as follows:

"*Packaging* means one or more receptacles and any other components or materials necessary for the receptacles to perform their containment and other safety functions."

[Delete the note after the definitions of "Packaging", "Large container" and "Small container"](#).

~~Add the following new note after the definition of "Recycled plastics material":~~

~~"NOTE: ISO 16103:2005 "Packaging—Transport packages for dangerous goods—Recycled plastics material", provides additional guidance on procedures to be followed in approving the use of recycled plastics material.".~~ [\[Already covered by 6.1.4.8.8\]](#)

6.5.1.2

In the definition of *Plastics Composite IBC*, [in the Note](#), insert "*material*" after "*Plastics*" and delete ", etc".

Insert the following new definitions in alphabetical order:

"*Animal material* means animal carcasses, animal body parts, or animal foodstuffs; "

"*Approval*

Multilateral approval, for the ~~transport~~[carriage](#) of Class 7 material, means approval by the relevant competent authority of the country of origin of the design or shipment, as applicable, and [by the competent authority of each country through or into which the consignment is to be carried](#)~~also, where the consignment is to be transported through or into any other country, approval by the competent authority of that country.~~ The term "through or into" specifically excludes "over", i.e. the approval and notification requirements shall not apply to a country over which radioactive material is carried in an aircraft, provided that there is no scheduled stop in that country;

Unilateral approval, for the ~~transport~~[carriage](#) of Class 7 material, means an approval of a design which is required to be given by the competent authority of the country of origin of the design only;"

"*Confinement system*, for the ~~transport~~[carriage](#) of Class 7 material, means the assembly of fissile material and packaging components specified by the designer and agreed to by the competent authority as intended to preserve criticality safety;"

"*Containment system*, for the ~~transport~~[carriage](#) of Class 7 material, means the assembly of components of the packaging specified by the designer as intended to retain the radioactive material during ~~transport~~[carriage](#);"

"Criticality safety index (CSI) assigned to a package, overpack or ~~freight~~-container containing fissile material, for the ~~transport~~carriage of Class 7 material, means a number which is used to provide control over the accumulation of packages, overpacks or ~~freight~~ containers containing fissile material;"

"Design, for the ~~transport~~carriage of Class 7 material, means the description of special form radioactive material, low dispersible radioactive material, package or packaging which enables such an item to be fully identified. The description may include specifications, engineering drawings, reports demonstrating compliance with regulatory requirements, and other relevant documentation;"

"Exclusive use, for the ~~transport~~carriage of Class 7 material, means the sole use, by a single consignor, of a conveyance or of a large ~~freight~~-container, in respect of which all initial, intermediate and final loading and unloading is carried out in accordance with the directions of the consignor or consignee;"

Consequential amendment:

In the note after the definition of "Full load", delete ", see 2.2.7.2".

"Maximum normal operating pressure, for the ~~transport~~carriage of Class 7 material, means the maximum pressure above atmospheric pressure at mean sea-level that would develop in the containment system in a period of one year under the conditions of temperature and solar radiation corresponding to environmental conditions in the absence of venting, external cooling by an ancillary system, or operational controls during ~~transport~~carriage;"

"Radiation level, for the ~~transport~~carriage of Class 7 material, means the corresponding dose rate expressed in millisieverts per hour;"

"Radioactive contents, for the ~~transport~~carriage of Class 7 material, mean the radioactive material together with any contaminated or activated solids, liquids, and gases within the packaging;"

"Transport index (TI) assigned to a package, overpack or ~~freight~~-container, or to unpackaged LSA-I or SCO-I, for the ~~transport~~carriage of Class 7 material, means a number which is used to provide control over radiation exposure;"

Chapter 1.6

~~4.1.1.3~~1.6.1.X Add ~~the following new paragraph at the end:~~a new transitional measure to read as follows:

"1.6.1.X ~~However,~~ IBCs manufactured before 1 January 2011 and conforming to a design type which has not passed the vibration test of 6.5.6.13 may still be used."

1.6.1.Y For IBCs, the marking of the maximum permitted stacking load required by 6.5.2.2.2 need not be displayed until the first inspection or test after 1 January 2011 is performed.

Chapter ~~1.5~~1.7

In the heading of the Chapter, replace "REQUIREMENTS" with "PROVISIONS".

~~Add a new Chapter 1.5 to read as follows:~~

~~"CHAPTER 1.5~~

~~GENERAL PROVISIONS CONCERNING CLASS 7~~

Amend the heading of 1.7.1 to read as follows:

~~1.5.1~~1.7.1 **Scope and application".**

~~1.5.1.1~~1.7.1.1 [Unchanged. The reference to TS-G-1.1 need to be updated when the revised edition will be published by IAEA.]

~~1.5.1.2~~1.7.1.2 [Unchanged.]

~~1.5.1.3~~1.7.1.3 [Unchanged.]

~~1.5.1.4~~1.7.1.4 Insert a new sub-section 1.7.1.4 to read as follows
[For reference: existing text of 2.2.7.1.2 as amended];

The provisions laid down in RID/ADR/ADN do not apply to the carriage of:~~These Regulations do not apply to:~~

- (a) Radioactive material that is an integral part of the means of transport;
- (b) Radioactive material moved within an establishment which is subject to appropriate safety regulations in force in the establishment and where the movement does not involve public roads or railways;
- (c) Radioactive material implanted or incorporated into a person or live animal for diagnosis or treatment;
- (d) Radioactive material in consumer products which have received regulatory approval, following their sale to the end user;
- (e) Natural material and ores containing naturally occurring radionuclides which are either in their natural state, or have only been processed for purposes other than for extraction of the radionuclides, and which are not intended to be processed for use of these radionuclides provided the activity concentration of the material does not exceed 10 times the values specified in 2.2.7.2.2.1 (b) [For reference: existing 2.2.7.7.2.1 (b)], or calculated in accordance with 2.2.7.2.2.2 to 2.2.7.2.2.6 [For reference: exiting 2.2.7.7.2.2 to 2.2.7.7.2.6];
- (f) Non-radioactive solid objects with radioactive substances present on any surfaces in quantities not in excess of the limit set out in the definition for "contamination" in 2.7.1.2 [For reference: existing 2.2.7.2].

Consequential amendment: In 1.1.3.1, 1.1.3.4 and 1.8.3.2 replace "2.2.7.1.2" with "1.7.1.4".

Insert a new sub-section 1.7.1.5 to read as follows:

[For reference: existing text of 2.2.7.9.1 as amended]

1.5.1.5 1.7.1.5 Specific provisions for the ~~transport~~carriage of excepted packages

~~1.5.1.5.1~~ 1.7.1.5.1 Excepted packages which may contain radioactive material in limited quantities, instruments, manufactured articles and empty packagings as specified in 2.2.7.2.4.1 may be ~~transported~~carried under the following conditions:

- (a) The applicable requirements specified in Chapter 1.3, ~~2.0.3.2~~, ~~[2.1.3]~~, 2.2.7.2.4.1.2 to 2.2.7.2.4.1.6 (as applicable), 3.3.1 (special provision 290), 4.1.9.1.2, [5.2.1.1] [This reference was already in the 14th revised edition of the recommendations but not in ADR.], 5.2.1.2, 5.2.1.57.1 to 5.2.1.57.3, 5.4.1.41.1 (a) and ~~7.1.8.5.27.5.11~~ CV33 (5.2);

[The working group should check whether the reference to 2.1.3.5.3 and 5.2.1.1 should be kept. These requirements are already listed in the 14th revised edition of the UN Recommendations but not in RID/ADR/ADN 2007.]

- (b) The requirements for excepted packages specified in 6.4.4; and
- (c) If the excepted package contains fissile material, one of the fissile exceptions provided by 2.2.7.2.3.5 shall apply and the requirement of 6.4.7.2 shall be met; ~~and.~~

~~(d) The requirements in 1.1.1.6 if transported by post.~~

~~1.5.1.5.2~~ 1.7.1.5.2 The following provisions do not apply to excepted packages and the controls for ~~transport~~carriage of excepted packages: Chapter ~~4.1.10~~, 2.2.7.4.1, 2.2.7.2.3.3.2, 4.1.9.1.3, 4.1.9.1.4, 4.1.9.1.6, 4.1.9.1.7, 5.1.3.2, 5.2.2.1.1211.1, 5.4.1.1.1, except (a), ~~5.4.1.5.7.1~~ 5.4.1.2.5.1, ~~5.4.1.5.7.25.4.1.2.5.2~~, ~~5.4.1.6~~, ~~5.4.3~~, 6.4.6.1, ~~7.1.8.1.1~~, ~~7.1.8.3.1~~, ~~7.1.8.5.1~~, ~~7.1.8.5.3~~ to ~~7.1.8.5.5~~, ~~7.1.8.6.1~~ and 7.5.11 CV33 except for paragraph 5.2 ~~and section 7.2.4~~.

Consequential amendment:

In Chapter 3.3, SP290, replace “2.2.7.9.1” with “1.7.1.5”.

1.5.21.7.2 [Heading unchanged.]

~~1.5.2.1~~ 1.7.2.1 [Unchanged.]

1.7.2.2 Amend to read as follows

[For reference: existing text of 1.7.2.3 as amended]:

~~1.5.2.2~~ 1.7.2.2 Protection and safety shall be optimized in order that the magnitude of individual doses, the number of persons exposed, and the likelihood of incurring exposure shall be kept as low as reasonably achievable, economic and social factors being taken into account, and doses to persons shall be below the relevant dose limits. A structured and systematic approach shall be adopted and shall include consideration of the interfaces between ~~transport~~carriage and other activities.”.

1.7.2.3 Amend to read as follows

[For reference: existing text of 1.7.2.2 as amended]:

~~“1.5.2.3~~1.7.2.3 The nature and extent of the measures to be employed in the programme shall be related to the magnitude and likelihood of radiation exposures. The programme shall incorporate the requirements in ~~1.5.2.2~~1.7.2.2, ~~1.5.2.4~~1.7.2.4 to ~~1.5.2.7~~1.7.2.7. Programme documents shall be available, on request, for inspection by the relevant competent authority.”

1.7.2.4 Add the following new note at the end:

~~1.5.2.4~~ For occupational exposures arising from transport activities, where it is assessed that the effective dose:

~~(a) Is likely to be between 1 and 6 mSv in a year, a dose assessment programme via workplace monitoring or individual monitoring shall be conducted;~~

~~(b) Is likely to exceed 6 mSv in a year, individual monitoring shall be conducted.~~

~~When individual monitoring or workplace monitoring is conducted, appropriate records shall be kept.~~ [Remainder unchanged]

“NOTE: For occupational exposures arising from transport activities, where it is assessed that the effective dose is most unlikely to exceed 1mSv in a year, no special work patterns, detailed monitoring, dose assessment programmes or individual record keeping need be required.”

Insert new sub-sections 1.7.2.5 to 1.7.2.7 to read as follows:

~~“1.5.2.5~~1.7.2.5 In the event of accidents or incidents during the ~~transport~~carriage of radioactive material, emergency provisions, as established by relevant national and/or international organizations, shall be observed to protect persons, property and the environment. Appropriate guidelines for such provisions are contained in "Planning and Preparing for Emergency Response to Transport Accidents Involving Radioactive Material", Safety Standard Series No. TS-G-1.2 (ST-3), IAEA, Vienna (2002).

~~1.5.2.6~~1.7.2.6 Emergency procedures shall take into account the formation of other dangerous substances that may result from the reaction between the contents of a consignment and the environment in the event of an accident.

~~1.5.2.7~~1.7.2.7 Workers~~[persons involved in the carriage of radioactive material]~~ shall receive appropriate training concerning the radiation hazards involved and the precautions to be observed in order to ensure restriction of their exposure and that of other persons who might be affected by their actions.”

[The Working group may decide to add an appropriate reference in Chapter 1.3]

~~1.5.3~~1.7.3 [Unchanged.]

~~1.5.4~~1.7.4 [Heading unchanged.]

~~1.5.4.1~~1.7.4.1 Delete "of radioactive material" after "consignments" and replace "the applicable requirements of ADR" with "the requirements of ADR applicable to radioactive material". ~~Special arrangement shall mean those provisions, approved by the competent authority, under which consignments which do not satisfy all the requirements of these Regulations applicable to radioactive material may be transported.~~

~~1.5.4.2~~1.7.4.2 [Unchanged.]

~~1.5.5~~1.7.5 [Unchanged.]

~~1.5.6~~**1.7.6** [\[Unchanged.\]](#)

Chapter ~~1.4~~**1.10**

Table ~~1.4.1~~**1.10.5** Add a new fourth line for Class 1, Division 1.4, to read as follows:

~~"Class 1, Division 1.4 — UN Nos. 0104, 0237, 0255, 0267, 0289, 0361, 0365, 0366, 0440, 0441, 0455, 0456 and 0500".~~

Class	Division	Substance or article	Quantity		
			Tank (l) ^a	Bulk (kg) ^a	Packages (kg) <u>0</u>
<u>1</u>	<u>1.4</u>	<u>Explosives of UN Nos. 0104, 0237, 0255, 0267, 0289, 0361, 0365, 0366, 0440, 0441, 0455, 0456 and 0500</u>			

~~Division~~Class 5.1, amend the ~~second entry~~text in the third column to read as follows:

~~"Division 5.1~~—Perchlorates, ammonium nitrate, ammonium nitrate fertilisers and ammonium nitrate emulsions or suspensions or gels, in bulk".

PART 2

Chapter ~~2.1~~**2.2**

~~2.1.3.5.2~~**2.2.1.1.7.2** In Note 2, replace "~~Hazard Division to firework types and/or sub-divisions by the specification~~" with "~~fireworks specified~~". [\[Unchanged.\]](#)

~~2.1.3.5.5~~**2.2.1.1.7.5** The amendment to the heading of the table does not apply to the English version.

In the table, against "Shell, spherical or cylindrical / preloaded mortar, shell in mortar", insert new third entry as follows:

Specification	Classification
Colour shell: > 25% flash composition as loose powder and/or report effects	1.1G

Amend Note 2 to read as follows:

"NOTE 2: "Flash composition" in this table refers to pyrotechnic compositions in powder form or as pyrotechnic units as presented in the fireworks, that are used to produce an aural effect, or used as a bursting charge or lifting charge, unless the time taken for the pressure rise is demonstrated to be more than 8 ms for 0.5 g of pyrotechnic composition in Test Series 2(c)(i) "Time/pressure test"."

~~2.2.2.1 (b) (ii)~~ At the end after "does", add "~~The oxidizing ability shall be determined by tests or by calculation in accordance with methods adopted by ISO (see ISO 10156:1996 and ISO 10156-2:2005)~~". [\[Already covered by 2.2.2.1.5 Oxidizing gases.\]](#)

~~2.2.3 (d)~~ At the end, add "~~(see ISO 10156:1996 and ISO 10156-2:2005)~~". [\[Already covered by 2.2.2.1.5 Oxidizing gases.\]](#)

2.3.2.52.2.3.1.5 At the beginning, replace "and non-corrosive" with "non-environmentally hazardous and non-corrosive". ~~Insert "or environmentally hazardous" at the end of the second indent.~~

2.4.2.412.2.41.1.18 Replace "and UN-3380" with ", UN-3380 and UN-3474".

2.5.3.242.2.52.4 In the table, amend the entries listed below as follows:

Organic peroxide		Column	Amendment
tert-AMYLPEROXY-3,5,5-TRIMETHYLHEXANOATE		Packing method	Replace "OP5" with "OP7"
		Number	Replace "3101" with "3105"
DICUMYL PEROXIDE (Concentration > 52-100)	(1 st row)	Inert solid	Delete "≤ 57"
DI-(2-ETHYLHEXYL) PEROXYDICARBONATE (Concentration ≤ 62 as a stable dispersion in water)	(3 rd row)	Number	Replace "3117" with "3119"
DI-(2-ETHYLHEXYL) PEROXYDICARBONATE (Concentration ≤ 52 as a stable dispersion in water)	(4 th row)	Delete	

Insert the following new entries:

Organic peroxide	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)
tert-AMYL PEROXYNEODECANOATE	≤ 47	≥ 53				OP8	0	+ 10	3119	
tert-BUTYL PEROXY 3,5,5-TRIMETHYLHEXANOATE	≤ 42			≥ 58		OP7			3106	
CUMYL PEROXYNEODECANOATE	≤ 87	≥ 13				OP7	- 10	0	3115	
2,2-DI-(tert-AMYLPEROXY)-BUTANE	≤ 57	≥ 43				OP7			3105	
1,1-DI-(tert-BUTYLPEROXY)-CYCLOHEXANE	≤ 72		≥ 28			OP5			3103	30)
1,1-DI-(tert-BUTYLPEROXY)-CYCLOHEXANE + tert-BUTYL PEROXY-2-ETHYLHEXANOATE	≤ 43 + ≤ 16	≥ 41				OP 7			3105	
1,1-DI-(tert-BUTYLPEROXY)-3,3,5-TRIMETHYLCYCLOHEXANE	≤ 90		≥ 10			OP5			3103	30)
DI-2,4-DICHLOROBENZOYL PEROXIDE	≤ 52 as a paste					OP8	+ 20	+ 25	3118	
3-HYDROXY-1,1-DIMETHYLBUTYL PEROXYNEODECANOATE	≤ 77	≥ 23				OP 7	- 5	+ 5	3115	
3-HYDROXY-1,1-DIMETHYLBUTYL PEROXYNEODECANOATE	≤ 52 as a stable dispersion in water					OP 8	- 5	+ 5	3119	
3-HYDROXY-1,1-DIMETHYLBUTYL PEROXYNEODECANOATE	≤ 52	≥ 48				OP 8	- 5	+ 5	3117	

Organic peroxide	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)
METHYL ISOPROPYL KETONE PEROXIDE(S)	See remark 31)	≥ 70				OP8			3109	31)
3,3,5,7,7-PENTAMETHYL-1,2,4-TRIOXEPANE	≤ 100					OP8			3107	

After the table, add the following new notes:

"30) Diluent type B with boiling point > 130 °C.

31) Active oxygen ≤ 6.7%."

~~2.6.3.2.3.6~~ 2.2.62.1.5.6

Renumber existing NOTE as NOTE 1.

In NOTE 1 (existing NOTE), add "*in the absence of any concern for infection (e.g. evaluation of vaccine induced immunity, diagnosis of autoimmune disease, etc.)*" after "*antibody detection in humans or animals*".

Add a new NOTE 2 to read as follows:

"**NOTE 2:** ~~For air transport~~ *When intended to be carried by air, packagings for specimens exempted under this paragraph shall meet the conditions in (a) to (c).*"

~~2.6.3.5.2~~ 2.2.62.1.11.2

Add at the end, before the notes: "For the assignment, international, regional or national waste catalogues may be taken into account."

~~2.6.3.6.2~~ 2.2.62.1.12.2

Amend the first sentence to read as follows:

"Animal material affected by pathogens of Category A or which would be assigned to Category A in cultures only, shall be assigned to UN 2814 or UN 2900 as appropriate."

Delete the second sentence.

[In RID/ADR/ADN, it may be appropriate to keep a reference to Regulations for dead animals as in the existing footnote related to this paragraph.]

Amend ~~Chapter-Section~~ 2.2.7 to read as follows and amend all references to renumbered paragraphs of ~~Chapter-section~~ 2.2.7, as appropriate (~~apply to 1.1.1.6 (b), 3.3.1 SP290, 4.1.9.1.1, 4.1.9.2.3 (b) and (c), 5.2.2.1.12.1, 5.2.2.1.12.2 (a)(i) and (d), 6.4.8.8, 6.4.10.3, 6.4.12.1, 6.4.12.2, 6.4.14, 6.4.24.1, 6.4.24.2 and 6.4.24.3~~):

In 1.6.6.1, 1.6.6.2.1 and 1.6.6.2.2, replace "2.2.7.7" with "2.2.7.2.2, 2.2.7.2.4.1.2, 2.2.7.2.4.4, 2.2.7.2.4.6.2, 2.2.7.2.4.6.3 and 2.2.7.2.4.6.4".

In 4.1.9.1.1, replace "2.2.7.7.1" with "2.2.7.2.4.1.2, 2.2.7.2.4.4, 2.2.7.2.4.6.2, 2.2.7.2.4.6.3 and 2.2.7.2.4.6.4".

In 4.1.9.2.3 (b), replace "2.2.7.2" with "2.2.7.1.2".

In 4.1.9.2.3 (c), replace "2.2.7.5 (a) (i)" with "2.2.7.2.3.2 (a) (i)".

In 5.2.2.1.11.2 (a) (i), replace "2.2.7.7.2.1" with "2.2.7.2.2.1".

For 5.2.2.1.11.2 (d) see amendments to 5.1.5.

In 6.4.8.8 and 6.4.10.3, replace "2.2.7.7.2.4 to 2.2.7.7.2.6" with "2.2.7.2.2.4 to 2.2.7.2.2.6".

In 6.4.12.1 and 6.4.12.2, replace "2.2.7.3.3, 2.2.7.3.4, 2.2.7.4.1, 2.2.7.4.2" with "2.2.7.2.3.1.3, 2.2.7.2.3.1.4, 2.2.7.2.3.3.1, 2.2.7.2.3.3.2".

In 6.4.14, replace "2.2.7.4.5 (a)" with "2.2.7.2.3.3.5 (a)".

"CHAPTER ~~2.7.2.7~~ 2.2.7 Class 7 Radioactive material

NOTE: For Class 7, the type of packaging may have a decisive effect on classification.

~~2.7.1~~ 2.2.7.1 Definitions

~~2.7.1.1~~ 2.2.7.1.1 *Radioactive material* means any material containing radionuclides where both the activity concentration and the total activity in the consignment exceed the values specified in 2.2.7.2.2.1 to 2.2.7.2.2.6.

~~2.7.1.2~~ 2.2.7.1.2 Contamination

Contamination means the presence of a radioactive substance on a surface in quantities in excess of 0.4 Bq/cm² for beta and gamma emitters and low toxicity alpha emitters, or 0.04 Bq/cm² for all other alpha emitters.

Non-fixed contamination means contamination that can be removed from a surface during routine conditions of ~~transport~~ carriage.

Fixed contamination means contamination other than non-fixed contamination.

~~2.7.1.3~~ 2.2.7.1.3 Definitions of specific terms

A_1 and A_2

A_1 means the activity value of special form radioactive material which is listed in the Table in 2.2.7.2.2.1 or derived in 2.2.7.2.2.2 and is used to determine the activity limits for the requirements of ~~these Regulations~~ RID/ADR/ADN.

A_2 means the activity value of radioactive material, other than special form radioactive material, which is listed in the Table in 2.2.7.2.2.1 or derived in 2.2.7.2.2.2 and is used to determine the activity limits for the requirements of RID/ADR/ADN ~~these Regulations~~.

Fissile material means uranium-233, uranium-235, plutonium-239, plutonium-241, or any combination of these radionuclides. Excepted from this definition is:

- (a) Natural uranium or depleted uranium which is unirradiated; and
- (b) Natural uranium or depleted uranium which has been irradiated in thermal reactors only.

Low dispersible radioactive material means either a solid radioactive material or a solid radioactive material in a sealed capsule, that has limited dispersibility and is not in powder form.

Low specific activity (LSA) material means radioactive material which by its nature has a limited specific activity, or radioactive material for which limits of estimated average specific activity apply. External shielding materials surrounding the LSA material shall not be considered in determining the estimated average specific activity.

Low toxicity alpha emitters are: natural uranium; depleted uranium; natural thorium; uranium-235 or uranium-238; thorium-232; thorium-228 and thorium-230 when contained in ores or physical and chemical concentrates; or alpha emitters with a half-life of less than 10 days.

Specific activity of a radionuclide means the activity per unit mass of that nuclide. The specific activity of a material shall mean the activity per unit mass of the material in which the radionuclides are essentially uniformly distributed.

Special form radioactive material means either:

- (a) An indispersible solid radioactive material; or
- (b) A sealed capsule containing radioactive material.

Surface contaminated object (SCO) means a solid object which is not itself radioactive but which has radioactive material distributed on its surfaces.

Unirradiated thorium means thorium containing not more than 10^{-7} g of uranium-233 per gram of thorium-232.

Unirradiated uranium means uranium containing not more than 2×10^3 Bq of plutonium per gram of uranium-235, not more than 9×10^6 Bq of fission products per gram of uranium-235 and not more than 5×10^{-3} g of uranium-236 per gram of uranium-235.

Uranium - natural, depleted, enriched means the following:

Natural uranium means uranium (which may be chemically separated) containing the naturally occurring distribution of uranium isotopes (approximately 99.28% uranium-238, and 0.72% uranium-235 by mass).

Depleted uranium means uranium containing a lesser mass percentage of uranium-235 than in natural uranium.

Enriched uranium means uranium containing a greater mass percentage of uranium-235 than 0.72%. In all cases, a very small mass percentage of uranium-234 is present.

2.2.7.2 **Classification**

2.2.7.2.1 **General provisions**

2.2.7.2.1.1 Radioactive material shall be assigned to one of the UN number specified in Table 2.2.7.2.1.1 depending on the activity level of the radionuclides contained in a package, the fissile or non-fissile properties of these radionuclides, the type of package to be presented for ~~transport~~carriage, and the nature or form of the contents of the package, or special arrangements governing the ~~transport~~carriage operation, in accordance with the provisions laid down in 2.2.7.2.2 to 2.2.7.2.5.

Table 2.2.7.2.1.1 Assignment of UN numbers

Excepted packages

(~~1.5.1.5~~1.7.1.5)

UN 2908	RADIOACTIVE MATERIAL, EXCEPTED PACKAGE - EMPTY PACKAGING
UN 2909	RADIOACTIVE MATERIAL, EXCEPTED PACKAGE - ARTICLES MANUFACTURED FROM NATURAL URANIUM or DEPLETED URANIUM or NATURAL THORIUM
UN 2910	RADIOACTIVE MATERIAL, EXCEPTED PACKAGE - LIMITED QUANTITY OF MATERIAL
UN 2911	RADIOACTIVE MATERIAL, EXCEPTED PACKAGE - INSTRUMENTS or

Table 2.2.7.2.1.1		Assignment of UN numbers	
ARTICLES			
Low specific activity radioactive material			
<u>(2.2.7.2.3.1)</u>			
UN 2912	RADIOACTIVE MATERIAL, LOW SPECIFIC ACTIVITY (LSA-I), non-fissile or fissile-excepted		
UN 3321	RADIOACTIVE MATERIAL, LOW SPECIFIC ACTIVITY (LSA-II), non fissile or fissile-excepted		
UN 3322	RADIOACTIVE MATERIAL, LOW SPECIFIC ACTIVITY (LSA-III), non fissile or fissile-excepted		
UN 3324	RADIOACTIVE MATERIAL, LOW SPECIFIC ACTIVITY (LSA-II), FISSILE		
UN 3325	RADIOACTIVE MATERIAL, LOW SPECIFIC ACTIVITY, (LSA-III), FISSILE		
Surface contaminated objects			
<u>(2.2.7.2.3.2)</u>			
UN 2913	RADIOACTIVE MATERIAL, SURFACE CONTAMINATED OBJECTS (SCO-I or SCO-II), non-fissile or fissile-excepted		
UN 3326	RADIOACTIVE MATERIAL, SURFACE CONTAMINATED OBJECTS (SCO-I or SCO-II), FISSILE		
Type A packages			
<u>(2.2.7.2.4.4)</u>			
UN 2915	RADIOACTIVE MATERIAL, TYPE A PACKAGE, non-special form, non-fissile or fissile-excepted		
UN 3327	RADIOACTIVE MATERIAL, TYPE A PACKAGE, FISSILE, non-special form		
UN 3332	RADIOACTIVE MATERIAL, TYPE A PACKAGE, SPECIAL FORM, non fissile or fissile-excepted		
UN 3333	RADIOACTIVE MATERIAL, TYPE A PACKAGE, SPECIAL FORM, FISSILE		
Type B(U) package			
<u>(2.2.7.2.4.6)</u>			
UN 2916	RADIOACTIVE MATERIAL, TYPE B(U) PACKAGE, non-fissile or fissile-excepted		
UN 3328	RADIOACTIVE MATERIAL, TYPE B(U) PACKAGE, FISSILE		
Type B(M) package			
<u>(2.2.7.2.4.6)</u>			
UN 2917	RADIOACTIVE MATERIAL, TYPE B(M) PACKAGE, non-fissile or fissile-excepted		
UN 3329	RADIOACTIVE MATERIAL, TYPE B(M) PACKAGE, FISSILE		
Type C package			
<u>(2.2.7.2.4.6)</u>			
UN 3323	RADIOACTIVE MATERIAL, TYPE C PACKAGE, non fissile or fissile-excepted		
UN 3330	RADIOACTIVE MATERIAL, TYPE C PACKAGE, FISSILE		
Special arrangement			
<u>(2.2.7.2.5)</u>			
UN 2919	RADIOACTIVE MATERIAL, TRANSPORTED UNDER SPECIAL ARRANGEMENT, non-fissile or fissile-excepted		
UN 3331	RADIOACTIVE MATERIAL, TRANSPORTED UNDER SPECIAL ARRANGEMENT, FISSILE		
Uranium hexafluoride			
<u>(2.2.7.2.4.5)</u>			
UN 2977	RADIOACTIVE MATERIAL, URANIUM HEXAFLUORIDE, FISSILE		
UN 2978	RADIOACTIVE MATERIAL, URANIUM HEXAFLUORIDE, non-fissile or fissile-excepted		

2.2.7.2.2 Determination of activity level

[For reference: existing 2.2.7.7.2.1 and 2.2.7.7.2.2.]

2.2.7.2.2.1 The following basic values for individual radionuclides are given in Table 2.2.7.2.2.1:

- (a) A_1 and A_2 in TBq;
- (b) Activity concentration for exempt material in Bq/g; and
- (c) Activity limits for exempt consignments in Bq.

Table 2.2.7.2.2.1: Basic radionuclides values for individual radionuclides

Insert here the Table of existing 2.2.7.7.2.1 with its footnotes (a) – (g).

2.2.7.2.2.2 For individual radionuclides which are not listed in Table 2.2.7.2.2.1 the determination of the basic radionuclide values referred to in 2.2.7.2.2.1 shall require multilateral approval. It is permissible to use an A_2 value calculated using a dose coefficient for the appropriate lung absorption type as recommended by the International Commission on Radiological Protection, if the chemical forms of each radionuclide under both normal and accident conditions of [transport/carriage](#) are taken into consideration. Alternatively, the radionuclide values in Table 2.2.7.2.2.2 may be used without obtaining competent authority approval.

Table 2.2.7.2.2.2: Basic radionuclide values for unknown radionuclides or mixtures

Radioactive contents	A_1	A_2	Activity concentration for exempt material	Activity limit for exempt consignments
	(TBq)	(TBq)	(Bq/g)	(Bq)
Only beta or gamma emitting nuclides are known to be present	0.1	0.02	1×10^1	1×10^4
Alpha emitting nuclides but no neutron emitters are known to be present	0.2	9×10^{-5}	1×10^{-1}	1×10^3
Neutron emitting nuclides are known to be present or no relevant data are available	0.001	9×10^{-5}	1×10^{-1}	1×10^3

2.2.7.2.2.3 In the calculations of A_1 and A_2 for a radionuclide not in Table 2.2.7.2.2.1, a single radioactive decay chain in which the radionuclides are present in their naturally occurring proportions, and in which no daughter nuclide has a half-life either longer than 10 days or longer than that of the parent nuclide, shall be considered as a single radionuclide; and the activity to be taken into account and the A_1 or A_2 value to be applied shall be those corresponding to the parent nuclide of that chain. In the case of radioactive decay chains in which any daughter nuclide has a half-life either longer than 10 days or greater than that of the parent nuclide, the parent and such daughter nuclides shall be considered as mixtures of different nuclides. [For reference: Existing 2.2.7.7.2.3.]

2.2.7.2.2.4 For mixtures of radionuclides, the determination of the basic radionuclide values referred to in 2.2.7.2.2.1 may be determined as follows:

$$X_m = \frac{1}{\sum_i \frac{f(i)}{X(i)}}$$

where,

- f(i) is the fraction of activity or activity concentration of radionuclide i in the mixture;
- X(i) is the appropriate value of A_1 or A_2 , or the activity concentration for exempt material or the activity limit for an exempt consignment as appropriate for the radionuclide i; and
- X_m is the derived value of A_1 or A_2 , or the activity concentration for exempt material or the activity limit for an exempt consignment in the case of a mixture.

[\[For reference: Existing 2.2.7.7.2.4\]](#)

[2.2.7.2.2.5](#) When the identity of each radionuclide is known but the individual activities of some of the radionuclides are not known, the radionuclides may be grouped and the lowest radionuclide value, as appropriate, for the radionuclides in each group may be used in applying the formulas in [2.2.7.2.2.4](#) and [2.2.7.2.4.4](#). Groups may be based on the total alpha activity and the total beta/gamma activity when these are known, using the lowest radionuclide values for the alpha emitters or beta/gamma emitters, respectively.

[\[For reference: Existing 2.2.7.7.2.5\]](#)

[2.2.7.2.2.6](#) For individual radionuclides or for mixtures of radionuclides for which relevant data are not available, the values shown in Table [2.2.7.2.2.2](#) shall be used.

[\[For reference: Existing 2.2.7.7.2.6\]](#)

[2.2.7.2.3](#) *Determination of other material characteristics*

[2.2.7.2.3.1](#) *Low specific activity (LSA) material*

[2.2.7.2.3.1.1](#) (Reserved)

[2.2.7.2.3.1.2](#) LSA material shall be in one of three groups:

- (a) LSA-I
 - (i) uranium and thorium ores and concentrates of such ores, and other ores containing naturally occurring radionuclides which are intended to be processed for the use of these radionuclides;
 - (ii) Natural uranium, depleted uranium, natural thorium or their compounds or mixtures, providing they are unirradiated and in solid or liquid form;
 - (iii) radioactive material for which the A_2 value is unlimited, excluding material classified as fissile according to [2.2.7.2.3.5](#); or
 - (iv) other radioactive material in which the activity is distributed throughout and the estimated average specific activity does not exceed 30 times the values for activity concentration specified in [2.2.7.2.2.1](#) to [2.2.7.2.2.6](#), excluding material classified as fissile according to [2.2.7.2.3.5](#);
- (b) LSA-II
 - (i) water with tritium concentration up to 0.8 TBq/L; or

- (ii) other material in which the activity is distributed throughout and the estimated average specific activity does not exceed 10^{-4} A₂/g for solids and gases, and 10^{-5} A₂/g for liquids;
- (c) LSA-III - Solids (e.g. consolidated wastes, activated materials), excluding powders, in which:
 - (i) the radioactive material is distributed throughout a solid or a collection of solid objects, or is essentially uniformly distributed in a solid compact binding agent (such as concrete, bitumen, ceramic, etc.);
 - (ii) the radioactive material is relatively insoluble, or it is intrinsically contained in a relatively insoluble matrix, so that, even under loss of packaging, the loss of radioactive material per package by leaching when placed in water for seven days would not exceed 0.1 A₂; and
 - (iii) the estimated average specific activity of the solid, excluding any shielding material, does not exceed 2×10^{-3} A₂/g.

[\[For reference: Existing 2.2.7.3.2\]](#)

[2.2.7.2.3.1.3](#) LSA-III material shall be a solid of such a nature that if the entire contents of a package were subjected to the test specified in [2.2.7.2.3.1.4](#) the activity in the water would not exceed 0.1 A₂.

[\[For reference: Existing 2.2.7.3.3\]](#)

[2.2.7.2.3.1.4](#) LSA-III material shall be tested as follows:

A solid material sample representing the entire contents of the package shall be immersed for 7 days in water at ambient temperature. The volume of water to be used in the test shall be sufficient to ensure that at the end of the 7 day test period the free volume of the unabsorbed and unreacted water remaining shall be at least 10% of the volume of the solid test sample itself. The water shall have an initial pH of 6-8 and a maximum conductivity of 1 mS/m at 20 °C. The total activity of the free volume of water shall be measured following the 7 day immersion of the test sample.

[\[For reference: Existing 2.2.7.3.4\]](#)

[2.2.7.2.3.1.5](#) Demonstration of compliance with the performance standards in [2.2.7.2.3.1.4](#) shall be in accordance with 6.4.12.1 and 6.4.12.2.

[\[For reference: Existing 2.2.7.3.5\]](#)

[2.2.7.2.3.2](#) *Surface contaminated object (SCO)*

SCO is classified in one of two groups:

- (a) SCO-I: A solid object on which:
 - (i) the non-fixed contamination on the accessible surface averaged over 300 cm² (or the area of the surface if less than 300 cm²) does not exceed 4 Bq/cm² for beta and gamma emitters and low toxicity alpha emitters, or 0.4 Bq/cm² for all other alpha emitters; and
 - (ii) the fixed contamination on the accessible surface averaged over 300 cm² (or the area of the surface if less than 300 cm²) does not exceed 4×10^4 Bq/cm²

for beta and gamma emitters and low toxicity alpha emitters, or 4×10^3 Bq/cm² for all other alpha emitters; and

- (iii) the non-fixed contamination plus the fixed contamination on the inaccessible surface averaged over 300 cm² (or the area of the surface if less than 300 cm²) does not exceed 4×10^4 Bq/cm² for beta and gamma emitters and low toxicity alpha emitters, or 4×10^3 Bq/cm² for all other alpha emitters;
- (b) SCO-II: A solid object on which either the fixed or non-fixed contamination on the surface exceeds the applicable limits specified for SCO-I in (a) above and on which:
- (i) the non-fixed contamination on the accessible surface averaged over 300 cm² (or the area of the surface if less than 300 cm²) does not exceed 400 Bq/cm² for beta and gamma emitters and low toxicity alpha emitters, or 40 Bq/cm² for all other alpha emitters; and
 - (ii) the fixed contamination on the accessible surface, averaged over 300 cm² (or the area of the surface if less than 300 cm²) does not exceed 8×10^5 Bq/cm² for beta and gamma emitters and low toxicity alpha emitters, or 8×10^4 Bq/cm² for all other alpha emitters; and
 - (iii) the non-fixed contamination plus the fixed contamination on the inaccessible surface averaged over 300 cm² (or the area of the surface if less than 300 cm²) does not exceed 8×10^5 Bq/cm² for beta and gamma emitters and low toxicity alpha emitters, or 8×10^4 Bq/cm² for all other alpha emitters.

[\[For reference: Existing 2.2.7.5\]](#)

2.2.7.2.3.3 *Special form radioactive material*

2.2.7.2.3.3.1 Special form radioactive material shall have at least one dimension not less than 5 mm. When a sealed capsule constitutes part of the special form radioactive material, the capsule shall be so manufactured that it can be opened only by destroying it. The design for special form radioactive material requires unilateral approval.

[\[For reference: Existing 2.2.7.4.1 as amended\]](#)

2.2.7.2.3.3.2 Special form radioactive material shall be of such a nature or shall be so designed that if it is subjected to the tests specified in 2.2.7.2.3.3.4 to 2.2.7.2.3.3.8, it shall meet the following requirements:

- (a) It would not break or shatter under the impact, percussion and bending tests 2.2.7.2.3.3.5 (a) (b) (c), 2.2.7.2.3.3.6 (a) as applicable;
- (b) It would not melt or disperse in the applicable heat test 2.2.7.2.3.3.5 (d) or 2.2.7.2.3.3.6 (b) as applicable; and
- (c) The activity in the water from the leaching tests specified in 2.2.7.2.3.3.7 and 2.2.7.2.3.3.8 would not exceed 2 kBq; or alternatively for sealed sources, the leakage rate for the volumetric leakage assessment test specified in ISO 9978:1992 "Radiation Protection - Sealed Radioactive Sources - Leakage Test Methods", would not exceed the applicable acceptance threshold acceptable to the competent authority.

[\[For reference: Existing 2.2.7.4.2\]](#)

[2.2.7.2.3.3.3](#) Demonstration of compliance with the performance standards in [2.2.7.2.3.3.2](#) shall be in accordance with 6.4.12.1 and 6.4.12.2.

[For reference: Existing [2.2.7.4.3](#)]

[2.2.7.2.3.3.4](#) Specimens that comprise or simulate special form radioactive material shall be subjected to the impact test, the percussion test, the bending test, and the heat test specified in [2.2.7.2.3.3.5](#) or alternative tests as authorized in [2.2.7.2.3.3.6](#). A different specimen may be used for each of the tests. Following each test, a leaching assessment or volumetric leakage test shall be performed on the specimen by a method no less sensitive than the methods given in [2.2.7.2.3.3.7](#) for indispersible solid material or [2.2.7.2.3.3.8](#) for encapsulated material.

[For reference: Existing [2.2.7.4.4](#)]

[2.2.7.2.3.3.5](#) The relevant test methods are:

- (a) Impact test: The specimen shall drop onto the target from a height of 9 m. The target shall be as defined in 6.4.14;
- (b) Percussion test: The specimen shall be placed on a sheet of lead which is supported by a smooth solid surface and struck by the flat face of a mild steel bar so as to cause an impact equivalent to that resulting from a free drop of 1.4 kg through 1 m. The lower part of the bar shall be 25 mm in diameter with the edges rounded off to a radius of (3.0 ± 0.3) mm. The lead, of hardness number 3.5 to 4.5 on the Vickers scale and not more than 25 mm thick, shall cover an area greater than that covered by the specimen. A fresh surface of lead shall be used for each impact. The bar shall strike the specimen so as to cause maximum damage;
- (c) Bending test: The test shall apply only to long, slender sources with both a minimum length of 10 cm and a length to minimum width ratio of not less than 10. The specimen shall be rigidly clamped in a horizontal position so that one half of its length protrudes from the face of the clamp. The orientation of the specimen shall be such that the specimen will suffer maximum damage when its free end is struck by the flat face of a steel bar. The bar shall strike the specimen so as to cause an impact equivalent to that resulting from a free vertical drop of 1.4 kg through 1 m. The lower part of the bar shall be 25 mm in diameter with the edges rounded off to a radius of (3.0 ± 0.3) mm;
- (d) Heat test: The specimen shall be heated in air to a temperature of 800 °C and held at that temperature for a period of 10 minutes and shall then be allowed to cool.

[For reference: Existing [2.2.7.4.5](#)]

[2.2.7.2.3.3.6](#) Specimens that comprise or simulate radioactive material enclosed in a sealed capsule may be excepted from:

- (a) The tests prescribed in [2.2.7.2.3.3.5](#) (a) and (b) provided the mass of the special form radioactive material:
 - (i) is less than 200 g and they are alternatively subjected to the Class 4 impact test prescribed in ISO 2919:1999 "Radiation protection - Sealed radioactive sources - General requirements and classification"; or
 - (ii) is less than 500 g and they are alternatively subjected to the Class 5 impact test prescribed in ISO 2919:1999 "Radiation protection - Sealed radioactive sources - General requirements and classification"; and

- (b) The test prescribed in 2.7.2.3.3.5 (d) provided they are alternatively subjected to the Class 6 temperature test specified in ISO 2919:1999 "Radiation protection - Sealed radioactive sources - General requirements and classification".

[For reference: Existing 2.2.7.4.6]

2.2.7.2.3.3.7 For specimens which comprise or simulate indispersible solid material, a leaching assessment shall be performed as follows:

- (a) The specimen shall be immersed for 7 days in water at ambient temperature. The volume of water to be used in the test shall be sufficient to ensure that at the end of the 7 day test period the free volume of the unabsorbed and unreacted water remaining shall be at least 10% of the volume of the solid test sample itself. The water shall have an initial pH of 6-8 and a maximum conductivity of 1 mS/m at 20 °C;
- (b) The water with specimen shall then be heated to a temperature of (50 ± 5) °C and maintained at this temperature for 4 hours;
- (c) The activity of the water shall then be determined;
- (d) The specimen shall then be kept for at least 7 days in still air at not less than 30 °C and relative humidity not less than 90%;
- (e) The specimen shall then be immersed in water of the same specification as in (a) above and the water with the specimen heated to (50 ± 5) °C and maintained at this temperature for 4 hours;
- (f) The activity of the water shall then be determined.

[For reference: Existing 2.2.7.4.7]

2.2.7.2.3.3.8 For specimens which comprise or simulate radioactive material enclosed in a sealed capsule, either a leaching assessment or a volumetric leakage assessment shall be performed as follows:

- (a) The leaching assessment shall consist of the following steps:
 - (i) the specimen shall be immersed in water at ambient temperature. The water shall have an initial pH of 6-8 with a maximum conductivity of 1 mS/m at 20 °C;
 - (ii) the water and specimen shall be heated to a temperature of (50 ± 5) °C and maintained at this temperature for 4 hours;
 - (iii) the activity of the water shall then be determined;
 - (iv) the specimen shall then be kept for at least 7 days in still air at not less than 30 °C and relative humidity of not less than 90%;
 - (v) the process in (i), (ii) and (iii) shall be repeated;

- (b) The alternative volumetric leakage assessment shall comprise any of the tests prescribed in ISO 9978:1992 "Radiation Protection - Sealed radioactive sources - Leakage test methods", which are acceptable to the competent authority.

[[For reference: Existing 2.2.7.4.8](#)]

[2.2.7.2.3.4](#) *Low dispersible material*

[2.2.7.2.3.4.1](#) The design for low dispersible radioactive material shall require multilateral approval. Low dispersible radioactive material shall be such that the total amount of this radioactive material in a package shall meet the following requirements:

- (a) The radiation level at 3 m from the unshielded radioactive material does not exceed 10 mSv/h;
- (b) If subjected to the tests specified in 6.4.20.3 and 6.4.20.4, the airborne release in gaseous and particulate forms of up to 100 µm aerodynamic equivalent diameter would not exceed 100 A₂. A separate specimen may be used for each test; and
- (c) If subjected to the test specified in [2.2.7.2.3.1.4](#) the activity in the water would not exceed 100 A₂. In the application of this test, the damaging effects of the tests specified in (b) above shall be taken into account.

[2.2.7.2.3.4.2](#) Low dispersible material shall be tested as follows:

A specimen that comprises or simulates low dispersible radioactive material shall be subjected to the enhanced thermal test specified in 6.4.20.3 and the impact test specified in 6.4.20.4. A different specimen may be used for each of the tests. Following each test, the specimen shall be subjected to the leach test specified in [2.2.7.2.3.1.4](#). After each test it shall be determined if the applicable requirements of [2.2.7.2.3.4.1](#) have been met.

[2.2.7.2.3.4.3](#) Demonstration of compliance with the performance standards in [2.2.7.2.3.4.1](#) and [2.2.7.2.3.4.2](#) shall be in accordance with 6.4.12.1 and 6.4.12.2.

[2.2.7.2.3.5](#) *Fissile material*

Packages containing fissile radionuclides shall be classified under the relevant entry of table [2.2.7.2.1.1](#) for fissile material unless one of the conditions (a) to (d) of this paragraph is met. Only one type of exception is allowed per consignment.

- (a) A mass limit per consignment such that:

$$\frac{\text{mass of uranium - 235 (g)}}{X} + \frac{\text{mass of other fissile material (g)}}{Y} < 1$$

where X and Y are the mass limits defined in Table [2.2.7.2.3.5](#), provided that the smallest external dimension of each package is not less than 10 cm and that either:

- (i) each individual package contains not more than 15 g of fissile material; for unpackaged material, this quantity limitation shall apply to the consignment being carried in or on the conveyance; or

- (ii) the fissile material is a homogeneous hydrogenous solution or mixture where the ratio of fissile nuclides to hydrogen is less than 5% by mass; or
- (iii) there are not more than 5 g of fissile material in any 10 litre volume of material.

Neither beryllium nor deuterium shall be present in quantities exceeding 1% of the applicable consignment mass limits provided in Table 2.2.7.2.3.5, except for deuterium in natural concentration in hydrogen.

- (b) Uranium enriched in uranium-235 to a maximum of 1% by mass, and with a total plutonium and uranium-233 content not exceeding 1% of the mass of uranium-235, provided that the fissile material is distributed essentially homogeneously throughout the material. In addition, if uranium-235 is present in metallic, oxide or carbide forms, it shall not form a lattice arrangement;
- (c) Liquid solutions of uranyl nitrate enriched in uranium-235 to a maximum of 2% by mass, with a total plutonium and uranium-233 content not exceeding 0.002% of the mass of uranium, and with a minimum nitrogen to uranium atomic ratio (N/U) of 2;
- (d) Packages containing, individually, a total plutonium mass not more than 1 kg, of which not more than 20% by mass may consist of plutonium-239, plutonium-241 or any combination of those radionuclides.

Table 2.2.7.2.3.5: Consignment mass limits for exceptions from the requirements for packages containing fissile material

Fissile material	Fissile material mass (g) mixed with substances having an average hydrogen density less than or equal to water	Fissile material mass (g) mixed with substances having an average hydrogen density greater than water
Uranium-235 (X)	400	290
Other fissile material (Y)	250	180

[For reference: Existing 6.4.11.2]

2.2.7.2.4 Classification of packages or unpacked material

The quantity of radioactive material in a package shall not exceed the relevant limits for the package type as specified below.

2.2.7.2.4.1 Classification as excepted package

2.2.7.2.4.1.1 Packages may be classified as excepted packages if:

- (a) They are empty packagings having contained radioactive material;
- (b) They contain instruments or articles in limited quantities;

- (c) They contain articles manufactured of natural uranium, depleted uranium or natural thorium; or
- (d) They contain radioactive material in limited quantities.

2.2.7.2.4.1.2 A package containing radioactive material may be classified as an excepted package provided that the radiation level at any point on its external surface does not exceed 5 µSv/h.

[For reference: Existing 2.2.7.9.2]

Table 2.2.7.2.4.1.2: Activity limits for excepted packages

Physical state of contents (1)	Instruments or article		Materials Package limits ^a (4)
	Item limits ^a (2)	Package limits ^a (3)	
Solids			
special form	$10^{-2} A_1$	A_1	$10^{-3} A_1$
other form	$10^{-2} A_2$	A_2	$10^{-3} A_2$
Liquids	$10^{-3} A_2$	$10^{-1} A_2$	$10^{-4} A_2$
Gases			
tritium	$2 \times 10^{-2} A_2$	$2 \times 10^{-1} A_2$	$2 \times 10^{-2} A_2$
special form	$10^{-3} A_1$	$10^{-2} A_1$	$10^{-3} A_1$
other forms	$10^{-3} A_2$	$10^{-2} A_2$	$10^{-3} A_2$

^a For mixtures of radionuclides, see 2.2.7.2.2.4 to 2.2.7.2.2.6.

[For reference: Existing Table 2.2.7.7.1.2.1]

2.2.7.2.4.1.3 Radioactive material which is enclosed in or is included as a component part of an instrument or other manufactured article may be classified under UN No. 2911, RADIOACTIVE MATERIAL, EXCEPTED PACKAGE - INSTRUMENTS or ARTICLES provided that:

- (a) The radiation level at 10 cm from any point on the external surface of any unpackaged instrument or article is not greater than 0.1 mSv/h; and
- (b) Each instrument or manufactured article bears the marking "RADIOACTIVE" except:
- (i) radioluminescent time-pieces or devices;
 - (ii) consumer products that either have received regulatory approval according to 1.5.1.41.7.1.4 (d) or do not individually exceed the activity limit for an exempt consignment in Table 2.2.7.2.2.1 (column 5), provided such products are ~~transported~~carried in a package that bears the marking "RADIOACTIVE" on an internal surface in such a manner that warning of the presence of radioactive material is visible on opening the package; and
- (c) The active material is completely enclosed by non-active components (a device performing the sole function of containing radioactive material shall not be considered to be an instrument or manufactured article); and
- (d) The limits specified in columns 2 and 3 of Table 2.2.7.2.4.1.2 are met for each individual item and each package, respectively.

[For reference: Existing 2.2.7.9.3]

[2.2.7.2.4.1.4](#) Radioactive material with an activity not exceeding the limit specified in column 4 of Table [2.2.7.2.4.1.2](#), may be classified under UN [No. 2910](#), RADIOACTIVE MATERIAL, EXCEPTED PACKAGE - LIMITED QUANTITY OF MATERIAL provided that:

- (a) The package retains its radioactive contents under routine conditions of ~~transport~~[carriage](#); and
- (b) The package bears the marking "RADIOACTIVE" on an internal surface in such a manner that a warning of the presence of radioactive material is visible on opening the package.

[For reference: Existing [2.2.7.9.4](#)]

[2.2.7.2.4.1.5](#) An empty packaging which had previously contained radioactive material with an activity not exceeding the limit specified in column 4 of Table [2.2.7.2.4.1.2](#) may be classified under UN [No. 2908](#), RADIOACTIVE MATERIAL, EXCEPTED PACKAGE - EMPTY PACKAGING, provided that:

- (a) It is in a well-maintained condition and securely closed;
- (b) The outer surface of any uranium or thorium in its structure is covered with an inactive sheath made of metal or some other substantial material;
- (c) The level of internal non-fixed contamination, when averaged over any 300 cm², does not exceed:
 - (i) 400 Bq/cm² for beta and gamma emitters and low toxicity alpha emitters; and
 - (ii) 40 Bq/cm² for all other alpha emitters; and
- (d) Any labels which may have been displayed on it in conformity with [5.2.2.1](#) ~~42~~[11.1](#) are no longer visible.

[For reference: Existing [2.2.7.9.6](#)]

[2.2.7.2.4.1.6](#) Articles manufactured of natural uranium, depleted uranium or natural thorium and articles in which the sole radioactive material is unirradiated natural uranium, unirradiated depleted uranium or unirradiated natural thorium may be classified under UN [No. 2909](#), RADIOACTIVE MATERIAL, EXCEPTED PACKAGE - ARTICLES MANUFACTURED FROM NATURAL URANIUM or DEPLETED URANIUM or NATURAL THORIUM, provided that the outer surface of the uranium or thorium is enclosed in an inactive sheath made of metal or some other substantial material.

[For reference: Existing [2.2.7.9.5](#)]

[2.2.7.2.4.2](#) *Classification as Low specific activity (LSA) material*

Radioactive material may only be classified as LSA material if the conditions of [2.2.7.2.3.1](#) and [4.1.9.2](#) are met.

[2.2.7.2.4.3](#) *Classification as Surface contaminated object (SCO)*

Radioactive material may be classified as SCO if the conditions of [2.2.7.2.3.2.1](#) and [4.1.9.2](#) are met.

| [2.2.7.2.4.4](#) *Classification as Type A package*

Packages containing radioactive material may be classified as Type A packages provided that the following conditions are met:

Type A packages shall not contain activities greater than the following:

- (a) For special form radioactive material - A_1 ; or
- (b) For all other radioactive material - A_2 .

For mixtures of radionuclides whose identities and respective activities are known, the following condition shall apply to the radioactive contents of a Type A package:

$$\sum_i \frac{B(i)}{A_1(i)} + \sum_j \frac{C(j)}{A_2(j)} \leq 1$$

where $B(i)$ is the activity of radionuclide i as special form radioactive material;

$A_1(i)$ is the A_1 value for radionuclide i ;

$C(j)$ is the activity of radionuclide j as other than special form radioactive material; and

$A_2(j)$ is the A_2 value for radionuclide j .

| [\[For reference: Existing 2.2.7.7.1.4\]](#)

| [2.2.7.2.4.5](#) *Classification of Uranium hexafluoride*

Uranium hexafluoride shall only be assigned to UN Nos. 2977, RADIOACTIVE MATERIAL, URANIUM HEXAFLUORIDE, FISSILE, or 2978, RADIOACTIVE MATERIAL, URANIUM HEXAFLUORIDE, non-fissile or fissile-excepted.

| [2.2.7.2.4.5.1](#) Packages containing uranium hexafluoride shall not contain:

- (a) A mass of uranium hexafluoride different from that authorized for the package design;
- (b) A mass of uranium hexafluoride greater than a value that would lead to an ullage smaller than 5 % at the maximum temperature of the package as specified for the plant systems where the package shall be used; or
- (c) Uranium hexafluoride other than in solid form or at an internal pressure above atmospheric pressure when presented for ~~transport~~[carriage](#).

| [2.2.7.2.4.6](#) *Classification as Type B(U), Type B(M) or Type C packages*

| [2.2.7.2.4.6.1](#) Packages not otherwise classified in [2.2.7.2.4](#) ([2.2.7.2.4.1](#) to [2.2.7.2.4.5](#)) shall be classified in accordance with the competent authority approval certificate for the package issued by the country of origin of design.

2.2.7.2.4.6.2 A package may only be classified as a Type B(U) if it does not contain:

- (a) Activities greater than those authorized for the package design;
- (b) Radionuclides different from those authorized for the package design; or
- (c) Contents in a form, or a physical or chemical state different from those authorized for the package design;

as specified in the certificate of approval.

[\[For reference: Existing 2.2.7.7.1.5.1\]](#)

2.2.7.2.4.6.3 A package may only be classified as a Type B(M) if it does not contain:

- (a) Activities greater than those authorized for the package design;
- (b) Radionuclides different from those authorized for the package design; or
- (c) Contents in a form, or a physical or chemical state different from those authorized for the package design;

as specified in the certificate of approval.

[\[For reference: Existing 2.2.7.7.1.5.1\]](#)

2.2.7.2.4.6.4 A package may only be classified as a Type C if it does not contain:

- (a) Activities greater than those authorized for the package design;
- (b) Radionuclides different from those authorized for the package design; or
- (c) Contents in a form, or physical or chemical state different from those authorized for the package design;

as specified in the certificate of approval.

[\[For reference: Existing 2.2.7.7.1.6\]](#)

2.2.7.2.5 *Special arrangements*

Radioactive material shall be classified as transported under special arrangement when it is intended to be ~~transported~~carried in accordance with ~~1-5.41.7.4~~".

~~2.2.8.1.6~~~~2-8-2-5~~ (c) ~~(ii)~~ In the first sentence of the second indent, replace "corrosion rate on steel" with "corrosion rate on either steel" and insert "when tested on both materials" at the end.

Add a new note at the end to read as follows:

"NOTE: Where an initial test on either steel or aluminium indicates the substance being tested is corrosive the follow up test on the other metal is not required."

PART 3

Amend the heading/title to read as follows:

“PART 3
Dangerous goods list, special provisions and exceptions
~~AND~~
~~LIMITED QUANTITIES AND EXCEPTED~~
~~QUANTITIES EXCEPTIONS”.~~

Chapter 3.1

3.1.2.2 Delete "each supplemented with the technical name of the goods (see 3.1.2.8.1)" after examples (a) and (b).

Chapter 3.2

3.2.1 Amend the explanatory text for Column 7 to read as follows:

“Column ~~(7a)~~ “Limited Quantities”

Contains an alphanumeric code with the following meaning:

- “LQ0” signifies that no exemption from the provisions of RID/ADR/ADN exists for the dangerous goods packed in limited quantities;
- All the other alphanumeric codes starting with the letters “LQ” signify that the provisions of RID/ADR/ADN are not applicable if the conditions indicated in Chapter 3.4 are fulfilled (general conditions of 3.4.1 and conditions of 3.4.3, 3.4.4, 3.4.5 and 3.4.6, as appropriate, for the relevant code).

Column (7b) “Excepted Quantities”

Contains an alphanumeric code with the following meaning:

- “E0” signifies that no exemption from the provisions of RID/ADR/ADN exists for the dangerous goods in excepted quantities;
- All the other alphanumeric codes starting with the letter “E” signify that the provisions of RID/ADR/ADN are not applicable if the conditions indicated in Chapter 3.5 are fulfilled.”.

~~this column provides the maximum quantity per inner packaging or article for transporting the carriage dangerous goods as limited quantities in accordance with Chapter 3.4.~~

~~Column 7b “Excepted Quantities” this column provides an alpha numeric code described in sub-section 3.5.1.2 and which indicates the maximum quantity per inner and outer packaging for transporting the carriage dangerous goods as excepted quantities in accordance with Chapter 3.5.”.~~

Dangerous goods list Table A

Renumber column (7) as (7a) and insert a new column (7b) with the heading "Excepted quantities" [and a reference to Chapter 3.5](#). Insert the following common heading for both columns (7a) and (7b): "Limited and Excepted quantity **provisions**".

Insert a new row below the headings with the corresponding reference paragraphs as follows:

	(2)	(3)	(4)	(5)	(6)	(7a)	(7b)	(8)	(9)	(10)	(11)
	3.1.2	2.0	2.0	2.0.1.3	3.3	3.4	3.5	4.1.4	4.1.4	4.2.5 4.3.2	4.2.5

In column (7a) replace "None" with "0" wherever it appears.

~~Delete the entries for which SP 320 has been assigned in column (6) (applies to UN Nos. 1366, 1370, 2005, 2445, 3051, 3052, 3053, 3076, 3433 and 3461). [Entries already deleted in RID/ADR/ADN 2007.]~~

Add E0 in column (7b) for:

- All goods of Classes 1, [5.2, 6.2](#) and 7;
- ~~All goods of Divisions 2.1, 2.3~~ [Class 2 for which only label 2.1 has been assigned in column \(5\), 5.2 and 6.2;](#)
- ~~All goods of Class 2 for which label 2.3 (with or without other label) has been assigned in column (5);~~
- All goods of [Class 2, for which labels 2.2+5.1 have been assigned in column \(5\)](#) ~~Division 2.2 with a subsidiary risk in column (4)~~ and UN Nos. 1044, 1950, 2037, 2857 and 3164;
- UN Nos. 1204, 2059, 3064, 3256, 3269, 3343, 3357, 3379 and 3473 in Class 3;
- All goods of Class 3 ~~with a subsidiary risk in column (4)~~ [for which labels 3+6.1, 3+8 or 3+6.1+8 have been assigned in column \(5\)](#), packing group I;
- All goods of ~~Division-Class~~ [4.1](#), packing group I, and UN Nos. ~~1327~~, 2304, 2448, 2555, 2556, 2557, 2907, 3176 (packing groups II and III), 3221 to 3240, 3319, ~~and~~ 3344 ~~and 3360~~;
- All goods of ~~Division-Class~~ [4.2](#), packing group I, ~~and UN 1856~~;
- All goods of ~~Division-Class~~ [4.3](#), packing group I, and UN 3292;
- All goods of ~~Division-Class~~ [5.1](#), packing group I, and UN Nos. 2426 and 3356;
- UN Nos. 1600, 1700, 2016, 2017, 2312 and 3250 of ~~Division-Class~~ [6.1](#);
- All goods of Class 8, packing group I, and UN Nos. 1774, 2028, 2215 (MOLTEN), 2576, 2794, 2795, 2800, 2803, 2809 and 3028;
- UN Nos. 1845, 2807, 2990, 3072, 3090, 3166, 3171, 3245, 3257, 3258, 3268, 3316, ~~and 3334, 3335, 3359 and 3363~~ of Class 9.

Add E1 in column (7b) for:

- All goods of Division 2.2, [for which only label 2.2 has been assigned in column \(5\)](#) ~~without subsidiary risk in column (4)~~;
- All goods of Class 3 [for which only label No 3 has been assigned in column \(5\)](#) ~~without a subsidiary risk in column (4)~~, packing group III, except for UN Nos. 2059, 3256 and 3269;
- All goods of Class 3 ~~with a subsidiary risk in column (4)~~ [for which labels 3+6.1 or 3+8 have been assigned in column \(5\)](#), packing group III;
- All goods of ~~Division-Class~~ [4.1](#), packing group III, except for UN Nos. 2304, 2448 and 3176;
- All goods of ~~Division-Class~~ [4.2](#), packing group III;

- All goods of ~~Division-Class~~ 4.3, packing group III;
- All goods of ~~Division-Class~~ 5.1, packing group III;
- All goods of ~~Division-Class~~ 6.1, packing group III;
- All goods of Class 8, packing group III, except for UN Nos. 2215 (MOLTEN), 2803 and 2809;
- All goods of Class 9, packing group III, except for UN 1845, 2807, 3257, 3258 and 3268.

Add E2 in column (7b) for:

- All goods of Class 3 for which only label No 3 has been assigned in column (5) ~~without a subsidiary risk in column (4)~~, packing group II, except for UN Nos. 1204, 2059, 3064, 3269 and 3357;
- All goods of Class 3 ~~with a subsidiary risk in column (4)~~ for which labels 3+6.1, 3+6.1+8 or 3+8 have been assigned in column (5), packing group II;
- All goods of ~~Division-Class~~ 4.1, packing group II, except for UN Nos. 2555, 2556, 2557, 2907, 3176, 3319 and 3344;
- All goods of ~~Division-Class~~ 4.2, packing group II;
- All goods of ~~Division-Class~~ 4.3, packing group II, except for UN 3292;
- All goods of ~~Division-Class~~ 5.1, packing group II, except for UN 3356;
- All goods of Class 8, packing group II, except for UN Nos. 1774, 2028 and 2576;
- All goods of Class 9, packing group II, except for UN Nos. 3090, 3091, 3480 and 3481.

Add E3 in column (7b) for all goods of Class 3 for which only label No 3 has been assigned in column (5) ~~without a subsidiary risk in column (4)~~, packing group I, except for UN Nos. 2059 and 3379.

Add E4 in column (7b) for all goods of ~~Division-Class~~ 6.1, packing group II, except for UN Nos. 1600, 1700, 2016, 2017, 2312 and 3250.

Add E5 in column (7b) for all goods of ~~Division-Class~~ 6.1, packing group I.

Delete "TP9" each time it appears in column (11) with the exception of UN 3375.

Delete "TP12" each time it appears in column (11).

~~For UN Nos. 0504, 3354, 3355, 3356, 3357 and 3374, add "0" in column (7a).~~

For UN 3357, replace "LQ4" with "LQ0" in column (7a).

For UN Nos. 1092, 1238, 1239 and 1244, packing group I, in column (10), replace "T14" with "T22" and add "TP35" in column (11).

For UN Nos. 1098, 1143, 1163, 1595, 1695, 1752, 1809, 2334, 2337, 2646 and 3023, packing group I, in column (10), replace "T14" with "T20" and add "TP35" in column (11).

For UN Nos. 1162, 1196, 1250, 1298, 1305, 1724, 1728, 1747, 1753, 1762, 1763, 1766, 1767, 1769, 1771, 1781, 1784, 1799, 1800, 1801, 1804, 1816, 2434, 2435, 2437, 2985, 2986, 2987, 3361 and 3362, replace "P001" with "P010" in column (8) and add "TP7" in column (11).

For UN Nos. 1162, 1196, 1298, 1724, 1728, 1747, 1753, 1762, 1763, 1766, 1767, 1769, 1771, 1781, 1784, 1799, 1800, 1801, 1804, 1816, 1818, 2434, 2435, 2437, 2985, 2986 and 2987, delete "IBC02" in column (8).

For UN Nos. 1162, 1196, 1298, 1724, 1728, 1747, 1753, 1762, 1763, 1766, 1767, 1769, 1771, 1781, 1784, 1799, 1800, 1801, 1804, 1816, 1818, 2434, 2435 and 2437, replace "T7" with "T10" in column (10).

For UN Nos. 1170, 1987 and 1993, [all packing groups](#), delete "330" in column (6).

For UN Nos. 1183, 1242 and 2988, replace "T10" with "T14".

For UN Nos. 1185, 1994 and 2480, packing group I, add "T22" in column (10) and "TP2-~~TP13~~" in column (11) respectively. [For UN 2480, add "FL" in column \(14\) and "663" in column \(20\).](#)

~~For UN 1239, packing group I, and for UN Nos. 1781, 1804, 1818, 2986 and 2987, add "TP13" in column (11).~~

For UN Nos. 1250 and 1305, replace "I" with "II" in column (5) and replace "T11" with "T10" in column (10). [Replace "LQ3" with "LQ4" in column \(7a\). Add "IBC02" in column \(8\). Replace "MP7 MP17" with "MP19" in column \(9b\). Replace "L10CH" with "L4BH" in column \(12\). Delete "TU14 TE21" in column \(13\). In column \(14\), replace category "1" with category "2" and \[ADR only\] replace tunnel code "C1E" with tunnel code "D1E".](#)

For UN Nos. ~~1463~~-1473, 1484, 1485, 1487, 1488, 1490, 1493, 1494, 1495, 1512, 1514, 1751, 2465, 2468, 2627 and 3247, add ~~"B2" in column (9).~~ ["V11" in column \(16\).](#)

For UN Nos. 1851, 3248 and 3249, packing groups II and III, delete "PP6" in column (9).

For UN Nos. 2813 and 3131, packing group I, add "T9" in column (10) and "TP7 TP33" in column (11) respectively. [Add "AT" in column \(14\). For UN 2813, add "X423" in column \(20\). For UN 3131, add "X482" in column \(20\).](#)

For UN ~~Nos. 2814 and~~ 3373, insert "BK1 BK2" in column (10). [For UN 2814, covered by the entry for animal carcasses of UN 2814. To be checked by the working group.](#)

For UN ~~Nos. 2814, 2900 and~~ 3373, insert "341" in column (6). [For UN Nos 2814 and 2900, covered by the entry for animal carcasses of UN 2814. To be checked by the working group.](#)

For UN Nos. 2908, 2909, 2910 and 2911, in columns (8) to (11), replace "See Chapter [2.2.7](#)" with "See Chapter [1.57](#)".

~~For UN Nos. 2913, 3321, 3322, 3324, 3325 and 3326, insert "336" in column (6).~~

~~For UN Nos. 2916, 2917, 3328 and 3329 insert "337" in column (6).~~

For UN Nos. 2985, 2986, 3361 and 3362, replace "T11" with "T14".

For UN Nos. 3077 and 3082, add "335" in column (6).

~~For UN Nos. 3129, 3130 and 3148, replace "g/kg" with "ml/l" in column (7a).~~

For UN Nos. 3269 and 3316, add "340" in column (6).

For UN Nos. 3361 and 3362, delete "IBC01" in column (8) ~~and add "TP27" in column (11).~~

- UN 0411 The amendment does not apply to the English version. [In the French text, insert “, PENTHRITE” before “, PETN” in column \(2\).](#)
- UN 1017 In column (45), add "+5.1". [In column \(3b\), replace “2TC” with “2TOC”. In column \(20\), replace “268” with “265”.](#)
- UN 1344 In column (2), add "(PICRIC ACID)" after "TRINITROPHENOL".
- ~~UN 1356 — In column (2), add "(TNT)" after "TRINITROTOLUENE".~~
- UN 1474 In column (6), add "332".
- UN 1569 In column (10), replace "T3" with "T20" and in column (11), replace "TP33" with "TP2 ~~TP13~~".
[\[The RID/ADR tank code may also need to be modified.\]](#)
- UN 1647 For packing group I, add "T20" in column (10) and "TP2~~TP13~~" in column (11).
- UN 1744 In column (8), replace "P601" with "P804" and in column (9a), delete "PP82".
[\[Delete “PR6” in column \(8\) and delete PR6 in 4.1.4.4\]](#)
- ~~UN 1790 (2 entries) — In the French text, delete "solution" in column (2).~~
- UN 1818 Replace "~~L~~LQ22" with "LQ0" in column (7a), replace "P001" with "P010" in column (8).
- UN 2031 For packing group II, in column (2), add "at least 65%, but" after "with", in column (45), add "+5.1", and in column (9), add "B15". [In column \(20\), replace “80” with “85”.](#)
- UN 2059 In column (8), for packing group II, add "IBC02" and for packing group III, add "IBC03".
- UN 2823 In column (9), add "B3".
- ~~UN 2844 — In column (9), delete "B2".~~
- UN 3077 In column (10), add "BK2".
- UN 3082 Add "PP1" in column (9).
- UN 3090 In column (2), amend the name and description to read: "LITHIUM METAL BATTERIES (including lithium alloy batteries)".
- UN 3091 In column (2), insert "METAL" after "LITHIUM" (twice) and “(including lithium alloy batteries)” after “WITH EQUIPMENT”.
- UN 3129 For packing group I, add "T14" in column (10) and "TP2 TP7" in column (11) respectively. For packing group II, add "T11" in column (10) and "TP2" in column (11) respectively. For packing group III, add "T7" in column (10) and "TP1" in column (11) respectively.
- UN 3148 For packing group I, add "T9" in column (10) and "TP2 TP7" in column (11) respectively. For packing group II, add "T7" in column (10) and "TP2" in column (11) respectively. For packing group III, add "T7" in column (10) and "TP1" in column (11) respectively.

- UN 3344 In column (2), add "(PENTAERYTHRITOL TETRANITRATE; PETN)" after "TETRANITRATE".
- UN 3432 In column (9), add "~~B2~~, B4" adjacent to "IBC08". [In column \(16\) add "V11"](#).
- UN 3468 In column (2), add at the end: "or HYDROGEN IN A METAL HYDRIDE STORAGE SYSTEM CONTAINED IN EQUIPMENT or HYDROGEN IN A METAL HYDRIDE STORAGE SYSTEM PACKED WITH EQUIPMENT".
- UN 3473 In column (2), replace "FUEL CELL CARTRIDGES" with "FUEL CELL CARTRIDGES or FUEL CELL CARTRIDGES CONTAINED IN EQUIPMENT or FUEL CELL CARTRIDGES PACKED WITH EQUIPMENT", in column (8), replace "P003" with "P004", and in column (9a), delete "PP88".

Add the following new entries:

[Information proposed for RID only is shown in italics.]

(1)	(2)	(3a)	(3b)	(4)	(5)	(6)	(7a)	(7b)	(8)	(9a)	(9b)	(10)	(11)	(12)	(13)	(14)	(15)	(16)	(17)	(18)	(19)	(20)
0505	SIGNALS, DISTRESS, ship		1.4G		<u>1.4</u>		0 LQ0	E0	P135		<u>MP23</u> <u>MP24</u>						<u>2</u> <u>(E)</u>	<u>W2</u> <u>V2</u>		<u>CW1</u> <u>CV1</u> <u>CV2</u> <u>CV3</u>	<u>S1</u>	<u>1.4G</u>
0506	SIGNALS, DISTRESS, ship		1.4S		<u>1.4</u>		<u>LQ0</u> 0	E0	P135		<u>MP23</u> <u>MP24</u>						<u>4</u> <u>(E)</u>	<u>W2</u>		<u>CW1</u> <u>CV1</u> <u>CV2</u> <u>CV3</u>	<u>CE1</u> <u>S1</u>	<u>1.4S</u>
0507	SIGNALS, SMOKE		1.4S		<u>1.4</u>		<u>LQ0</u> 0	E0	P135		<u>MP23</u> <u>MP24</u>						<u>4</u> <u>(E)</u>	<u>W2</u>		<u>CW1</u> <u>CV1</u> <u>CV2</u> <u>CV3</u>	<u>CE1</u> <u>S1</u>	<u>1.4S</u>
0508	1-HYDROXY-BENZOTRIAZOLE, ANHYDROUS, dry or wetted with less than 20% water, by mass		1.3C		<u>1</u>		<u>LQ0</u> 0	E0	P114(b)	PP48 PP50	<u>MP20</u>						<u>1</u> <u>(C5000</u> <u>D)</u>	<u>W2</u> <u>W3</u> <u>V2</u> <u>V3</u>		<u>CW1</u> <u>CV1</u> <u>CV2</u> <u>CV3</u>	<u>S1</u>	<u>1.3C</u>
2031	NITRIC ACID, other than red fuming, with less than 65% nitric acid	8	<u>CO1</u>	II	<u>8</u>		++ <u>LQ22</u>	E2	P001 IBC02	PP81 B15	<u>MP15</u>	T8	TP2	<u>L4BN</u>		<u>AT</u>	<u>2</u> <u>(E)</u>				<u>CE6</u>	<u>80</u>
3474	1-HYDROXYBENZOTRIAZOLE, ANHYDROUS, WETTED with not less than 20% water, by mass	4.1	<u>D</u>	I	<u>4.1</u>	28	0 <u>LQ0</u>	E0	P406	PP48	<u>MP2</u>						<u>1</u> <u>(B)</u>	<u>W1</u>			<u>S17</u>	<u>40</u>
3475	ETHANOL AND GASOLINE MIXTURE or ETHANOL AND MOTOR SPIRIT MIXTURE or ETHANOL AND PETROL MIXTURE, with more than 10% ethanol	3	<u>F1</u>	II	<u>3</u>	333	++ <u>LQ4</u>	E2	P001 IBC02		<u>MP19</u>	T4	TP1	<u>LGB</u> <u>F</u>		<u>FL</u>	<u>2</u> <u>(D1E)</u>				<u>CE7</u> <u>S2</u> <u>S20</u>	<u>33</u>

(1)	(2)	(3a)	(3b)	(4)	(5)	(6)	(7a)	(7b)	(8)	(9a)	(9b)	(10)	(11)	(12)	(13)	(14)	(15)	(16)	(17)	(18)	(19)	(20)
3476	FUEL CELL CARTRIDGES or FUEL CELL CARTRIDGES CONTAINED IN EQUIPMENT or FUEL CELL CARTRIDGES PACKED WITH EQUIPMENT, containing water-reactive substances	4.3	W3		4.3	328 334	500 ml or 500 g LQ10 LQ11	E0	P004								[...] [...]	W1 V1		CW23 CV23	[...]	423
3477	FUEL CELL CARTRIDGES or FUEL CELL CARTRIDGES CONTAINED IN EQUIPMENT or FUEL CELL CARTRIDGES PACKED WITH EQUIPMENT, containing corrosive substances	8	C11		8	328 334	1 L or 1 kg LQ12 LQ13	E0	P004								[...]				[...]	80
3478	FUEL CELL CARTRIDGES or FUEL CELL CARTRIDGES CONTAINED IN EQUIPMENT or FUEL CELL CARTRIDGES PACKED WITH EQUIPMENT, containing liquefied flammable gas	2+	2F			328 338	120 ml LQ1	E0	P004								[...]				[...]	23
3479	FUEL CELL CARTRIDGES or FUEL CELL CARTRIDGES CONTAINED IN EQUIPMENT or FUEL CELL CARTRIDGES PACKED WITH EQUIPMENT, containing hydrogen in metal hydride	2+	2F			328 339	120 ml LQ1	E0	P004								[...]				[...]	23

(1)	(2)	(3a)	(3b)	(4)	(5)	(6)	(7a)	(7b)	(8)	(9a)	(9b)	(10)	(11)	(12)	(13)	(14)	(15)	(16)	(17)	(18)	(19)	(20)
3480	LITHIUM ION BATTERIES (including lithium ion polymer batteries)	9	M4		II	188 230 310 636	θ LQ0	E0	P903 P903a P903b								2 (E)				CE2	90
3481	LITHIUM ION BATTERIES CONTAINED IN EQUIPMENT or LITHIUM ION BATTERIES PACKED WITH EQUIPMENT (including lithium ion polymer batteries)	9	M4		II	188 230 636	θ LQ0	E0	P903 P903a P903b								2 (E)				CE2	90

Chapter 3.3

3.3.1 **SP188** At the beginning, replace "Lithium cells" with "Cells".

In (a), replace "lithium equivalent content is not more than 1.5 g" with "Watt-hour rating is not more than 20 Wh".

In (b), replace "aggregate lithium-equivalent content is not more than 8 g;" with "Watt-hour rating is not more than 100 Wh. Lithium ion batteries subject to this provision shall be marked with the Watt-hour rating on the outside case;".

Replace (d) and (e) with the following new sub-paragraphs (d) to (i):

- "(d) Cells and batteries, except when installed in equipment, shall be packed in inner packagings that completely enclose the cell or battery. Cells and batteries shall be protected so as to prevent short circuits. This includes protection against contact with conductive materials within the same packaging that could lead to a short circuit. The inner packagings shall be packed in strong outer packagings which conform to the provisions of 4.1.1.1, 4.1.1.2, and 4.1.1.5;
- (e) Cells and batteries when installed in equipment shall be protected from damage and short circuit, and the equipment shall be equipped with an effective means of preventing accidental activation. When lithium batteries are installed in equipment, the equipment shall be packed in strong outer packagings constructed of suitable material of adequate strength and design in relation to the packaging's capacity and its intended use unless the battery is afforded equivalent protection by the equipment in which it is contained;
- (f) Except for packages containing no more than four cells installed in equipment or no more than two batteries installed in equipment, each package shall be marked with the following:
- (i) an indication that the package contains "lithium metal" or "lithium ion" cells or batteries, as appropriate;
 - (ii) an indication that the package shall be handled with care and that a flammability hazard exists if the package is damaged;
 - (iii) an indication that special procedures shall be followed in the event the package is damaged, to include inspection and repacking if necessary; and
 - (iv) a telephone number for additional information;
- (g) Each consignment of one or more packages marked in accordance with paragraph (f) shall be accompanied with a document including the following:
- (i) an indication that the package contains "lithium metal" or "lithium ion" cells or batteries, as appropriate;
 - (ii) an indication that the package shall be handled with care and that a flammability hazard exists if the package is damaged;

- (iii) an indication that special procedures shall be followed in the event the package is damaged, to include inspection and repacking if necessary; and
- (iv) a telephone number for additional information;
- (h) Except when lithium batteries are installed in equipment, each package shall be capable of withstanding a 1.2 m drop test in any orientation without damage to cells or batteries contained therein, without shifting of the contents so as to allow battery to battery (or cell to cell) contact and without release of contents; and
- (i) Except when lithium batteries are installed in or packed with equipment, packages shall not exceed 30 kg gross mass."

In the last sentence, delete ", except in the case of a lithium ion cell the "lithium-equivalent content" in grams is calculated to be 0.3 times the rated capacity in ampere hours".

Insert a new last paragraph to read as follows:

"Separate entries exist for lithium metal batteries and lithium ion batteries to facilitate the ~~transport~~carriage of these batteries for specific modes of ~~transport~~carriage and to enable the application of different emergency response actions."

SP198 Replace "UN Nos. 1210, ~~UN~~-1263 and ~~UN~~-3066" with "UN Nos. 1210, 1263, 3066, 3469 and 3470".

SP199 Replace "are considered insoluble. See ISO 3711:1990 *“Lead chromate pigments and lead chromate - molybdate pigments - Specifications and methods of test”*." with "(see ISO 3711:1990 *“Lead chromate pigments and lead chromate-molybdate pigments – Specifications and methods of test”*) are considered insoluble and are not subject to ~~these Regulations~~the requirements of RID/ADR/ADN unless they meet the criteria for inclusion in another ~~hazard-class-or-division~~".

SP236 In the last sentence, replace “Column 7” with “Column 7a”.

SP251 In the first paragraph, replace “Column (7)” with “Column 7a”~~“the word “NONE” has been indicated in column 7” with “the quantity 0 has been indicated in column 7a”~~
In the last paragraph, insert "for limited quantities" after "quantity limits" and replace "7" with "7a".

SP289 Replace "Air bags or seat-belts" with "Air bag inflators, air bag modules or seat-belt pretensioners".

~~**SP301** In the fourth and the last sentences, replace "in column 7" by "in column 7a".~~

SP307 In (b) Insert "and/or mineral calcium sulphate" after "dolomite".

SP310 At the beginning, replace "100 lithium cells" with "100 cells".

~~**SP320** Delete.~~

SP328 Amend to read as follows:

"**328** This entry applies to fuel cell cartridges including when contained in equipment or packed with equipment. Fuel cell cartridges installed in or integral to a fuel cell system are regarded as contained in equipment. Fuel cell cartridge means an article that stores fuel for discharge into the fuel cell through a valve(s) that controls the discharge of fuel into the fuel cell. Fuel cell cartridges, including when contained in equipment, shall be designed and constructed to prevent fuel leakage under normal conditions of ~~transport~~carriage.

Fuel cell cartridge design types using liquids as fuels shall pass an internal pressure test at a pressure of 100 kPa (gauge) without leakage.

Except for fuel cell cartridges containing hydrogen in metal hydride which shall be in compliance with Special Provision 339, each fuel cell cartridge design type shall be shown to pass a 1.2 meter drop test onto an unyielding surface in the orientation most likely to result in failure of the containment system with no loss of contents.

Fuel cell cartridges containing hydrogen in a metal hydride ~~transported~~carried under this entry shall have a water capacity less than or equal to 120 ml."

SP330 Delete.

Add the following new special provisions:

"**332** Magnesium nitrate hexahydrate is not subject to ~~these Regulations~~ the requirements of RID/ADR/ADN.

333 Ethanol and gasoline, motor spirit or petrol mixtures for use in spark-ignition engines (e.g. in automobiles, stationary engines and other engines) shall be assigned to this entry regardless of variations in volatility.

334 A fuel cell cartridge may contain an activator provided it is fitted with two independent means of preventing unintended mixing with the fuel during ~~transport~~carriage.

335 Mixtures of solids which are not subject to ~~these Regulations~~the requirements of RID/ADR/ADN and environmentally hazardous liquids or solids shall be classified as UN 3077 and may be ~~transported~~carried under this entry, provided there is no free liquid visible at the time the substance is loaded or at the time the packaging or transport unit is closed. Each transport unit shall be leakproof when used as a bulk packaging. Sealed packets and articles containing less than 10 ml of an environmentally hazardous liquid, absorbed into a solid material but with no free liquid in the packet or article, or containing less than 10 g of an environmentally hazardous solid, are not subject to ~~these Regulations~~the requirements of RID/ADR/ADN.

336 A single package of non-combustible solid LSA-II or LSA-III material, if [to be] carried by air, shall not contain an activity greater than 3000 A₂.

- 337 Type B(U) and Type B(M) packages, if [to be] transported by air, shall not contain activities greater than the following:
- (a) For low dispersible radioactive material: as authorized for the package design as specified in the certificate of approval;
 - (b) For special form radioactive material: 3000 A₁ or 100 000 A₂, whichever is the lower; or
 - (c) For all other radioactive material: 3000 A₂.
- 338 Each fuel cell cartridge ~~transported~~carried under this entry and designed to contain a liquefied flammable gas shall:
- (a) Be capable of withstanding, without leakage or bursting, a pressure of at least two times the equilibrium pressure of the contents at 55 °C;
 - (b) Not contain more than 200 ml of liquefied flammable gas with a vapour pressure not exceeding 1 000 kPa at 55 °C; and
 - (c) Pass the hot water bath test prescribed in ~~6.2.4.1~~6.2.4.3.2.1 of Chapter 6.2.
- 339 Fuel cell cartridges containing hydrogen in a metal hydride ~~transported~~carried under this entry shall have a water capacity less than or equal to 120 ml.

The pressure in the fuel cell cartridge shall not exceed 5 MPa at 55 °C. The design type shall withstand, without leaking or bursting, a pressure of two (2) times the design pressure of the cartridge at 55 °C or 200 kPa more than the design pressure of the cartridge at 55 °C, whichever is greater. The pressure at which this test is conducted is referred to in the Drop Test and the Hydrogen Cycling Test as the "minimum shell burst pressure".

Fuel cell cartridges shall be filled in accordance with procedures provided by the manufacturer. The manufacturer shall provide the following information with each fuel cell cartridge:

- (a) Inspection procedures to be carried out before initial filling and before refilling of the fuel cell cartridge;
- (b) Safety precautions and potential hazards to be aware of;
- (c) Method for determining when the rated capacity has been achieved;
- (d) Minimum and maximum pressure range;
- (e) Minimum and maximum temperature range; and
- (f) Any other requirements to be met for initial filling and refilling including the type of equipment to be used for initial filling and refilling.

The fuel cell cartridges shall be designed and constructed to prevent fuel leakage under normal conditions of ~~transport~~carriage. Each cartridge design type,

including cartridges integral to a fuel cell, shall be subjected to and shall pass the following tests:

Drop test

A 1.8 metre drop test onto an unyielding surface in four different orientations:

- (a) Vertically, on the end containing the shut-off valve assembly;
- (b) Vertically, on the end opposite to the shut-off valve assembly;
- (c) Horizontally, onto a steel apex with a diameter of 38 mm, with the steel apex in the upward position; and
- (d) At a 45° angle on the end containing the shut-off valve assembly.

There shall be no leakage, determined by using a soap bubble solution or other equivalent means on all possible leak locations, when the cartridge is charged to its rated charging pressure. The fuel cell cartridge shall then be hydrostatically pressurized to destruction. The recorded burst pressure shall exceed 85% of the minimum shell burst pressure.

Fire test

A fuel cell cartridge filled to rated capacity with hydrogen shall be subjected to a fire engulfment test. The cartridge design, which may include a vent feature integral to it, is deemed to have passed the fire test if :

- (a) The internal pressure vents to zero gauge pressure without rupture of the cartridge; or
- (b) The cartridge withstands the fire for a minimum of 20 minutes without rupture.

Hydrogen cycling test

This test is intended to ensure that a fuel cell cartridge design stress limits are not exceeded during use.

The fuel cell cartridge shall be cycled from not more than 5% rated hydrogen capacity to not less than 95% rated hydrogen capacity and back to not more than 5% rated hydrogen capacity. The rated charging pressure shall be used for charging and temperatures shall be held within the operating temperature range. The cycling shall be continued for at least 100 cycles.

Following the cycling test, the fuel cell cartridge shall be charged and the water volume displaced by the cartridge shall be measured. The cartridge design is deemed to have passed the hydrogen cycling test if the water volume displaced by the cycled cartridge does not exceed the water volume displaced by an uncycled cartridge charged to 95% rated capacity and pressurized to 75% of its minimum shell burst pressure.

Production leak test

Each fuel cell cartridge shall be tested for leaks at $15\text{ °C} \pm 5\text{ °C}$, while pressurized to its rated charging pressure. There shall be no leakage, determined by using a soap bubble solution or other equivalent means on all possible leak locations.

Each fuel cell cartridge shall be permanently marked with the following information:

- (a) The rated charging pressure in ~~megapascals~~ (MPa);
- (b) The manufacturer's serial number of the fuel cell cartridges or unique identification number; and
- (c) The date of expiry based on the maximum service life (year in four digits; month in two digits).

340 Chemical kits, first aid kits and polyester resin kits containing dangerous substances in inner packagings which do not exceed the quantity limits for excepted quantities applicable to individual substances as specified in column 7b of [Table A of Chapter 3.2](#), ~~the Dangerous Goods List~~ may be ~~transported~~ carried in accordance with Chapter 3.5. ~~Division~~ Class 5.2 substances, although not individually authorized as excepted quantities in ~~the Dangerous Goods List~~ column 7b of Table A of Chapter 3.2, are authorized in such kits and are assigned Code E2 (see 3.5.1.2).

[341 Bulk ~~transport~~ carriage of infectious substances in BK1 and BK2 bulk containers is only permitted for infectious substances contained in animal material as defined in 1.2.1 (See ~~4.3.2.4.1~~ 7.3.2.6.1)."]

[To be discussed by the Working Group. The Working Group may also want to check whether 7.3.2.6.1 should be adapted including for example the addition of requirements for 3373.]

Chapter 3.4

~~3.4.1~~ ~~—————~~ ~~In the second and the third sentences, replace "in column 7" with "in column 7a".~~

~~—————~~ ~~In the third sentence, replace "the word "None"" with "the quantity "0"".~~

~~3.4.2, 3.4.3, 3.4.4, 3.4.5~~ Replace "Column (7)" with "Column (7a)".

Chapter 3.5

Add a new Chapter 3.5 to read as follows:

**"CHAPTER 3.5
DANGEROUS GOODS
PACKED IN EXCEPTED QUANTITIES**

3.5.1 Excepted quantities

3.5.1.1 Excepted quantities of dangerous goods of certain classes, other than articles, meeting the provisions of this Chapter are not subject to any other provisions of ~~these Regulations~~ [RID/ADR/ADN](#) except for:

- (a) The training requirements in Chapter 1.3;
- (b) The classification procedures and packing group criteria in Part 2, Classification;
- (c) The packaging requirements of 4.1.1.1, 4.1.1.2, 4.1.1.4, ~~4.1.1.4.1~~ and 4.1.1.6 ~~in Part 4.~~

NOTE: In the case of radioactive material, the requirements for radioactive material in excepted packages in ~~1.5.1.5~~ [1.7.1.5](#) apply.

3.5.1.2 Dangerous goods which may be carried as excepted quantities in accordance with the provisions of this Chapter are shown in column 7b of ~~the dangerous goods~~ [Table A of Chapter 3.2](#) list by means of an alphanumeric code as follows:

Code	Maximum quantity per inner packaging	Maximum quantity per outer packaging
E0	Not permitted as Excepted Quantity	
E1	30g/30ml	1kg/1L
E2	30g/30ml	500g/500ml
E3	30g/30ml	300g/300ml
E4	1g/1ml	500g/500ml
E5	1g/1ml	300g/300ml

For gases, the volume indicated for inner packagings refers to the water capacity of the inner receptacle and the volume indicated for outer packagings refers to the combined water capacity of all inner packagings within a single outer package.

3.5.1.3 Where dangerous goods in excepted quantities for which different codes are assigned are packaged together the total quantity per outer packaging shall be limited to that corresponding to the most restrictive Code.

3.5.2 Packagings

Packagings used for the ~~transport~~[carriage](#) of dangerous goods in excepted quantities shall be in compliance with the following:

- (a) There shall be an inner packaging and each inner packaging shall be constructed of plastic (when used for liquid dangerous goods it shall have a thickness of not less than 0.2 mm), or of glass, porcelain, stoneware, earthenware or metal (see also 4.1.1.2) and the closure of each inner packaging shall be held securely in place with wire, tape or other positive means; any receptacle having a neck with moulded screw threads shall have a leak proof threaded type cap. The closure shall be resistant to the contents;

- (b) Each inner packaging shall be securely packed in an intermediate packaging with cushioning material in such a way that, under normal conditions of ~~transport~~carriage, they cannot break, be punctured or leak their contents. The intermediate packaging shall completely contain the contents in case of breakage or leakage, regardless of package orientation. For liquid dangerous goods, the intermediate packaging shall contain sufficient absorbent material to absorb the entire contents of the inner packaging. In such cases, the absorbent material may be the cushioning material. Dangerous goods shall not react dangerously with cushioning, absorbent material and packaging material or reduce the integrity or function of the materials;
- (c) The intermediate packaging shall be securely packed in a strong, rigid outer packaging (wooden, fibreboard or other equally strong material);
- (d) Each package type shall be in compliance with the provisions in 3.5.1.4;
- (e) Each package shall be of such a size that there is adequate space to apply all necessary markings; and
- (f) Overpacks may be used and may also contain packages of dangerous goods or goods not subject to ~~these Regulations~~the requirements of RID/ADR/ADN.

3.5.3 Tests for packages

3.5.3.1 The complete package as prepared for ~~transport~~carriage, with inner packagings filled to not less than 95% of their capacity for solids or 98% for liquids, shall be capable of withstanding, as demonstrated by testing which is appropriately documented, without breakage or leakage of any inner packaging and without significant reduction in effectiveness:

- (a) Drops onto a rigid, non-resilient flat and horizontal surface from a height of 1.8 m:
 - (i) Where the sample is in the shape of a box, it shall be dropped in each of the following orientations:
 - flat on the base;
 - flat on the top;
 - flat on the longest side;
 - flat on the shortest side;
 - on a corner;
 - (ii) Where the sample is in the shape of a drum, it shall be dropped in each of the following orientations:
 - diagonally on the top chime, with the centre of gravity directly above the point of impact;
 - diagonally on the base chime;
 - flat on the side.

NOTE: Each of the above drops may be performed on different but identical packages.

- (b) A force applied to the top surface for a duration of 24 hours, equivalent to the total weight of identical packages if stacked to a height of 3 m (including the drop sample).

3.5.3.2 For the purposes of testing, the substances to be ~~transported~~ carried in the packaging may be replaced by other substances except where this would invalidate the results of the tests. For solids, when another substance is used, it must have the same physical characteristics (mass, grain size, etc.) as the substance to be carried. In the drop tests for liquids, when another substance is used, its relative density (specific gravity) and viscosity should be similar to those of the substance to be ~~transported~~ carried.


3.5.4 Marking of packages

3.5.4.1 Packages containing excepted quantities of dangerous goods prepared in accordance with this Chapter shall be durably and legibly marked with the mark shown in Figure 3.5.1. The label numbers indicated in column (5) of Table A of Chapter 3.2 ~~for primary hazard class or, when assigned, the division of~~ each of the dangerous goods contained in the package shall be shown in the mark. Where the name of the consignor or consignee is not shown elsewhere on the package this information shall be included within the mark.

3.5.4.2 The dimensions of the mark shall be a minimum of 100 mm × 100 mm.

3.5.4.3 An overpack containing dangerous goods in excepted quantities shall display the markings required by 3.5.1.5.1, unless such markings on packages within the overpack are clearly visible.

Figure 3.5.1



Excepted quantities mark

Hatching and symbol of the same colour, black or red,
on white or suitable contrasting background

- * The ~~Class or, when assigned, the Division Number(s)~~ label numbers indicated in column (5) of Table A of Chapter 3.2 shall be shown in this location.
- ** The name of the consignor or of the consignee shall be shown in this location if not shown elsewhere on the package.

	reconstituted wood (4F)	400 kg
	fibreboard (4G)	400 kg
	expanded plastics (4H1)	60 kg
	solid plastics (4H2)	400 kg
Single packagings		Maximum capacity (see 4.1.3.3)
Drums		
	steel, non-removable head (1A1)	450 l
Jerricans		
	steel, non-removable head (3A1)	60 l
Composite packagings		
	plastics receptacle in steel drums (6HA1)	250 l

P099 Insert "for these goods" before "by the competent authority" and add the following new sentence at the end: "A copy of the competent authority approval shall accompany each consignment or the transport document shall include an indication that the packaging was approved by the competent authority."

P114(b) Add the following new special packing provision:

"PP48 For UN No. 0508, metal packagings shall not be used."

In special packing provision PP50, replace "For UN [Nos.](#) 0160 and ~~UN~~0161" with "For UN Nos. 0160, 0161 and 0508" and replace "required" with "necessary".

P200 In paragraph (~~35~~) (b), amend the second sentence to read as follows:

"The use of test pressures and filling ratios other than those in the table is permitted, except where ([410](#)), special packing provision "o" applies, provided that:

- (i) the criterion of ([410](#)), special packing provision "r" is met when applicable; or
- (ii) the above criterion is met in all other cases."

In paragraph ([410](#)), in the third paragraph of special packing provision "k", replace "assemblies (groups)" with "groups".

In paragraph ([410](#)), amend special packing provision "n" to read as follows:

"n: Cylinders and individual cylinders in a bundle shall contain not more than 5 kg of the gas. When bundles containing UN 1045 Fluorine, compressed are divided into groups of cylinders in accordance with special packing provision "k" each group shall contain not more than 5 kg of the gas."

In paragraph ([104](#)), insert a new special packing provision "[ra](#)" to read as follows:

"[ra](#): The filling ratio of this gas shall be limited such that, if complete decomposition occurs, the pressure does not exceed two thirds of the test pressure of the pressure receptacle."

In paragraph (410), add a new paragraph at the end of special packing provision "z" to read as follows:

"Mixtures containing UN 2192 germane, other than mixtures of up to 35% germane in hydrogen or nitrogen or up to 28% germane in helium or argon, shall be filled to a pressure such that, if complete decomposition of the germane occurs, two thirds of the test pressure of the pressure receptacle shall not be exceeded."

In Table 1, amend the values in columns "Test pressure" and "Maximum working pressure" as follows:

UN No.	Name	Test pressure, bar		Maximum working pressure
		Existing	Amended	
1660	Nitric oxide, compressed	200	225	33

In Table 2: For UN 1017 add "5.1" in column "Subsidiary risk".

For UN 2192 replace "1.02" with "0.064" in column "Filling ratio" and add ", ra" in column "Special packing provisions".

For UN 2203 delete "d, " in column "Special packing provisions" (twice).

For UN 2676, insert ", ra" in column "Special packing provisions".

For UN 2189, add a new test-pressure/filling-ratio entry as follows:

Test pressure, bar	Filling ratio
200	1.08

In Table 2, amend the values in column "Filling ratio" as follows:

UN No.	Name	Test pressure, bar	Filling ratio
1011	Butane	10	0.52
1013	Carbon dioxide	190	0.68
1013	Carbon dioxide	250	0.76
1020	Chloropentafluoroethane (R115)	25	1.05
1022	Chlorotrifluoromethane (R13)	250	1.11
1035	Ethane	120	0.30
1035	Ethane	300	0.40
1048	Hydrogen bromide	60	1.51
1080	Sulphur hexafluoride	70	1.06
1080	Sulphur hexafluoride	140	1.34
1080	Sulphur hexafluoride	160	1.38
1962	Ethylene	300	0.38
1973	R502	31	1.01
1976	Octafluorocyclobutane (RC318)	11	1.32
1982	Tetrafluoromethane (R14)	200	0.71
1982	Tetrafluoromethane (R14)	300	0.90
1984	Trifluoromethane (R23)	190	0.88
1984	Trifluoromethane (R23)	250	0.96
2035	1,1,1-trifluoroethane (R143a)	35	0.73
2036	Xenon	130	1.28
2193	Hexafluoroethane (R116)	200	1.13
2196	Tungsten hexafluoride	10	3.08
2198	Phosphorus pentafluoride	300	1.25

UN No.	Name	Test pressure, bar	Filling ratio
2424	Octafluoropropane (R218)	25	1.04
2454	Methyl fluoride (R41)	300	0.63
2599	R503	31	0.12
2599	R503	42	0.17
2599	R503	100	0.64

In Table 2, amend the values in columns "Test pressure" and "Filling ratio" as follows:

UN No.	Name	Test pressure, bar		Filling ratio
		Existing	Amended	
1005	Ammonia, anhydrous	33	29	0.54
1018	Chlorodifluoromethane (R22)	29	27	Unchanged
1021	1-Chloro-1,2,2,2-tetrafluoroethane (R124)	12	11	Unchanged
1027	Cyclopropane	20	18	0.55
1028	Dichlorodifluoromethane (R12)	18	16	Unchanged
1030	1,1-Difluoroethane (R152a)	18	16	Unchanged
1053	Hydrogen sulphide	55	48	Unchanged
1077	Propylene	30	27	Unchanged
1079	Sulphur dioxide	14	12	Unchanged
1978	Propane	25	23	0.43
2204	Carbonyl sulphide	26	30	0.87
2676	Stibine	20	200	0.49
3159	1,1,1,2-Tetrafluoroethane (R134a)	22	18	1.05
3220	Pentafluoroethane (R125)	36	35	0.87
3296	Heptafluoropropane (R227ea)	15	13	1.21
3338	R407A	36	32	Unchanged
3339	R407B	38	33	Unchanged
3340	R407C	35	30	Unchanged

P406 Add the following new special packing provision:

PP48 For UN No. 3474, metal packagings shall not be used."

P601 In (2), delete "or additionally, for UN [No](#) 1744 only, in polyvinylidene fluoride (PVDF) inner packagings,".

Delete PP82.

P620 ~~In (a) (i) and (ii), replace "watertight" with "leakproof".~~

Amend sub-paragraph (b) to read as follows:

"A rigid outer packaging. The smallest external dimension shall be not less than 100 mm."

In additional requirement 2 (b), replace "6.3.1.1" with "6.3.3".

Insert the following new additional requirement:

"(4.) Alternative packagings for the ~~transport~~carriage of animal material may be authorized by the competent authority ~~in accordance with the provisions of 4.1.3.7.~~".

P621 In the second sentence, delete "and the special provisions of 4.1.8".

P650 In (6), replace "6.3.2.5" with "6.3.5.3" and "6.3.2.2 to 6.3.2.4" with "6.3.5.2".

Insert the following new additional requirement at the end:

"Additional requirement:

(1) Alternative packagings for the ~~transport~~carriage of animal material may be authorized by the competent authority ~~in accordance with the provisions of 4.1.3.7.~~".

P801 Insert ", except 4.1.1.3," after "provisions of 4.1.1".

P903, P903a and P903b In the first row after the packing instruction number, replace "and 3091" with ", 3091, 3480 and 3481".

Delete "lithium" before "cells and batteries" (twice).

Add the following new packing instructions **P004** and **P804**:

P004	PACKING INSTRUCTION	P004
	This instruction applies to UN Nos. 3473, 3476, 3477, 3478 and 3479	
	The following packagings are authorized provided the general provisions of 4.1.1.1, 4.1.1.2, 4.1.1.3, 4.1.1.6 and 4.1.3 are met:	
	(1) For fuel cell cartridges, packagings conforming to the packing group II performance level; and	
	(2) For fuel cell cartridges contained in equipment or packed with equipment, strong outer packagings. Large robust equipment (see 4.1.3.8) containing fuel cell cartridges may be transported carried unpackaged. When fuel cell cartridges are packed with equipment, they shall be packed in inner packagings or placed in the outer packaging with cushioning material or divider(s) so that the fuel cell cartridges are protected against damage that may be caused by the movement or placement of the contents within the outer packaging. Fuel cell cartridges which are installed in equipment shall be protected against short circuit and the entire system shall be protected against inadvertent operation.	

P804	PACKING INSTRUCTION	P804
This instruction applies to UN 1744.		
The following packagings are authorized provided the general provisions of 4.1.1 and 4.1.3 are met and the packagings are hermetically sealed:		
(1) Combination packagings with a maximum gross mass of 25 kg, consisting of one or more glass inner packaging(s) with a maximum capacity of 1.3 litres each and filled to not more than 90% of their capacity, the closure(s) of which shall be physically held in place by any means capable of preventing back-off or loosening by impact or vibration during transport carriage, together with cushioning and absorbent material sufficient to absorb the entire contents of the glass inner packaging(s), further packed in 1A2, 1B2, 1N2, 1H2, 1D, 1G, 4A, 4B, 4C1, 4C2, 4D, 4F, 4G or 4H2 outer packagings.		
(2) Combination packagings consisting of metal or polyvinylidene fluoride (PVDF) inner packagings, not exceeding 5 litres in capacity individually packed with absorbent material sufficient to absorb the contents and inert cushioning material in 1A2, 1B2, 1N2, 1H2, 1D, 1G, 4A, 4B, 4C1, 4C2, 4D, 4F, 4G or 4H2 outer packagings with a maximum gross mass of 75 kg. Inner packagings shall not be filled to more than 90% of their capacity. The closure of each inner packaging shall be physically held in place by any means capable of preventing back-off or loosening of the closure by impact or vibration during transport carriage;		
(3) Packagings consisting of:		
Outer packagings:		
Steel or plastic drums, removable head (1A2 or 1H2) tested in accordance with the test requirements in 6.1.5 at a mass corresponding to the mass of the assembled package either as a packaging intended to contain inner packagings, or as a single packaging intended to contain solids or liquids, and marked accordingly;		
Inner packagings:		
Drums and composite packagings (1A1, 1B1, 1N1, 1H1 or 6HA1) meeting the requirements of Chapter 6.1 for single packagings, subject to the following conditions:		
(a) The hydraulic pressure test shall be conducted at a pressure of at least 300 kPa (3 bar) (gauge pressure);		
(b) The design and production leakproofness tests shall be conducted at a test pressure of 30 kPa (0,3 bar);		
(c) They shall be isolated from the outer drum by the use of inert shock-mitigating cushioning material which surrounds the inner packaging on all sides;		
(d) Their capacity shall not exceed 125 litres;		
(e) Closures shall be of a screw type that are:		
(i) Physically held in place by any means capable of preventing back-off or loosening of the closure by impact or vibration during transport carriage;		
(ii) Provided with a cap seal;		
(f) The outer and inner packagings shall be subjected periodically to an internal inspection and leakproofness test according to (b) at intervals of not more than two and a half years; and		
(g) The outer and inner packagings shall bear in clearly legible and durable characters:		

P804	PACKING INSTRUCTION	P804
<p>(i) the date (month, year) of the initial test and the latest periodic test and inspection of the inner packaging; and</p> <p>(ii) the name or authorized symbol of the expert performing the tests and inspections;</p> <p>(4) Pressure receptacles, provided that the general provisions of 4.1.3.6 are met.</p> <p>(a) They shall be subjected to an initial test and periodic tests every 10 years at a pressure of not less than 1 MPa (10 bar) (gauge pressure);</p> <p>(b) They shall be subjected periodically to an internal inspection and leakproofness test at intervals of not more than two and a half years;</p> <p>(c) They may not be equipped with any pressure relief device;</p> <p>(d) Each pressure receptacle shall be closed with a plug or valve(s) fitted with a secondary closure device; and</p> <p>(e) The materials of construction for the pressure receptacle, valves, plugs, outlet caps, luting and gaskets shall be compatible with each other and with the contents.</p>		

4.1.4.2 **IBC01, IBC02 and IBC03** Delete the additional requirement.

IBC02 Add a new special packing provision to read as follows:

"B15 For UN 2031 with more than 55% nitric acid, the permitted use of rigid plastics IBCs and of composite IBCs with a rigid plastics inner receptacle shall be two years from their date of manufacture."

~~**IBC03** — In the special packing provision B11, insert at the beginning "Notwithstanding the provisions of 4.1.1.10".~~

[IBC05, IBC06, IBC07 and IBC08 In special packing provision B2, delete "packing group II".]

[To be discussed by the Working Group:

IBC05 V1 is assigned to all goods of PGII except for UN 3244. It is proposed to add V11 in column (16) for UN 3244 and for all goods of PGI.

IBC06 Only V12 is assigned to some goods of PG III. It is proposed to add V11 in column (16) for these goods (UN Nos. 1313, 1318, 1330, 2714, 2715, 2925, 2926, 3089, 3179 and 3180).

For goods of PG II, either V1 and/or V11 is assigned.

PG I, For UN Nos. 1491, 2466 et 2547, it is proposed to add V11 in column (16).

IBC07 For goods of PG II, either V1 and/or V11 is assigned.

For PG I, it is proposed to add V11 in column (16).

IBC08 For goods of PG II, either V1 and/or V11 is assigned.

For PGIII, it is proposed to add V11 in column (16) except when V1 is already assigned in column (16).]

IBC99 Insert "for these goods" before "by the competent authority" and add the following new sentence at the end: "A copy of the competent authority approval shall accompany each consignment or the transport document shall

include an indication that the packaging was approved by the competent authority".

IBC520 For UN 3109, in the entry for tert-Butyl peroxy-3,5,5-trimethylhexanoate, not more than 32% in diluent type A (third entry), replace "32%" with "37%".

For UN 3119, in the entry for Di-(2-ethylhexyl) peroxydicarbonate, not more than 52%, stable dispersion, in water (ninth entry), replace "52%" with "62%".

Insert the following new entries:

UN No.	Organic peroxide	Type of IBC	Maximum quantity (litres)	Control temperature	Emergency temperature
3109	tert-Butyl peroxybenzoate, not more than 32% in diluent type A	31A	1250		
3109	1,1-Di-(tert-Butylperoxy)cyclohexane, not more than 37% in diluent type A	31A	1250		
3119	tert-Amyl peroxy-pivalate, not more than 32% in diluent type A	31A	1250	+10	+15
3119	tert-Butyl peroxyneodecanoate, not more than 52%, stable dispersion, in water	31A	1250	-5	+5
3119	Di-(2-neodecanoylperoxyisopropyl)benzene, not more than 42%, stable dispersion, in water	31A	1250	-15	-5
3119	3-Hydroxy-1,1-dimethylbutyl peroxy-neodecanoate, not more than 52%, stable dispersion, in water	31A	1250	-15	-5

4.1.4.3 **LP99** Insert "for these goods" before "by the competent authority" and add the following new sentence at the end: "A copy of the competent authority approval shall accompany each consignment or the transport document shall include an indication that the packaging was approved by the competent authority".

4.1.6.1-2 Delete the second and third ~~and fourth~~ sentences ("Pressure receptacles for UN 1001 acetylene ... compatible with the pressure receptacles.").

4.1.8 Replace "~~(Division-Class 6.2)~~" with "of Category A (~~Division-Class 6.2~~, UN 2814 and UN 2900)".

4.1.8.2 Replace "liquids shall be filled into packagings, including IBCs, which" with "liquids shall only be filled into packagings which".

4.1.8.3 Delete "For UN No. 2814 and UN No. 2900," and "and assignment to UN Nos 2814 or ~~UN~~ 2900".

4.1.8.4 Delete "thoroughly" and add "to nullify any hazard" after "sterilized".

4.1.8.5 Replace with the text of existing 6.3.2.8.

4.1.9.1.1 Add at the end: "The types of packages for radioactive materials covered by ~~these Regulations~~[RID/ADR](#), are:

- (a) Excepted package (see ~~4.5.1.5~~[1.7.1.5](#));
- (b) Industrial package Type 1 (Type IP-1 package);
- (c) Industrial package Type 2 (Type IP-2 package);
- (d) Industrial package Type 3 (Type IP-3 package);
- (e) Type A package;
- (f) Type B(U) package;
- (g) Type B(M) package;
- (h) Type C package.

Packages containing fissile material or uranium hexafluoride are subject to additional requirements."

4.1.9.1.6 to 4.1.9.1.11 Insert the following new paragraphs:

"4.1.9.1.6 Before the first shipment of any package, the following requirements shall be fulfilled:

- (a) If the design pressure of the containment system exceeds 35 kPa (gauge), it shall be ensured that the containment system of each package conforms to the approved design requirements relating to the capability of that system to maintain its integrity under that pressure;
- (b) For each Type B(U), Type B(M) and Type C package and for each package containing fissile material, it shall be ensured that the effectiveness of its shielding and containment and, where necessary, the heat transfer characteristics and the effectiveness of the confinement system, are within the limits applicable to or specified for the approved design;
- (c) For packages containing fissile material, where, in order to comply with the requirements of 6.4.11.1, neutron poisons are specifically included as components of the package, checks shall be performed to confirm the presence and distribution of those neutron poisons.

[For reference: Text of existing [5.1.5.1.1](#)]

4.1.9.1.7 Before each shipment of any package, the following requirements shall be fulfilled:

- (a) For any package it shall be ensured that all the requirements specified in the relevant provisions of ~~these Regulations~~[RID/ADR](#) have been satisfied;
- (b) It shall be ensured that lifting attachments which do not meet the requirements of 6.4.2.2 have been removed or otherwise rendered incapable of being used for lifting the package, in accordance with 6.4.2.3;

- (c) For each package requiring competent authority approval, it shall be ensured that all the requirements specified in the approval certificates have been satisfied;
- (d) Each Type B(U), Type B(M) and Type C package shall be held until equilibrium conditions have been approached closely enough to demonstrate compliance with the requirements for temperature and pressure unless an exemption from these requirements has received unilateral approval;
- (e) For each Type B(U), Type B(M) and Type C package, it shall be ensured by inspection and/or appropriate tests that all closures, valves, and other openings of the containment system through which the radioactive contents might escape are properly closed and, where appropriate, sealed in the manner for which the demonstrations of compliance with the requirements of 6.4.8.8 and 6.4.10.3 were made;
- (f) For each special form radioactive material, it shall be ensured that all the requirements specified in the approval certificate and the relevant provisions of ~~these Regulations~~[RID/ADR](#) have been satisfied;
- (g) For packages containing fissile material the measurement specified in 6.4.11.4 (b) and the tests to demonstrate closure of each package as specified in 6.4.11.7 shall be performed where applicable;
- (h) For each low dispersible radioactive material, it shall be ensured that all the requirements specified in the approval certificate and the relevant provisions of ~~these Regulations~~[RID/ADR](#) have been satisfied.

[For reference: [Text of existing 5.1.5.1.2](#)]

4.1.9.1.8 The consignor shall also have a copy of any instructions with regard to the proper closing of the package and any preparation for shipment before making any shipment under the terms of the certificates.

[For reference: [Text of existing 5.1.5.3.2 second sentence](#)]

4.1.9.1.9 Except for consignments under exclusive use, the transport index of any package or overpack shall not exceed 10, nor shall the criticality safety index of any package or overpack exceed 50.

[For reference: [Text of existing 2.2.7.8.1](#)]

4.1.9.1.10 Except for packages or overpacks ~~transported-carried~~ under exclusive use ~~by rail or by road~~ under the conditions specified in [7.5.11, CV33 \(3.5\)\(a\)](#), ~~7.2.3.1.2 (a), or under exclusive use and special arrangement by vessel or by air under the conditions specified in 7.2.3.2.1 or 7.2.3.3.3 respectively~~, the maximum radiation level at any point on any external surface of a package or overpack shall not exceed 2 mSv/h.

[For reference: [Text of existing 2.2.7.8.2](#)]

4.1.9.1.11 The maximum radiation level at any point on any external surface of a package or overpack under exclusive use shall not exceed 10 mSv/h."

[For reference: [Text of existing 2.2.7.8.3](#)]

4.1.9.3 Insert a new sub-section to read as follows:

"4.1.9.3 *Packages containing fissile material*

Unless not classified as fissile in accordance with [2.2.7.2.3.5](#), packages containing fissile material shall not contain:

- (a) A mass of fissile material different from that authorized for the package design;
- (b) Any radionuclide or fissile material different from those authorized for the package design; or
- (c) Contents in a form or physical or chemical state, or in a spatial arrangement, different from those authorized for the package design;

as specified in their certificates of approval where appropriate."

[\[For reference: Text of existing 2.2.7.7.1.7\]](#)

Chapter 4.2

~~Wherever it appears, replace the word "shipper" with "consignor" (apply to 4.2.1.9.1 (twice), 4.2.2.7.1, 4.2.3.6.1 and 4.2.4.5.5).~~

4.2.5.2.6 **T23** For UN 3119, in the entry for Di-(3,5,5-trimethylhexanoyl) peroxide, not more than 38% in diluent type A, add "or type B" after "type A".

Insert the following new entry:

UN No	Substance	Min. test pressure (bar)	Min. shell thickness (mm-reference steel)	Bottom opening requirements	Pressure-relief requirements	Degree of filling	Control temp.	Emergency temp.
3119	tert-Amyl peroxyneodecanoate, not more than 47% in diluent type A						-10	-5

4.2.5.3 Delete TP12.

Add the following new Special Provision:

"**TP35** Portable tank instruction T14 prescribed in ~~the Model Regulations annexed to the 14th revised edition of the Recommendations on the Transport of Dangerous Goods~~[RID/ADR applicable up to 31 December 2008](#) may continue to be applied until 31 December 2014."

PART 5

Chapter 5.1

5.1.2.1 Add ~~at the end:~~ ", except as required in 5.2.2.1.1211." after "unless the markings and the labels representative of all dangerous goods contained in the overpack are visible".

5.1.3.2 Replace "Tanks and ~~intermediate bulk containers~~ IBCs" with "Packagings, including IBCs, and tanks".

5.1.5.1 Delete. Renumber subsequent paragraphs 5.1.5.2 to 5.1.5.3.3 accordingly.

Consequential amendments:

Section 5.1.5 Amend all references to renumbered paragraphs, as appropriate.

6.4.23.14 (h) Replace "5.1.5.2.2" with "5.1.5.1.2".

6.4.22.2, 6.4.22.3 and 6.4.23.2 (c) Replace "5.1.5.3.1" with "5.1.5.2.1".

5.1.5.2.2 (current 5.1.5.3.2) Delete the second sentence.

5.1.5.3 Insert a new sub-section to read as follows:

[\[For reference: existing 2.2.7.6.1.1\]](#)

"5.1.5.3 Determination of transport index (TI) and criticality safety index (CSI)

5.1.5.3.1 The transport index (TI) for a package, overpack or ~~freight~~ container, or for unpackaged LSA-I or SCO-I, shall be the number derived in accordance with the following procedure:

- (a) Determine the maximum radiation level in units of millisieverts per hour (mSv/h) at a distance of 1 m from the external surfaces of the package, overpack, ~~freight~~ container, or unpackaged LSA-I and SCO-I. The value determined shall be multiplied by 100 and the resulting number is the transport index. For uranium and thorium ores and their concentrates, the maximum radiation level at any point 1 m from the external surface of the load may be taken as:

0.4 mSv/h for ores and physical concentrates of uranium and thorium;

0.3 mSv/h for chemical concentrates of thorium;

0.02 mSv/h for chemical concentrates of uranium, other than uranium hexafluoride;

- (b) For tanks, ~~freight~~ containers and unpackaged LSA-I and SCO-I, the value determined in step (a) above shall be multiplied by the appropriate factor from Table 5.1.5.3.1;

- (c) The value obtained in steps (a) and (b) above shall be rounded up to the first decimal place (e.g. 1.13 becomes 1.2), except that a value of 0.05 or less may be considered as zero.

Table 5.1.5.3.1: Multiplication factors for tanks, ~~freight~~ containers and unpackaged LSA-I and SCO-I

Size of load ^a	Multiplication factor
size of load $\leq 1 \text{ m}^2$	1
$1 \text{ m}^2 < \text{size of load} \leq 5 \text{ m}^2$	2
$5 \text{ m}^2 < \text{size of load} \leq 20 \text{ m}^2$	3
$20 \text{ m}^2 < \text{size of load}$	10

^a *Largest cross-sectional area of the load being measured.*

5.1.5.3.2 The transport index for each overpack, ~~freight~~ container or ~~conveyance~~ vehicle/wagon/[ADN: conveyance] shall be determined as either the sum of the TIs of all the packages contained, or by direct measurement of radiation level, except in the case of non-rigid overpacks for which the transport index shall be determined only as the sum of the TIs of all the packages.

[For reference: existing 2.2.7.6.1.2]

5.1.5.3.3 The criticality safety index for each overpack or ~~freight~~ container shall be determined as the sum of the CSIs of all the packages contained. The same procedure shall be followed for determining the total sum of the CSIs in a consignment or aboard a ~~conveyance~~ vehicle/wagon.

[For reference: existing 2.2.7.6.2.2]

5.1.5.3.4 Packages and overpacks shall be assigned to either category I-WHITE, II-YELLOW or III-YELLOW in accordance with the conditions specified in Table 5.1.5.3.4 and with the following requirements:

- (a) For a package or overpack, both the transport index and the surface radiation level conditions shall be taken into account in determining which is the appropriate category. Where the transport index satisfies the condition for one category but the surface radiation level satisfies the condition for a different category, the package or overpack shall be assigned to the higher category. For this purpose, category I-WHITE shall be regarded as the lowest category;
- (b) The transport index shall be determined following the procedures specified in 5.1.5.3.1 and 5.1.5.3.2;
- (c) If the surface radiation level is greater than 2 mSv/h, the package or overpack shall be ~~transported~~ carried under exclusive use and under the provisions of ~~7.2.3.1.3, 7.2.3.2.1, or 7.2.3.3.3~~ 7.5.1, CV33/CW33 (1.3) and (3.5) (a), as appropriate;
- (d) A package ~~transported~~ carried under a special arrangement shall be assigned to category III-YELLOW except when otherwise specified in the competent authority approval certificate of the country of origin of design (see 2.2.7.2.4.6);
- (e) An overpack which contains packages ~~transported~~ carried under special arrangement shall be assigned to category III-YELLOW except when otherwise specified in the competent authority approval certificate of the country of origin of design (see 2.2.7.2.4.6).

[For reference: Existing 2.2.7.8.4]

Table 5.1.5.3.4: Categories of packages and overpacks

Conditions		
Transport index	Maximum radiation level at any point on external surface	Category
0 ^a	Not more than 0.005 mSv/h	I-WHITE
More than 0 but not more than 1 ^a	More than 0.005 mSv/h but not more than 0.5 mSv/h	II-YELLOW
More than 1 but not more than 10	More than 0.5 mSv/h but not more than 2 mSv/h	III-YELLOW
More than 10	More than 2 mSv/h but not more than 10 mSv/h	III-YELLOW ^b

^a If the measured TI is not greater than 0.05, the value quoted may be zero in accordance with 5.1.5.3.1(c).

^b Shall also be ~~transported~~carried under exclusive use."

Consequential amendment:

In 3.2.1, description of Column (5), and in 5.2.2.1.11.1, replace "2.2.7.8.4" with "5.1.5.3.4".

In 5.2.2.1.11.2 (d), replace "2.2.7.6.1.1 and 2.2.7.6.1.2" with "5.1.5.3.1 and 5.1.5.3.2".

Chapter 5.2

~~5.2.1.5.2~~5.2.1.7.2

Amend to read as follows:

~~5.2.1.5.2~~5.2.1.7.2 In the case of excepted packages marking the proper shipping name is not required."

~~5.2.1.7.1~~5.2.1.9.1

~~In the third indent, delete "open".~~

~~5.2.1.7.2~~5.2.1.9.2 (a) ~~Insert "except for cryogenic receptacles" after "pressure receptacles". Delete "closed".~~

~~5.2.1.7.2~~5.2.1.9.2 (d) ~~Replace "type B(U), B(M) or C" with "type IP-2, type IP-3, type A, type B(U), type B(M) or type C".~~

5.2.2.1.~~12~~11.1 In the first sentence, replace "Except as provided for large ~~freight~~ containers and tanks in accordance with ~~5.3.1.1.5.1~~5.3.1.1.3" with "Except when enlarged labels are used in accordance with ~~5.3.1.1.5.1~~5.3.1.1.3".

5.2.2.1.~~12~~11.2(d) Replace "See ~~2.2.7.6.1.1~~ and ~~2.2.7.6.1.2~~" with "The number determined in accordance with 5.1.5.3.1 and 5.1.5.3.2".

5.2.2.2.1.1 Replace "They ~~shall~~ have a line of the same colour as the symbol, 5 mm inside the edge and running parallel with it." with "They shall have a line 5 mm inside the edge and running parallel with it. In the upper half of a label the line shall have the same colour as the symbol and in the lower half it shall have the same colour as the figure in the bottom corner."

5.2.2.2.1.2 Replace "ISO 7225:1994" with "ISO 7225:2005" and "ISO 7225" with "ISO 7225:2005" (twice).

5.2.2.2.1.3 Amend to read as follows:

"5.2.2.2.1.3 With the exception of Divisions 1.4, 1.5 and 1.6, the upper half of the label shall contain the pictorial symbol and the lower half shall contain the class ~~or division~~-number and the compatibility group letter~~(and for goods of Class 1, the compatibility group letter)~~ as appropriate. The label may include text such as the UN number or words describing the hazard ~~class or division~~ (e.g. "flammable") in accordance with 5.2.2.2.1.5 provided the text does not obscure or detract from the other required label elements."

5.2.2.2.1.6 Insert a new-sub paragraph (c) to read as follows:

"(c) the ~~Division~~-Class 5.2 label, where the symbol may be shown in white; and".

Consequential amendments:

5.2.2.2.1.6 (b) Delete "and".

5.2.2.2.1.6 (c) Renumber as (d).

5.2.2.2.2 Under ~~the labels for Division No. 2.1~~, replace "5.2.2.2.1.6 (c)" with "5.2.2.2.1.6 (d)".

Chapter 5.3

~~5.3.2.1.2 (a)~~ Amend to read as follows:

~~"(a) Against a white background in the area below the pictorial symbol and above the class or division number and the compatibility group letter in a manner that does not obscure or detract from the other required label elements (see Figures 5.3.1 and 5.3.2); or"~~

Chapter 5.4

~~5.4.1.2-5.4.1.4.2~~ Amend footnote ~~1-2~~ to read as follows:

¹ ~~For standardized formats, see also~~If used, the relevant recommendations of the UNECE United Nations Centre for Trade Facilitation and Electronic Business (UN/CEFACT) may be consulted, in particular Recommendation No. 1 (United Nations Layout Key for Trade Documents) (ECE/TRADE/137, edition 81.3), UN Layout Key for Trade Documents - Guidelines for Applications (ECE/TRADE/270, edition 2002), Recommendation No. 11 (Documentary Aspects of the International Transport of Dangerous Goods) (ECE/TRADE/204, edition 96.1 – currently under revision) and Recommendation No. 22 (Layout Key for Standard Consignment Instructions) (ECE/TRADE/168, edition 1989). Refer also to the UN/CEFACT Summary of Trade Facilitation Recommendations (ECE/TRADE/346, edition 2006) and the United Nations Trade Data Elements Directory (UNTDDED) (ECE/TRADE/362, edition 2005)."

~~5.4.1.5.2~~ Replace "in column 7" by "in column 7a".

~~5.4.1.5.9~~5.4.1.1.11 Insert a new paragraph ~~5.4.1.5.9~~Amend to read as follows:

~~5.4.1.5.9~~5.4.1.1.11 ~~Transport~~Carriage of IBCs or portable tanks after the date of expiry of the last periodic test or inspection

For ~~transport~~carriage in accordance with 4.1.2.2 (b), 6.7.2.19.6 (b), 6.7.3.15.6 (b) or 6.7.4.14.6 (b), a statement to this effect shall be included in the transport

document, as follows: "~~Transport~~Carriage in accordance with 4.1.2.2 (b)", "~~Transport~~Carriage in accordance with 6.7.2.19.6 (b)", "~~Transport~~Carriage in accordance with 6.7.3.15.6 (b)" or "~~Transport~~Carriage in accordance with 6.7.4.14.6 (b)" as appropriate."

~~[5.4.2.25.4.2 Footnote 4~~ Add the following new sentence at the end: "Facsimile signatures are acceptable where applicable laws and regulations recognize the legal validity of facsimile signatures."

In 5.4.2 Footnote 4, add:

~~5.4.2.3~~ ~~—~~ ~~Add the following new sub-section:~~

5.4.2.3 If the dangerous goods documentation is presented to the carrier by means of electronic data processing (EDP) or electronic data interchange (EDI) transmission techniques, the signature(s) may be replaced by the name(s) (in capitals) of the person authorized to sign." [[To be checked against the amendments to the IMDG Code.]

Chapter 5.5

[5.5.2.2 ~~Replace—Add~~ "~~When the fumigated unit has been ventilated to remove harmful concentrations of fumigant gas, the warning sign shall be removed.~~" with "The marking, as required by this paragraph, shall remain on the unit until the following provisions are met:

- (a) The fumigated unit has been ventilated to remove harmful concentrations of fumigant gas; and
- (b) The fumigated goods or materials have been unloaded.".]

Figure 5.5.1 In the Fumigation warning sign, insert "VENTILATED ON (date)" before "DO NOT ENTER".

PART 6

6.1.1.4. 6.3.2.2 (as amended), 6.5.4.1 and 6.6.1.2 At the end, add a new note to read as follows:

"NOTE: ISO 16106:2006 "Packaging – Transport packages for dangerous goods – Dangerous goods packagings, intermediate bulk containers (IBCs) and large packagings – Guidelines for the application of ISO 9001" provides acceptable guidance on procedures which may be followed."

Chapter 6.1

6.1.2.6 Insert the new following note after the list:

"NOTE: Plastics materials, is taken to include other polymeric materials such as rubber."

6.1.3.1 (a) Replace the first sentence after the symbol with: "This symbol shall not be used for any purpose other than certifying that a packaging complies with the relevant requirements in Chapter 6.1, 6.2, 6.3, 6.5 or 6.6."

6.1.5.1.2 Replace the first sentence with "Each packaging design type shall successfully pass the tests prescribed in this Chapter before being used."

6.1.5.3.4 Amend to read as follows:

"6.1.5.3.4 *Target*

The target shall be a non-resilient and horizontal surface and shall be:

- Integral and massive enough to be immovable;
- Flat with a surface kept free from local defects capable of influencing the test results;
- Rigid enough to be non-deformable under test conditions and not liable to become damaged by the tests; and
- Sufficiently large to ensure that the test package falls entirely upon the surface.

Chapter 6.2

[In the title, replace "AND SMALL RECEPTACLES CONTAINING GAS (GAS CARTRIDGES)" with ", SMALL RECEPTACLES CONTAINING GAS (GAS CARTRIDGES) AND FUEL CELL CARTRIDGES CONTAINING LIQUEFIED FLAMMABLE GAS".

6.2.1 In the Note, replace "*and small receptacles containing gas (gas cartridges)*" with ", *small receptacles containing gas (gas cartridges) and fuel cell cartridges containing liquefied flammable gas*".]

~~6.2.1.1.6 Replace "Manifolds shall be designed such that they are protected from impact." with "Manifold assemblies (e.g. manifold, valves, and pressure gauges) shall be designed and constructed such that they are protected from impact damage and forces normally encountered in transport. Manifolds shall have at least the same test pressure as the cylinders."~~

~~Replace "means shall be provided" with "each pressure receptacle shall have an isolation valve".~~ [\[Included in the amendments adopted by the Joint Meeting at its March Session.\]](#)

~~6.2.1.1.9 Insert a new paragraph 6.2.1.1.9 with the heading "*Additional requirements for the construction of pressure receptacles for acetylene*" and with the text of the third and fourth sentences of existing 4.1.6.1.2 ("*Pressure receptacles for UN 1001 acetylene ... compatible with the pressure receptacles.*").~~ [\[Included in the amendments adopted by the Joint Meeting at its March Session.\]](#)

~~6.2.1.3.1 Amend to read as follows:~~

~~"6.2.1.3.1 Valves, piping and other fittings subjected to pressure, excluding pressure relief devices, shall be designed and constructed so that the burst pressure is at least 1.5 times the test pressure of the pressure receptacle."~~ [\[Included in the amendments adopted by the Joint Meeting at its March Session.\]](#)

6.2.1.4 Renumber sub-section 6.2.1.4 as 6.2.1.5 and renumber subsequent paragraphs and cross-references accordingly.

6.2.1.5 Renumber sub-section 6.2.1.5 as 6.2.1.6 and renumber subsequent paragraphs [and cross-references](#) accordingly.

~~Consequential amendments:~~

~~In 4.1.6.1.4, 4.1.6.1.10, 4.2.4.2 and 6.7.5.12.4, replace "6.2.1.5" with "6.2.1.6".~~

6.2.1.5.1 (renumbered 6.2.1.6.1) Add a new paragraph (e) at the end, after the notes, to read as follows:

"(e) Check of service equipment, other accessories and pressure-relief devices, if to be reintroduced into service."

6.2.1.5.2 (renumbered 6.2.1.6.2) Amend to read as follows:

"6.2.1.6.2 Pressure receptacles intended for the ~~transport~~carriage of UN [No.](#) 1001 acetylene, dissolved and UN 3374 acetylene, solvent free, shall be examined only as specified in 6.2.1.6.1 (a), (c) and (e). In addition the condition of the porous material (e.g. cracks, top clearance, loosening, settlement) shall be examined."

6.2.1.6 Renumber sub-section 6.2.1.6 as 6.2.1.4 and renumber subsequent paragraphs accordingly.

~~6.2.2.1.3~~ ~~In the table for "cylinder shell", delete the last entry (ISO 11118:1999).~~ [\[Included in the amendments adopted by the Joint Meeting at its March Session.\]](#)

6.2.2.2 Add the following new note at the end:

"NOTE: The limitations imposed in ISO 11114-1 on high strength steel alloys at ultimate tensile strength levels up to 1 100 MPa do not apply to SILANE (UN [No.](#) 2203)."

6.2.2.4 Amend the three first entries of the table to read as follows:

ISO 6406:2005	Seamless steel gas cylinders – Periodic inspection and testing
ISO 10461:2005/A1:2006	Seamless aluminium-alloy gas cylinders – Periodic inspection and testing
ISO 10462:2005	Transportable cylinders for dissolved acetylene – Periodic inspection and maintenance

~~6.2.2.7.1 (a)~~ ~~Replace the first sentence after the symbol with: "This symbol shall not be used for any purpose other than certifying that a packaging complies with the relevant requirements in Chapter 6.1, 6.2, 6.3, 6.5 or 6.6."~~ [\[Included in the amendments adopted by the Joint Meeting at its March Session.\]](#)

~~[6.2.4~~[6.2.6](#) In the title, replace "**and small receptacles containing gas (gas cartridges)**" with "**small receptacles containing gas (gas cartridges) and fuel cell cartridges containing liquefied flammable gas**".

~~6.2.4.1~~[6.2.6.3.1](#) In the title, insert "**and fuel cell cartridges containing liquefied flammable gas**" after "**(gas cartridges)**".

~~6.2.4.1.1~~6.2.6.3.1.1 In the first sentence, insert "or fuel cell cartridge" after "Each receptacle" at the beginning ~~and insert "or the fuel cell cartridge" after "the receptacle" in the text between brackets.~~

6.2.6.3.1.2 In the second sentence, insert "or the fuel cell cartridges" after "receptacles" ~~and~~

6.2.6.3.1.3 Insert "or fuel cell cartridge" after "receptacle" ~~respectively~~ in the first and third sentence.

~~6.2.4.1.2~~6.2.6.3.1.3 Insert "or fuel cell cartridge" after "receptacle" twice.]

Chapter 6.3

In the title, replace "SUBSTANCES" with "INFECTIOUS SUBSTANCES OF CATEGORY A".

Sections 6.3.1 to 6.3.3 Amend to read as follows:

6.3.1 General

6.3.1.1 The requirements of this Chapter apply to packagings intended for the ~~transport~~carriage of infectious substances of Category A.

6.3.2 Requirements for packagings

6.3.2.1 The requirements for packagings in this section are based on packagings, as specified in 6.1.4, currently used. In order to take into account progress in science and technology, there is no objection to the use of packagings having specifications different from those in this Chapter provided that they are equally effective, acceptable to the competent authority and able successfully to withstand the tests described in 6.3.5. Methods of testing other than those described in ~~these Regulations~~RID/ADR are acceptable provided they are equivalent.

6.3.2.2 Packagings shall be manufactured and tested under a quality assurance programme which satisfies the competent authority in order to ensure that each packaging meets the requirements of this Chapter.

6.3.2.3 *Text of existing 6.3.1.3*

6.3.3 Code for designating types of packagings

6.3.3.1 The codes for designating types of packagings are set out in 6.1.2.7.

6.3.3.2 The letters "U" or "W" may follow the packaging code. The letter "U" signifies a special packaging conforming to the requirements of 6.3.5.1.6. The letter "W" signifies that the packaging, although, of the same type indicated by the code is manufactured to a specification different from that in 6.1.4 and is considered equivalent under the requirements of 6.3.2.1."

Add new sections 6.3.4 and 6.3.5 as follows:

"6.3.4 Marking

NOTE 1: *The marking indicates that the packaging which bears it corresponds to a successfully tested design type and that it complies with the requirements of this Chapter which are related to the manufacture, but not to the use, of the packaging.*

NOTE 2: *The marking is intended to be of assistance to packaging manufacturers, reconditioners, packaging users, carriers and regulatory authorities.*

NOTE 3: *The marking does not always provide full details of the test levels, etc., and these may need to be taken further into account, e.g. by reference to a test certificate, to test reports or to a register of successfully tested packagings.*

6.3.4.1 Each packaging intended for use according to ~~these Regulations~~ RID/ADR shall bear markings which are durable, legible and placed in a location and of such a size relative to the packaging as to be readily visible. For packages with a gross mass of more than 30 kg, the markings or a duplicate thereof shall appear on the top or on a side of the packaging. Letters, numerals and symbols shall be at least 12 mm high, except for packagings of 30 litres or 30 kg capacity or less, when they shall be at least 6 mm in height and for packagings of 5 litres or 5 kg or less when they shall be of an appropriate size.

6.3.4.2 *Text of existing 6.3.1.1, with the following modifications:*

At the beginning, replace "6.3.2" with "6.3.5".

In (a), add at the end: "This symbol shall not be used for any purpose other than certifying that a packaging complies with the relevant requirements in Chapter 6.1, 6.2, 6.3, 6.5 or 6.6;"

In (g), replace "6.3.2.9" with "6.3.5.1.6".

At the end, delete the text after sub-paragraphs (a) to (g).

6.3.4.3 Marking shall be applied in the sequence shown in 6.3.4.2 (a) to (g); each element of the marking required in these sub-paragraphs shall be clearly separated, e.g. by a slash or space, so as to be easily identifiable. For examples, see 6.3.4.4.

Any additional markings authorized by a competent authority shall still enable the parts of the mark to be correctly identified with reference to 6.3.4.1.

6.3.4.4 *Text of existing 6.3.1.2, with the following modifications:*

In the marking, replace "01" with "06".
Replace "6.3.1.1" with "6.3.4.2" (twice).
Replace "(e)," with "(e) and".

6.3.5 *Heading of existing 6.3.2.*

6.3.5.1 Performance and frequency of tests

6.3.5.1.1 The design type of each packaging shall be tested as provided in this section in accordance with procedures established by the competent authority.

6.3.5.1.2 Each packaging design type shall successfully pass the tests prescribed in this Chapter before being used. A packaging design type is defined by the design, size, material and thickness, manner of construction and packing, but may include various surface treatments. It also includes packagings which differ from the design type only in their lesser design height.

6.3.5.1.3 Tests shall be repeated on production samples at intervals established by the competent authority.

6.3.5.1.4 Tests shall also be repeated after each modification which alters the design, material or manner of construction of a packaging.

6.3.5.1.5 *Text of existing 6.3.2.7, with the following modifications:*

Replace "of inner packagings or inner packagings of lower net mass" with "or lower net mass of primary receptacles".

Delete ", bags".

6.3.5.1.6 *Text of existing 6.3.2.9, with the following modifications:*

At the beginning, replace "Inner" with "Primary", "intermediate (secondary)" with "secondary" and "outer" with "rigid outer".

In (a), replace "intermediate/outer packaging combination" with "rigid outer packaging", "6.3.2.3" with "6.3.5.2.2" and "inner" with "primary".

In (b), replace "inner" with "primary" (twice).

In (c), replace "inner" with "primary" (seven times) and "intermediate" with "secondary" (twice). Add "spaces" at the end.

In (d), replace "outer" with "rigid outer" and "inner receptacles" with "packagings".

In (e), replace "inner" with "primary" (twice).

In (f), replace "outer" with "rigid outer" and "inner" with "primary" (twice).

In (g), replace "6.3.1.1" with "6.3.4.2" (twice).

6.3.5.1.7 The competent authority may at any time require proof, by tests in accordance with this section, that serially-produced packagings meet the requirements of the design type tests.

6.3.5.1.8 Provided the validity of the test results is not affected and with the approval of the competent authority, several tests may be made on one sample.

6.3.5.2 *Preparation of packagings for testing*

6.3.5.2.1 *Text of existing 6.3.2.2, with the following modifications:*

Replace "98% capacity" with "not less than 98 % of its capacity".

Add a new note at the end to read as follows:

"NOTE: *The term water includes water/antifreeze solution with a minimum specific gravity of 0.95 for testing at – 18 °C."*

6.3.5.2.2 *Tests and number of samples required*

Tests required for packaging types

Type of packaging ^a			Tests required					Stack 6.1.5.6
Rigid outer packaging	Primary receptacle		Water spray 6.3.5.3.6.1	Cold conditioning 6.3.5.3.6.2	Drop 6.3.5.3	Additional drop 6.3.5.3.6.3	Puncture 6.3.5.4	
	Plastics	Other	No. of samples	No. of samples	No. of samples	No. of samples	No. of samples	
Fibreboard box	x		5	5	10	Required on one sample when the packaging is intended to contain dry ice.	2	Required on three samples when testing a "U"-marked packaging as defined in 6.3.5.1.6 for specific provisions.
		x	5	0	5		2	
Fibreboard drum	x		3	3	6		2	
		x	3	0	3		2	
Plastics box	x		0	5	5		2	
		x	0	5	5		2	
Plastics drum/jerrican	x		0	3	3		2	
		x	0	3	3		2	
Boxes of other material	x		0	5	5		2	
		x	0	0	5		2	
Drums/jerricans of other material	x		0	3	3	2		
		x	0	0	3	2		

^a "Type of packaging" categorizes packagings for test purposes according to the kind of packaging and its material characteristics.

NOTE 1: In instances where a primary receptacle is made of two or more materials, the material most liable to damage determines the appropriate test.

NOTE 2: The material of the secondary packagings are not taken into consideration when selecting the test or conditioning for the test.

Explanation for use of the table:

If the packaging to be tested consists of a fibreboard outer box with a plastics primary receptacle, five samples must undergo the water spray test (see 6.3.5.3.6.1) prior to dropping and another five must be conditioned to – 18 °C (see 6.3.5.3.6.2) prior to dropping. If the packaging is to contain dry ice then one further single sample shall be dropped five times after conditioning in accordance with 6.3.5.3.6.3.

Packagings prepared as for ~~transport~~carriage shall be subjected to the tests in 6.3.5.3 and 6.3.5.4. For outer packagings, the headings in the table relate to fibreboard or similar materials whose performance may be rapidly affected by moisture; plastics which may embrittle at low temperature; and other materials such as metal whose performance is not affected by moisture or temperature.

6.3.5.3 *Drop test*

6.3.5.3.1 Samples shall be subjected to free-fall drops from a height of 9 m onto a non-resilient, horizontal, flat, massive and rigid surface in conformity with 6.1.5.3.4.

6.3.5.3.2 Where the samples are in the shape of a box; five shall be dropped one in each of the following orientations:

- (a) flat on the base;
- (b) flat on the top;
- (c) flat on the longest side;
- (d) flat on the shortest side;
- (e) on a corner.

6.3.5.3.3 Where the samples are in the shape of a drum, three shall be dropped one in each of the following orientations:

- (a) diagonally on the top chime, with the centre of gravity directly above the point of impact;
- (b) diagonally on the base chime;
- (c) flat on the side.

6.3.5.3.4 While the sample shall be released in the required orientation, it is accepted that for aerodynamic reasons the impact may not take place in that orientation.

6.3.5.3.5 Following the appropriate drop sequence, there shall be no leakage from the primary receptacle(s) which shall remain protected by cushioning/absorbent material in the secondary packaging.

6.3.5.3.6 *Special preparation of test sample for the drop test*

6.3.5.3.6.1 *Fibreboard - Water spray test*

Fibreboard outer packagings: The sample shall be subjected to a water spray that simulates exposure to rainfall of approximately 5 cm per hour for at least one hour. It shall then be subjected to the test described in 6.3.5.3.1.

6.3.5.3.6.2 *Plastics material – Cold conditioning*

Plastics primary receptacles or outer packagings: The temperature of the test sample and its contents shall be reduced to -18 °C or lower for a period of at least 24 hours and within 15 minutes of removal from that atmosphere the test sample shall be subjected to the test described in 6.3.5.3.1. Where the sample contains dry ice, the conditioning period shall be reduced to 4 hours.

6.3.5.3.6.3 *Packagings intended to contain dry ice – Additional drop test*

Where the packaging is intended to contain dry ice, a test additional to that specified in 6.3.5.3.1 and, when appropriate, in 6.3.5.3.6.1 or 6.3.5.3.6.2 shall be carried out. One sample shall be

stored so that all the dry ice dissipates and then that sample shall be dropped in one of the orientations described in 6.3.5.3.2 which shall be that most likely to result in failure of the packaging.

6.3.5.4 *Puncture test*

6.3.5.4.1 *Packagings with a gross mass of 7 kg or less*

Text of existing 6.3.2.6 (a), with the following modification:

Replace "not exceeding 38 mm" with "of 38 mm".

6.3.5.4.2 *Packagings with a gross mass exceeding 7 kg*

Text of existing 6.3.2.6 (b), with the following modifications:

In the fourth sentence, replace "the primary receptacle(s) and the outer surface" with "the centre of the primary receptacle(s) and the outer surface".

In the fifth sentence, insert "with its top face lowermost" before "in a vertical free fall".

In the last but one sentence, replace "the steel rod would penetrate" with "the steel rod would be capable of penetrating".

In the last sentence, replace "there shall be no leakage" with "penetration of the secondary packaging is acceptable provided that there is no leakage".

6.3.5.5 *Heading of existing 6.3.3*

6.3.5.5.1 *Text of existing 6.3.3.1, with the following modifications:*

At the beginning, insert "written" before "test report".

In the 4th indent, replace "the test report" with "the test and of the report".

Amend the 8th indent to read as follows: "8. Test contents;".

6.3.5.5.2 *Text of existing 6.3.3.2."*

Chapter 6.4

6.4.5.4.1 (b) Amend to read as follows:

"(b) They are designed to satisfy the requirements prescribed for packing group I or II in Chapter 6.1 ~~of these Regulations~~; and".

6.4.5.4.2 Delete "Tank-containers and" at the beginning.

6.4.5.4.2 (b) ~~Amend to read as follows:~~

~~"(b) They are designed to satisfy the requirements prescribed in Chapter 6.7 of these Regulations and are capable of withstanding a test pressure of 265 kPa; and"~~

Delete "or Chapter 6.8".

6.4.5.4.3 Delete "and tank-containers" and replace "that they conform to standards at least equivalent to those prescribed in 6.4.5.4.2." with "that:

- (a) They satisfy the requirements of 6.4.5.1;
- (b) They are designed to satisfy the requirements prescribed in Chapter 6.8 [or in other regional or national regulations for the ~~transport~~carriage of dangerous goods and are capable of withstanding a test pressure of 265 kPa;] and
- (c) They are designed so that any additional shielding which is provided shall be capable of withstanding the static and dynamic stresses resulting from handling and routine conditions of ~~transport~~carriage and of preventing an increase of more than 20% in the maximum radiation level at any external surface of the tanks."

According to the IAEA Regulations (para. 626) ADR/RID tanks would be allowed for LSA-I and LSA-II liquids and gases only. The secretariat notes that columns 12 and 13 of Table A of Chapter 3.2 include ADR/RID tank codes for LSA-III material (UN No. 3322), which is not consistent with this paragraph 6.4.5.4.3.

6.4.5.4.4 In the first sentence, insert "of a permanent enclosed character" after "~~Freight~~ containers".

6.4.5.4.5 (b) Amend the text before (i) and (ii) to read as follows:

"(b) They are designed to satisfy the requirements prescribed in Chapter 6.5 ~~of these Regulations~~ for packing group I or II, and if they were subjected to the tests prescribed in that Chapter, but with the drop test conducted in the most damaging orientation, they would prevent:"

6.4.11.2 In the first sentence, replace "of this paragraph" with "of 2.2.7.2.3.5". Delete subparagraphs (a) to (d) and Table 6.4.11.2.

6.4.11.13 Add a new sub-section to read as follows:

"6.4.11.13 The criticality safety index (CSI) for packages containing fissile material shall be obtained by dividing the number 50 by the smaller of the two values of N derived in 6.4.11.11 and 6.4.11.12 (i.e. $CSI = 50/N$). The value of the criticality safety index may be zero, provided that an unlimited number of packages is subcritical (i.e. N is effectively equal to infinity in both cases)."

[For reference: Existing 2.2.7.6.2.1.]

6.4.23.14 (o) Insert "6.4.8.4," before "6.4.8.5".

6.4.23.15 Add at the end "under 6.4.22.2, 6.4.22.3, 6.4.22.4, 6.4.24.2 and 6.4.24.3".

Chapter 6.5

6.5.2.1.1 (a) Insert a new sentence after the symbol to read as follows: "This symbol shall not be used for any purpose other than certifying that a packaging complies with the relevant requirements in Chapter 6.1, 6.2, 6.3, 6.5 or 6.6."


6.5.2.2.1 Add the following new entry to the table and the following new note b after the table:

Additional marking	Category of IBC				
	Metal	Rigid Plastics	Composite	Fibreboard	Wooden
Maximum permitted stacking load ^b	X	X	X	X	X


^b See 6.5.2.2.2. This additional marking shall apply to all IBCs manufactured, repaired or remanufactured as from 1 January 2011 ([see also 1.6.1.Y](#)).

6.5.2.2.2 Add a new 6.5.2.2.2 to read as follows and renumber subsequent paragraphs accordingly:

"6.5.2.2.2 The maximum permitted stacking load applicable when the IBC is in use shall be displayed on a symbol as follows:



IBCs capable of being stacked



IBCs NOT capable of being stacked

The symbol shall be not less than 100 mm × 100 mm, be durable and clearly visible. The letters and numbers indicating the mass shall be at least 12 mm high.

The mass marked above the symbol shall not exceed the load imposed during the design type test (see 6.5.6.6.4) divided by 1.8.

NOTE: The provisions of 6.5.2.2.2 shall apply to all IBCs manufactured, repaired or remanufactured as from 1 January 2011 ([see also 1.6.1.Y](#)).

6.5.4.4.2 In the first sentence, add "at least equally effective as the test prescribed in 6.5.6.7.3" after "a suitable leakproofness test". After the sub-paragraphs (a) and (b), replace "For this test the IBC need not have its closures fitted." with "For this test the IBC shall be fitted with the primary bottom closure."

6.5.6.1.1 Replace the first sentence with "Each IBC design type shall successfully pass the tests prescribed in this Chapter before being used."

~~6.5.6.3.5~~ 6.5.6.3.7 Replace the seven first columns with the following new eight first columns (3 last columns unchanged):

Type of IBC	Vibration f	Bottom lift	Top lift a	Stacking b	Leak- proofness	Hydraulic pressure	Drop
Metal: 11A, 11B, 11N	-	1st ^a	2nd	3rd	-	-	4th ^e
21A, 21B, 21N	-	1st ^a	2nd	3rd	4th	5th	6th ^e
31A, 31B, 31N	1st	2nd ^a	3rd	4th	5th	6th	7th ^e
Flexible ^d	-	-	x ^c	x	-	-	x
Rigid plastics: 11H1, 11H2	-	1st ^a	2nd	3rd	-	-	4th
21H1, 21H2	-	1st ^a	2nd	3rd	4th	5th	6th
31H1, 31H2	1st	2nd ^a	3rd	4th	5th	6th	7th
Composite: 11HZ1, 11HZ2	-	1st ^a	2nd	3rd	-	-	4th ^e
21HZ1, 21HZ2	-	1st ^a	2nd	3rd	4th	5th	6th ^e
31HZ1, 31HZ2	1st	2nd ^a	3rd	4th	5th	6th	7th ^e
Fibreboard	-	1st	-	2nd	-	-	3rd
Wooden	-	1st	-	2nd	-	-	3rd

Insert a new note f after the table to read as follows:

^f *Another IBC of the same design may be used for the vibration test.*
[and rename existing note "f" as "g".](#)

6.5.6.5.5 (a) Amend to read as follows:

"(a) Metal, rigid plastics and composite IBCs: the IBC remains safe for normal conditions of ~~transport~~carriage, there is no observable permanent deformation of the IBC, including the base pallet, if any, and no loss of contents;"

6.5.6.7.3 Delete the last sentence.

6.5.6.9.3 Amend the first sentence to read as follows: "The IBC shall be dropped on its base onto a non-resilient, horizontal, flat, massive and rigid surface in conformity with the requirements of 6.1.5.3.4, in such a manner as to ensure that the point of impact is that part of the base of the IBC considered to be the most vulnerable."

6.5.6.9.5 Add a new sub-paragraph (d) to read as follows:

"(d) All IBCs: no damage which renders the IBC unsafe to be ~~transported~~carried for salvage or for disposal, and no loss of contents. In addition, the IBC shall be capable of being lifted by an appropriate means until clear of the floor for five minutes."

6.5.6.13 Add a new 6.5.6.13 to read as follows and renumber the subsequent paragraphs accordingly:

"6.5.6.13 *Vibration test*

6.5.6.13.1 *Applicability*

For all IBCs used for liquids, as a design type test.

NOTE: *This test applies to design types for IBCs manufactured after 31 December 2010 [\(see also 1.6.1.X\)](#).*

6.5.6.13.2 *Preparation of the IBC for test*

A sample IBC shall be selected at random and shall be fitted and closed as for ~~transport~~carriage. The IBC shall be filled with water to not less than 98% of its maximum capacity.

6.5.6.13.3 *Test method and duration*

6.5.6.13.3.1 The IBC shall be placed in the center of the test machine platform with a vertical sinusoidal, double amplitude (peak-to peak displacement) of 25 mm \pm 5%. If necessary, restraining devices shall be attached to the platform to prevent the specimen from moving horizontally off the platform without restricting vertical movement.

6.5.6.13.3.2 The test shall be conducted for one hour at a frequency that causes part of the base of the IBC to be momentarily raised from the vibrating platform for part of each cycle to such a degree that a metal shim can be completely inserted intermittently at, at least, one point between the base of the IBC and the test platform. The frequency may need to be adjusted after the initial set point to prevent the packaging from going into resonance. Nevertheless, the test frequency shall continue to allow placement of the metal shim under the IBC as described in this paragraph. The continuing ability to insert the metal shim is essential to passing the test. The metal shim used for this test shall be at least 1.6 mm thick, 50 mm wide, and be of sufficient length to be inserted between the IBC and the test platform a minimum of 100 mm to perform the test.

6.5.6.13.4 *Criteria for passing the test*

No leakage or rupture shall be observed. In addition, no breakage or failure of structural components, such as broken welds or failed fastenings, shall be observed."

Consequential amendments:

6.5.6.2.1 Replace "6.5.6.12" by "6.5.6.13".

6.5.6.2.3 Replace "6.5.6.13" by "6.5.6.14".

Chapter 6.6

6.6.3.1 (a) Insert a new sentence after the symbol to read as follows: "This symbol shall not be used for any purpose other than certifying that a packaging complies with the relevant requirements in Chapter 6.1, 6.2, 6.3, 6.5 or 6.6."

6.6.5.1.2 Replace the first sentence with "Each large packaging design type shall successfully pass the tests prescribed in this Chapter before being used."

6.6.5.3.4.3 Amend the text after the heading to read as follows: "The large packaging shall be dropped onto a non resilient, horizontal, flat, massive and rigid surface in conformity with the requirements of 6.1.5.3.4, in such a manner as to ensure that the point of impact is that part of the base of the large packaging considered to be the most vulnerable."

Chapter 6.7

6.7.4.14.4 In the last sentence, insert "and tests" after "periodic inspection".

6.7.4.14.5 Delete.

6.7.5.3.2 In the last sentence, replace "isolated by a valve into assemblies of not more than 3 000 litres" with "divided into groups of not more than 3 000 litres each isolated by a valve".

6.7.5.4.1 Replace "shall be isolated by a valve into assemblies of not more than 3 000 litres. Each assembly shall be fitted" with "divided into groups of not more than 3 000 litres each isolated by a valve. Each group shall be fitted".

PART 7

Chapter 7.1

7.1.3.2.3 Replace "and inorganic nitrates of Class 5.1 (UN Nos. 1942 and 2067)" with "(UN Nos. 1942 and 2067) and alkali metal nitrates (e.g. UN 1486) and alkaline earth metal nitrates (e.g. UN 1454)".

[Chapter ~~4.3~~7.3

~~7.3.2.6~~4.3.2.4 In the heading, delete "*waste*".

~~4.3.2.4.1~~7.3.2.6.1 ~~Amend the heading to read "*Bulk transport carriage of animal material of Division 6.2*".~~

Replace the text before the indents with the following:

~~Insert the following new text before the indents:~~

"Animal material containing infectious substances (UN Nos. 2814, 2900 and 3373) including animal carcasses, is authorized for ~~transport~~carriage in bulk containers provided the following conditions are met:".

In (a), replace "For wastes ~~goods~~ of UN Nos. 2814 and 2900, sheeted" with "Sheeted" at the beginning.

Amend sub-paragraph (c) to read as follows: "The animal material shall be thoroughly treated with an appropriate disinfectant before loading prior to ~~transport~~carriage;"

In (d), replace "Wastes ~~goods~~ of UN Nos. 2814 and 2900 in a sheeted" with "Sheeted" at the beginning.

In (e), delete "used for the ~~transport~~carriage of wastes ~~goods~~ of UN Nos. 2814 and 2900".

Insert the following new note after the indents:

"NOTE: Additional provisions may be required by appropriate national health authorities." [Amendments to 7.3.2.6 to be checked by the working group.]