

**Draft Corrigendum 2 to Revision 6 to Regulation No. 16 (Safety belts)**

**I. PROPOSAL**

*Paragraph 6.2.6.3.1., correct to read:*

“6.2.6.3.1. After being submitted to conditioning in accordance with paragraph **7.9.1.**, operation of the pre-loading device must not have been activated by temperature and the device shall operate normally.”

*Paragraph 6.4.1.2., correct to read:*

“6.4.1.2. The dynamic test shall be performed on two belt assemblies which have not previously been under load, except in the case of belt assemblies forming part of restraint systems when the dynamic test shall be performed on the restraint systems intended for one group of seats which have not previously been under load. The buckles of the belt assemblies to be tested shall have met the requirements of paragraph 6.2.2.4. above. In the case of safety-belts with retractors, the retractor shall have been subjected to the dust resistance test laid down in paragraph 7.6.3.; in addition, in the case of safety-belts or restraint systems equipped with a pre-loading device comprising pyrotechnic means, the device shall have been subjected to the conditioning specified in paragraph **7.9.1.**”

*Paragraph 7.4.1., correct to read:*

“7.4.1. Conditioning of straps for the breaking-strength test

Samples cut from the strap referred to in paragraph **3.2.2.3.** above shall be conditioned as follows:”

**II. JUSTIFICATION**

The references to conditioning test in paragraphs 6.2.6.3.1. and 6.4.1.2. are made to non existing paragraphs since several years ago. Also for paragraph 7.4.1. wrong reference is made regarding samples cut from the strap. The current proposal is aimed at introducing the right references in the above mentioned paragraphs.

---