

Amending ECE/TRANS/WP.29/GRB/2011/11

I. Proposal

Annex 6

Paragraph 3.5., amend to read:

"3.5. Duration and speed.

When the deceleration method is selected, the following requirements apply:

- (a) **The deceleration j shall be determined in exact $d\omega/dt$ or approximate $\Delta\omega/\Delta t$ form, where ω is angular velocity, t – time**
- (b) For duration Δt , the time increments shall not exceed 0.5 s;
- (c) Any variation of the test drum speed shall not exceed 1 km/h within one time increment."

Paragraph 4.6.2., amend to read:

"4.6.2. Deceleration method

The deceleration method follows the procedure below:

- (a) Remove the tyre from the test surface;
- (b) Record the deceleration of the test drum $\Delta\omega_{D0}/\Delta t$ and that of the unloaded tyre $\Delta\omega_{T0}/\Delta t^3$ **or record the deceleration of the test drum j_{D0} and that of the unloaded tyre j_{T0} in exact or approximate form in accordance with paragraph 3.5.**

Paragraph 5.1.5., amend to read:

"5.1.5. Deceleration method

Calculate the parasitic losses F_{pl} , in newton.

$$F_{pl} = \frac{I_D}{R} \left(\frac{\Delta\omega_{D0}}{\Delta t_0} \right) + \frac{I_T}{R_r} \left(\frac{\Delta\omega_{T0}}{\Delta t_0} \right)$$

Where:

- I_D is the test drum inertia in rotation, in kilogram meter squared,
- R is the test drum surface radius, in meter,
- ω_{D0} is the test drum angular speed, without tyre, in radians per second,
- Δt_0 is the time increment chosen for the measurement of the parasitic losses without tyre, in second,
- I_T is the spindle, tyre and wheel inertia in rotation, in kilogram meter squared,
- R is the tyre rolling radius, in metre,

ω_{T0} is the tyre angular speed, unloaded tyre, in radian per second.

Or

$$F_{pl} = \frac{I_D}{R} j_{D0} + \frac{I_T}{R_r} j_{T0}$$

where:

ID is the test drum inertia in rotation, in kilogram meter squared;

R is the test drum surface radius, in meter;

j_{D0} is the deceleration of the test drum, without tyre, in radians per second squared;

IT is the spindle, tyre and wheel inertia in rotation, in kilogram meter squared;

R_r is the tyre rolling radius, in metre;

j_{T0} is the deceleration of unloaded tyre, in radians per second squared."

Paragraph 5.2.5., amend to read:

"5.2.5. Deceleration method

The rolling resistance F_r , in newton, is calculated using the equation:

$$F_r = \frac{I_D}{R} \left(\frac{\Delta\omega_v}{\Delta t_v} \right) + \frac{RI_T}{R_r^2} \left(\frac{\Delta\omega_v}{\Delta t_v} \right) - F_{pl}$$

Where:

ID is the test drum inertia in rotation, in kilogram metre squared,

R is the test drum surface radius, in meter,

F_{pl} represents the parasitic losses as calculated in paragraph 5.1.5.,

Δt_v is the time increment chosen for measurement, in second,

Δω_v is the test drum angular speed increment, without tyre, in radian per second,

I_T is the spindle, tyre and wheel inertia in rotation, in kilogram metre squared,

R_r is the tyre rolling radius, in metre,

F_r is the rolling resistance, in newton.

Or

$$Fr = \frac{I_D}{R} j_V + \frac{RI_T}{R_r^2} j_V - F_{pl}$$

where:

Where:

ID is the test drum inertia in rotation, in kilogram metre squared,

R is the test drum surface radius, in meter,

F_{pl} represents the parasitic losses as calculated in paragraph 5.1.5.,

j_V is the deceleration of the test drum, in radians per second squared,

I_T is the spindle, tyre and wheel inertia in rotation, in kilogram metre squared,

R_r is the tyre rolling radius, in metre,

F_r is the rolling resistance, in newton."

Annex 6, Appendix 1

Paragraph 4, amend to read:

"4. Control accuracy

...

(d) time: +/- ~~0.02 s~~ **0.5 ms**

..."
