

GFV-20-02a
Presented to GFV in view of submitting
Informal document GRPE-64-xx2
(64nd GRPE, 4 – 8 June 2012,
agenda items 4(c) and 9)

Consolidated proposal for an amendment to Regulation No. 49 in view of type-approving Heavy-Duty dual-fuel vehicles

Submitted to GFV by the informal GFV-HDDF Task Force

I. Proposal

Insert a new paragraph 2.13., to read:

"2.13 **"Diesel mode"** means the normal operating mode of a dual-fuel engine during which the engine does not use any gaseous fuel for any engine operating condition;"

Insert a new paragraphs 2.15. to 2.17., to read:

"2.15 **"Dual-fuel engine"** means an engine system that is designed to simultaneously operate with diesel fuel and a gaseous fuel, both fuels being metered separately, where the consumed amount of one of the fuels relative to the other one may vary depending on the operation;

2.16 **"Dual-fuel mode"** means the normal operating mode of a dual-fuel engine during which the engine simultaneously uses diesel fuel and a gaseous fuel at some engine operating conditions;

2.17 **"Dual-fuel vehicle"** means a vehicle that is powered by a dual-fuel engine and that supplies the fuels used by the engine from separate on-board storage systems;"

Insert a new paragraph 2.59., to read (including footnote 1):

"2.59 **"Service mode"** means a special mode of a dual-fuel engine that is activated for the purpose of repairing, or of moving the vehicle from the traffic when operation in the dual-fuel mode is not possible¹"

Paragraphs 2.13. (former), renumber as paragraph 2.14.

Paragraphs 2.14. (former) to 2.54., renumber as paragraphs 2.18. to 2.58.

Paragraphs 2.55. (former) to 2.61., renumber as paragraphs 2.60. to 2.67.

¹ For example in case of an empty gas tank.

Paragraph 4.3., amend to read (deleting also footnote 1):

"4.3. **In order to receive a type-approval of a dual-fuel engine or engine family as a separate technical unit, type-approval of a dual-fuel vehicle with an approved dual-fuel engine with regard to emissions, or a type-approval of a dual-fuel vehicle with regard to emissions, the manufacturer shall, in addition to the requirements of paragraphs 4.1 demonstrate that the dual-fuel vehicles or engine are subject to the tests and comply with the requirements set out in Annex 15.**"

Insert a new paragraph 4.5.1., to read:

"4.5.1. **Tables summarizing the requirements for approval of NG-Fuelled engines, LPG-Fuelled engines and dual-fuelled engines are provided in Appendix 4.**"

Paragraph 4.6.1., amend to read:

"4.6.1. The parent engine shall meet the requirements of this Regulation on the appropriate reference fuels specified in Annex 5. Specific requirements shall apply to **engines fuelled with natural gas/biomethane (including dual-fuel engines)**~~natural gas fuelled engines~~, as laid down in paragraph 4.6.3."

Paragraph 4.6.3., renumber and amend to read:

"4.6.3. In the case of a natural gas/**biomethane** fuelled engine the manufacturer shall demonstrate the parent engines capability to adapt to any fuel composition that may occur across the market.

4.6.3.1. In the case of **compressed** natural gas/**biomethane (CNG)** there are generally two types of fuel, high calorific fuel (H-gas) and low calorific fuel (L-gas), but with a significant spread within both ranges; they differ significantly in their energy content expressed by the Wobbe Index and in their λ -shift factor (S_λ). Natural gases with a λ -shift factor between 0.89 and 1.08 ($0.89 \leq S_\lambda \leq 1.08$) are considered to belong to H-range, while natural gases with a λ -shift factor between 1.08 and 1.19 ($1.08 \leq S_\lambda \leq 1.19$) are considered to belong to L-range. The composition of the reference fuels reflects the extreme variations of S_λ .

The parent engine shall meet the requirements of this Regulation on the reference fuels G_R (fuel 1) and G_{25} (fuel 2), as specified in Annex 5, without any **manual** readjustment to the **engine fuelling system** between the two tests (**self-adaptation is required**). One adaptation run over one WHTC hot cycle without measurement is permitted after the change of the fuel. After the adaptation run the engine shall be cooled down in accordance with paragraph 7.6.1. of Annex 4."

Paragraph 4.6.3.1. (former), renumber as 4.6.3.1.1.

Insert a new paragraph 4.6.3.2., to read:

"4.6.3.2 **In the case of liquefied natural gas/liquefied biomethane (LNG) the parent engine shall meet the requirements of this Regulation on the reference fuels G_R (fuel 1) and G_{20} (fuel 2), as specified in Annex 5, without any manual readjustment to the engine fuelling system between the two tests (self adaptation is required). One adaptation run over one WHTC hot cycle without measurement is permitted after the change of the fuel. After the adaptation run, the engine shall be cooled down in accordance with paragraph 7.6.1. of Annex 4.**"

Paragraph 4.6.4., amend to read:

"4.6.4. In the case of an engine fuelled with **compressed** natural gas/**biomethane** (CNG) which is self-adaptive for the range of H-gases on the one hand and the range of L-gases on the other hand, and which switches between the H-range and the L-range by means of a switch, the parent engine shall be tested on the relevant reference fuel as specified in Annex 5 for each range, at each position of the switch. ..."

Paragraph 4.7., amend to read:

"4.7. Requirements on restricted fuel range type-approval in case of positive ignition engines fuelled with **compressed** natural gas/**biomethane** (CNG) or LPG."

Insert a new paragraphs 4.8. to 4.8.2.1., to read (including footnote 2):

"4.8. **Requirements on fuel-specific type-approval in the case of engines fuelled with liquefied natural gas/liquefied biomethane (LNG)**

In case of liquefied natural gas/liquefied biomethane, a fuel specific type-approval may be granted subject to the requirements specified in sections 4.8.1. to 4.8.2.

4.8.1. *Conditions for applying for a fuel-specific type approval in the case of engines fuelled with liquefied natural gas/liquefied biomethane (LNG).*

4.8.1.1. **The manufacturer can only apply for a fuel specific type-approval in the case of the engine being calibrated for a specific LNG gas composition² resulting in a λ -shift factor not differing by more than 3 per cent from the λ -shift factor of the G₂₀ fuel specified in Annex 5; and the ethane content of which does not exceed 1.5 per cent.**

4.8.1.2. **In all other cases the manufacturer shall apply for a universal fuel type approval according to the specifications of paragraph 4.6.3.2.**

4.8.2. *Specific test requirements in the case of a fuel-specific type approval (LNG).*

4.8.2.1 **In the case of a dual-fuel engine family where the engines are calibrated for a specific LNG gas composition² resulting in a λ -shift factor not differing by more than 3 per cent from the λ -shift factor of the G₂₀ fuel specified in Annex 5, and the ethane content of which does not exceed 1.5 per cent, the parent engine shall only be tested on the G₂₀ reference gas fuel, as specified in Annex 5."**

Paragraphs 4.8 (former) to 4.8.2. (former), renumber as paragraphs 4.9. to 4.9.2.

Paragraphs 4.9 (former), delete.

Paragraph 4.12.3.3.6., amend to read:

"4.12.3.3.6. ...

- (f) HLt in the case of the engine being approved and calibrated for a specific gas composition in either the H-range or the L-range of gases and transformable to another specific gas in either the H-range or the L-range of gases by fine tuning of the engine fuelling-;

² This would typically be the case of a liquefied bio-methane.

- (g) LNG₂₀ in case of the engine being approved and calibrated for a specific liquefied natural gas / liquefied biomethane composition resulting in a λ -shift factor not differing by more than 3 per cent the λ -shift factor of the G₂₀ gas specified in Annex 5, and the ethane content of which does not exceed 1.5 per cent;
- (h) LNG in case of the engine being approved and calibrated for any other liquefied natural gas / liquefied biomethane composition."

Insert a new paragraph 4.12.3.3.7., to read:

"4.12.3.3.7. For dual-fuel engines the approval mark shall contain a series of digits after the national symbol, the purpose of which is to distinguish for which dual-fuel engine type and with which range of gases the approval has been granted.

This series of digits will be constituted of two digits for the dual-fuel type followed by the letter(s) specified in paragraphs 4.12.3.3.1 to 4.12.3.3.6. as appropriate.

The two digits identifying the dual-fuel engines types according to the definitions of Annex 15 are the following:

- (a) 1A for dual-fuel engines of Type 1A;
- (b) 1B for dual-fuel engines of Type 1B;
- (c) 2A for dual-fuel engines of Type 2A;
- (d) 2B for dual-fuel engines of Type 2B;
- (e) 3B for dual-fuel engines of Type 3B."

Insert a new paragraph 6.2.1., to read:

"6.2.1. The installation of a dual-fuel engine type-approved as a separate technical unit on a vehicle shall, in addition, meet the requirements of paragraph 6.3. of Annex 15 and, according to section 8.2. of Annex 15, meet the manufacturer's installation requirements as specified in Part 1 of Annex 1."

Paragraph 7.1., amend to read:

"7.1. Parameters defining the engine family

The engine family, as determined by the engine manufacturer shall comply with paragraph 5.2. of Annex 4.

In case of a dual-fuel engine, the engine family shall also comply with the additional requirements of paragraph 3.1.1. of Annex 15."

Paragraph 7.2., amend to read:

"7.2. Choice of the parent engine

The parent engine of the family shall be selected in accordance with the requirements set out in paragraph 5.2.4. of Annex 4.

In case of a dual-fuel engine, the parent engine family shall also comply with the additional requirements of paragraph 3.1.2. of Annex 15."

Insert new paragraphs 7.3. to 7.3.3., to read:

"7.3. Extension to include a new engine system into an engine-family

- 7.3.1. At the request of the manufacturer and upon approval of the Approval Authority, a new engine system may be included as a member of a certified engine family if the criteria specified in paragraph 7.1. are met.
- 7.3.2. If the elements of design of the parent engine system are representative of those of the new engine system according to paragraph 7.2. or, in the case of dual-fuel engines, to paragraph 3.1.2. of Annex 15, then the parent engine system shall remain unchanged and the manufacturer shall modify the information document specified in Annex 1.
- 7.3.3. If the new engine system contains elements of design that are not represented by the parent engine system according to paragraph 7.2. or, in the case of dual-fuel engines, to paragraph 3.1.2. of Annex 15, but itself would represent the whole family according to these paragraphs, then the new engine system shall become the new parent engine. In this case the new elements of design shall be demonstrated to comply with the provisions of this Regulation and the information document specified in Annex 1 shall be modified."

Paragraph 7.3. (former), renumber as paragraphs 7.4.

Appendix 4, the title, amend to read:

"Summary of approval process for **engines fuelled with natural gas, engines fuelled with and LPG fuelled engines and dual-fuel engines fuelled with natural gas/biomethane or LPG**"

Appendix 4, insert new table at the end, to read:

Approval for dual engines fuelled with natural gas/biomethane or LPG

<i>Dual-fuel type¹</i>	<i>Diesel mode</i>	<i>Dual-fuel mode</i>			
		<i>CNG</i>	<i>LNG</i>	<i>LNG20</i>	<i>LPG</i>
1A		Universal or restricted	Universal 1 (2 tests)	Fuel specific	Universal or restricted
		(2 tests)		(1 test)	(2 tests)
1B	Universal	Universal or restricted	Universal 1 (2 tests)	Fuel specific	Universal or restricted
	(1 test)	(2 tests)		(1 test)	(2 tests)
2A		Universal or restricted	Universal 1 (2 tests)	Fuel specific	Universal or restricted
		(2 tests)		(1 test)	(2 tests)
2B	Universal	Universal or restricted	Universal 1 (2 tests)	Fuel specific	Universal or restricted
	(1 test)	(2 tests)		(1 test)	(2 tests)
3B	Universal	Universal or restricted	Universal 1 (2 tests)	Fuel specific	Universal or restricted

	(1 test)	(2 tests)		(1 test)	(2 tests)
¹ According to the definitions of Annex 15.					

Annex1, part 1, table, amend to read (also inserting new rows):

"Essential characteristics of the (parent) engine and the engine types within an engine family

		Parent Engine or Engine Type	Engine Family Members				
			A	B	C	D	E
...	...						
3.2.1.1.	Working principle: positive ignition/compression ignition/ dual fuel ⁽¹⁾ Cycle four stroke / two stroke/ rotary ⁽¹⁾						
3.2.1.1.1.	Type of dual-fuel engine: Type 1A/Type 1B/Type 2A/Type 2B/Type 3B ⁽¹⁾ ^(df) Gas Energy Ratio over the hot part of the WHTC cycle ^(df) :%						
...	...						
3.2.1.6.2.	Idle on Diesel: yes/no ⁽¹⁾ ^(df)						
...	...						
3.2.2.2.	Heavy duty vehicles Diesel/Petrol/LPG/NG-H/NG-L/NG-HL/Ethanol (ED95)/Ethanol (E85)/ dual fuel ⁽¹⁾						
...	...						
3.2.4.2.	By fuel injection (only compression ignition only or dual fuel): yes/no ⁽¹⁾						
...	...						
3.2.12.7.0.6	When appropriate, manufacturer reference of the documentation for installing the dual-fuel engine in a vehicle						
...	...						
3.2.17.	Specific information related to gas fuelled engines and dual fuel engines for heavy-duty vehicles (in the case of systems laid out in a different manner, supply equivalent information)						
...	...						
3.5.4.1.	CO ₂ mass emissions WHSC test ^(dg) : (g/kWh)						
3.5.4.1.1.	For dual-fuel engines, CO₂ mass emissions WHSC test in diesel mode ^(d) :g/kWh For dual-fuel engines, CO₂ mass emissions WHSC test in dual-fuel mode ^(d) (if applicable): g/kWh						
3.5.4.2.	CO ₂ mass emissions WHTC test ^(dg) :						

	Parent Engine or Engine Type	Engine Family Members				
		A	B	C	D	E
..... (g/kWh)						
3.5.4.2.1.	For dual-fuel engines, CO₂ mass emissions WHTC test in diesel mode ^(d): g/kWh For dual-fuel engines, CO₂ mass emissions WHTC test in dual-fuel mode ^(d): g/kWh					
3.5.5.	Fuel consumption for heavy duty engines					
3.5.5.1.	Fuel consumption WHSC test ^(dg) : (g/kWh)					
3.5.5.1.1.	For dual-fuel engines, Fuel consumption WHSC test in diesel mode ^(d): g/kWh For dual-fuel engines, Fuel consumption WHSC test in dual-fuel mode ^(d): g/kWh					
3.5.5.2.	Fuel consumption WHTC test ^(e) ^(dg) : (g/kWh)					
3.5.5.2.1.	For dual-fuel engines, Fuel consumption WHTC test in diesel mode ^(d): g/kWh For dual-fuel engines, Fuel consumption WHTC test in dual-fuel mode ^(d): g/kWh					
...	...					

Annex 1, Appendix to information document, paragraph 5.1, amend to read:

"5.1 Engine test speeds for emissions test according to annex ~~III~~ 4 ⁽⁹⁾ or engine test speeds for emissions test in dual-fuel mode according to annex 4 ^{(9)(df)}."

Annex 1, Appendix to information document, insert a new paragraph 5.1.1., to read:

"5.1.1. Engine test speeds for emissions test in diesel mode according to annex 4 ^{(9)(df)(di)}

Low speed (nlo) rpm

High speed (nhi) rpm

Idle speed rpm

Preferred speed rpm

n95h rpm"

Annex 1, Appendix to information document, paragraph 5.2, amend to read:

"5.2. Declared values for power test according to Regulation 85 or declared values for power test in dual-fuel mode according to Regulation 85 ^(df)."

Annex 1, Appendix to information document, insert new paragraphs 5.2.6. to 5.2.6.5., to read:

"5.2.6.	Declared values for power test in diesel mode according to Regulation 85 <small>(df)(di)</small>	
5.2.6.1.	Idle speed rpm
5.2.6.2.	Speed at maximum power rpm
5.2.6.3.	Maximum power kW
5.2.6.4.	Speed at maximum torque rpm
5.2.6.5.	Maximum torque Nm"

Annex 1, Appendix 1, amend to read:

" ...

- (c) This figure shall be rounded off to the nearest tenth of a millimetre.
 - (d) **When required by this Regulation.**
 - (df) **In case of a dual-fuel engine or vehicle (types as defined in Annex 15).**
 - (dg) **Except for dual-fuel engines or vehicles (types as defined in Annex 15).**
 - (dh) **In case of a dual-fuel engine or vehicle, the type of gaseous fuel used in dual-fuel mode shall not be struck out.**
 - (di) **In the case of Type 1B, Type 2B, and Type 3B of dual-fuel engines (types as defined in Annex 15).**
 - (m) This value shall be calculated and rounded off to the nearest cm³.
- ..."

Annex 2A, Addendum to Type-approval Communication No ... concerning the type-approval of an engine type or family as a separate technical unit with regard to exhaust emissions pursuant to Regulation No. 49, 06 series of amendments, and

Annex 2C, Addendum to Type-approval Communication No ... concerning the type-approval of a vehicle type with regard to the emission of pollutants pursuant to Regulation No. 49, 06 series of amendments,

Paragraphs 1.1.5., amend to read:

"1.1.5. Category of engine: Diesel/Petrol/LPG/NG-H/NG-L/NG-HL/Ethanol (ED95)/ Ethanol (E85)/**dual fuel**⁽¹⁾"

Insert new paragraphs 1.1.5.1., to read:

"**1.1.5.1. Type of dual-fuel engine: Type 1A/Type 1B/Type 2A/Type 2B/Type 3B**⁽¹⁾
(df)"

Paragraphs 1.4., amend to read:

"1.4. Emission levels of the engine/parent engine⁽¹⁾
Deterioration Factor (DF): calculated/fixed⁽¹⁾
Specify the DF values and the emissions on the WHSC (if applicable) and WHTC tests in the table below
In case of ~~if CNG and LPG fuelled engines are~~ tested on different reference fuels, the tables shall be reproduced for each reference fuel tested.

In case of Type 1B and Type 2B dual-fuel engines, the tables shall be reproduced for each mode tested (dual-fuel and diesel modes)."

Paragraphs 1.4.1. and 1.4.2., amend to read:

"1.4.1. WHSC test

**Table 4
WHSC test**

WHSC test (if applicable)							
DF	CO	THC	NMHC ^(d)	NO _x	PM Mass	NH ₃	PM Number
Mult/add ⁽¹⁾							
Emissions	CO (mg/kWh)	THC (mg/kWh)	NMHC ^(d) (mg/kWh)	NO _x (mg/kWh)	PM Mass (mg/kWh)	NH ₃ ppm	PM Number (#/kWh)
Test result							
Calculated with DF							
CO ₂ emissions mass emission ^(d) :g/kWh CO ₂ emissions (mass emission, g/kWh)							
Fuel consumption ^(d) :g/kWh Fuel consumption (g/kWh)							

Formatted: Indent: Left: 0 cm, Sp After: 0 pt, Keep with next

1.4.2. WHTC Test

**Table 5
WHTC Test**

WHTC test								
DF	CO	THC ^(d)	NMHC ^(d)	CH ₄ ^(d)	NO _x	PM Mass	NH ₃	PM Number
Mult/add ⁽¹⁾								
Emissions	CO (mg/kWh)	THC ^(d) (mg/kWh)	NMHC ^(d) (mg/kWh)	CH ₄ ^(d) (mg/kWh)	NO _x (mg/kWh)	PM Mass (mg/kWh)	NH ₃ ppm	PM Number (#/kWh)
Cold start								
Hot start w/o regeneration								
Hot start with regeneration ⁽¹⁾								
k _{r,u} (mult/add) ⁽¹⁾								
k _{r,d} (mult/add) ⁽¹⁾								
Weighted test result								
Final test result with DF								
CO ₂ emissions mass emission ^(d) :g/kWh CO ₂ emissions (mass emission, g/kWh)								
Fuel consumption ^(d) :g/kWh Fuel consumption (g/kWh)								

Annex 3, Table 2, amend to read:

"Table 2
Engine type codes for approval marks

<i>Engine type</i>	<i>Code</i>
Diesel fuelled CI engine	D
Ethanol (ED95) fuelled CI engine	ED
Ethanol (E85) fuelled PI engine	E85
Petrol fuelled PI engine	P
LPG fuelled PI engine	Q
Natural gas fuelled PI engine	See paragraph 4.12.3.3.6. of this Regulation
Dual-fuel engines	See paragraph 4.12.3.3.7. of this Regulation

Annex 4, Equation (15), amend to read:

$$k_{w,e} = \left(\frac{1}{1 + a \times 0,005 \times (c_{CO_2} + c_{CO})} - k_{w1} \right) * 1,008 \quad (15)$$

Field Code Changed

Annex 4, Equation (17), amend to read:

$$k_{w1} = \frac{1,608 \times H_a}{1000 + (1,608 \times H_a)} \quad (17)$$

Field Code Changed

Annex 4, Equation (18), amend to read:

$$k_{w,e} = \left[\left(1 - \frac{\alpha \times c_{CO_2w}}{200} \right) - k_{w2} \right] \times 1,008 \quad (18)$$

Field Code Changed

Annex 4, Equation (19), amend to read:

$$k_{w,e} = \left[\left(\frac{(1 - k_{w2})}{1 + \frac{\alpha \times c_{CO_2d}}{200}} \right) \right] \times 1,008 \quad (19)$$

Field Code Changed

Annex 4, Equation (20), amend to read:

$$k_{w2} = \frac{1,608 \times \left[H_d \times \left(1 - \frac{1}{D} \right) + H_a \times \left(\frac{1}{D} \right) \right]}{1000 + \left\{ 1,608 \times \left[H_d \times \left(1 - \frac{1}{D} \right) + H_a \times \left(\frac{1}{D} \right) \right] \right\}} \quad (20)$$

Field Code Changed

Annex 4, Equation (21), amend to read:

$$k_{w,d} = (1 - k_{w3}) \times 1,008 \quad (21)$$

Field Code Changed

Annex 4, Equation (22), amend to read:

$$k_{w2} = \frac{1,608 \times H_d}{1000 + (1,608 \times H_d)} \quad (22)$$

Field Code Changed

Annex 5, the title of the first section, amend to read:

"Technical data on fuels for testing compression-ignition **and dual fuel** engines"

Annex 5, insert new table at the end of the first section, to read:

"Type: Natural gas/Biomethane

Characteristics	Units	Basis	Limits		Test method
			minimum	maximum	
Reference fuel G₂₀					
Composition:					
Methane	% mole	100	99	100	ISO 6974
Balance ⁽¹⁾	% mole	—	—	1	ISO 6974
N ₂	% mole	—	—	—	ISO 6974
Sulphur content	mg/m ³ ⁽²⁾	—	—	10	ISO 6326-5
Wobbe Index (net)	MJ/m ³ ⁽³⁾	48.2	47.2	49.2	
⁽¹⁾ Inerts (different from N ₂) + C ₂ + C ₂ +					
⁽²⁾ Value to be determined at 293,2 K (20 °C) and 101,3 kPa.					
⁽³⁾ Value to be determined at 273,2 K (0 °C) and 101,3 kPa.					

Annex 5, the title of the second section, amend to read:

"Technical data on fuels for testing positive ignition **and dual fuel** engines"

Annex 7, paragraph 3.7.1., amend to read:

"3.7.1. The engines shall meet the respective emission limits for each pollutant, as given in paragraph 5.3. of this Regulation, after application of the deterioration factors to the test result as measured in accordance with Annex ~~III~~-4 (e_{gas}, e_{PM}). Depending on the type of deterioration factor (DF), the following provisions shall apply:

..."

Annex 9B, paragraph 4.2., amend to read:

"4.2. Monitoring requirements

All emission-related components and systems included in an engine system shall be monitored by the OBD system in accordance with the requirements set in Appendix 3 **and, in the case of dual-fuel engines or vehicles in section 7 of Annex 15**. However, the OBD system is not required to use a unique monitor to detect each malfunction referred to in Appendix 3 **and, in the case of dual-fuel engines or vehicles in section 7 of Annex 15**.

..."

Annex 9B, paragraph 4.2.1., amend to read:

"4.2.1. Selection of the monitoring technique

Approval authorities may approve a manufacturer's use of another type of monitoring technique than the one mentioned in Appendix 3 **or, in the case of dual-fuel engines or vehicles in section 7 of Annex 15**. The chosen type of monitoring shall be shown by the manufacturer, to be robust, timely and efficient (i.e. through technical considerations, test results, previous agreements, etc.).

In case a system and/or component is not covered by Appendix 3 **or, in the case of dual-fuel engines or vehicles in section 7 of Annex 15**, the manufacturer shall submit for approval to the Approval Authority an

approach to monitoring. The Approval Authority will approve the chosen type of monitoring and monitoring technique (i.e. emission threshold monitoring, performance monitoring, total functional failure monitoring, or component monitoring) if it has been shown by the manufacturer, by reference to those detailed in Appendix 3 **or, in the case of dual-fuel engines or vehicles in section 7 of Annex 15**, to be robust, timely and efficient (i.e. through either technical considerations, test results, previous agreements, etc.)."

Annex 9B, paragraph 6.3.2.1.2., amend to read:

6.3.2.1.2. Performance monitoring

At the request of the manufacturer and with the agreement of the Approval Authority, in the case of performance monitoring, the OTL may be exceeded by more than 20 per cent. Such request shall be justified on a case by case basis.

In the case when the performance monitoring of an abnormality of the gaseous fuel consumption of a dual-fuel engine or vehicle is required by Annex 15, a deteriorated component is qualified without reference to the OTL."

Annex 9B, Appendix 4, section with the title "Item 1 to the technical compliance report (example)", first line of text, amend to read:

"Information concerning the ~~OBS~~-OBD system"

Annex 9B, Appendix 4, section with the title "Item 2 to the technical compliance report (example)", paragraph 2, the first row of the table, amend to read:

"

<p><i>Monitoring</i></p> <p>The monitors comply with the requirements of paragraph section 4.2. of this annex:</p>	<p>YES / NO</p>
--	-----------------

"

Insert a new Annex 15, to read (including footnotes):

"Annex 15

Technical requirements for diesel-gas dual-fuel engines and vehicles

1. **Scope**
This annex shall apply to dual-fuel engines and dual-fuel vehicles.
2. **Definitions and abbreviations**
 - 2.1. **"Gas Energy Ratio (GER)"** means in case of a dual-fuel engine the ratio (expressed as a percentage) of the energy content of the gaseous fuel¹ over the energy content of both fuels (diesel and gaseous).

¹ Based on the lower heating value.

- 2.2. "Average gas ratio" means the average gas energy ratio calculated over a specific operating sequence.
- 2.3. "Heavy-Duty Dual-Fuel (HDDF) Type 1A engine" means a dual-fuel engine that operates over the hot part of the WHTC test-cycle with an average gas ratio that is not lower than 90 per cent ($GER_{WHTC} \geq 90 \%$), and that does not idle using exclusively diesel fuel, and that has no diesel mode.
- 2.4. "Heavy-Duty Dual-Fuel (HDDF) Type 1B engine" means a Dual-Fuel engine that operates over the hot part of the WHTC test-cycle with an average gas ratio that is not lower than 90 per cent ($GER_{WHTC} \geq 90 \%$), and that does not idle using exclusively diesel fuel in dual-fuel mode, and that has a diesel mode.
- 2.5. "Heavy-Duty Dual-Fuel (HDDF) Type 2A engine" means a Dual-Fuel engine that operates over the hot part of the WHTC test-cycle with an average gas ratio between 10 per cent and 90 per cent ($10 \% < GER_{WHTC} < 90 \%$) and that has no diesel mode or that operates over the hot part of the WHTC test-cycle with an average gas ratio that is not lower than 90 per cent ($GER_{WHTC} \geq 90 \%$), but that idles using exclusively diesel fuel, and that has no diesel mode.
- 2.6. "Heavy-Duty Dual-Fuel (HDDF) Type 2B engine" means a Dual-Fuel engine that operates over the hot part of the WHTC test-cycle with an average gas ratio between 10 per cent and 90 per cent ($10 \% < GER_{WHTC} < 90 \%$) and that has a diesel mode or that operates over the hot part of the WHTC test-cycle with an average gas ratio that is not lower than 90 per cent ($GER_{WHTC} \geq 90 \%$), but that can idle using exclusively diesel fuel in dual-fuel mode, and that has a diesel mode.
- 2.7. "Heavy-Duty Dual-Fuel (HDDF) Type 3B engine"² means a dual-fuel engine that operates over the hot part of the WHTC test-cycle with an average gas ratio that does not exceed 10 per cent ($GER_{WHTC} \leq 10 \%$) and that has a diesel mode.
3. Dual-fuel specific additional approval requirements
- 3.1. Dual-fuel-engine family
- 3.1.1. Criteria for belonging to a dual-fuel engine family
- All engines within a dual-fuel engine family shall belong to the same type of dual-fuel engines defined in section 2³, and operate with the same types of fuel or when appropriate with fuels declared according to this Regulation as being of the same range(s).
- All engines within a dual-fuel engine family shall meet the criteria defined by this Regulation for belonging to a compression ignition engine family.
- The difference between the highest and the lowest GER_{WHTC} (i.e. the highest GER_{WHTC} minus the lowest GER_{WHTC}) within a dual-fuel engine family shall not exceed 30 per cent.

² HDDF Type 3A are neither defined nor allowed by this Regulation.

³ For example HDDF Type 1A, or HDDF Type 2B, or etc.

- 3.1.2. Selection of the parent engine**
 The parent engine of a dual-fuel engine family shall be selected according to the criteria defined by this Regulation for selecting the parent engine of a compression ignition engine family.
- 4. General requirements**
- 4.1. Operating modes of dual-fuel engines and vehicles**
- 4.1.1. Conditions for a dual-fuel engine to operate in diesel mode**
 A dual-fuel engine may only operate in diesel mode if, when operating in diesel mode, it has been certified according to all the requirements of this Regulation concerning diesel engines.
 When a dual-fuel engine is developed from an already certified diesel engine, then re-certification is required in the diesel mode
- 4.1.2. Conditions for a HDDF engine to idle using diesel fuel exclusively**
- 4.1.2.1. HDDF Type 1A engines shall not idle using diesel fuel exclusively except under the conditions defined in section 4.1.3. for warm-up and start.**
- 4.1.2.2. HDDF Type 1B engines shall not idle using diesel fuel exclusively in dual-fuel mode.**
- 4.1.2.3. HDDF Types 2A, 2B and 3B engines may idle using diesel fuel exclusively.**
- 4.1.3. Conditions for a HDDF engine to warm-up or start using diesel fuel solely**
- 4.1.3.1. A Type 1B, Type 2B, or Type3B dual-fuel engine may warm-up or start using diesel fuel solely. However, in that case, it shall operate in diesel mode.**
- 4.1.3.2. A Type 1A or Type 2A dual-fuel engine may warm-up or start using diesel fuel solely. However, in that case, the strategy shall be declared as an AES and the following additional requirements shall be met:**
- 4.1.3.2.1. The strategy shall cease to be active when the coolant temperature has reached a temperature of 343 K (70 °C), or within 15 minutes after it has been activated, whichever occurs first; and**
- 4.1.3.2.2. The service mode shall be activated while the strategy is active.**
- 4.2. Service mode**
- 4.2.1. Conditions for dual-fuel engines and vehicles to operate in service mode**
 When its engine is operating in service mode, a dual-fuel vehicle is subject to an operability restriction and is temporarily exempted from complying with the requirements related to exhaust emissions, OBD and NO_x control described in this Regulation.
- 4.2.2. Operability restriction in service mode**
 The operability restriction applicable to dual-fuel vehicles when they operate in service mode is the one activated by the "severe inducement system" specified in Annex 11.

The operability restriction shall not be deactivated by either the activation or deactivation of the warning and inducement systems specified in Annex 11.

The activation and the deactivation of the service mode shall not activate or deactivate the warning and inducement systems specified in Annex 11.

Illustrations of the operability restriction requirements are given in Appendix 2.

4.2.2.1. Activation of the operability restriction

The operability restriction shall be automatically activated when the service mode is activated.

In the case where the service mode is activated according to paragraph 4.2.3 because of a malfunction of the gas supply system or because of an abnormality of gas consumption, the operability restriction shall become active after the next time the vehicle is stationary or within 30 minutes operating time after the service mode is activated, whichever comes first.

In the case where the service mode is activated because of an empty gas tank, the operability restriction shall become active as soon as the service mode is activated.

4.2.2.2. Deactivation of the operability restriction

The operability restriction system shall be deactivated when the vehicle no longer operates in service mode.

4.2.3. Unavailability of gaseous fuel when operating in a dual-fuel mode

In order to permit the vehicle to keep moving and eventually to move out of the main-stream traffic, upon detection of an empty gaseous fuel tank, or of a malfunctioning gas supply system according to paragraph 7.2., or of an abnormality of gas consumption in dual-fuel mode according to paragraph 7.3.:

- (a) Dual-fuel engines of Types 1A and 2A shall activate the service mode;
- (b) Dual-fuel engines of Types 1B, 2B and 3B shall operate in diesel mode.

4.2.3.1. Unavailability of gaseous fuel – empty gaseous fuel tank

In the case of an empty gaseous fuel tank, the service mode or, as appropriate according to paragraph 4.2.3., the diesel mode shall be activated as soon as the engine system has detected that the tank is empty.

When the gas availability in the tank again reaches the level that justified the activation of the empty tank warning system specified in paragraph 0, the service mode may be deactivated, or, when appropriate, the dual-fuel mode may be reactivated.

4.2.3.2. Unavailability of gaseous fuel – malfunctioning gas supply

In the case of a malfunctioning gas supply system according to paragraph 7.2., the service mode or, as appropriate according to paragraph 4.2.3., the diesel mode shall be activated when the DTC relevant to that malfunction has the confirmed and active status.

As soon as the diagnostic system concludes that the malfunction is no longer present or when the information, including DTCs relative to the failures, justifying its activation is erased by a scan tool, the service mode may be deactivated, or, when appropriate, the dual-fuel mode may be reactivated.

4.2.3.2.1. If the counter specified in paragraph 4.4 and associated with a malfunctioning gas supply system is not at zero, and is consequently indicating that the monitor has detected a situation when the malfunction may have occurred for a second or subsequent time, the service mode or, as appropriate, the diesel mode shall be activated when the DTC has the status "potential".

4.2.3.3. Unavailability of gaseous fuel – abnormality of gas consumption

In case of an abnormality of gas consumption in dual-fuel mode according to paragraph 7.3., the service mode or, as appropriate according to paragraph 4.2.3., the diesel mode shall be activated when the DTC relevant to that malfunction has reached the potential status.

As soon as the diagnostic system concludes that the malfunction is no longer present or when the information, including DTCs relative to the failures, justifying its activation is erased by a scan tool, the service mode may be deactivated, or, when appropriate, the dual-fuel mode may be reactivated.

4.3. Dual-fuel indicators

4.3.1. Dual-fuel operating mode indicator

Dual-fuel engines and vehicles shall provide to the driver a visual indication of the mode under which the engine operates (dual-fuel mode, diesel mode, or service mode).

The characteristics and the location of this indicator are left to the decision of the manufacturer and may be part of an already existing visual indication system.

This indicator may be completed by a message display. The system used for displaying the messages referred to in this paragraph may be the same as the ones used for OBD, correct operation of NO_x control measures, or other maintenance purposes.

The visual element of the dual-fuel operating mode indicator shall not be the same as the one used for the purposes of OBD (that is, the MI – malfunction indicator), for the purpose of ensuring the correct operation of NO_x control measures, or for other engine maintenance purposes.

Safety alerts always have display priority over the operating mode indication.

4.3.1.1. The dual-fuel mode indicator shall be set to service mode as soon as the service mode is activated (i.e. before it becomes actually active) and the indication shall remain as long as the service mode is active.

4.3.1.2. The dual-fuel mode indicator shall be set for at least one minute on dual-fuel mode or diesel mode as soon as the engine operates on dual-fuel or on diesel mode. This indication is required at key-on for at least 1 minute. The indication shall also be given upon driver's request.

- 4.3.2. Empty gaseous fuel tank warning system (dual-fuel warning system)**
- A dual-fuel vehicle shall be equipped with a dual-fuel warning system that alerts the driver that the gaseous fuel tank will soon become empty.
- The dual-fuel warning system shall remain active until the tank is refuelled to a level above which the warning system is activated.
- The dual-fuel warning system may be temporarily interrupted by other warning signals providing important safety-related messages.
- It shall not be possible to turn off the dual-fuel warning system by means of a scan-tool as long as the cause of the warning activation has not been rectified.
- 4.3.2.1. Characteristics of the dual-fuel warning system**
- The dual-fuel warning system shall consist of a visual alert system (icon, pictogram, etc...) left to the choice of the manufacturer.
- It may include, at the choice of the manufacturer, an audible component. In that case, the cancelling of that component by the driver is permitted.
- The visual element of the dual-fuel warning system shall not be the same as the one used for the OBD system (that is, the MI – malfunction indicator), for the purpose of ensuring the correct operation of NO_x control measures, or for other engine maintenance purposes.
- In addition the dual-fuel warning system may display short messages, including messages indicating clearly the remaining distance or time before the activation of the operability restriction.
- The system used for displaying the messages referred to in this paragraph may be the same as the one used for displaying additional OBD messages, messages related to correct operation of NO_x control measures, or messages for other maintenance purposes.
- A facility to permit the driver to dim the visual alarms provided by the warning system may be provided on vehicles for use by the rescue services or on vehicles designed and constructed for use by the armed services, civil defense, fire services and forces responsible for maintaining public order.
- 4.4. Malfunctioning gas supply counter**
- The system shall contain a counting system to record the number of hours during which the engine has been operated while the system has detected a malfunctioning gas supply system according to paragraph 7.2.
- 4.4.1. The activation and deactivation criteria and mechanisms of the counter shall comply with the specifications of Appendix 2.**
- 4.4.2. It is not required to have a counter as specified in paragraph 4.4., when the manufacturer can demonstrate to the approval authority (e.g. by means of a strategy description, experimental elements, etc...) that the dual-fuel engine automatically switches to diesel mode in case malfunction is detected.**

- 4.5. Demonstration of the dual-fuel indicators and operability restriction**
As part of the application for type-approval under this Regulation, the manufacturer shall demonstrate the operation of dual-fuel indicators and of the operability restriction in accordance with the provisions of Appendix 3.
- 4.6. Communicated torque**
- 4.6.1. Communicated torque when a dual-fuel engine operates in dual-fuel mode**
When a dual-fuel engine operates in dual-fuel mode:
- (a) The reference torque curve retrievable according to the requirements related to data stream information specified in Annex 9B and referred to by Annex 8 shall be the one obtained according to Annex 4 when that engine is tested on an engine test bench in the dual-fuel mode;
 - (b) The recorded actual torques (indicated torque and friction torque) shall be the result of the dual-fuel combustion and not the one obtained when operating with diesel fuel exclusively.
- 4.6.2. Communicated torque when an dual-fuel engine operates in diesel mode**
When a dual-fuel engine operates in diesel mode, the reference torque curve retrievable according to the requirements related to data stream information specified in Annex 9B and referred to by Annex 8 shall be the one obtained according to Annex 4 when the engine is tested on an engine test bench in diesel mode.
- 4.7. Requirements to limit Off-Cycle Emissions (OCE) and in-use emissions**
Dual-fuel engines shall be subject to the requirements of Annex 10, whether operating in dual-fuel mode or in the case of Type 1B, Type 2B, and Type 3B in diesel mode.
- 4.7.1. PEMS tests at certification**
The PEMS demonstration test at type-approval required in Annex 10 shall be performed by testing the parent engine of a dual-fuel engine family when operating in dual-fuel mode.
- 4.7.1.1. In the case of Type 1B, Type 2B and Type 3B dual-fuel engines, an additional PEMS test shall be performed in diesel mode on the same engine and vehicle immediately after of before the PEMS demonstration test performed in dual-fuel mode.**
In that case, certification can only be granted if both the PEMS demonstration test in dual-fuel mode and the PEMS demonstration test in diesel mode have concluded to a pass.
- 4.7.2. Additional requirements**
- 4.7.2.1. Adaptive strategies of a dual-fuel engine are allowed, provided that:**
- (a) The engine always remains in the HDDF type (that is Type 1A, Type 2B, etc...) that has been declared for type-approval; and

- (b) In case of a Type 2 engine, the resulting difference between the highest and the lowest GER_{WHTC} within the family shall never exceed the percentage specified in paragraph 3.1.1.; and
- (c) These strategies are declared and satisfy the requirements of Annex 10.

5. Performance requirements

5.1. Emission limits applicable to HDDF Type 1A and Type 1B engines

5.1.1. The emission limits applicable to HDDF Type 1A engines and HDDF Type 1B engines operating in dual-fuel mode are those defined for PI engines in paragraph 5.3. of this Regulation.

5.1.2. The emission limits applicable to HDDF Type 1B engines operating in diesel mode are those defined for CI engines in paragraph 5.3. of this Regulation.

5.2. Emission limits applicable to HDDF Type 2A and Type 2B engines

5.2.1. Emission limits applicable over the WHSC test-cycle

5.2.1.1. For HDDF Type 2A and Type 2B engines, the exhaust emission limits (incl. the PM number limit) over the WHSC test-cycle applicable to HDDF Type 2A engines and HDDF Type 2B engines operating in dual-fuel mode are those applicable to CI engines over the WHSC test-cycle and defined in the table of paragraph 5.3. of this Regulation.

5.2.1.2. The emission limits (incl. the PM number limit) over the WHSC test-cycle applicable to HDDF Type 2B engines operating in diesel mode are those defined for CI engines in paragraph 5.3. of this Regulation.

5.2.2. Emission limits applicable over the WHTC test-cycle

5.2.2.1. Emission limits for CO, NO_x, NH₃ and PM mass

The CO, NO_x, NH₃ and PM mass emission limits over the WHTC test-cycle applicable to HDDF Type 2A engines and HDDF Type 2B engines operating in dual-fuel mode are those applicable to both CI and PI engines over the WHTC test-cycle and defined in paragraph 5.3. of this Regulation.

5.2.2.2. Emission limits for Hydrocarbons

5.2.2.2.1. NG engines

The THC, NMHC and CH₄ emission limits over the WHTC test-cycle applicable to HDDF Type 2A engines and HDDF Type 2B engines operating with Natural Gas in dual-fuel mode are calculated from those applicable to CI and PI engines over the WHTC test-cycle and defined in paragraph 5.3. of this Regulation. The calculation procedure is specified in paragraph 5.3. of this Annex.

5.2.2.2.2. LPG engines

The THC emission limits over the WHTC test-cycle applicable to HDDF Type 2A engines and HDDF Type 2B engines operating with LPG in dual-fuel mode are those applicable to CI engines over the WHTC test-cycle and defined in paragraph 5.3. of this Regulation.

5.2.2.3. Emission limits for PM number

5.2.2.3.1. The PM number limit over the WHTC test-cycle applicable to HDDF Type 2A engines and HDDF Type 2B engines operating in dual-fuel mode are those applicable to CI engines over the WHTC test-cycle and defined in paragraph 5.3. of this Regulation. In the case a PM number limit applicable to PI engines over the WHTC test-cycle would be defined in paragraph 5.3. of this Regulation, then the requirements of paragraph 5.2.4. shall apply for calculating the limit applicable to HDDF Type 2A engines and HDDF Type 2B engines over that cycle.

5.2.2.3.2. The emission limits (incl. the PM number limit) over the WHTC test-cycle applicable to HDDF Type 2B engines operating in diesel mode are those defined for CI engines in paragraph 5.3. of this Regulation

5.2.3. Hydrocarbon limits (in mg/kWh) applicable to HDDF Type 2A engines and to HDDF Type 2B engines operating in dual-fuel mode during the WHTC test cycle.

The following calculation procedure applies for HDDF Type2A and HDDF Type 2B engines tested in the WHTC cycle while operating in dual-fuel mode:

Calculate the average gas ratio GER_{WHTC} over the hot part of the WHTC test cycle.

Calculate a corresponding THC_{GER} in mg/kWh using the following formula:

$$THC_{GER} = NMHC_{PI} + (CH4_{PI} * GER_{WHTC})$$

Determine the applicable THC limit in mg/kWh using the following method:

If $THC_{GER} \leq CH4_{PI}$, then

- (a) THC limit value = THC_{GER} ; and
- (b) No applicable CH_4 and NMHC limit value

If $THC_{GER} > CH4_{PI}$, then


- (a) No applicable THC limit value; and
- (b) Both the $NMHC_{PI}$ and $CH4_{PI}$ limit values are applicable.

In this procedure:

$NMHC_{PI}$ is the NMHC emission limit over the WHTC test-cycle and made applicable to PI engine by paragraph 5.3. of this Regulation;

$CH4_{PI}$ is the CH_4 emission limit over the WHTC test-cycle and applicable to PI engine by paragraph 5.3. of this Regulation.

Figure 1
Illustration of the HC limits in the case of a HDDF Type2 engine operating in dual-fuel mode during the WHTC cycle (natural gas dual-fuel engines)



5.2.4. PM number limit (in #/kWh) applicable to HDDF Type 2A engines and to HDDF Type 2B engines operating in dual-fuel mode during the WHTC test cycle.

In the case a PM number limit applicable to PI engines over the WHTC test-cycle would be defined in paragraph 5.3. of this Regulation, the following calculation procedure shall apply to HDDF Type 1A engines, to HDDF Type 1B engines, to HDDF Type 2A engines, to HDDF Type2A and to HDDF Type 2B engines tested in the WHTC cycle while operating in dual-fuel mode:

Calculate the average gas ratio GER_{WHTC} over the hot part of the WHTC test cycle, then

Calculate the PM number limit values $PN\ limit_{WHTC}$ in #/kWh applicable over the WHTC test-cycle using the following formula (linear interpolation between the CI and PI PM number limit values):


$$PN\ limit_{WHTC} = PN\ limit_{CI/WHTC} + (PN\ limit_{PI/WHTC} - PN\ limit_{CI/WHTC}) * GER_{WHTC}$$

where:

$PN\ limit_{PI/WHTC}$ is the PM number limit applicable to PI engines over the WHTC test cycle;

$PN\ limit_{CI/WHTC}$ is the PM number limit applicable to CI engines over the WHTC test cycle.

Figure 2
Illustration of the PN limits in the case of a HDDF Type2 engine operating in dual-fuel mode during the WHTC cycle



5.3. Emission limits applicable to HDDF Type 3B engines operating in dual-fuel mode

The emissions limits applicable to HDDF Type 3B engines whether operating in dual-fuel mode or in diesel mode are the exhaust emission limits applicable to CI engines.

5.4. Conformity factors

Principally, the emission limit applicable for applying the conformity factor used when performing a PEMS test, whether a PEMS test at certification or a PEMS test when checking and demonstrating the conformity of in-service engines and vehicles, shall be determined on the basis of the actual GER calculated from the fuel consumption measured over the on-road test.

However, in absence of a robust way to measure the gas or the diesel fuel consumption, the manufacturer is allowed to use the GER_{WHTC} determined on the hot part of the WHTC.

6. Demonstration requirements

6.1. Dual-fuel engines shall be subject to the laboratory tests specified in table 1

Table 1
Laboratory tests to be performed by a HDDF engine

	<i>Type 1A</i>	<i>Type 1B</i>	<i>Type 2A</i>
WHTC	NMHC; CH ₄ ; CO; NO _x ; PM; PN;NH ₃	<u>Dual-fuel mode:</u>	THC; NMHC; CH ₄ ;
		NMHC; CH ₄ ;	CO; NO _x ; PM;
		CO; NO _x ;	PN;NH ₃
		PM; PN;NH ₃	
		<u>Diesel mode:</u>	
		THC;	
		CO; NO _x ;	
PM; PN;NH ₃			
WHSC	no test	<u>Dual-fuel mode:</u>	NMHC;
		no test	CO; NO _x ;
			PM; PN;NH ₃
		<u>Diesel mode:</u>	
		THC;	
		CO; NO _x ;	
PM; PN;NH ₃			
WNTE laboratory test	no test	<u>Dual-fuel mode:</u>	[HC];
		no test	CO; NO _x ;
			PM
		<u>Diesel mode:</u>	
		THC;	
		CO; NO _x ;	
PM			

6.2. Demonstrations in case of installation of type-approved HDDF engines

In addition to the requirements of this Regulation related to the installation of an engine that is type-approved as separate technical unit, a demonstration of the correct installation on a vehicle of a dual-fuel engine shall be done on the basis of appropriate elements of design, results of verification tests, etc. It shall address the conformity of the following elements to the requirements of this Annex:

- (a) The dual-fuel indicators and warnings as specified in this Annex (pictogram, activation schemes, etc.);
- (b) The fuel storage system;
- (c) The performance of the vehicle in service mode.

Correct indicator illumination and warning system activation will be checked. But any check shall not force dismantling the engine system (e.g. an electric disconnection may be selected).

- 6.3. **Demonstration requirements in case of a Type2 engine**
 The manufacturer shall present the approval authority with evidence showing that the GER_{WHTC} span of all members of the dual-fuel engine family remains within the percentage specified in paragraph 3.1.1. (for example, through algorithms, functional analyses, calculations, simulations, results of previous tests, etc.).
- 6.4. **Additional demonstration requirements in case of a universal fuel range type-approval**
 On request of the manufacturer and with approval of the approval authority, a maximum of two times the last 10 minutes of the WHTC may be added to the adaptation run between the demonstration tests.
- 6.5. **Demonstration requirements for demonstrating the durability of a dual-fuel engine**
 Provisions of Annex 7 shall apply.
7. **OBD requirements**
- 7.1. **General OBD requirements**
 All dual-fuel engines and vehicles shall comply with the requirements specified in Annex 9A and applicable to diesel engines, independent whether operating in dual-fuel or diesel mode.
 In case a dual fuel engine system is equipped with oxygen sensor(s), the requirements applicable to gas engines in item 13 in Appendix 3 of Annex 9B shall apply.
 In case a dual fuel engine system is equipped with a 3-way catalyst, the requirements applicable to gas engines in items 7, 10., and 15 in Appendix 3 of Annex 9B shall apply.
- 7.1.1. **Additional general OBD requirements in case of Type 1B, Type 2B and Type 3B dual-fuel engines and vehicles.**
- 7.1.1.1. **In the case of malfunctions the detection of which does not depend on the operation mode of the engine, the mechanisms specified in Annex 9B that are associated with the DTC status shall not depend on the operation mode of the engine (for example, if a DTC reached the potential status in dual-fuel mode, it will get the confirmed and active status the next time the failure is detected, even in diesel mode).**
- 7.1.1.2. **In the case of malfunctions where the detection depends on the operation mode of the engine, DTCs shall not get a previously active status in a different mode than the mode in which they reached the confirmed and active status.**
- 7.1.1.3. **A change of the mode of operation (dual-fuel to diesel or vice-versa) shall not stop nor reset the OBD mechanisms (counters, etc.). However, in the case of failures the detection of which depends on the actual operation mode, the counters associated with these malfunctions may, at the request of the manufacturer and upon approval of the type-approval authority:**

- (a) halt and, when applicable, hold their present value when the operation mode changes;
- (b) restart and, when applicable, continue counting from the point at which they have been held when the operation mode changes back to the other operation mode.
- 7.1.1.4. A possible influence of the mode of operation on the malfunction detection shall not be used to extend the time until an operability restriction becomes active.
- 7.1.1.5. In case of a Type 1B, Type 2B, or Type 3B dual-fuel engine, the manufacturer shall specify which malfunctions are operation mode dependent. This information shall be included in the information package required in paragraph 8.1. (a) of Annex 9B. The justification for operation mode dependency shall be included in the information package required in paragraph 8.1. (b) of Annex 9B.
- 7.1.1.5. The following piece of information shall be added to table 1 in Appendix 5 of Annex 9B.

	<i>Freeze frame</i>	<i>Data stream</i>
In case of Type 1B, Type 2B and Type 3B dual-fuel engines, operation mode of the Dual-fuel Engine (dual-fuel or diesel)	x	x

- 7.2. **Monitoring of the gas supply system**
- HDDF engines and vehicles shall monitor the gas supply system within the engine system (incl. the signals coming from outside of the engine system) according to the specifications of item 1 in Appendix 3 to Annex 9B – component monitoring.
- 7.3. **Monitoring of the gaseous fuel consumption**
- Dual-fuel vehicles shall include a means of determining gas fuel consumption and providing off-board access to consumption information. Abnormality of the gaseous fuel consumption (e.g. a deviation of 50 per cent of the normal gaseous fuel consumption) shall be monitored – performance monitoring.
- The monitor for insufficient gaseous fuel consumption shall run continuously whenever in dual-fuel mode, however the maximum detection period is 48 hours of operation in dual-fuel mode.
- The monitor shall not be subject to the “IUPR” requirements.
- 7.4. **OBD Deficiencies**
- The deficiency rules specified in Annex 9B and applicable to diesel engines shall apply to dual-fuel engines.
- A deficiency that is present both in diesel mode and in dual-fuel mode shall not be counted for each mode separately.

- 7.5. Erasing of failure information by means of a scan-tool**
- 7.5.1.** Erasing of information by means of a scan tool, including DTCs relative to the malfunctions considered in this Annex shall be performed in accordance with Annex 9B.
- 7.5.2.** The erasing of failure information shall only be possible under "engine-off" conditions.
- 7.5.3.** When failure information related to the gas supply system as specified in paragraph 7.2., including the DTC, is erased, the counter associated with this failure shall not be erased.
- 8. Requirements to ensure the correct operation of NO_x control measures**
- 8.1.** Annex 11 (on correct operation of NO_x control measures) shall apply to Hddf engines and vehicles, whether operating in dual-fuel or diesel mode.
- 8.2. Additional general OBD requirements in case of Type 1B, Type 2B and Type 3B dual-fuel engines and vehicles**
- 8.2.1.** In case of Hddf Type 1B, Type 2B and Type 3B, the torque considered to apply low level inducement defined in Annex 11 shall be the lowest of the torques obtained in diesel mode and in dual-fuel mode.
- 8.2.2.** The requirements of section 7.1.1. concerning additional general OBD requirements in case of Type 1B, Type 2B and Type 3B dual-fuel engines and vehicles shall also apply to the diagnostic system related to the correct operation of NO_x control systems.
- In particular:**
- 8.2.2.1.** A possible influence of the mode of operation on the malfunction detection shall not be used to extend the time until an operability restriction becomes active.
- 8.2.2.2.** A change of the mode of operation (dual-fuel to diesel or vice-versa) shall not stop nor reset the mechanisms implemented to comply with the specification of Annex 11 (counters, etc.). However, in the case where one of these mechanisms (for example a diagnostic system) depends on the actual operation mode the counter associated with that mechanism may, at the request of the manufacturer and upon approval of the type-approval authority:
- (a) Halt and, when applicable, hold their present value when the operation mode changes;
 - (b) Restart and, when applicable, continue counting from the point at which they have been held when the operation mode changes backs to the other operation mode.
- 9. Conformity of in-service engines or vehicles/engines**
- The conformity of in-service dual-fuel engines and vehicles shall be performed according to the requirements specified in Annex 8.
- The PEMS tests shall be performed in dual-fuel mode.
- 9.1.** In the case of Type 1B, Type 2B and Type 3B dual-fuel engines, an additional PEMS test shall be performed in Diesel mode on the same

engine and vehicle immediately after, or before, a PEMS test is performed in dual-fuel mode.

In that case the pass or fail decision of the lot considered in the statistical procedure specified in Annex 8 shall be based on the following:

- (a) A pass decision is reached for an individual vehicle if both the PEMS test in dual-fuel mode and the PEMS test in Diesel mode have concluded a pass;
- (b) A fail decision is reached for an individual vehicle if either the PEMS test in dual-fuel mode or the PEMS test in Diesel mode has concluded a fail.

10. Additional test procedures

10.1. Additional emission test procedure requirements for dual-fuel engines

10.1.1. Dual-fuel engines shall comply with the requirements of Appendix 4 in addition to the requirements of this Regulation (incl. Annex 4) when performing an emission test.

10.2. Additional PEMS emission test procedure requirements for dual-fuel engines

10.2.1. When subject to a PEMS test, dual-fuel engines shall comply with the requirements of Appendix 5 in addition to the other PEMS requirements of this Regulation.

10.2.2. Torque correction

When necessary, for instance because of variation of the gas fuel composition, the manufacturer may decide to correct the ECU Torque signal. In that case the following requirements shall apply.

10.2.2.1. Correction of the PEMS torque signal

The manufacturer shall submit to the approval authority a description of the relationship permitting to extrapolate the real torque from the torques obtained during emission testing with the 2 appropriate reference fuels and from the actually retrievable torque in the ECU.

10.2.2.1.1. In the case when the torques obtained with the two reference fuels may be considered of the same magnitude (that is within the 7 per cent considered in paragraph 9.4.2.5. of this Regulation), the use of the corrected ECU value is not necessary,

10.2.2.2. Torque value to consider in a PEMS test

For PEMS test (work based window) the corrected torque value shall result from that interpolation

10.2.2.3. Conformity of the ECU torque-signal

The "Maximum torque" method specified in Appendix 4 to Annex 8 shall be understood as demonstrating that a point between the reference maximum torque curves obtained at a certain engine speed when testing with the 2 applicable reference fuels has been reached during vehicle testing.

The value of that point shall be estimated with the agreement of the approval authority on the basis of the actual fuel composition sampled as close as possible to the engine and the power curves obtained with each of the reference fuels during the emission certification test.

10.3 Additional dual-fuel specific CO₂ determination provisions

Section 3.1. of Annex 12 regarding the determination of CO₂ emissions in case of raw measurement is not applicable to dual-fuel engines. Instead the following provisions shall apply.

The measured test-averaged fuel consumption according to section 4.3. of Annex 12 shall be used as the base for calculating the test averaged CO₂ emissions.

The mass of each fuel consumed shall be used to determine, according to section A.6.4. of this Annex, the molar hydrogen ratio and the mass fractions of the fuel mix in the test.

The total fuel mass shall be determined according to equations 23 and 24.

$$m_{fuel,corr} = m_{fuel} - \left(m_{THC} + \frac{A_C + \alpha \times A_H}{M_{CO}} \times m_{CO} + \frac{w_{GAM} + w_{DEL} + w_{EPS}}{100} \times m_{fuel} \right) \quad (23)$$

Field Code Changed

$$m_{CO_2,fuel} = \frac{M_{CO_2}}{A_C + \alpha \times A_H} \times m_{fuel,corr} \quad (24)$$

Field Code Changed

where:

$m_{fuel,corr}$	is the corrected fuel mass of both fuels, g/test
m_{fuel}	total fuel mass of both fuels, g/test
m_{THC} g/test	mass of total hydrocarbon emissions in the exhaust gas, g/test
m_{CO} g/test	mass of carbon monoxide emissions in the exhaust gas, g/test
$m_{CO_2,fuel}$	CO ₂ mass emission coming from the fuel, g/test
w_{GAM}	sulphur content of the fuels, per cent mass
w_{DEL}	nitrogen content of the fuels, per cent mass
w_{EPS}	oxygen content of the fuels, per cent mass
α	molar hydrogen ratio of the fuels (H/C)

The CO₂ emission resulting from urea shall be calculated with equation 25:

$$m_{CO_2,urea} = \frac{c_{urea}}{100} \times \frac{M_{CO_2}}{M_{CO(NH_2)_2}} \times m_{urea} \quad (25)$$

where:

$m_{CO_2,urea}$ CO₂ mass emission resulting from urea, g/test

c_{urea} urea concentration, per cent

m_{urea} total urea mass consumption, g/test

Then the total CO₂ emission shall be calculated with equation 26:

$$m_{CO_2} = m_{CO_2,fuel} + m_{CO_2,urea} \quad (26)$$

The brake specific CO₂ emissions, e_{CO_2} shall then be calculated according to section 3.3. of Annex 12.

11. Documentation requirements

11.1. Documentation for installing in a vehicle a type approved HDDF engine

The manufacturer of a dual-fuel engine type-approved as separate technical unit shall include in the installation documents of its engine system the appropriate requirements that will ensure that the vehicle, when used on the road or elsewhere as appropriate, will comply with the requirements of this annex. This documentation shall include but is not limited to:

- (a) The detailed technical requirements, including the provisions ensuring the compatibility with the OBD system of the engine system;
- (b) The verification procedure to be completed.

The existence and the adequacy of such installation requirements may be checked during the approval process of the engine system.

11.1.1. In the case when the vehicle manufacturer who applies for approval of the installation of the engine system on the vehicle is the same manufacturer who received the type-approval of the dual-fuel engine as separate technical unit, the documentation specified in paragraph 11.2. is not required.

12. Appendices

Appendix 1 Types of HDDF engines and vehicles - illustration of the definitions and requirements

Appendix 2 Activation and deactivation mechanisms of the counter(s), warning system, operability restriction, service mode in case of HDDF engines and vehicles- Description and illustrations

Appendix 3 HDDF dual-fuel indicator, warning system, operability restriction - Demonstration requirements

Appendix 4 Additional emission test procedure requirements for dual-fuel engines

Appendix 5 Additional PEMS emission test procedure requirements for dual-fuel engines

Appendix 6 Determination of molar component ratios and u_{gas} values for dual-fuel engines

Annex 15 - Appendix 1

Types of HDDF engines and vehicles - illustration of the definitions and main requirements

	<i>GER_{WHTC}^d</i>	<i>Idle on diesel</i>	<i>Warm-up on diesel</i>	<i>Operation on diesel solely</i>	<i>Operation in absence of gas</i>	<i>Comments</i>
Type 1A	GER_{WHTC} ≥ 90 %	NOT Allowed	Allowed only on service mode	Allowed only on service mode	Service mode	
Type 1B	GER_{WHTC} ≥ 90 %	Allowed only on Diesel mode	Allowed only on diesel mode	Allowed only on diesel & service modes	Diesel mode	
Type 2A	10 % < GER_{WHTC} < 90 %	Allowed	Allowed only on service mode	Allowed only on service mode	Service mode	GER_{WHTC} ≥ 90 % allowed
Type 2B	10 % < GER_{WHTC} < 90 %	Allowed	Allowed only on diesel mode	Allowed only on diesel & service modes	Diesel mode	GER_{WHTC} ≥ 90 % allowed
Type 3A	NEITHER DEFINED NOR ALLOWED					
Type 3B	GER_{WHTC} ≤ 10 %	Allowed	Allowed only on diesel mode	Allowed only on diesel & service modes	Diesel mode	

^d This average Gas Energy Ratio GER_{WHTC} is calculated over the hot part of the WHTC test-cycle


Annex 15 - Appendix 2

Activation and deactivation mechanisms of the counter(s), warning system, operability restriction, service mode in case of HDDF engines and vehicles -

- A.2.1. Description of the counter mechanism
 - A.2.1.1. General
 - A.2.1.1.1. To comply with the requirements of this annex, the system shall contain a counter to record the number of hours during which the engine has been operated while the system has detected a malfunctioning gas supply.
 - A.2.1.1.2. This counter shall be capable of counting up to 30 minutes operating time. The counter intervals shall be no longer than 3 minutes. When reaching its maximum value permitted by the system, it shall hold that value unless the conditions allowing the counter to be reset to zero are met.
 - A.2.1.2. Principle of the counter mechanism
 - A.2.1.2.1. The counters shall operate as follows:
 - A.2.1.2.1.1. If starting from zero, the counter shall begin counting as soon as a malfunctioning gas supply is detected according to paragraph 7.2 of this Annex and the corresponding diagnostic trouble code (DTC) has the status confirmed and active.
 - A.2.1.2.1.2. The counter shall halt and hold its current value if a single monitoring event occurs and the malfunction that originally activated the counter is no longer detected or if the failure has been erased by a scan tool or a maintenance tool.
 - A.2.1.2.1.2.1. The counter shall also halt and hold its current value when the service mode becomes active.
 - A.2.1.2.1.3. Once frozen, the counter shall be reset to zero and restart counting if a malfunction relevant to that counter is detected and the service mode activated.
 - A.2.1.2.1.3.1. Once frozen, the counter shall also be reset to zero when the monitors relevant to that counter have run at least once to completion of their monitoring cycle without having detected a malfunction and no malfunction relevant to that counter has been detected during 36 engine operating hours since the counter was last held.
 - A.2.1.3. Illustration of the counter mechanism

Figures A2.1.1 to A2.1.3 give via three use-cases an illustration of the counter mechanism

Figure A2.1.1
Illustration of the gas supply counter mechanism (Type A HDDF) - use-case 1



A malfunction of the gas supply is detected for the very first time.

The service mode is activated and the counter starts counting once the DTC gets the “confirmed and active” status (2nd detection).

The vehicle encounters a stand-still situation before reaching 30 minutes operating time after the service mode is activated.


The service mode becomes active and the vehicle speed is limited to 20 km/h (see paragraph 4.2.2.1. of this Annex).

The counter freezes at its present value.

Field Code Changed

ECE/TRANS/WP.29/2012/GRPE/2012/13

Figure A2.1.2
Illustration of the gas supply counter mechanism (Type A HDDF) - use-case 2




A malfunction of the gas supply is detected while the gas supply malfunction counter is not at zero (in this use-case it indicates the value it reached in use-case 1 when the vehicle became standstill).

The service mode is activated and the counter restarts counting from zero as soon as the DTC gets the “potential” status (1st detection: see paragraph 4.2.3.2.1. of this Annex).

After 30 minutes of operation without a standstill situation, the service mode becomes active and the vehicle speed is limited to 20 km/h (see paragraph 4.2.2.1 of this Annex).

The counter freezes at a value of 30 minutes operating time.

Figure A2.1.3
Illustration of the gas supply counter mechanism (Type A HDDF) - use-case 3



After 36 operating hours without detection of a malfunction of the gas supply, the counter is reset to zero (see paragraph A.2.1.2.3.2.1).

A malfunction of the gas supply is again detected while the gas supply malfunction counter is at zero (1st detection).

The service mode is activated and the counter starts counting once the DTC gets the “confirmed and active” status (2nd detection).

After 30 minutes of operation without a standstill situation, the service mode becomes active and the vehicle speed is limited to 20 km/h (see paragraph 4.2.2.1 of this Annex).

The counter freezes at a value of 30 minutes operating time.

Field Code Changed


ECE/TRANS/WP.29/2012/GRPE/2012/13

A.2.2. Illustration of the other activation and deactivation mechanisms

A.2.2.1. Empty gas tank

Figure A2.2 gives an illustration of the events occurring in the case of a HDDF vehicle when a gas tank becomes empty through one typical use-case.

Figure A2.2
Illustration of the events occurring in case of an empty gas tank (Types A and B HDDF)



In that use case:

- (a) The warning system specified in paragraph 0. of this Annex becomes active when the level of gas reaches the critical level defined by the manufacturer;
- (b) The service mode is activated (in the case of a Type A HDDF) or the engine switches to Diesel mode (in the case of a Type B HDDF).

In the case of a Type A HDDF, the service mode becomes active and the vehicle speed is limited to 20 km/h after the next time the vehicle is stationary or after 30 minutes operating time without standstill (see paragraph 4.2.2.1 of this Annex).


The gas tank is refilled.

The vehicle operates again in dual-fuel mode as soon as the tank is refilled above the critical level.

A.2.2.2. Malfunctioning gas supply

Figure A2.3 gives via one typical use-case an illustration of the events occurring in the case of a malfunction of the gas supply system. This illustration should be understood as complementary to that given in section A.2.1 and dealing with the counter mechanism.

Figure A2.3
Illustration of the events occurring in case of a malfunctioning gas supply system (Types A and B HDDF)



In that use case:

- The failure of the gas supply system occurs for the very first time. The DTC gets the potential status (1st detection);
- The service mode is activated (in the case of a Type A HDDF) or the engine switches to Diesel mode (in the case of a Type B HDDF) as soon as the DTC gets the “confirmed and active” status (2nd detection).


In the case of a Type A HDDF, the service mode becomes active and the vehicle speed is limited to 20 km/h after the next time the vehicle is stationary or after 30 minutes operating time without standstill (see paragraph 4.2.2.1 of this Annex).

The vehicle operates again in dual-fuel mode as soon as the failure is repaired.

A.2.2.3. Abnormality of the gas consumption

Figure A2.4 gives via one typical use-case an illustration of the events occurring in the case of an abnormality of the gas consumption.

Figure A2.4
Illustration of the events occurring in case of abnormality of gas consumption (Types A and B HDDF)



In that use case the service mode is activated (in the case of a Type A HDDF) or the engine switches to Diesel mode (in the case of a Type B HDDF) as soon as the DTC gets the “potential” status (1st detection).

In the case of a Type A HDDF, the service mode becomes active and the vehicle speed is limited to 20 km/h after the next time the vehicle is stationary or after 30 minutes operating time without standstill (see paragraph 4.2.2.1 of this Annex).

The vehicle operates again in dual-fuel mode as soon as the abnormality is rectified.

Annex 15 - Appendix 3

HDDF dual-fuel indicator, warning system, operability restriction - Demonstration requirements

A.3.1. Dual-fuel indicators

A.3.1.1. Dual-fuel mode indication

Formatted: English (U.S.)

In the case where a dual-fuel engine is type approved as a separate technical unit, the ability of the engine system to command the activation of the dual-fuel mode indication when operating in dual-fuel mode shall be demonstrated at type-approval.

In the case where a dual-fuel vehicle is type approved as regards to its emissions, the activation of the dual-fuel mode indication when operating in dual-fuel mode shall be demonstrated at type-approval.

Note: Installation requirements related to the dual-fuel mode indication of an approved dual-fuel engine are specified in paragraph 6.2. of this Annex.

A.3.1.2. Diesel mode indication

Formatted: English (U.S.)

In the case where a dual-fuel engine of Type 1B, Type 2B, or Type 3B is type approved as a separate technical unit, the ability of the engine system to command the activation of the diesel mode indication when operating in diesel mode shall be demonstrated at type-approval.

In the case where a dual-fuel vehicle of Type 1B, Type 2B, or Type 3B is type approved as regards to its emissions, the activation of the diesel mode indication when operating in diesel mode shall be demonstrated at type-approval.

Note: Installation requirements related to the diesel mode indication of an approved Type 1B, Type 2B, or Type 3B dual-fuel engine are specified in paragraph 6.2. of this Annex.

A.3.1.3. Service mode indication

Formatted: English (U.S.)

In the case where a dual-fuel engine is type approved as a separate technical unit, the ability of the engine system to command the activation of the service mode indication when operating in service mode shall be demonstrated at type-approval.

In the case where a dual-fuel engine is type approved with regard to its emissions, the activation of the service mode indication when operating in service mode shall be demonstrated at type-approval.

Note: Installation requirements related to the service mode indication of an approved dual-fuel engine are specified in paragraph 6.2. of this Annex.

- A.3.1.3.1. When so-equipped it is sufficient to perform the demonstration related to the service mode indication by activating a service mode activation switch and to present the approval authority with evidence showing that the activation occurs when the service mode is commanded by the engine system itself (for example, through algorithms, simulations, result of in-house tests, etc ...).

A.3.2. Warning system

Formatted: English (U.S.)

In the case where a dual-fuel engine is type approved as a separate technical unit, the ability of the engine system to command the activation

of the warning system in the case that the amount of gas in the tank is below the warning level, shall be demonstrated at type-approval.

In the case where a dual-fuel vehicle is type-approved as regards to its emissions the activation of the warning system in the case that the amount of gas in the tank is below the warning level, shall be demonstrated at type-approval. For that purpose, at the request of the manufacturer and with the approval of the approval authority, the actual amount of gas may be simulated.

Note: Installation requirements related to the warning system of an approved dual-fuel engine are specified in paragraph 6.2. of this Annex.

A.3.3. Operability restriction

In the case where a type 1A or type 2A dual-fuel engine is type approved as a separate technical unit, the ability of the engine system to command the activation of the operability restriction upon detection of an empty gaseous fuel tank, of a malfunctioning gas supply system, and of an abnormality of gas consumption in dual-fuel shall be demonstrated at type-approval.

In the case where a type 1A or type 2A dual-fuel vehicle is type approved as regards to its emissions, the activation of the operability restriction upon detection of an empty gaseous fuel tank, of a malfunctioning gas supply system, and of an abnormality of gas consumption in dual-fuel mode shall be demonstrated at type-approval.

Note: Installation requirements related to the operability restriction of an approved dual-fuel engine are specified in paragraph 6.2. of this Annex.

A.3.3.1. The malfunctioning of the gas supply and the abnormality of gas consumption may be simulated at the request of the manufacturer and with the approval of the approval authority.

In the case where a type 1A or type 2A dual-fuel engine is type approved as a separate technical unit, the ability of the engine system to command the activation of the operability restriction upon detection of an empty gaseous fuel tank, of a malfunctioning gas supply system, and of an abnormality of gas consumption in dual-fuel shall be demonstrated at type-approval.

In the case where a type 1A or type 2A dual-fuel vehicle is type approved as regards to its emissions, the activation of the operability restriction upon detection of an empty gaseous fuel tank, of a malfunctioning gas supply system, and of an abnormality of gas consumption in dual-fuel mode shall be demonstrated at type-approval.

Note: Installation requirements related to the operability restriction of an approved dual-fuel engine are specified in paragraph 6.2. of this Annex.

A.3.3.1. The malfunctioning of the gas supply and the abnormality of gas consumption may be simulated at the request of the manufacturer and with the approval of the approval authority.

A.3.3.2. It is sufficient to perform the demonstration in a typical use-case selected with the agreement of the Approval Authority and to present that authority with evidence showing that the operability restriction occurs in the other possible use-cases (for example, through algorithms, simulations, result of in-house tests, etc ...

Annex 15 - Appendix 4

Additional emission test procedure requirements for dual-fuel engines

A.4.1. General

This appendix defines the additional requirements and exceptions to Annex 4 of this regulation to enable emission testing of dual-fuel engines.

Emission testing of a dual-fuel engine is complicated by the fact that the fuel used by the engine can vary between pure diesel fuel and a combination of mainly gaseous fuel with only a small amount of diesel fuel as an ignition source. The ratio between the fuels used by a dual-fuel engine can also change dynamically depending of the operating condition of the engine. As a result special precautions and restrictions are necessary to enable emission testing of these engines.

A.4.2. Test conditions (Annex 4, section 6.)

A.4.2.1. Laboratory test conditions (Annex 4, paragraph 6.1.)

The parameter f_a for dual-fuel engines shall be determined with formula (a)(2) in paragraph 6.1. of Annex 4 to this regulation.

A.4.3. Test procedures (Annex 4, section 7.)

A.4.3.1. Measurement procedures (Annex 4, paragraph 7.1.3.)

The recommended measurement procedure for dual-fuel engines is procedure (b) listed in paragraph 7.1.3. of Annex 4 (CVS system).

This measurement procedure ensures that the variation of the fuel composition during the test will only influence the hydrocarbon measurement results. This shall be compensated via one of the methods described in section 4.4.

Other measurement methods such as method (a) listed in paragraph 7.1.3 of Annex 4 (raw gaseous/partial flow measurement) can be used with some precautions regarding exhaust mass flow determination and calculation methods. Fixed values for fuel parameters and u_{gas} -values shall be applied as described in Appendix 6.

A.4.4. Emission calculation (Annex 4, section 8.)

The emissions calculation on a molar basis, in accordance with Annex 7 of gtr No. 11 concerning the exhaust emission test protocol for Non-Road Mobile Machinery (NRMM), is not permitted.

A.4.4.1. Dry/wet correction (Annex 4, section 8.1.)

A.4.4.1.1. Raw exhaust gas (Annex 4, paragraph 8.1.1.)

Equations 15 and 17 in Annex 4 paragraph 8.1.1. shall be used to calculate the dry/wet correction.

The fuel specific parameters shall be determined according to sections A.6.2 and A.6.3. of Appendix 6.

A.4.4.1.2. Diluted exhaust gas (Annex 4, paragraph 8.1.2.)

Equations 19 and 20 in Annex 4 paragraph 8.1.2. Shall be used to calculate the wet/dry correction.

The molar hydrogen ratio α of the combination of the two fuels shall be used for the dry/wet correction. This molar hydrogen ratio shall be calculated from the fuel consumption measurement values of both fuels according to section A.6.4. of Appendix 6.

A.4.4.2. NO_x correction for humidity (Annex 4, section 8.2.)

The NO_x humidity correction for compression ignition engines as specified in paragraph 8.2.1 of Annex 4 shall be used to determine the NO_x humidity correction for dual-fuel engines.

$$k_{h,D} = \frac{15,698 \times H_a}{1\,000} + 0,832 \quad (\text{A4.1})$$

where:

H_a is the intake air humidity, g water per kg dry air

A.4.3. Partial flow dilution (PFS) and raw gaseous measurement (Annex 4, section 8.4.)

A.4.3.1. Determination of exhaust gas mass flow (Annex 4, section 8.4)

The exhaust mass flow shall be determined according to the direct measurement method as described in section 8.4.1.3.

Alternatively the airflow and air to fuel ratio measurement method according to section 8.4.1.6. (equations 30, 31 and 32) may be used only if α , γ , δ and ε values are determined according to section A.6.4. of Appendix 6. [The use of a zirconia type sensor to determine the air fuel ratio is not allowed.]

A.4.3.2. Determination of the gaseous components (Annex 4, section 8.4.2.)

The calculations shall be performed according to Annex 4, section 8. but the u_{gas} -values and molar ratios as described in sections A.6.2. and A.6.3. of Appendix 6 shall be used.

A.4.3.3. Particulate determination (Annex 4, section 8.4.3.)

For the determination of particulate emissions with the partial dilution measurement method the calculation shall be performed according to Annex 4, section 8.4.3.2.

For controlling the dilution ratio one of the following two methods may be used:

- The direct mass flow measurement as described in section 8.4.1.3.
- The airflow and air to fuel ratio measurement method according to section 8.4.1.6. (Equations 30, 31 and 32) may only be used when this is combined with the look ahead method described in section 8.4.1.2.

The quality check according to section 9.4.6.1. shall be performed for each measurement.

A.4.3.4. Additional requirements regarding the exhaust gas mass flow meter

The flow meter referred to in sections 4.3.1 and 4.3.3. shall not be sensitive to the changes in exhaust gas composition and density. The small errors of eg. pitot tube or orifice type of measurement (equivalent with the square root of the exhaust density) may be neglected.

Field Code Changed

Comment [FD1]: to be updated according to the OICA document GRPE/2012/7

-
- A.4.4. Full flow dilution measurement (CVS) (Annex 4, section 8.5.)**
- The possible variation of the fuel composition will only influence the hydrocarbons measurement results calculation. For all other components the appropriate calculation formula's from section 8.5.2. of Annex 4 shall be used.
- The exact equations shall be applied for the calculation of the hydrocarbon emissions using the molar hydrogen ratio determined from the fuel consumption measurements of both fuels according to section A.6.4. of Appendix 6.
- A.4.4.1. Determination of the background corrected concentrations (Annex 4, paragraph 8.5.2.3.2.)**
- To determine the stoichiometric factor, the molar hydrogen ratio α of the fuel shall be calculated as the average molar hydrogen ratio of the fuel mix during the test according to section A.6.4. of Appendix 6.
- Alternatively the F_3 value of the gaseous fuel may be used in equation 59 or 60 of Annex 4.
- A.4.5. Equipment specification and verification (Annex 4, section 9.)**
- A.4.5.1. Oxygen interference check gases (Annex 4, paragraph 9.3.3.4.)**
- The oxygen concentrations required for dual-fuel engines are equal to those required for compression ignition engines listed in table 8 in paragraph 9.3.3.4. of Annex 4.
- A.4.5.2. Oxygen interference check (Annex 4, paragraph 9.3.7.3.)**
- Instruments used to measure dual-fuel engines shall be checked using the same procedures as those used to measure compression ignition engines. The 21 per cent oxygen blend shall be used under item (b) in paragraph 9.3.7.3. of Annex 4.
- A.4.5.3. Water quench check (Annex 4, paragraph 9.3.9.2.2.)**
- The water quench check in paragraph 9.3.9.2.2. of Annex 4 to this regulation applies to wet NO_x concentration measurements only. For dual-fuel engines fuelled with natural gas this check should be performed with an assumed H/C ratio of 4 (Methane). In that case $H_m = 2 \times A$. For dual-fuel engines fuelled with LPG this check should be performed with an assumed H/C ratio of 2.525. In that case $H_m = 1.25 \times A$.

Annex 15 - Appendix 5

Additional PEMS emission test procedure requirements for dual-fuel engines

A.5.1 General

This appendix defines the additional requirements and exceptions to Annex 8 of this regulation to enable PEMS emission testing of dual-fuel engines.

Emission testing of a dual fuel engine is complicated by the fact that the fuel used by the engine can vary between pure diesel fuel and a combination of mainly gaseous fuel with only a small amount of diesel fuel as an ignition source. The ratio between the fuels used by a dual-fuel engine can also change dynamically depending of the operating condition of the engine. As a result special precautions and restrictions are necessary to enable emission testing of these engines.

A.5.2. The following amendments to Appendix 1 of Annex 8 shall apply:

A.5.2.1. Note (2) of Table 1 in paragraph A.1.2.2. shall read:

⁽²⁾ Only for engines fuelled with natural gas

A.5.2.2. Paragraph A.1.3.3. "Dry-Wet correction" shall read:

If the concentration is measured on a dry basis, it shall be converted to a wet basis according to paragraph 8.1. of Annex 4 and paragraph 4.1.1. of Appendix 4 to this Annex.

A.5.2.3. Paragraph A.1.3.5. "Calculation of the instantaneous gaseous emissions" shall read:

The mass emissions shall be determined as described in paragraph 8.4.2.3. of Annex 4. The u_{gas} values shall be determined according to appendix 6 of Annex 15.

"Annex 15 - Appendix 6

Determination of molar component ratios and u_{gas} values for dual-fuel engines

A.6.1. General

This appendix defines the determination of molar component ratios and u_{gas} values for the dry-wet factor and emissions calculations for emission testing of dual-fuel engines.

A.6.2. Operation in dual-fuel mode

A.6.2.1. For type 1A or 1B dual-fuel engines operating in dual-fuel mode the molar component ratios and the u_{gas} values of the gaseous fuel shall be used.

A.6.2.2. For type 2A or 2B dual-fuel engines operating in dual-fuel mode the molar component ratios and the u_{gas} values from tables A6.1 and A6.2 shall be used.

Table A6.1: Molar component ratios for a mixture of 50% gaseous fuel and 50% diesel fuel (mass %)

Table A6.2: Molar component ratios for a mixture of 50% gaseous fuel and 50% diesel fuel (mass %)

Gaseous Fuel	α	γ	δ	ε
CH ₄	2,8681			
CNG	2,7676			
G ₂₃	2,7986			
G ₂₅	2,7542			
Propane				
Butane				
LPG A				
LPG B	2,17			

Comment [HJD2]: these tables still need to be completed

Table A6.2: Raw exhaust gas u_{gas} values and component densities for a mixture of 50% gaseous fuel and 50% diesel fuel (mass %)

Gaseous Fuel	ρ_e	Gas					
		NO _x	CO	HC	CO ₂	O ₂	CH ₄
		$\rho_{gas} [kg/m^3]$					
		2.053	1.250	a)	1.9636	1.4277	0.716
		b)					
		u_{gas}					
CH ₄							
CNG ^{c)}				d)			
Propane							
Butane							
LPG ^{e)}							

a) depending on fuel
b) at $\lambda = 2$, dry air, 273 K, 101.3 kPa

c)	u accurate within 0.2 % for mass composition of: C = 66 - 76 %; H = 22 - 25 %; N = 0 - 12 % (including G ₂₅)
d)	NMHC on the basis of CH _{2,93} (for total HC the u_{gas} coefficient of CH ₄ shall be used)
e)	u accurate within 0.2 % for mass composition of: C3 = 70 - 90 %; C4 = 10 - 30 % (LPG Fuel B)

A.6.2.3. For type 3B dual-fuel engines operating in dual-fuel mode the molar component ratios and the u_{gas} values of diesel fuel shall be used.

A.6.2.4. For the calculation of the hydrocarbon emissions of all types of dual-fuel engines operating in dual-fuel mode, the following shall apply:

- For the calculation of the THC emissions, the u_{gas} value of the gaseous fuel shall be used.
- For the calculation of the NMHC emissions, the u_{gas} value on the basis of CH_{2,93} shall be used.
- For the calculation of the CH₄ emissions, the u_{gas} value of CH₄ shall be used.

A.6.3. Operation in diesel mode

For type 1B, 2B or 3B dual-fuel engines operating in diesel mode, the molar component ratios and the u_{gas} values of diesel fuel shall be used.

A.6.4. Determination of the molar component ratios when the fuel mix is known

A.6.4.1. Calculation of the fuel mixture components

$$W_{ALF} = \frac{W_{ALF1} \times q_{mf1} + W_{ALF2} \times q_{mf2}}{q_{mf1} + q_{mf2}} \quad (\text{A6.1})$$

$$W_{BET} = \frac{W_{BET1} \times q_{mf1} + W_{BET2} \times q_{mf2}}{q_{mf1} + q_{mf2}} \quad (\text{A6.2})$$

$$W_{GAM} = \frac{W_{GAM1} \times q_{mf1} + W_{GAM2} \times q_{mf2}}{q_{mf1} + q_{mf2}} \quad (\text{A6.3})$$

$$W_{DEL} = \frac{W_{DEL1} \times q_{mf1} + W_{DEL2} \times q_{mf2}}{q_{mf1} + q_{mf2}} \quad (\text{A6.4})$$

$$W_{EPS} = \frac{W_{EPS1} \times q_{mf1} + W_{EPS2} \times q_{mf2}}{q_{mf1} + q_{mf2}} \quad (\text{A6.5})$$

where:

- q_{mf1} fuel mass flow rate of fuel1, kg/s
 q_{mf2} fuel mass flow rate of fuel2, kg/s
 W_{ALF} hydrogen content of fuel, per cent mass

w_{BET}	carbon content of fuel, per cent mass
w_{GAM}	sulphur content of fuel, per cent mass
w_{DEL}	nitrogen content of fuel, per cent mass
w_{EPS}	oxygen content of fuel, per cent mass

A.6.4.2. Calculation of the molar ratios of H, C, S, N and O related to C for the fuel mixture (according to ISO8178-1, Annex A-A.2.2.2).

$$\alpha = 11.9164 \times \frac{w_{ALF}}{w_{BET}} \quad (\text{A6.6})$$

$$\gamma = 0.37464 \times \frac{w_{GAM}}{w_{BET}} \quad (\text{A6.7})$$

$$\delta = 0.85752 \times \frac{w_{DEL}}{w_{BET}} \quad (\text{A6.8})$$

$$\varepsilon = 0.75072 \times \frac{w_{EPS}}{w_{BET}} \quad (\text{A6.9})$$

where:

w_{ALF}	hydrogen content of fuel, per cent mass
w_{BET}	carbon content of fuel, per cent mass
w_{GAM}	sulphur content of fuel, per cent mass
w_{DEL}	nitrogen content of fuel, per cent mass
w_{EPS}	oxygen content of fuel, per cent mass
α	molar hydrogen ratio (H/C)
γ	molar sulphur ratio (S/C)
δ	molar nitrogen ratio (N/C)
ε	molar oxygen ratio (O/C)

referring to a fuel $\text{CH}_\alpha\text{O}_\varepsilon\text{N}_\delta\text{S}_\gamma$

A.6.4.3. Calculation of the u_{gas} values for a fuel mixture

The raw exhaust gas u_{gas} values for a fuel mixture can be calculated with the exact equations in section 8.4.2.4. of Annex 4 and the molar ratios calculated according to this section.

For systems with constant mass flow, equation 57 in section 8.5.2.3.1. of Annex 4 is needed to calculate the diluted exhaust gas u_{gas} values.

II. Justification

The text reproduced above was prepared by the Chair of the Heavy Duty Dual Fuel–Task-Force (HDDF-TF) of the informal group on Gaseous Fuelled Vehicles (GFV) to introduce amendments to the 06 series of amendments of Regulation No. 49 in view of permitting the type approval of Heavy Duty dual-fuel engines and vehicles.

It is a consolidated version of

- Working document **ECE/TRANS/WP.29/GRPE/2012/13/Rev.1.**
- Informal document **GRPE-64-xx1**

GFV presented in March 2012 to the attention of GRPE working document **GRPE/2012/13/Rev.1.** that contains all the major amendments to Regulation No. 49 that are considered necessary to type approve Heavy-Duty dual-fuel engines and vehicles., except appendices 3, 4, 5 and 6 of the dual-fuel dedicated annex (Annex 15) that were not finalized at the time when the working document was published.

Accordingly, the working document announced that these appendixes would be submitted as an informal document to the GRPE once they are finalized and approved by the experts of the GFV. In addition, some necessary amendments and typographic corrigenda to rev.6 of Regulation No 49 were considered by the GFV-HDDF experts as worth to be proposed. These additional proposals are included in document **GRPE-64-xx1**
