

4 November 2009

## **AGREEMENT**

### **CONCERNING THE ADOPTION OF UNIFORM TECHNICAL PRESCRIPTIONS FOR WHEELED VEHICLES, EQUIPMENT AND PARTS WHICH CAN BE FITTED AND/OR BE USED ON WHEELED VEHICLES AND THE CONDITIONS FOR RECIPROCAL RECOGNITION OF APPROVALS GRANTED ON THE BASIS OF THESE PRESCRIPTIONS \*/**

(Revision 2, including the amendments which entered into force on 16 October 1995)

#### **Addendum 42: Regulation No. 43**

#### **Revision 2 – Amendment 4**

Supplement 11 to the original version of the Regulation: Date of entry into force: 22 July 2009

### **UNIFORM PROVISIONS CONCERNING THE APPROVAL OF SAFETY GLAZING MATERIALS AND THEIR INSTALLATION ON VEHICLES**



UNITED NATIONS

---

\*/ Former title of the Agreement:

Agreement Concerning the Adoption of Uniform Conditions of Approval and Reciprocal Recognition of Approval for Motor Vehicle Equipment and Parts, done at Geneva on 20 March 1958.

Annex 3,

Paragraph 6.3.1.1.2., amend to read:

"6.3.1.1.2. below 70 per cent in the case of a windscreen in the zone where the regular light transmittance is measured as defined in paragraph 9.1.2.2. below."

Paragraph 6.4.1.5., amend to read:

"6.4.1.5. Expression of results

Report visual evaluations of exposed test specimens, comparing the appearance of each with that of the unexposed control.

The regular light transmittance measured shall not differ from the original test on unexposed samples by more than 5 per cent and shall not fall below:

70 per cent in the case of a windscreen and other glazing that is located in a position requisite for driving visibility."

Paragraph 9.1.4., amend to read:

"9.1.4. Interpretation of results

The regular light transmittance shall be measured according to Paragraph 9.1.2. of this annex and the result shall be recorded. In the case of a windscreen, it shall not be less than 70 per cent. In the case of glazing other than a windscreen, the requirements are specified in Annex 21."

Annex 7,

Paragraph 1.1.5, amend to read:

"1.1.5 Any special treatment which one or more layers of glass may have undergone."

Annex 20, paragraph 3.6.1., amend to read:

"3.6.1. Tests

Representatives...

The check...

Windscreens and other glazing panes having a regular light transmittance measured during type approval of not less than 75 per cent, and glass panes whose symbol is V (see paragraph 5.5.2. of this Regulation), shall be exempted from this test."

Annex 21, paragraph 4.1.1., amend to read:

"4.1.1. The regular light transmittance shall not be less than 70 per cent."