

28 April 2010

## **AGREEMENT**

**CONCERNING THE ADOPTION OF UNIFORM TECHNICAL PRESCRIPTIONS  
FOR WHEELED VEHICLES, EQUIPMENT AND PARTS WHICH CAN BE FITTED  
AND/OR BE USED ON WHEELED VEHICLES AND THE CONDITIONS FOR  
RECIPROCAL RECOGNITION OF APPROVALS GRANTED ON THE BASIS OF  
THESE PRESCRIPTIONS \*/**

(Revision 2, including the amendments which entered into force on 16 October 1995)

---

**Addendum 15: Regulation No. 16**

**Revision 6 – Corrigendum 1**

Corrigendum 1 to Revision 6, subject of Depositary Notification C.N.130.2010.TREATIES-1  
dated 3 March 2010

**UNIFORM PROVISIONS CONCERNING THE APPROVAL OF:**

- I. SAFETY-BELTS, RESTRAINT SYSTEMS, CHILD RESTRAINT SYSTEMS  
AND ISOFIX CHILD RESTRAINT SYSTEMS FOR OCCUPANTS OF POWER-  
DRIVEN VEHICLES**
- II. VEHICLES EQUIPPED WITH SAFETY-BELTS, SAFETY-BELT REMINDERS,  
RESTRAINT SYSTEMS, CHILD RESTRAINT SYSTEMS AND ISOFIX CHILD  
RESTRAINT SYSTEMS**



**UNITED NATIONS**

---

\*/ Former title of the Agreement:

Agreement Concerning the Adoption of Uniform Conditions of Approval and Reciprocal Recognition of Approval for Motor Vehicle Equipment and Parts, done at Geneva on 20 March 1958.

GE.10-

Paragraph 6.3.1.2., amend to read:

"6.3.1.2. The width of the strap under load of 980 daN + 100 - 0 daN shall be ..."

Paragraph 7.4.1.1., amend to read:

"7.4.1.1. Temperature-conditioning and Hygrometrics

The strap shall be conditioned in accordance with ISO 139 (2005), using the standard atmosphere or the standard alternative atmosphere. ..."

Paragraph 7.4.1.2.1., amend to read:

"7.4.1.2.1. The provisions of Recommendation ISO 105-B02 (1994 / Amd2:2000) shall apply. ..."

Paragraph 7.4.1.2.2., amend to read:

"7.4.1.2.2 After exposure the strap shall be conditioned as described under paragraph 7.4.1.1. If the test is not carried out immediately after conditioning the ..."

Paragraph 7.4.1.3.1., amend to read:

"7.4.1.3.1. The strap shall be conditioned as described under paragraph 7.4.1.1."

Paragraph 7.4.1.6.2., amend to read

"7.4.1.6.2. The samples shall be conditioned as described under paragraph 7.4.1.1. The ambient temperature during the abrasion procedure shall be between 15 and 30° C."

Paragraph 7.4.3.3., amend to read:

"7.4.3.3. When the load reaches 980 daN + 100 - 0 daN, ..."

Paragraph 7.6.2.2., amend to read:

"7.6.2.2. A suitable apparatus for the tests specified in paragraph 7.6.2.1. above is described in Annex 4 to this Regulation. The design of any such test apparatus shall ensure that the required acceleration is given before the webbing is withdrawn out of the retractor by more than 5 mm and that the withdrawal takes place at an average rate of increase of acceleration of at least 55 g/s 4/ and not more than 150 g/s 4/ in testing sensitivity for strap movement and of at least 25 g/s 4/ and not more than 150 g/s 4/ in testing sensitivity for vehicle deceleration. 4/"