

9 November 2000

## **AGREEMENT**

**CONCERNING THE ADOPTION OF UNIFORM TECHNICAL PRESCRIPTIONS  
FOR WHEELED VEHICLES, EQUIPMENT AND PARTS WHICH CAN BE FITTED  
AND/OR  
BE USED ON WHEELED VEHICLES AND THE CONDITIONS FOR RECIPROCAL  
RECOGNITION  
OF APPROVALS GRANTED ON THE BASIS OF THESE PRESCRIPTIONS \*/**

(Revision 2, including the amendments entered into force on 16 October 1995)

---

### **Addendum 20: Regulation No. 21**

#### **Revision 2 - Corrigendum 1**

Corrigendum 1 the 01 series of amendments  
subject of Depository Notification C.N.423.2000.TREATIES-1 dated 27 June 2000

**UNIFORM PROVISIONS CONCERNING THE APPROVAL OF VEHICLES  
WITH REGARD TO THEIR INTERIOR FITTINGS**



**UNITED NATIONS**

---

\*/ Former title of the Agreement:

Agreement Concerning the Adoption of Uniform Conditions of Approval and Reciprocal Recognition of Parts, done at Geneva on 20 March 1958.

GE.00-

Paragraph 4.4.1., footnote 1/, amend to read:

"1/ . . . . . 24 for Ireland, . . . . . 32 for Latvia, 33 (vacant), 34 for Bulgaria, 35-36 (vacant), 37 for Turkey, 38-39 (vacant), 40 for The former Yugoslav Republic of Macedonia, 41 (vacant), 42 for the European Community (Approvals are granted by its Member States using their respective ECE symbol), 43 for Japan, 44 (vacant), 45 for Australia and 46 for Ukraine. Subsequent numbers shall be assigned to other countries in the chronological order in which they ratify or accede to the Agreement Concerning the Adoption of Uniform Technical Prescriptions for Wheeled Vehicles, Equipment and Parts which can be Fitted and/or be Used on Wheeled Vehicles and the Conditions for Reciprocal Recognition of Approvals Granted on the Basis of these Prescriptions, and the numbers thus assigned shall be communicated by the Secretary-General of the United Nations to the Contracting Parties to the Agreement."

Paragraph 5.3.4.1., correct to read:

"5.3.4.1. Components mounted on the roof, but which are not part of the roof structure, such as grab handles, lamps and sun visors, etc. shall have a radius of curvature not less than 3.2 mm. In addition, the width of the projecting parts shall not be less than the amount of their downward projection; alternatively these projecting parts shall pass the energy-dissipating test in accordance with the requirements of annex 4."

---