

E/ECE/324 } Rev.2/Add.103/Amend.3/Corr.1
E/ECE/TRANS/505 }

24 June 2008

AGREEMENT

CONCERNING THE ADOPTION OF UNIFORM TECHNICAL PRESCRIPTIONS FOR WHEELED VEHICLES, EQUIPMENT AND PARTS WHICH CAN BE FITTED AND/OR BE USED ON WHEELED VEHICLES AND THE CONDITIONS FOR RECIPROCAL RECOGNITION OF APPROVALS GRANTED ON THE BASIS OF THESE PRESCRIPTIONS */

(Revision 2, including the amendments which entered into force on 16 October 1995)

Addendum 103: Regulation No. 104

Amendment 3 - Corrigendum 1

Corrigendum 1 to Supplement 3, subject of Depository Notification C.N.255.2008.TREATIES-2
dated 9 April 2008

UNIFORM PROVISIONS CONCERNING THE APPROVAL OF RETRO- REFLECTIVE MARKINGS FOR VEHICLES OF CATEGORY M, N AND O



UNITED NATIONS

*/ Former title of the Agreement:

Agreement Concerning the Adoption of Uniform Conditions of Approval and Reciprocal Recognition of Approval for Motor Vehicle Equipment and Parts, done at Geneva on 20 March 1958.

GE.08-

Annex 8

Paragraph 5.2.1., amend to read:

"5.2.1 When subjected to a continuous spraying action for 60 seconds on the test component in its normal mounting conditions, a test sample shall show no damage to the retro-reflective surface or delamination from the substrate or separation from the sample mounting surface under the following set-up parameters:

- (a) Water/wash solution pressure 8 ± 0.2 MPa;
- (b) Water/wash solution temperature $60^{\circ} - 5^{\circ}$ °C;
- (c) Water/wash solution flow rate 7 ± 1 l/min;
- (d) The tip of the cleaning wand to be positioned at distance of 600 ± 20 mm away from the retro-reflective surface;
- (e) Cleaning wand to be held at no greater angle than 45 degrees from perpendicular to the retro-reflective surface;
- (f) 40 degree nozzle creating wide fan pattern."
