



**Economic and Social
Council**

Distr.

RESTRICTED

TRANS/WP.29/496

3 May 1996

ENGLISH

Original: ENGLISH
and FRENCH

ECONOMIC COMMISSION FOR EUROPE

INLAND TRANSPORT COMMITTEE

Working Party on the Construction of Vehicles

DRAFT SUPPLEMENT 6 TO THE 02 SERIES OF AMENDMENTS TO REGULATION No. 30
(Pneumatic tyres)

Note: The text reproduced below was adopted by the Administrative Committee (AC.1) of the amended 1958 Agreement at its second session, following the recommendation by the Working Party at its one-hundred-and-eighth session. It is based on document TRANS/WP.29/R.723, as amended (TRANS/WP.29/487, paras. 56, 57 and 92).

The distribution of documents of the Inland Transport Committee and its subsidiary bodies is limited. They are distributed only to governments, to specialized agencies and to governmental and non-governmental organizations which take part in the work of the Committee and of its subsidiary bodies, and should not be given to newspapers or periodicals.

Insert a new paragraph 3.1.10., to read:

"3.1.10. An identification of the tyre to rim fitment configuration when it differs from the standard configuration."

Paragraph 4.1.4., amend to read (in conformity with paragraph 2.1.4.):

"4.1.4. Structure: diagonal (bias ply), bias belted or radial;"

Paragraph 4.2., amend to read:

"The application for approval shall be accompanied (all in triplicate) by a sketch, or a representative photograph, which identify the tyre tread pattern and a sketch of the envelope of the inflated tyre mounted on the measuring rim showing the relevant dimensions (see paragraphs 6.1.1. and 6.1.2.) of the type submitted for approval. It shall also be accompanied either by the test report issued by the approved Test Laboratory or by one or two samples of the tyre type, at the discretion of the competent authority. Drawings or photographs of the side wall and tread of the tyre shall be submitted once production has been established, no later than one year after the date of issue of the type approval."

Annex 5, insert a new Table IV, to read:

"Table IV: 45 Series - Radial on TR Metric 5° Rims

Size	Measuring rim width	Overall diameter	Tyre section width
280/45 R 415	240	661	281

"