



**Economic and Social
Council**

Distr.
GENERAL

TRANS/WP.29/918
17 April 2003

ENGLISH
Original: ENGLISH and FRENCH

ECONOMIC COMMISSION FOR EUROPE

INLAND TRANSPORT COMMITTEE

World Forum for Harmonization of Vehicle Regulations (WP.29)

DRAFT SUPPLEMENT 3 TO REGULATION No. 98

(Headlamps with gas-discharge light sources)

Note: The text reproduced below was adopted by the Administrative Committee (AC.1) of the amended 1958 Agreement at its twenty-third session, following the recommendation by WP.29 at its one-hundred-and-twenty-ninth session. It is based on document TRANS/WP.29/2003/11, not amended (TRANS/WP.29/909, para. 123).

Annex 4, paragraph 1.1.1.1., add a new subparagraph (d) to read:

- "(d) In the case of a passing beam designed to provide bend lighting with the addition of a light source, this light source shall be switched on for 1 minute, and switched off for 9 minutes during the activation of the passing beam only (see annex 4 - appendix 1)."

Insert new Annex 4 - appendix 1, to read:


"Annex 4 - Appendix 1

OVERVIEW OF OPERATIONAL PERIODS
CONCERNING TEST FOR STABILITY OF PHOTOMETRIC PERFORMANCE


Abbreviations:	P:	passing beam lamp
	D:	driving beam lamp (D ₁ + D ₂ means two driving beams)
	F:	front fog lamp
	— — — —	means a cycle of 15 minutes off and 5 minutes lit.
	means a cycle of 9 minutes off and 1 minutes lit

All following grouped headlamps and front fog lamps together with the added marking symbols are given as examples and are not exhaustive.


1. P or D or F (HC or HR or B)



2. P+F (HC B) or P+D (HCR)



3. P+F (HC B/) or HC/B or P+D (HC/R)



_____ "