

Comparison of locking requirements in FMVSS 206 with ECE-R11

US-206	Door location	Fully Latched position	Secondary latched position	Locks required?	Operating means	Latch release with engaged lock(s)			
					outside	inside	inside		
US 206 §	Front side	Y	Y	Y	--	Y			
	Rear side	Y	Y	Y	--	Y	N		
	Cargo side	Y	--	--	--	--			
	Back door	Y	--	Y	Y	Y			
ECE R11 §	Front side	Y	Y hinged	--	--	--	P		
	Rear side	Y	Y hinged	--	--	--	P		

Front Side Doors											
		Operating on outside				Operating on inside					
		action	reason	action	reason	action	reason	action	reason	action	reason
	status	R/C Key		Door handle		Lock operation		Door Handle		Power locks	
US 206 §	Locked	n/a	n/a	NO	Security	unlock	Security	unlatch	?	n/a	n/a
ECE	Locked	unlock	Function	NO	Security	unlock	Security	unlatch	convenience	unlock	Function

Comparison of locking requirements in FMVSS 206 with ECE-R11

Rear Side Doors										
		Operating on outside:				Operating on inside:				
status	R/C / Key		Door handle		Lock operation		Door Handle		Power locks	
	action	reason	action	reason	action	reason	action	reason	action	reason
US 206 §	Locked	n/a	n/a	--	Security	unlock	Security	--	Security	n/a
ECE R11	Locked	unlock	Function	--	Security	unlock	Security	Unlock/unlatch	Function/convenience	unlock
US 206	Locked	unlock	Function	--	Security	unlock	Security	--	Security	unlock
ECE	unlocked Childlock engaged	--	Function	unlatch	Safety	n/a	function	--	safety	no

Hinged Back Doors										
		Operating on outside:				Operating on inside:				
status	R/C / Key		Door handle		Lock operation		Door Handle		Power locks	
	action	reason	action	reason	action	reason	action	reason	action	reason
US 206 §	Locked	unlock	Security?	--	Security	unlock	Security	--	Security	n/a
US 206	lached	--	--	unlatch	safety	--	--	unlatch	--	n/a
ECE	Locked	unlock	Function	--	Security	unlock	Security	unlatch	convenience	unlock
US 206	locked	unlock	security	--	Security	unlock	Security	--	Security	unlock
ECE	unlocked Childlock engaged	--	Function	unlatch	Safety	n/a	function	no	safety	no