



**Economic and Social
Council**

Distr.
GENERAL

TRANS/WP.29/2003/71
31 July 2003

Original: ENGLISH

ECONOMIC COMMISSION FOR EUROPE

INLAND TRANSPORT COMMITTEE

World Forum for Harmonization of Vehicle Regulations (WP.29)
(One-hundred-and-thirty-first session,
11-14 November 2003, agenda item 4.2.38.)

PROPOSAL FOR DRAFT SUPPLEMENT 1 TO THE 01 SERIES OF AMENDMENTS
TO REGULATION No. 107

(M₂ and M₃ vehicles)

Transmitted by the Working Party on General Safety Provisions (GRSG)

Note: The text reproduced below was adopted by GRSG at its eighty-fourth session, and is transmitted for consideration to WP.29 and to AC.1. It is based on documents TRANS/WP.29/GRSG/2003/12, not amended (TRANS/WP.29/GRSG/63, para. 41).

This document is a working document circulated for discussion and comments. The use of this document for other purposes is the entire responsibility of the user.

Documents are also available via the INTERNET:
<http://www.unece.org/trans/main/welcwp29.htm>

Annex 1, part 1, appendices 1 and 2, add a new explanatory note 2/, to read:

"2/ In the case of an articulated vehicle, specify the number of seats in each rigid section."

Paragraph 7.6.1.5., amend to read:

"7.6.1.5. Each rigid section of an articulated vehicle shall be treated as a separate vehicle for the purpose of determination of the minimum number and the position of exits. The connecting passage between them shall not be considered as an exit. The number of passengers shall be determined for each rigid section. The plane, which lies through the geometric centre of the turning section floor, and perpendicular to the longitudinal axis of a vehicle, when it moves straight, shall be considered as the border between sections."

Paragraph 7.6.10.9., amend to read:

"7.6.10.9. When the passenger door is opened, the retractable step shall be securely held in the extended position. When a mass of 136 kg is placed in the centre of a single step or a mass of 272 kg is placed in the centre of a double step the deflection at any point on the step, measured relative to the body of vehicle, shall not exceed 10 mm."

Note by the secretariat: Given the possible adoption of the 01 series of amendments to Regulation 107 and the consideration by GRSG of a proposal for draft 02 series of amendments to the Regulation (TRANS/WP.29/GRSG/2003/21), the secretariat will recommend to return back this proposal to GRSG.