UNITED NATIONS



Economic and Social Council

Distr.

GENERAL

TRANS/WP.29/GRSG/2004/1 23 January 2004

ENGLISH

Original: ENGLISH

ENGLISH AND FRENCH ONLY

ECONOMIC COMMISSION FOR EUROPE

INLAND TRANSPORT COMMITTEE

World Forum for Harmonization of Vehicle Regulations (WP.29)

Working Party on General Safety Provisions (GRSG) (Eighty-sixth session, 19-23 April 2004, agenda item 2.)

PROPOSAL FOR DRAFT AMENDMENTS TO REGULATION No. 52 (Small capacity passenger vehicles, M2 and M3 category)

Transmitted by the expert from the Russian Federation

<u>Note</u>: The text reproduced below was prepared by the expert from the Russian Federation. It is based on the text of a document (informal document No.17) distributed without a symbol at the eighty-fifth session (TRANS/WP.29/GRSG/64, para. 7.)

Note: This document is distributed to the Experts on General Safety Provisions only.

A. PROPOSAL

Paragraph 5.7.8.1., amend to read:

"5.7.8.1. Over each seating position and its associated foot space, there shall be measured a free space with a height of not less than 90 cm, measured from the highest point of the uncompressed seat cushion and at least 135 cm from the mean level of the floor in the foot space. In the case of vehicles to which paragraph 5.7.1.9. applies, and also for the first row of seats, these values may be reduced to 120 cm, measured from the floor, where the feet of the seated passenger rest."

* * *

B. JUSTIFICATION

Regarding the tests of the vehicles with a capacity of up to 12 passenger seats corresponding to prescriptions of Regulation No. 52, the technical services and vehicle manufacturers of the Russian Federation have the following question:

Paragraph 5.2.1.3. (area available for passengers), and also paragraph 5.7.8.1. of Regulation No. 52, concerning free space above places for seated passengers of buses (to which paragraph 5.7.1.9. is applicable) permits the reduction of free space from the floor, where the feet of the seated passenger rest, from 135 cm to 120 cm. The minimum clearance from the highest point of the undepressed cushion should be 90 cm.

According to paragraph 5.7.8.3., the height of the undepressed seat cushion from the floor up to the upper point of the seat cushion is between 40 and 50 cm, if the seats are not located on wheel arches.

The sum of the two obligatory minimum dimensions is 130 cm (90 + 40) which does not allow for vehicles with up to 12 passenger seats to reduce this dimension to 120 cm.

In this respect, the expert from the Russian Federation would like to have clarification about these requirements and the applications of the prescriptions of paragraph 5.7.8.1. in other countries.
