

Specifications and performance criteria of Regulations Nos. 12, 94 and 95

ECE R12:

- 6.1 Compliance with the requirements of Paragraph **5.1 to 5.4** above shall be checked in accordance with the methods set out in Annexes 3, 4 and 5 to this Regulation. **Compliance with the requirements of paragraph 5.5 above shall be checked in accordance with the methods set out in annex 3 to this Regulation.** All measurements should be done on the basis of ISO 6487-1987.

ECE R94:

“5.2. Specifications

The test...at the same time.

~~{Additionally, vehicles equipped with electric power train shall meet the requirements of paragraph 5.2.8. in addition. This can could be demonstrated in-~~ met by a separate ~~crash~~ impact test at the request of the manufacturer and after validation by the Technical Service, ~~given-~~ provided that the electrical components do not influence the occupant protection performance of the vehicle type as defined in paragraphs 5.2.1. to 5.2.5. of this Regulation. **In case of this condition the requirements of paragraph 5.2.8 shall be checked in accordance with the methods set out in annex 3 to this Regulation, except paragraphs 2., 5. and 6. in annex 3. But a dummy corresponding to the specifications for Hybrid III 1/fitted with a 45° ankle and meeting the specifications for its adjustment shall be installed in each of the front outboard seats”**

ECE R95:

“5.2. Performance criteria

~~{Additionally, vehicles equipped with electric power train shall meet the requirements of paragraph 5.3.6. in addition. This can could be demonstrated in-~~ met by a separate ~~crash~~ impact test at the request of the manufacturer and after validation by the Technical Service, ~~given-~~ provided that the electrical components do not influence the occupant protection performance of the vehicle type as defined in paragraphs 5.2.1. to 5.3.4. of this Regulation. **In case of this condition the requirements of paragraph 5.3.6 shall be checked in accordance with the methods set out in annex 4 to this Regulation, except paragraphs 6, 7 and Appendix 1 and 2. But the side-impact dummy shall be installed in the front seat on the impact side.**