Proposal for Corrigendum 1 to Supplement 7 to the 04 series of amendments to Regulation No. 48 (Installation of lighting and light-signalling devices)

<u>Note</u>: The modifications to the current text of the regulation (ECE/TRANS/WP.29/2011/11) are marked in bold or strikethrough characters.

I. Proposal

Paragraph 6.3.6.2.1., amend to read:

"6.3.6.2.1. Where a levelling device is fitted for a front fog lamp, independent or grouped with other front lighting and light signalling functions, it shall be such that the vertical inclination, under all the static loading conditions of Annex 5 of this Regulation, shall remain between the limits prescribed in paragraph 6.3.6.1.2.1. 6.3.6.1.2.2.1.

Paragraph 6.3.6.2.3., amend to read:

"6.3.6.2.3. The levelling device may also be used to automatically adapt the inclination of the front fog beam in relation to the prevailing ambient conditions, provided that the limits for the downward inclination specified in paragraph 6.3.6.1.2.1. 6.3.6.1.2.2.1. are not exceeded."

II. Justification

There are mistakes of paragraph renumbers shown below.

Paragraph renumbers in Supplement 7 to the 04 series of amendments

6.3.6.1.2.2. 6.3.6.1.2.2.1., the vertical inclination of the cut-off shall under all the static conditions of Annex 5 automatically remain between the following values: $h \leq 0.8$ Limits: between -1.0 per cent and - 3.0 per cent Initial aiming: between -1.5 per cent and -2.0 per cent 6.3.6.1.2.2.2.The value of this indicated downward inclination shall be defined in accordance with paragraph 6.3.6.1.2.2. 6.3.6.1.2.2.1. (: correct), it shall be such that the vertical inclination, under all the static loading 6.3.6.2.1. conditions of Annex 5 of this Regulation, shall remain between the limits prescribed in paragraph 6.3.6.1.2.2. 6.3.6.1.2.1. (: mistake), provided that the limits for the downward inclination specified in 6.3.6.2.3. paragraph 6.3.6.1.2.2. 6.3.6.1.2.1. (: mistake) are not exceeded.