

**Ratio for these following simulations: 10:6.**

Séquence200 x1:

Variable intensity turn-indicator frequency **90** flash/minutes (period of 660 ms: 330ms on, 330ms off)

Variation time: 200ms



Séquence200 x1.exe

Séquence200 x3:

Variable intensity turn-indicator frequency **90** flash/minutes (period of 660 ms: 330ms on, 330ms off)

Variation time: **330ms**



Séquence200 x3.exe

Séquence500 x1:

Variable intensity turn-indicator frequency **60** flash/minutes (period of 1,000ms: 500ms on, 500ms off)

Variation time: 200ms



Séquence500 x1.exe

Séquence500 x2:

Variable intensity turn-indicator frequency 60 flash/minutes (period of 1,000ms: 500ms on, 500ms off)

Variation time: **300ms**



Séquence500 x2.exe

Séquence500 x3:

Variable intensity turn-indicator frequency 60 flash/minutes (period of 1,000ms: 500ms on, 500ms off)

Variation time: **400ms**



Séquence500 x3.exe

**Ratio for these following simulations: 1:1.**

Séquence200 x2: **Ratio 10:6**

Variable intensity turn-indicator frequency 90 flash/minutes (period of 660 ms: 330ms on, 330ms off) Variation time: **300ms**



Séquence200 x2.exe

**Direction Indicator:**

Vid200ratio1: **Ratio 1:1**

Variable intensity turn indicator frequency 90 flash/minutes ( period of 660 ms: 330ms on, 330ms off) variation time : **300ms**



Vid200ratio1.exe

## Hazard Warning:

### Ratio 10:6

VidWarningFix :

**Hazard Warning signal standard.**



VidWarningFix\_standard.exe

VidWarning200:

**Hazard Warning signal.** Variable intensity. frequency 90 flash/minutes ( period of 660 ms: 330ms on, 330ms off) variation time : **300ms**



VidWarning200 ratio 10\_6 and 300ms.exe

## Ratio 1:1

VidWarningRatio1\_fix:

**Hazard Warning signal standard.**



VidWarningRatio1\_fix ratio 1\_1\_standard.exe

VidWarningRatio1\_tracer.:

**Hazard Warning signal.** Variable intensity. frequency 90 flash/minutes ( period of 660 ms: 330ms on, 330ms off) variation time : **300ms**



VidWarningRatio1\_tracerratio 1\_1 and 300 ms.exe