



Economic and Social Council

Distr.: General
30 October 2018

Original: English

Economic Commission for Europe

Inland Transport Committee

World Forum for Harmonization of Vehicle Regulations

176th session

Geneva, 13-16 November 2018

Item 4.12.2 of the provisional agenda

1958 Agreement:

Consideration of proposals for new UN Regulations submitted
by the Working Parties subsidiary to the World Forum

Proposal for a new UN Regulation on Road Illumination Devices (RID)

Submitted by the Working Party on Lighting and Light-Signalling*

Corrigendum

Table 9, Part A, amend to read:

"...

Tabled requirements expressed in cd			Position / deg.			Passing beam								
			horizontal		vertical	Class C		Class V		Class E		Class W		
No.	Element	At/from	to	at	min	max	min	max	min	max	min	max		
Part A	1	B50L	L 3.43	-	U 0.57	50 ⁴	350	50	350	50	625 ⁷	50	625	
	3	BR	R 2.50	-	U 1.00	50 ⁴	1 750	50	880	50	1 750	50	2 650	
	4	Segment BRR	R 8.00	R 20	U 0.57	50 ⁴	3 550	-	880	-	3 550	-	5 300	
	5	Segment BLL	L 8.00	L 20	U 0.57	50 ⁴	625	-	880	-	880	-	880	
	6	P	L 7.00	-	H	63	-	-	-	-	-	-	63	-
	7	Zone III	As specified in Table 11			-	625	-	625	-	880	-	880	
	8a	S50+S50LL+S50RR ⁵	-	-	U 4.00	190 ⁶	-	-	-	190 ⁶	-	190 ⁶	-	
	9a	S100+S100LL+S100RR ⁵	-	-	U 2.00	375 ⁶	-	-	-	375 ⁶	-	375 ⁶	-	
	10	50 R	R 1.72	-	D 0.86	-	-	5 100	-	-	-	-	-	

* In accordance with the programme of work of the Inland Transport Committee for 2018–2019 (ECE/TRANS/274, para. 123 and ECE/TRANS/2018/21/Add.1, cluster 3.1), the World Forum will develop, harmonize and update UN Regulations in order to enhance the performance of vehicles. The present document is submitted in conformity with that mandate.

11	75 R	R 1.15	-	D 0.57	10 100	-	-	-	15 200	-	20 300	-
12	50 V	V	-	D 0.86	5 100	-	5 100	-	10 100	-	10 100	-
13	50 L	L 3.43	-	D 0.86	3 550	13 200 ⁸	3 550	13 200 ⁸	6 800	-	6 800	26 400 ⁸
14	25 LL	L 16.00	-	D 1.72	1 180	-	845	-	1 180	-	3 400	-
15	25 RR	R 11.00	-	D 1.72	1 180	-	845	-	1 180	-	3 400	-
16	Segment 20 and below	L 3.50	V	D 2.00	-	-	-	-	-	-	-	17 600 ²
17	Segment 10 and below	L 4.50	R 2.00	D 4.00	-	12 300 ¹	-	12 300 ¹	-	12 300 ¹	-	7 100 ²
18	I _{max} ³	-	-	-	16 900	44 100	8 400	44 100	16 900	79 300 ⁷	29 530	70 500 ²

"