

Proposal for amendments to ECE/TRANS/WP.29/GRSP/2019/27 (the 10 series of amendments to UN Regulation No. 17 (Strength of seats))

Agenda Item 9

Submitted by the expert from Japan,

The text reproduced below was prepared by the expert from Japan to make additional corrections to the official document ECE/TRANS/WP.29/GRSP/2019/27. The modifications to the ECE/TRANS/WP.29/GRSP/2019/27 are marked in red bold in new and red strikethrough for deleted characters.

The amendments proposed in ECE/TRANS/WP.29/GRSP/2019/27 are marked in black bold as it appears in ECE/TRANS/WP.29/GRSP/2019/27.

I. Proposal

5. Requirements

Paragraph 5.6.3., amend to read;

5.6.3. Minimum width

When measured in accordance with Annex 24, the lateral width of a head restraint shall be not less than 85 mm on either side of the torso line (distances L and L').

6. Tests

Paragraph 6.4.2., amend to read:

6.4.2. In the case of a bench seat, where part or all of the supporting frame (including that of the head restraints) is common to more than one seating position, the **displacement** test shall be conducted simultaneously for all those seating positions.

6.4.3. **Test for determining rearward displacement for the head restraint**

II. Justification

- 5.6.3. Editorial correction
 - 6.4.2. Necessary improvement of clarity due to the addition of new requirement (height retention) to clarify that paragraph 6.4.2. is aimed at the test for determining rearward displacement for the head restraint prescribed in 6.4.3 .
-