

PROPOSAL FOR A CORRIGENDUM TO REGULATION No. [110]

(Specific Components for CNG, documents TRANS/WP.29/704 and TRANS/WP.29/762)

Transmitted by the expert from Italy

Note: The text reproduced below was prepared by the expert from Italy in order to introduce some editorial changes to the text of Regulation No. 110 (doc. TRANS/WP.29/704) in addition to those contained in document TRANS/WP.29/762.

Annex 4A, paragraphs 5.5. and 5.6., amend to read:

"5.5. The excess flow valve shall cut off at a pressure difference over the valve of max 650 kPa.

5.6. When the excess flow valve is at cut off position, the flow through the by-pass shall not exceed 0.13 m³/min at a differential pressure of 10,000 kPa."

It is also suggested that Annex 3 should be amended in order to take account of the final version of ISO standard 11439. */

*/ Proposal to be prepared.

Filename: 41-inf04.doc
Directory: C:\MyFiles\INTERNET\TRANS\MAIN\wp29\wp29wgs\wp29grpe
 \grpeinfdoc
Template: C:\Program Files\Microsoft Office\Templates\Normal.dot
Title:
Subject:
Author: xxx
Keywords:
Comments:
Creation Date: 11/01/01 16.58
Change Number: 5
Last Saved On: 12/01/01 13.02
Last Saved By: UNECE
Total Editing Time: 37 Minutes
Last Printed On: 12/01/01 15.20
As of Last Complete Printing
 Number of Pages: 1
 Number of Words: 148 (approx.)
 Number of Characters: 849 (approx.)