



**Economic and Social
Council**

Distr.
GENERAL

TRANS/WP.29/2004/49
21 July 2004

ENGLISH
Original: ENGLISH AND FRENCH

ECONOMIC COMMISSION FOR EUROPE

INLAND TRANSPORT COMMITTEE

World Forum for Harmonization of Vehicle Regulations (WP.29)
(One-hundred-and-thirty-fourth session,
16-19 November 2004, agenda item 5.2.20.)

PROPOSAL FOR DRAFT SUPPLEMENT 2 TO REGULATION No. 108
(Retreaded pneumatic tyres)

Transmitted by the Working Party on Brakes and Running Gear (GRRF)

Note: The text reproduced below was adopted by GRRF at its thirty-fifth session and is transmitted for consideration to WP. 29 and AC.1 (TRANS/WP.29/GRRF/55, para. 45). It is based on document TRANS/WP.29/GRRF/2002/18/Rev.2, as amended by para. 44. of the report.

This document is a working document circulated for discussion and comments. The use of this document for other purposes is the entire responsibility of the user.

Documents are also available via the INTERNET:

<http://www.unece.org/trans/main/welcwp29.htm>

Paragraph 2.21.2., amend to read:

".....annex 5 to this Regulation, or, depending on the tyre design type, the nominal outer diameter expressed in mm;"

Insert a new paragraph 2.21.4., to read:

"2.21.4. an indication of the tyre to rim fitment configuration when it differs from the standard configuration."

Insert a new paragraph 2.23.1., to read:

"2.23.1. "Tyre to rim fitment configuration" means the type of rim to which the tyre is designed to be fitted. In the case of non-standard rims this will be identified by a symbol applied to the tyre, for example, "CT", "TR", "TD" or "A"."

Insert a new paragraph 3.2.9., to read:

"3.2.9. No later than two years after the date of entry into force of this amendment, tyres manufactured using the "bead to bead" process as defined in paragraph 2.37.3., or any process in which the sidewall material is renewed, shall have the identification referred to in paragraph 2.21.4. placed only immediately after the rim diameter marking referred to in paragraph 2.21.3."

Annex 3, amend to read:

"Annex 3

ARRANGEMENT OF RETREAD TYRE MARKINGS

1. Example of the

.....
.....
..... or 28 of the year 2003.

2. In the particular case of tyres having a tyre to rim fitment configuration "A", the marking shall be in the form of the following example:

185-560 R 400A where:

185 is the nominal section width in mm

560 is the outer diameter expressed in mm

R is an indication of the structure of the tyre (see paragraph 3.2.3. of this Regulation).

400 is the nominal diameter of the rim expressed in mm

A is the tyre to rim fitment configuration.

The marking of the load index, speed category date of manufacture and other markings, shall be as given in the example above.

3. The positioning and order of
- (a) the size designation as defined in paragraph 2.21. of this Regulation shall be grouped as shown in the examples:
185/70 R 14 and 185-560 R 400A;
 - (b) the service description comprising the load index and the speed symbol shall be placed immediately after the tyre size designation as defined in paragraph 2.21. of this Regulation;
 - (c) the symbols.....
 - (d) the word "
-