

CORRIGENDA TO DOCUMENT TRANS/WP29/GRSG/2003/22/Rev.2
DEFINITION OF OPEN ROOF VEHICLES

Transmitted by the expert from OICA

Insert a new paragraph 2.1.9., to read:

"2.1.9. "Vehicle without a roof" means a vehicle without a roof over all or part of its deck. In the case of a double-decked vehicle this shall be the upper deck. Spaces for standing passengers shall not be provided on any deck without a roof."

Annex 3

Add a new paragraph 7.6.1.15.:

"7.6.1.15 In the case of a vehicle without a roof, the exits on the deck without a roof shall be such as to fulfil those prescriptions that are not incompatible with the absence of the roof."

Add a new paragraph 7.8.1.6.:

"7.8.1.6. In the case of a double-decked vehicle without a roof, at least one lighting device shall be provided as near as practicable to the top of every staircase leading to the upper deck."

Add a new paragraph 7.12.2.:

"7.12.2. Every vehicle without a roof shall have:

- a continuous front panel over the full width of that part of the vehicle that does not have a roof, with a height of not less than [1200] mm from the general level of the floor adjacent to the front panel;
- continuous protection around the side and rear that part of the vehicle that does not have a roof, with a height of not less than [1100] mm at the sides and [1200] mm at the rear of the vehicle, measured from the general level of the floor adjacent to the panels. The protection shall consist of continuous side and rear panels with a height of not less than [700] mm from the general level of the floor adjacent to the panels, combined with one or more continuous guard rail(s) that fulfils the following characteristics:
 - no dimension of its section must be less than 20 mm, or more than 45 mm;
 - the size of any aperture between a guard rail and any adjacent guard rail or panel shall not exceed [200] mm;
 - it shall be firmly attached to the structure of the vehicle."