



**Economic and Social
Council**

Distr.
GENERAL

TRANS/WP.29/2005/2
22 December 2004

Original: ENGLISH

ECONOMIC COMMISSION FOR EUROPE

INLAND TRANSPORT COMMITTEE

World Forum for Harmonization of Vehicle Regulations (WP.29)
(One-hundred-and-thirty-fifth session, 8-11 March 2005,
agenda item 4.2.5.)

PROPOSAL FOR DRAFT SUPPLEMENT 1 TO THE 10 SERIES OF AMENDMENTS TO
REGULATION No. 13
(Braking)

Transmitted by the Working Party on Brakes and Running Gear (GRRF)

Note: The text reproduced below was adopted by GRRF at its fifty-sixth session (TRANS/WP.29/GRRF/56, para. 8) and is transmitted for consideration to WP.29 and to AC.1. It is based on the text of document TRANS/WP.29/GRRF/2004/11, not amended.

This document is a working document circulated for discussion and comments. The use of this document for other purposes is the entire responsibility of the user.

Documents are also available via the INTERNET:
<http://www.unece.org/trans/main/welcwp29.htm>

Paragraph 5.2.2.2., amend to read:

"5.2.2.2. Trailers of category O₂ must be equipped with a service braking system either of the continuous or semi-continuous or the inertia (overrun) type. The latter type shall be permitted only for centre-axle trailers. However, electrical braking systems conforming to the requirements of Annex 14 to this Regulation shall be permitted."

Annex 4,

Paragraph 1.3.2., amend to read:

"1.3.2. Behaviour of the vehicle during braking on a road on which adhesion is reduced. The behaviour of vehicles of categories M₁, M₂, M₃, N₁, N₂, N₃, O₂, O₃, and O₄ on a road on which adhesion is reduced must meet the requirements of Annex 10 and/or Annex 13 to this Regulation."

Annex 10,

Paragraph 1.1., amend to read:

"1.1. Vehicles of categories M, N, O₂, O₃ and O₄ which are not equipped with an anti-lock system as defined in annex 13 to this Regulation shall meet all the requirements of this annex. If a special device is used ..."

Footnote 5/ to paragraph 3.1.1., amend to read:

"5/ The provisions of paragraphs 3.1.1. or 5.1.1. do not affect the requirements of Annex 4 to this Regulation relating to the braking performance. However, if, in tests made under the provisions of paragraphs 3.1.1. or 5.1.1., braking performances"

Paragraph 5.1.1., including the addition of new sub paragraphs 5.1.1.1. to 5.1.1.3., amend to read:

"5.1.1. For full trailers with two axles the following requirements apply:

5.1.1.1. For k values between 0.2 and 0.8: 5/

$$z \geq 0.1 + 0.85 (k - 0.2)$$

5.1.1.2. For all states of load of the vehicle, the adhesion utilization curve of the rear axle shall not be situated above that for the front axle for all braking rates between 0.15 and 0.30. This condition is also considered satisfied if, for braking rates between 0.15 and 0.30, the adhesion utilization curves for each axle are situated between two lines parallel to the line of ideal adhesion utilization given by the equations $k = z + 0.08$ and $k = z - 0.08$ as shown in diagram 1B of this annex and the adhesion utilization curve for the rear axle for braking rates $z \geq 0.3$ complies with the relation

$$z \geq 0.3 + 0.74 (k - 0.38).$$

5.1.1.3. For the verification of the requirements of paragraphs 5.1.1.1. and 5.1.1.2. the procedure should be as that in the provisions of paragraph 3.1.4."

Paragraph 5.1.2., amend to read:

"5.1.2. For full trailers with more than two axles the requirements of paragraph 5.1.1. of this annex shall apply. The requirements of paragraph 5.1.1. of this annex with respect to wheel lock sequence shall be considered to be met if, in the case of braking rates between 0.15 and 0.30, the adhesion utilized by at least one of the front axles is greater than that utilized by at least one of the rear axles."

The heading of "Diagram 1B", amend to read:

"VEHICLES OTHER THAN THOSE OF CATEGORIES M1 AND N1 AND FULL TRAILERS
(see paragraphs 3.1.2.3. and 5.1.1.2. of this annex)"
