



**Economic and Social
Council**

Distr.
GENERAL

ECE/TRANS/WP.29/2006/35

24 March 2006

Original: ENGLISH

ECONOMIC COMMISSION FOR EUROPE

INLAND TRANSPORT COMMITTEE

World Forum for Harmonization of Vehicle Regulations (WP.29)

One-hundred-and-thirty-ninth session
Geneva, 20-23 June 2006,
Item 4.2.14. of the provisional agenda

**PROPOSAL FOR SUPPLEMENT 2 TO THE 04 SERIES OF AMENDMENTS
TO REGULATION No. 44**

(Child restraint systems)

Submitted by the Working Party on Passive Safety (GRSP)

Note: The text reproduced below was adopted by GRSP at its thirty-eighth session and is submitted for consideration to WP.29 and AC.1 (TRANS/WP.29/GRSP/38, para. 22). It is based on the text of TRANS/WP.29/GRSP/2005/15 as amended by paragraph 22 of the report.

This document is a working document circulated for discussion and comments. The use of this document for other purposes is the entire responsibility of the user.

Documents are also available via the INTERNET:

<http://www.unece.org/trans/main/welcwp29.htm>

Paragraphs 2.1.3. to 2.1.3.3., amend to read (deleting paragraph 2.1.3.3.):

"2.1.3. The retention system of child restraint systems may be of two classes:

an integral class if the retention of the child within the restraint system is independent of any means directly connected to the vehicle;

a non-integral class if the retention of the child within the restraint system is dependent upon any means directly connected to the vehicle;

2.1.3.1. "partial restraint" means a device, such as a booster cushion, which, when used in conjunction with an adult seat belt, which passes around the body of the child or restrains the device in which the child is placed, forms a complete child restraint system;

2.1.3.2. "booster cushion" means a firm cushion, which can be used with an adult seat belt."

Insert a new paragraph 2.8.8., to read:

"2.8.8. "guide strap" means a strap which constrains the shoulder strap of the adult seat belt in a position to suit the child and where the effective position at which the shoulder strap changes direction can be adjusted by means of a device which can be moved up and down the strap to locate the wearer's shoulder, and then locked into that position. This guide strap is not meant to carry a significant part of the dynamic load."
