

CLEPA's comments on ECE/TRANS/WP.29/GRE/2006/39

Note: The text reproduced below was prepared by the experts from CLEPA in order to propose amendments to ECE/TRANS/WP29/GRE/2006/39, tabled by India. The modifications to ECE/TRANS/WP29/GRE/2006/39 are marked in **bold** and/or ~~striketrough~~ characters.

A. PROPOSAL

Paragraph 7.2.1., amend to read:

"7.2.1. When subjected to a continuous spraying action for 60 seconds on the test component in its normal mounting conditions, a test sample shall show no damage to the retro-reflective surface or delaminate from the substrate or separation from the sample mounting surface under the following set-up parameters:

- (a) Water/wash solution pressure **8 ± 0.2** MPa;
- (b) Water/wash solution temperature **60° ± 5** °C;
- ~~(c) Water/wash solution flow rate 6 to 7 l/min;~~
- (c) The tip of the cleaning wand to be positioned at distance of **600 ± 20** mm away from the retro-reflective surface;
- (d) Cleaning wand to be held at no greater angle than 45 degrees from perpendicular to the retro-reflective surface;
- (e) 40 degree nozzle creating wide fan pattern."

B. JUSTIFICATION

This proposal is in a line with the proposal by CLEPA for amendments to Regulation No. 104 (ECE/TRANS/WP.29/2006/66 and ECE/TRANS/WP.29/2006/66/Amend.1), adopted by WP.29 and AC.1 at their June 2006 sessions (see report ECE/TRANS/WP.29/1052, paras. 53 and 80).
