



Economic and Social Council

Distr.: General
16 August 2013

Original: English

Economic Commission for Europe

Inland Transport Committee

World Forum for Harmonization of Vehicle Regulations

161st session

Geneva, 12-15 November 2013

Item 4.6.20 of the provisional agenda

1958 Agreement – Consideration of draft amendments to existing Regulations submitted by GRE

Proposal for Supplement 17 to Regulation No. 77 (Parking lamps)

Submitted by the Working Party on Light and Light-signalling*

The text reproduced below was adopted by the Working Party on Light and Light-signalling (GRE) at its sixty-ninth session (ECE/TRANS/WP.29/GRE/69, paras. 19 and 20). It is based on ECE/TRANS/WP.29/GRE/2013/17 not amended and on ECE/TRANS/WP.29/GRE/2013/31 as amended by Annex V to the report. It is submitted to the World Forum for Harmonization of Vehicle Regulations (WP.29) and to the Administrative Committee AC.1 for consideration.

* In accordance with the programme of work of the Inland Transport Committee for 2010–2014 (ECE/TRANS/208, para. 106 and ECE/TRANS/2010/8, programme activity 02.4), the World Forum will develop, harmonize and update regulations in order to enhance the performance of vehicles. The present document is submitted in conformity with that mandate.

Insert a new paragraph 3.2.4., to read:

"3.2.4. In the case of a non-replaceable filament lamp(s) or light source module(s) equipped with non-replaceable filament lamp(s), the documents according to paragraph 6.5. of this Regulation."

Insert a new paragraph 6.5., to read:

"6.5. In the case of non-replaceable filament lamp(s) or light source module(s) equipped with non-replaceable filament lamp(s), the applicant shall annex to the type approval documentation a report (by the light source manufacturer indicated in the type approval documentation), acceptable to the Type Approval Authority, that demonstrates compliance of these non-replaceable filament lamp(s) with the requirements as specified in paragraph 2.11. of IEC 60809, Edition 3."

Paragraph 12.1., amend to read:

"12.1. Parking lamps shall be so manufactured as to conform to the type approved under this Regulation.

The compliance with the requirements set forth in paragraphs 7. and 9. above shall be verified as follows:"

Paragraph 12.2. (former), renumber as paragraph 12.1.1.

Paragraph 12.3. (former), renumber as paragraph 12.1.2.

Paragraph 12.4. (former), renumber as paragraph 12.2.

Insert a new paragraph 12.3, to read:

"12.3. In the case of non-replaceable filament lamp(s) or light source module(s) equipped with non-replaceable filament lamps, a report (by the light source manufacturer indicated in the type approval documentation) shall demonstrate compliance of these non-replaceable filament lamp(s) with lifetime requirements and, in the case of colour coated filament lamps, also with colour endurance requirements, as specified in paragraph 2.11. of IEC 60809, Edition 3."

Annex 5, paragraphs 1.2. to 1.3., amend to read:

"1.2. With respect to photometric performances, the conformity of mass-produced lamps shall not be contested if, when testing according to paragraph 8. of this Regulation, the photometric performances as set forth in paragraph 7. of this Regulation of any lamp chosen at random and equipped with a standard light source, or when the lamps are equipped with non-replaceable light sources (filament lamps or other), and when all measurements are made at 6.75 V, 13.5 V or 28.0 V respectively:

1.2.1. No measured value deviates unfavourably by more than 20 per cent from the values prescribed in this Regulation.

For the minimum values required throughout the fields specified in Annex 3 the respective maximum deviations of the measured values shall correspond to the values shown in the table below:

<i>Required minimum value</i>	<i>Equivalent 20 per cent</i>	<i>Equivalent 30 per cent</i>
<i>cd</i>	<i>cd</i>	<i>cd</i>
0.05	0.02	0.03

- 1.2.2. In the case of a lamp equipped with a replaceable light source, if results of the test described above do not meet the requirements, tests on lamps shall be repeated using another standard light source.
- 1.3. The chromaticity coordinates shall be complied with when the lamp is equipped with a standard light source, or for lamps equipped with non-replaceable light sources (filament lamps or other), when the colorimetric characteristics are verified with the light source present in the lamp."

Annex 5, insert new paragraphs 1.4. to 1.4.2., to read:

- "1.4. In the case of non-replaceable filament lamp(s) or light source module(s) equipped with non-replaceable filament lamps, at any conformity of production check:
- 1.4.1. The holder of the approval mark shall demonstrate the use in normal production and show the identification of the non-replaceable filament lamp(s) as indicated in the type approval documentation;
- 1.4.2. In the case where doubt exists in respect to compliance of the non-replaceable filament lamp(s) with lifetime requirements and/or, in the case of colour coated filament lamps, with colour endurance requirements, as specified in paragraph 2.11. of IEC 60809, Edition 3, conformity shall be checked (by the light source manufacturer indicated in the type approval documentation) as specified in paragraph 2.11. of IEC 60809, Edition 3."

Annex 6, amend to read:

"Annex 6

Minimum requirements for sampling by an inspector

1. General
- 1.1. The conformity requirements shall be considered satisfied from a mechanical and a geometric standpoint, in accordance with the requirements of this Regulation, if any, if the differences do not exceed inevitable manufacturing deviations.
- 1.2. With respect to photometric performances, the conformity of mass-produced parking lamps shall not be contested if, when testing according to paragraph 8. of this Regulation, the photometric performances as set forth in paragraph 7. to this Regulation of any lamp chosen at random and equipped with a standard light source, or when the lamps are equipped with non-replaceable light sources (filament lamps or other), and when all measurements are made at 6.75 V, 13.5 V or 28.0 V respectively:
- 1.2.1. According to the requirements in paragraph 1.2.1. of Annex 5 to this Regulation are met.
- 1.2.2. In the case of a lamp equipped with a replaceable light source, if results of the test described above do not meet the requirements, tests on lamps shall be repeated using another standard light source.
- 1.2.3. Lamps with apparent defects are disregarded.
- 1.3. The chromaticity coordinates shall be complied with when the lamp is equipped with a standard light source, or for lamps equipped with non-

replaceable light sources (filament lamps or other), when the colorimetric characteristics are verified with the light source present in the lamp.

2. First sampling

In the first sampling four parking lamps are selected at random. The first sample of two is marked A, the second sample of two is marked B.

2.1. The conformity of mass-produced parking lamps shall not be contested if the deviation of any specimen of samples A and B (all four lamps) is not more than 20 per cent.

In the case, that the deviation of both lamps of sample A is not more than 0 per cent, the measurement can be closed.

2.2. The conformity of mass-produced parking lamps shall be contested if the deviation of at least one specimen of sample A or B is more than 20 per cent.

The manufacturer shall be requested to bring his production in line with the requirements (alignment) and a repeated sampling according to paragraph 3. below shall be carried out within two months' time after the notification. The samples A and B shall be retained by the Technical Service until the entire Conformity of Production process is finished.

3. First repeated sampling

A sample of four lamps is selected at random from stock manufactured after alignment.

The first sample of two is marked C, the second sample of two is marked D.

3.1. The conformity of mass-produced parking lamps shall not be contested if the deviation of any specimen of samples C and D (all four lamps) is not more than 20 per cent.

In the case, that the deviation of both lamps of sample C is not more than 0 per cent the measurement can be closed.

3.2. The conformity of mass-produced parking lamps shall be contested if the deviation of at least:

3.2.1. One specimen of sample C or D is more than 20 per cent but the deviation of all specimen of these samples is not more than 30 per cent.

The manufacturer shall be requested again to bring his production in line with the requirements (alignment).

A second repeated sampling according to paragraph 4. below shall be carried out within two months' time after the notification. The samples C and D shall be retained by the Technical Service until the entire Conformity of Production process is finished.

3.2.2. One specimen of sample C or D is more than 30 per cent.

In this case the approval shall be withdrawn and paragraph 5. below shall be applied.

4. Second repeated sampling

A sample of four lamps is selected at random from stock manufactured after alignment.

The first sample of two is marked E, the second sample of two is marked F.

- 4.1. The conformity of mass-produced parking lamps shall not be contested if the deviation of any specimen of samples E and F (all four lamps) is not more than 20 per cent.
In the case, that the deviation of both lamps of sample E is not more than 0 per cent, the measurement can be closed.
- 4.2. The conformity of mass-produced parking lamps shall be contested if the deviation of at least one specimen of sample E or F is more than 20 per cent.
In this case the approval shall be withdrawn and paragraph 5. below shall be applied.
5. Approval withdrawn
Approval shall be withdrawn according to paragraph 13. of this Regulation."

Figure 1 shall be deleted.
