



# Economic and Social Council

Distr.: General  
2 December 2013  
English  
Original: English and Russian

---

## Economic Commission for Europe

### Inland Transport Committee

#### Working Party on Inland Water Transport

##### Working Party on the Standardization of Technical and Safety Requirements in Inland Navigation

###### Forty-fourth session

Geneva, 12–14 February 2014

Item 7 (c) of the provisional agenda

###### Recommendations on Harmonized Europe-Wide Technical Requirements for Inland Navigation Vessels (Resolution No. 61, revised)

### Draft proposal of Chapter 15a “Specific requirements for passenger sailing vessels”

Transmitted by the Group of Volunteer Experts on Resolution No. 61<sup>1</sup>

#### I. Mandate

1. At its forty-third session, the Working Party on the Standardization of Technical and Safety Requirements in Inland Navigation (SC.3/WP.3) invited Governments to consider the draft Chapter 15a, prepared by the Group of Volunteer Experts on Resolution No. 61 with due regard to EU Directive 2006/87/EC laying down technical requirements for inland waterway vessels (ECE/TRANS/SC.3/WP.3/86, para. 32). The proposal of the Group was presented in Informal document SC.3/WP.3 No. 11 (2013).

2. The request for the comments on the draft proposal was circulated by the secretariat in the questionnaire for the forty-fourth session of SC.3/WP.3. The official draft proposal, based on the text, submitted by the group of Volunteer Experts with the explanatory footnotes, is presented below. The original text of the Directive is available in ECE/TRANS/SC.3/WP.3/2013/11.

---

<sup>1</sup> This document is submitted in line with the output/activities of cluster 2:6: Inland water transport, paragraph 1B(c) of the work plan 2012–2016 (ECE/TRANS/2012/12) adopted by the Inland Transport Committee on 1 March 2012 (ECE/TRANS/224, para. 94). Paragraph 1B(c) provides a mandate for updating of Resolution No. 61 in order to ensure a high level of safety of navigation.

3. The Working Party may wish to consider and finalize the draft proposal so that it can be transmitted for the adoption at the fifty-eighth session of the Working Party on Inland Water Transport.

## II. Draft Chapter 15a “Specific requirements for passenger sailing vessels”

### 15A-1<sup>2</sup> APPLICATION OF CHAPTER 3 TO CHAPTER 23

In addition to the provisions of chapters 3 to chapter 23, the requirements in this chapter shall apply to passenger sailing vessels.

### 15A-2 EXCEPTIONS FOR CERTAIN PASSENGER SAILING VESSELS

15a-2.1<sup>3</sup> For passenger sailing vessels having an  $L_{WL}$  not exceeding 45 m and a maximum permissible number of passengers not exceeding  $L_{WL}$  in whole meters, the following provisions shall not apply:

- (i) Section 3-6.1 provided that anchors are not transported in hawse pipes;<sup>4</sup>
- (ii) Paragraph 10-2.1, fifth bullet, with regard to length;
- (iii) Paragraph 15-8.3(i);
- (iv) Paragraph 15-14.6.<sup>5</sup>

15a-2.2 By way of derogation from paragraph 15a-2.1, the number of passengers may be raised to 1,5 times the  $L_{WL}$  in whole meters, if sails, rigging and deck fittings so permit.

### 15A-3<sup>6</sup> STABILITY REQUIREMENTS FOR VESSELS UNDER SAIL

15a-3.1 For the calculation of the heeling moment according to paragraph 15-3.3, the furled sails shall be taken into account when determining the centre of gravity of the vessel.

15a-3.2 Taking into consideration all load conditions according to paragraph 15-3.2, and using a standard arrangement of sails, the heeling moment caused by wind pressure shall not be so high as to exceed a heeling angle of 20°. At the same time

- (i) a constant wind pressure of 0.07 kN/m<sup>2</sup> shall be applied for the calculation,
- (ii) the residual safety clearance shall be at least 100 mm, and
- (iii) the residual freeboard shall not be negative.

15a-3.3 The righting lever of static stability shall

- (i) reach its maximum value at a heeling angle of 25° or over,
- (ii) amount to at least 200 mm at a heeling angle of 30° or over,

---

<sup>2</sup> Based on Article 15a.01 of the Directive. The adjustments in cross-references and in numbering are not indicated.

<sup>3</sup> Based on Article 15a.02 of the Directive.

<sup>4</sup> It is recalled that a new section 3-6 was added to the Resolution as part of the amendments adopted by the fifty-seventh session of the Working Party on Inland Water Transport (ECE/TRANS/SC.3/2013/195, para. 35).

<sup>5</sup> In the original English text of the Directive the reference is made Article 15.15(9)(a), which does not exist in the Directive.

<sup>6</sup> Based on Article 15a.03 of the Directive.

(iii) be positive at a heeling angle of up to 60°.

15a-3.4 The area under the righting lever curve shall not be less than

- (i) 0.055 mrad up to 30°;
- (ii) 0.09 mrad up to 40° or at the angle at which an unprotected opening reaches the water surface and which is less than 40°.

Between

- (iii) 30° and 40°, or
- (iv) 30° and the angle at which an unprotected opening reaches the water surface and which is less than 40°,

this area shall not be less than 0.03 mrad.

#### 15A-4<sup>7</sup> SHIPBUILDING AND MECHANICAL REQUIREMENTS

15a-4.1 By way of derogation from paragraphs 6-1.3, and 9-1.1.2, the equipment must be designed for permanent lists of up to 20°.

15a-4.2 By way of derogation from paragraphs 15-6.5(i) and 15-6.9(ii), the competent authority<sup>8</sup> may, in the case of passenger sailing vessels not more than 25 m long, authorise a clear width of less than 800 mm for connecting corridors and companionways. However, the clear width shall be at least 600 mm.

15a-4.3 By way of derogation from paragraph 15-6.11(i), the competent authority may, in specific cases, authorise the use of removable guard rails in areas where this is necessary for controlling the sails.

15a-4.4 Within the meaning of section 15-7, sails rank as a main propulsion system.

15a-4.5 By way of derogation from paragraph 15-14.5(iii), the height of the lower edge of the door opening may be reduced to 20 cm above the floor of the passenger area. Once opened, the door shall close and lock automatically.

15a-4.6 If there is a possibility of the propeller idling while the vessel is under sail, any endangered parts of the propulsion system shall be protected against potential damage.

#### 15A-5<sup>9</sup> RIGGING IN GENERAL

15a-5.1 The parts of the rigging shall be arranged in such a way as to prevent unacceptable chafing.

15a-5.2 If a material other than wood is used or if special types of rigging are used, such a design shall guarantee equivalent levels of safety with the dimensions and strength values laid down in this chapter. As evidence of the strength

- (i) a strength calculation shall be carried out, or
- (ii) confirmation of sufficient strength shall have been obtained from an approved classification society, or
- (iii) dimensioning shall be based on the procedures set out in a recognised regulatory framework (e.g. Middendorf, Kusk-Jensen).

<sup>7</sup> Based on Article 15a.04 of the Directive.

<sup>8</sup> Here and hereafter, the reference to inspection body is replaced by the reference to competent authority, as referred to in section 2-5.1 of the Resolution.

<sup>9</sup> Based on Article 15a.05 of the Directive.

The evidence shall be presented to the competent authority.

15A-6<sup>10</sup>      MASTS AND SPARS IN GENERAL

15a-6.1      All spars shall be made of high-quality material.

15a-6.2      Wood for masts shall:

- (i)      be free of knot concentrations;
- (ii)     be free of sapwood within the required dimensions;
- (iii)    as far as possible be straight-grained;
- (iv)    contain as little as possible twisted growth.

15a-6.3      If the chosen timber is either pitch pine or Oregon pine of quality level 'clear and better' the diameters in the tables reproduced in sections 15a-7 to 15a-12 can be reduced by 5 %.

15a-6.4      If the timbers used for masts, topmasts, yardarms, booms and bowsprits are not round in cross-section, such timbers must be of equivalent strength.

15a-6.5      Mast pedestals, mast trunks and fastenings on deck, on floor-plates and on stem or stern shall be constructed in such a way that they can either absorb the forces they are subjected to or transfer them to other connected parts of the structure.

15a-6.6      Depending on the stability of the vessel and the external forces it is subjected to and also the distribution of the available sail area, the competent authority may, on the basis of the dimensions laid down in sections 15a-7 to 15a-12, allow reductions in the cross-sections of the spars and, where appropriate, of the rigging. Evidence shall be submitted in accordance with paragraph 15a-5.2.

15a-6.7      If the vessel's period of oscillation/period of roll, in seconds, is less than three quarters of its breadth, in metres, the dimensions set out in sections 15a-7 to 15a-12 shall be increased. Evidence shall be submitted in accordance with paragraph 15a-5.2.

15a-6.8      In the tables reproduced in sections 15a-7 to 15a-12 and 15a-14, possible intermediate values shall be interpolated.

15A-7<sup>11</sup>      SPECIAL PROVISIONS FOR MASTS

15a-7.1      Wooden masts shall meet the following minimum requirements:

| <i>Length</i> <sup>12</sup><br>(m) | <i>Diameter on deck</i><br>(cm) | <i>Diameter on the cross-tree</i><br>(cm) | <i>Diameter on the mast cap</i><br>(cm) |
|------------------------------------|---------------------------------|---|---|
| 10                                 | 20                              | 17  | 15                                      |
| 11                                 | 22                              | 17  | 15                                      |
| 12                                 | 24                              | 19  | 17                                      |
| 13                                 | 26                              | 21  | 18                                      |
| 14                                 | 28                              | 23  | 19                                      |
| 15                                 | 30                              | 25  | 21                                      |
| 16                                 | 32                              | 26  | 22                                      |

<sup>10</sup> Based on Article 15a.06 of the Directive.

<sup>11</sup> Based on Article 15a.07 of the Directive.

<sup>12</sup> It is proposed to add here a footnote, reading "Distance from the cross-tree to the deck".

| <i>Length<sup>12</sup></i><br>(m) | <i>Diameter on deck</i><br>(cm) | <i>Diameter on the cross-tree</i><br>(cm) | <i>Diameter on the mast cap</i><br>(cm) |
|-----------------------------------|---------------------------------|---|---|
| 17                                | 34                              | 28  | 23                                      |
| 18                                | 36                              | 29  | 24                                      |
| 19                                | 39                              | 31  | 25                                      |
| 20                                | 41                              | 33  | 26                                      |
| 21                                | 43                              | 34  | 28                                      |
| 22                                | 44                              | 35  | 29                                      |
| 23                                | 46                              | 37  | 30                                      |
| 24                                | 49                              | 39  | 32                                      |
| 25                                | 51                              | 41  | 33                                      |

If a mast has two yards, the diameters shall be increased by at least 10 %.

If a mast has more than two yards, the diameters shall be increased by at least 15 %.

In the case of masts fitted through the deck, the diameter at the mast foot shall be at least 75 % of the diameter of the mast at deck level.

15a-7.2 Mast fittings, mast bands, cross-trees and mast caps shall be sufficiently strongly dimensioned and attached.

#### 15A-8<sup>13</sup> SPECIAL PROVISIONS FOR TOPMASTS

15a-8.1 Wooden topmasts shall meet the following minimum requirements:

| <i>Length<sup>14</sup></i><br>(m) | <i>Diameter at the foot</i><br>(cm) | <i>Half-length diameter</i><br>(cm) | <i>Diameter at fitting<sup>15</sup></i><br>(cm) |
|-----------------------------------|-------------------------------------|-------------------------------------|---|
| 4                                 | 8                                   | 7                                   | 6   |
| 5                                 | 10                                  | 9                                   | 7   |
| 6                                 | 13                                  | 11                                  | 8   |
| 7                                 | 14                                  | 13                                  | 10  |
| 8                                 | 16                                  | 15                                  | 11  |
| 9                                 | 18                                  | 16                                  | 13  |
| 10                                | 20                                  | 18                                  | 15  |
| 11                                | 23                                  | 20                                  | 16  |
| 12                                | 25                                  | 22                                  | 17  |
| 13                                | 26                                  | 24                                  | 18  |
| 14                                | 28                                  | 25                                  | 20  |
| 15                                | 31                                  | 27                                  | 21  |

If square sails are attached to a topmast, the dimensions set out in the table shall be increased by 10 %.

<sup>13</sup> Based on Article 15a.08 of the Directive.

<sup>14</sup> It is proposed to add here a footnote, reading "Total length of the topmast, without the masthead".

<sup>15</sup> It is proposed to add here a footnote, reading "Diameter of the topmast at the level of the masthead fitting".

15a-8.2 The overlap between the topmast and the mast shall be at least 10 times the required foot diameter of the topmast.

15A-9<sup>16</sup> SPECIAL PROVISIONS FOR BOWSPRITS

15a-9.1 Wooden bowsprits shall meet the following minimum requirements:

| <i>Length<sup>17</sup></i><br><i>(m)</i> | <i>Diameter at stem</i><br><i>(cm)</i> | <i>Half-length diameter</i><br><i>(cm)</i> |
|--|--|--|
| 4  | 14,5                                   | 12,5                                       |
| 5  | 18                                     | 16   |
| 6  | 22                                     | 19   |
| 7  | 25                                     | 23   |
| 8  | 29                                     | 25   |
| 9  | 32                                     | 29   |
| 10                                       | 36                                     | 32   |
| 11                                       | 39                                     | 35   |
| 12                                       | 43                                     | 39   |

15a-9.2 The inboard section of the bowsprit shall have a length of at least four times the diameter of the bowsprit at the stem.

15a-9.3 The diameter of the bowsprit at its head shall be at least 60 % of the diameter of the bowsprit at the stem.

15A-10<sup>18</sup> SPECIAL PROVISIONS FOR JIB-BOOMS

15a-10.1 Wooden jib-booms shall meet the following minimum requirements:

|                                  |   |    |    |    |    |    |    |    |    |
|----------------------------------|---|----|----|----|----|----|----|----|----|
| <i>Length<sup>19</sup></i> (m)   | 2 | 3  | 4  | 5  | 6  | 7  | 8  | 9  | 10 |
| <i>Diameter at the stem</i> (cm) | 7 | 10 | 14 | 17 | 21 | 24 | 28 | 31 | 35 |

15a-10.2 The diameter of the jib-boom at its head shall be at least 60 % of the diameter at the stem.

15A-11<sup>20</sup> SPECIAL PROVISIONS FOR MAIN BOOMS

15a-11.1 Wooden main booms shall meet the following minimum requirements:

|                                |    |    |    |    |    |    |    |    |    |    |    |    |
|--------------------------------|----|----|----|----|----|----|----|----|----|----|----|----|
| <i>Length<sup>21</sup></i> (m) | 5  | 6  | 7  | 8  | 9  | 10 | 11 | 12 | 13 | 14 | 15 | 16 |
| <i>Diameter</i> (cm)           | 14 | 15 | 16 | 17 | 18 | 20 | 21 | 23 | 24 | 25 | 26 | 27 |

15a-11.2 The diameter at the swivel pin shall be at least 72 % of the diameter specified in the table.

15a-11.3 The diameter at the clew shall be at least 85 % of the diameter specified in the table.

<sup>16</sup> Based on Article 15a.09 of the Directive.

<sup>17</sup> It is proposed to add here a footnote, reading "Total length of the bowsprit".

<sup>18</sup> Based on Article 15a.10 of the Directive.

<sup>19</sup> It is proposed to add here a footnote, reading "Total length of the jib-boom".

<sup>20</sup> Based on Article 15a.11 of the Directive.

<sup>21</sup> It is proposed to add here a footnote, reading "Total length of the main boom".

15a-11.4 Measured from the mast, the greatest diameter shall be at two thirds of the length.

15a-11.5 Where:

- (i) there is an angle of less than 65° between the main boom and the after leech and the main sheet is attached to the end of the boom, or
- (ii) the attachment point of the sheet is not abreast of the clew,

the competent authority may, according to paragraph 15a-5.2, require a greater diameter.

15a-11.6 For sail areas of less than 50 m<sup>2</sup>, the competent authority may authorise reductions in the dimensions set out in the table.

#### 15A-12<sup>22</sup> SPECIAL PROVISIONS FOR GAFFS

15a-12.1 Wooden gaffs shall meet the following minimum requirements:

|                                 |    |    |    |    |    |    |    |
|---------------------------------|----|----|----|----|----|----|----|
| <i>Length</i> <sup>23</sup> (m) | 4  | 5  | 6  | 7  | 8  | 9  | 10 |
| <i>Diameter</i> (cm)            | 10 | 12 | 14 | 16 | 17 | 18 | 20 |

15a-12.2 The unsupported length of the gaff shall be not more than 75 %.

15a-12.3 The breaking strength of the crowfoot shall be at least equal to 1,2 times the breaking strength of the peak halyard.

15a-12.4 The top angle of the crowfoot shall be a maximum of 60°.

15a-12.5 If, by way of derogation from paragraph 4 15a-12.4, the top angle of the crowfoot is greater than 60°, the tensile strength shall be adjusted to accommodate the forces that will then occur.

15a-12.6 For sail areas of less than 50 m<sup>2</sup>, the competent authority may authorise reductions in the dimensions set out in the table.

#### 15A-13<sup>24</sup> GENERAL PROVISIONS FOR STANDING AND RUNNING RIGGING

15a-13.1 Standing and running rigging shall comply with the strength requirements set out in sections 15a-14 and 15a-15.

15a-13.2 Wire cable connections may take the form of:

- (a i) splicings,
- (b ii) compression sleeves, or
- (c iii) sealing sleeves.

Splicings shall be marled and ends shall be whipped.

15a-13.3 Eye splices shall be provided with thimbles.

15a-13.4 Ropes shall be routed in such a way as not to obstruct entrances and companionways.

#### 15A-14<sup>25</sup> SPECIAL PROVISIONS FOR STANDING RIGGING

15a-14.1 Forestays and shrouds shall meet the following minimum requirements:

<sup>22</sup> Based on Article 15a.12 of the Directive.

<sup>23</sup> It is proposed to add here a footnote, reading "Total length of the gaff".

<sup>24</sup> Based on Article 15a.13 of the Directive.

<sup>25</sup> Based on Article 15a.14 of the Directive.

| <i>Mast length<sup>26</sup> (m)</i>        | 11  | 12  | 13  | 14  | 15  | 16  | 17  | 18  |
|--|-----|-----|-----|-----|-----|-----|-----|-----|
| Tensile strength of the forestay (kN)      | 160 | 172 | 185 | 200 | 220 | 244 | 269 | 294 |
| Tensile strength of the shrouds (kN)       | 355 | 415 | 450 | 485 | 525 | 540 | 630 | 720 |
| Number of shroud cables and ropes per side | 3   | 3   | 3   | 3   | 3   | 3   | 4   | 4   |

15a-14.2 Backstays, topmasts, flying jib-stays, jib-booms and bowsprit shrouds shall meet the following minimum requirements:

| <i>Mast length<sup>27</sup> (m)</i>            | <13 | 13-18 | >18 |
|--|-----|-------|-----|
| Tensile strength of the backstay (kN)          | 89  | 119   | 159 |
| Tensile strength of the topmast (kN)           | 89  | 119   | 159 |
| Length of topmast (m)                          | <6  | 6-8   | >8  |
| Tensile strength of the flying jib-stay (kN)   | 58  | 89    | 119 |
| Length of jib-boom (m)                         | <5  | 5-7   | >7  |
| Tensile strength of the bow sprit shrouds (kN) | 58  | 89    | 119 |

15a-14.3 The preferred rope design shall be based on Rope Construction Method 6 × 7 FE in the strength class 1550 N/mm<sup>2</sup>. Alternatively, at the same strength class, Construction Method 6 × 36 SE or 6 × 19 FE may be used. Because of the higher elasticity of Construction Method 6 × 19, the tensile strengths given in the table shall be increased by 10 %. Use of a different rope design shall be permitted provided it has comparable properties.

15a-14.4 If rigid rigging is used, the tensile strengths shown in the table shall be increased by 30 %.

15a-14.5 For rigging, only approved forks, round eyes and bolts may be used.

15a-14.6 Bolts, forks, round eyes and turnbuckles shall be capable of being properly secured.

15a-14.7 The tensile strength of the bobstay shall be at least 1,2 times the tensile strength of the respective jib-stay and flying jib-stay.

15a-14.8 For vessels with less than 30 m<sup>3</sup> water displacement, the competent authority may permit the reductions in tensile strengths shown in the table set out below:

| <i>Water displacement divided by the number of masts (m<sup>3</sup>)</i> | <i>Reduction (%)</i> |
|--|----------------------|
| >20 to 30  | 20                   |
| 10 to 20   | 35                   |
| < 10   | 60                   |

#### 15A-15<sup>28</sup> SPECIAL PROVISIONS FOR RUNNING RIGGING

15a-15.1 For running rigging, fibre ropes or steel wire ropes shall be used. The minimum tensile strength and the diameter for running rigging shall, in relation to the sail area, meet the following minimum requirements:

<sup>26</sup> It is proposed to add here a footnote, reading "Distance from the top or cross-tree to the deck".

<sup>27</sup> It is proposed to add here a footnote, reading "Distance from the top or cross-tree to the deck".

<sup>28</sup> Based on Article 15a.15 of the Directive.

| <i>Type of running rigging</i> | <i>Rope material</i>   | <i>Sail area (m<sup>2</sup>)</i>   | <i>Minimum tensile strength (kN)</i> | <i>Diameter of rope (mm)</i> |
|--------------------------------|--|--|--------------------------------------|------------------------------|
| Staysail halyards              |  | up to 35   | 20                                   | 6                            |
|                                | Steel wire   | > 35   | 38                                   | 8                            |
|                                | Fibre (polypropylene-PP)   | Rope diameter of at least 14 mm and one rope sheave for every 25 m <sup>2</sup> or part thereof  |                                      |                              |
| Gaff sail halyards             |  | up to 50   | 20                                   | 6                            |
| Top sail halyards              |  | > 50 to 80   | 30                                   | 8                            |
|                                |  | > 80 to 120  | 60                                   | 10                           |
|                                | Steel wire   | >120 to 160  | 80                                   | 12                           |
|                                | Fibre (PP)   | Rope diameter of at least 18 mm and one rope sheave for every 30 m <sup>2</sup> or part thereof  |                                      |                              |
| Staysail sheets                |  | up to 40   | 14                                   |                              |
|                                | Fibre (PP)   | > 40   | 18                                   |                              |
|                                | For sail areas of more than 30 m <sup>2</sup> , the sheet shall take the form of a tackle or shall be capable of being operated by a winch |  |                                      |                              |
| Gaff-/Top-sail sheets          |  | < 100  | 60                                   | 10                           |
|                                |  | 100 to 150   | 85                                   | 12                           |
|                                |  | > 150  | 116                                  | 14                           |
|                                | Steel wire   | For top sail sheets, elastic connection elements (fore runners) are necessary.   |                                      |                              |
|                                | Fibre (PP)   | Rope diameter of at least 18 mm and at least three rope sheaves. Where the sail area is greater than 60 m <sup>2</sup> , one rope sheave per 20 m <sup>2</sup> |                                      |                              |

15a–15.2 Running rigging forming part of the staying shall have a tensile strength which corresponds to that of the respective stay or shrouds.

15a–15.3 If materials other than those stated in paragraph 15a–15.1 are used, the strength values given in the table in paragraph 15a–15.1 shall be complied with.

Fibre ropes of polyethylene shall not be used.

#### 15A–16<sup>29</sup> FITTINGS AND PARTS OF THE RIGGING

15a–16.1 If steel wire ropes or fibre ropes are used, the diameters of the rope sheaves (measured from centre of rope to centre of rope) shall meet the following minimum requirements:

|                         |     |     |     |     |     |     |     |
|-------------------------|-----|-----|-----|-----|-----|-----|-----|
| <i>Steel wire (mm)</i>  | 6   | 7   | 8   | 9   | 10  | 11  | 12  |
| <i>Fibre (mm)</i>       | 16  | 18  | 20  | 22  | 24  | 26  | 28  |
| <i>Rope sheave (mm)</i> | 100 | 110 | 120 | 130 | 145 | 155 | 165 |

15a–16.2 By way of derogation from paragraph 15a–16.1, the diameter of the rope sheaves may be equal to six times the diameter of the steel wire, provided that the steel wire does not constantly run over sheaves.

<sup>29</sup> Based on Article 15a.16 of the Directive.

15a-16.3 The tensile strength of the fittings (e.g. forks, round eyes, turnbuckles, eye-plates, bolts, rings and shackles) shall be compatible with the tensile strength of the standing or running rigging that is attached to them.

15a-16.4 The fastenings of stay and shroud futtocks shall be designed to take up the forces they are subjected to.

15a-16.5 Only one shackle, along with the relevant stay or shroud, may be attached to each eye.

15a-16.6 Blocks of halyards and topping lifts shall be securely fastened to the mast, and the revolving crowfeet used for this purpose shall be in good condition.

15a-16.7 Attachments of eye-bolts, cleats, belaying pins and fife-rails shall be designed to cope with the forces they are subjected to.

#### 15A-17<sup>30</sup> SAILS

15a-17.1 It shall be ensured that sails can be taken in simply, swiftly and safely.

15a-17.2 The sail area shall be appropriate for the type of vessel and the water displacement.

#### 15A-18<sup>31</sup> EQUIPMENT

15a-18.1 Vessels that are fitted with a jib-boom or a bowsprit shall have a jib-net and an adequate number of appropriate holding and tensioning devices.

15a-18.2 The equipment according to paragraph 15a-18.1 may be dispensed with if the jib-boom or bowsprit is equipped with a hand becket and a foot rope adequately dimensioned to allow for the attachment of a safety harness to be carried on board.

15a-18.3 For work on the rigging, a boatswain's chair shall be provided.

#### 15A-19<sup>32</sup> TESTING

15a-19.1 The rigging shall be tested by the competent authority every 2,5 years. As a minimum, the test shall cover the following:

- (i) the sails, including leeches, clews and reef eyes;
- (ii) the state of the masts and spars;
- (iii) the state of the standing and running rigging together with cable wire connections;
- (iv) facilities for taking in the sail swiftly and safely;
- (v) the secure fastening of blocks of halyards and topping lifts;
- (vi) the fastening of mast trunks and other fastening points for standing and running rigging that are attached to the vessel;
- (vii) the winches for operating the sails;
- (viii) other facilities fitted for the purposes of sailing, such as lee-boards and the fittings for operating them;

---

<sup>30</sup> Based on Article 15a.17 of the Directive.

<sup>31</sup> Based on Article 15a.18 of the Directive.

<sup>32</sup> Based on Article 15a.19 of the Directive.

(ix) the measures taken to prevent the chafing of the spars, the running and standing rigging and the sails;

(x) the equipment according to section 15a–18.

15a–19.2 That part of the wooden mast passing through the deck and located below the deck shall be re-examined at intervals to be determined by the competent authority, but at the very least on the occasion of each periodical inspection according to section 2–4. The mast shall be extracted for this purpose.

15a–19.3 A certificate of the last inspection carried out in accordance with paragraph 15a–19.1 and issued, dated and signed by the competent authority, shall be carried on board.

---