



Economic and Social Council

Distr.: General
19 December 2016

Original: English

Economic Commission for Europe

Inland Transport Committee

World Forum for Harmonization of Vehicle Regulations

171st session

Geneva, 14-17 March 2017

Item 4.9.7 of the provisional agenda

1958 Agreement:

Consideration of draft amendments

to existing Regulations submitted by GRE

Proposal for Supplement 1 to the 04 series of amendments to Regulation No. 27 (Advance warning triangles)

Submitted by the Working Party on Lighting and Light-Signalling*

The text reproduced below was adopted by the Working Party on Lighting and Light-Signalling (GRE) at its seventy-sixth session (ECE/TRANS/WP.29/GRE/76, para. 10). It is based on ECE/TRANS/WP.29/2014/31. It is submitted to the World Forum for Harmonization of Vehicle Regulations (WP.29) and to the Administrative Committee AC.1 for consideration at their March 2017 sessions.

* In accordance with the programme of work of the Inland Transport Committee for 2016–2017 (ECE/TRANS/254, para. 159 and ECE/TRANS/2016/28/Add.1, cluster 3.1), the World Forum will develop, harmonize and update Regulations in order to enhance the performance of vehicles. The present document is submitted in conformity with that mandate.

Supplement 1 to the 04 series of amendments to Regulation No. 27 (Advance warning triangles)

Paragraph 10.1., amend to read:

- "10.1. Advance-warning triangles shall be so manufactured as to conform to the type approved under this Regulation.
- The compliance with the requirements set forth in paragraphs 6., 7. and 8. above shall be verified as follows:"

Paragraphs 10.1.2., amend to read:

- "10.1.2. The minimum requirements for Conformity of Production (CoP) control procedures set forth in Annex 7 to this Regulation shall be complied with."

Annex 8,

Paragraphs 2. to 4. and figure 1, shall be deleted.

Insert new paragraphs 2. to 6., to read:

- "2. First sampling
- In the first sampling four advance-warning triangles are selected at random. The first sample of two is marked A, the second sample of two is marked B.
- 2.1. The conformity of mass-produced advance-warning triangles shall not be contested if the deviation of any specimen of samples A and B (all four advance-warning triangles) is not more than 20 per cent.
- In the case that the deviation of both advance-warning triangles of sample A is not more than 0 per cent, the measurement can be closed.
- 2.2. The conformity of mass-produced advance-warning triangles shall be contested if the deviation of at least one specimen of samples A or B is more than 20 per cent.
- The manufacturer shall be requested to bring his production in line with the requirements (alignment) and a repeated sampling according to paragraph 3. below shall be carried out within two months' time after the notification. The samples A and B shall be retained by the Technical Service until the entire CoP process is finished.
3. First repeated sampling
- A sample of four advance-warning triangles is selected at random from stock manufactured after alignment,
- The first sample of two is marked C, the second sample of two is marked D.
- 3.1. The conformity of mass-produced advance-warning triangles shall not be contested if the deviation of any specimen of samples C and D (all four advance-warning triangles) is not more than 20 per cent.
- In the case that the deviation of both advance-warning triangles of sample C is not more than 0 per cent, the measurement can be closed.
- 3.2. The conformity of mass-produced advance-warning triangles shall be contested if the deviation of at least:
- 3.2.1. One specimen of samples C or D is more than 20 per cent but the deviation of all specimens of these samples is not more than 30 per cent.

The manufacturer shall be requested again to bring their production in line with the requirements (alignment).

A second repeated sampling according to paragraph 4. below shall be carried out within two months' time after the notification. The samples C and D shall be retained by the Technical Service until the entire CoP process is finished.

- 3.2.2. One specimen of samples C and D is more than 30 per cent.

In this case the approval shall be withdrawn and paragraph 5. below shall be applied.

4. Second repeated sampling

A sample of four advance-warning triangles, is selected at random from stock manufactured after alignment.

The first sample of two is marked E, the second sample of two is marked F.

- 4.1. The conformity of mass-produced advance-warning triangles shall not be contested if the deviation of any specimen of samples E and F (all four advance-warning triangles) is not more than 20 per cent

In the case that the deviation of both advance-warning triangles of sample E is not more than 0 per cent, the measurement can be closed.

- 4.2. The conformity of mass-produced advance-warning triangles shall be contested if the deviation of at least one specimen of samples E or F is more than 20 per cent.

In this case the approval shall be withdrawn and paragraph 5. below shall be applied.

5. Approval withdrawn

Approval shall be withdrawn according to paragraph 9. of this Regulation.

6. Additional Tests

With respect to the verification of the normal use the following procedures shall be applied:

One additional advance-warning triangle shall be tested according to the procedures described in paragraph 1.5.3. to 1.8.3. of Annex 5.

The advance-warning triangles shall be considered as acceptable if the tests have been passed.

However, if the test on this sample is not complied with, the two other additional advance-warning triangles shall be subjected to the same procedure and both shall pass the test."