



Economic and Social Council

Distr.: General
15 August 2018

Original: English

Economic Commission for Europe

Inland Transport Committee

World Forum for Harmonization of Vehicle Regulations

176th session

Geneva, 13-16 November 2018

Item 4.8.5 of the provisional agenda

1958 Agreement:

Consideration of draft amendments to existing

UN Regulations submitted by GRSP

Proposal for Supplement 15 to the 04 series of amendments to UN Regulation No. 44 (Child restraint systems)

Submitted by the Working Party on Passive Safety*

The text reproduced below was adopted by the Working Party on Passive Safety (GRSP) at its sixty-third session (ECE/TRANS/WP.29/GRSP/63, para. 42). It is based on ECE/TRANS/WP.29/GRSP/2017/27 as amended in Annex X to the report. It is submitted to the World Forum for Harmonization of Vehicle Regulations (WP.29) and to the Administrative Committee AC.1 for consideration at their November 2018 sessions.

* In accordance with the programme of work of the Inland Transport Committee for 2018–2019 (ECE/TRANS/274, para. 123 and ECE/TRANS/2018/21/Add.1, cluster 3.1), the World Forum will develop, harmonize and update UN Regulations in order to enhance the performance of vehicles. The present document is submitted in conformity with that mandate.

Supplement 15 to the 04 series of amendments to UN Regulation No. 44 (Child restraint systems)

Paragraph 4.4., amend to read:

"4.4. On the visible inner surface (including the inside surface of a side wing beside the child's head) in the approximate area where the child's head rests within the child restraint system, rearward facing restraints shall have the shown label permanently attached.

The overall dimensions of the label shall be at least 120 x 60 mm or the equivalent area.

The label may be adapted in such a way that the layout differs from the example shown here; however, the content shall meet the precise prescriptions. Furthermore, no other type of information shall be included on the label unless it is placed outside a clearly marked rectangle with at least the overall dimensions as required above. In derogation to the aforementioned, a part number, bar code or similar identification mark not exceeding 8 mm x 35 mm or the equivalent area may be placed on the label.

It shall also be ensured that no deviations in the shape and orientation of the provided pictograms are permitted, notably that any customised appearance of the prescribed pictogram images shall be prohibited, with the exception of the hand with pointing index finger and the open face booklet with letter 'i' on its right page provided that they are clearly recognisable as such.

Small irregularities concerning line thickness, label imprinting and other relevant production tolerances shall be accepted.

The label shall ... any configuration.

Figure A
Warning label

...

Figure B
Pictogram according to ISO 2575:2004 - Z.01 that shall be used and that shall have an outer diameter of at least 38 mm



Figure C
Pictogram depicting airbag deployment danger that shall be used and that shall measure 40 mm in width and 28 mm in height or proportionally larger

