# Proposal for amendments to UN Regulation No. 79 Proposal for an alternative to the actuation of the remote control device for the use of RCP

## 1. Proposal

Paragraph 5.6.1.2.2, amend to read (paragraph 5.6.1.2.1. unchanged):

- 5.6.1.2. Additional provisions for RCP
- 5.6.1.2.1. The parking manoeuvre shall be initiated by the driver but controlled by the system. A direct influence on steering angle, value of acceleration and deceleration via the remote control device **or by the motion of the driver** shall not be possible.
- "5.6.1.2.2. Either a continuous actuation of the remote control device by the driver or alternatively (for systems based on detection of driver position and motion) a continuous motion of the driver in the same longitudinal direction, is required during the parking manoeuvre."

#### Paragraph 5.6.1.2.3, amend to read:

#### "5.6.1.2.3. For systems based on continuous actuation of the remote control device, the vehicle shall stop immediately if

- the continuous actuation is interrupted or
- the distance between vehicle and remote control device exceeds the specified maximum RCP operating range (S<sub>RCPmax</sub>) or
- the signal between remote control and vehicle is lost,

the vehicle shall stop immediately.

For systems based on detection of driver position and motion, the vehicle shall stop immediately if

- the continuous motion of the driver is interrupted or
- the distance between vehicle and remote control device exceeds the specified maximum RCP operating range (S<sub>RCPmax</sub>) or
- the detection of the driver is lost."

A new *paragraph* 5.6.1.3.1.4 is added:

"5.6.1.3.1.4. For RCP systems based on detection of driver position and motion the manufacturer shall provide the technical authorities with an explanation how a person is identified as the driver and how this person is tracked."

### 2. Justifications

- 1. This proposal aims at allowing an alternative to the continuous actuation of the remote control device.
- 2. With this proposal the continued movement of the driver is introduced as an alternative means to support driver attentiveness.
- 3. This alternative possibility requires driver engagement and supports the driver to focus on the area around the vehicle.
- 4. Here is a link to <u>GRVA-05-47</u>