12 December 2011

Agreement

Concerning the adoption of uniform technical prescriptions for wheeled vehicles, equipment and parts which can be fitted and/or be used on wheeled vehicles and the conditions for reciprocal recognition of approvals granted on the basis of these prescriptions*

(Revision 2, including the amendments which entered into force on 16 October 1995)

Addendum 52: Regulation No. 53

Revision 2 – Amendment 5

Supplement 13 to the 01 series of amendments - Date of entry into force: 28 October 2011

Uniform provisions concerning the approval of category L_3 vehicles with regard to the installation of lighting and light-signalling devices



UNITED NATIONS

^{*} Former title of the Agreement: Agreement Concerning the Adoption of Uniform Conditions of Approval and Reciprocal Recognition of Approval for Motor Vehicle Equipment and Parts, done at Geneva on 20 March 1958.

Paragraph 5.13., amend to read:

"5.13. Colours of the lights

The colours of the lights referred to in this Regulation shall be as follows:

Driving beam headlamp: white
Passing beam headlamp: white
Direction-indicator lamp: amber
Stop lamp: red
Rear-registration plate lamp: white

Front position lamp: white or amber

Rear position lamp: red Rear retro-reflector, non-triangular: red

Side retro-reflector, non-triangular: amber at the front

amber or red at the rear

Vehicle-hazard warning signal: amber

Front fog lamp: white or selective yellow

Rear fog lamp: red"

Insert a new paragraph 6.3.7., to read:

"6.3.7. May not be "reciprocally incorporated" with any other lamp, except amber front position lamp."

Paragraphs 6.3.7. to 6.3.8.4. (former), renumber as paragraphs 6.3.8. to 6.3.9.4.

Paragraph 6.4.7., amend to read:

"6.4.7. "Tell-tale"

Tell-tale optional; where fitted, this tell-tale shall be a tell-tale consisting of a non-flashing warning light which comes on in the event of the malfunctioning of the stop lamps."

Paragraph 6.6.1., amend to read:

"6.6.1. Number

One or two if coloured white

or

Two (one per side) if coloured amber"

Paragraph 6.6.7., amend to read:

"6.6.7. Other requirements

When the front position lamp is reciprocally incorporated in the front direction indicator lamp, the electrical connection shall be such that the position lamp on the same side as the direction indicator lamp is switched off when the direction indicator lamp is flashing."

2