

6 December 2012

Agreement

Concerning the adoption of uniform technical prescriptions for wheeled vehicles, equipment and parts which can be fitted and/or be used on wheeled vehicles and the conditions for reciprocal recognition of approvals granted on the basis of these prescriptions*

(Revision 2, including the amendments which entered into force on 16 October 1995)

Addendum 106: Regulation No. 107

Revision 3 – Amendment 5

Supplement 2 to the 04 series of amendments - Date of entry into force: 18 November 2012

Uniform provisions concerning the approval of category M₂ or M₃ vehicles with regard to their general construction



UNITED NATIONS

* Former title of the Agreement: Agreement Concerning the Adoption of Uniform Conditions of Approval and Reciprocal Recognition of Approval for Motor Vehicle Equipment and Parts, done at Geneva on 20 March 1958.

Annex 3,

Insert a new paragraph 7.6.5.1.5., to read:

"7.6.5.1.5. May activate a starting prevention device;"

Paragraphs 7.6.5.1.5. to 7.6.5.1.8. (former), renumber as paragraphs 7.6.5.1.6. to 7.6.5.1.9.

Paragraph 7.7.5.1., amend to read:

"7.7.5.1. The gangway(s) of a vehicle shall be so designed and constructed as to permit the free passage of a gauging device consisting of two co-axial cylinders with an inverted truncated cone interposed between them, the gauging device having the dimensions shown in Annex 4, Figure 6.

The gauging device may come into contact with strap hangers, if fitted, or other flexible objects such as seat belt components and move them easily away;

In vehicles of classes I and A, the gauging device according to Annex 4, Figure 6 shall not come into contact with any monitor or display device mounted from the ceiling above the gangway.

In vehicles of classes II, III and B, the gauging device according to Annex 4, Figure 6 may come into contact with any monitor or display device mounted from the ceiling above the gangway provided the maximum force necessary to move any such monitor or display device out of the way, when applying the gauging device along the gangway in both directions, does not exceed 20 Newton. After being moved out of the way, the monitor or display device shall remain in the retracted position."

Paragraph 7.7.8.1.3., amend to read:

"7.7.8.1.3. For vehicles not exceeding a width of 2.35 m:

7.7.8.1.3.1. the width of the available space for each seating position, measured from a vertical plane passing through the centre of that seating position at heights between 270 mm and 650 mm above the uncompressed seat cushion, shall be 200 mm (see Annex 4, Figure 9A). In case of compliance with this paragraph the requirements of paragraph 7.7.8.1.2. shall not apply; and

7.7.8.1.3.2. In the case of vehicles of Class III, the minimum width of the seat cushion, dimension "F" (Annex 4, Figure 9A), measured from a vertical plane passing through the centre of that seating position, shall be a minimum of 200 mm. In case of compliance with this paragraph the requirements of paragraph 7.7.8.1.1.2. shall not apply."