



**Economic and Social
Council**

Distr.
GENERAL

TRANS/WP.29/577
15 July 1997

ENGLISH
Original: ENGLISH
and FRENCH

ECONOMIC COMMISSION FOR EUROPE

INLAND TRANSPORT COMMITTEE

Working Party on the Construction of Vehicles

DRAFT SUPPLEMENT 10 TO REGULATION No. 54

(Pneumatic tyres for commercial vehicles)

Note: The text reproduced below was adopted by the Administrative Committee (AC.1) of the amended 1958 Agreement at its sixth session, following the recommendation by the Working Party at its one-hundred-and-twelfth session. It is based on document TRANS/WP.29/R.803, as amended (TRANS/WP.29/566, paras. 59 and 123).

Paragraph 1. to 1.3., replace by the following text (including a new footnote */):

"1. SCOPE

This Regulation covers new pneumatic tyres designed primarily, but not only, for vehicles in categories M₂, M₃, N and O₃ and O₄. */
However, it does not apply to tyre types identified by speed category symbols corresponding to speeds below 80 km/h.

*/ As defined in the Consolidated Resolution R.E.3 (document TRANS/SC1/WP29/78/Amend.3)."

Paragraph 2.1.1., amend to read:

"2.1.1. The manufacturer;"

Paragraph 2.17.1.3.1., add the following new nominal rim diameter codes at the end of the table:

"Nominal rim diameter code ("d" symbol)	Value of the "d" symbol expressed in mm
.	.
.	.
.	.
26	660
28	711
30	762"

Paragraph 8. and 8.1., amend to read:

"8. CONFORMITY OF PRODUCTION

The conformity of production procedures shall comply with those set out in the Agreement, Appendix 2 (E/ECE/324-E/ECE/TRANS/505/Rev. 2), with the following requirements:

8.1. Tyres approved under this Regulation shall be so manufactured as to conform to the type approved, by meeting the requirements set forth in paragraph 6. above."

Paragraph 8.2. to 8.4.4., should be deleted.

Paragraph 8.4.5., renumber as paragraph 8.2. and amend to read:

"8.2. The authority which has granted type approval may at any time verify the conformity control methods applied in each production facility. For each production facility, the normal frequency of these verifications shall be once every two years."

Annex 1, item 1, amend to read:

"1. Manufacturer's name or trade mark(s) on the tyre type:"

Annex 5, Part II, table D, amend the title of the table to read:

"Table D

CODE DESIGNATED TYRES FOR SPECIAL SERVICES
DIAGONAL AND RADIAL"

and, in addition, add at the end the following new tyre size:

Tyre size designation	Measuring rim width code	Nominal rim diameter d (mm)	Outer diameter D (mm) 1/		Section width S (mm) 2/
			(a)	(b)	
.
.
.
24 R 21	18	533	1372	-	610

Note: Footnotes 1/ and 2/ not modified.
